

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	rp98927	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 18 Sec
Total Counter :	250052	Total Running Time :	3295 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	174	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.66	kN	No		
HEP :	25.0 %	9.29	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	7.58	kN	Yes	15	Times
Ref :		7.43	kN			
LCP :	2.0 %	7.28	kN	Yes	15	Times
LEP :	25.0 %	5.57	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.20	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.39	kN	Min :	1.26	kN	Punch NO.;	50
		4.70	%	Max :	1.57	kN	Punch NO.;	53
Mean Main Pressure :		7.26	kN	Min :	6.79	kN	Punch NO.;	35
	SD :	3.70	%	Max :	7.77	kN	Punch NO.;	32
Filling Depth :	Increase ;	180	Times	Decrease ;	162	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.55	mm	Main Thickness ;	3.55	mm
Filling Depth :	9.17	mm	Current Cam :	Cam C	
Main Air pressure :	0.763	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	2
Lower Punch :	Average ;	0.25	kN		
	Max ;	0.54	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250052	Tablets			
A.W.C Counter :	243570	Tablets			
HEP :	171 (0.1%)	Tablets	LEP :	152 (0.1%)	Tablets
GOOD :	243247 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	rp98927	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 18 Sec
Total Counter :	250052	Total Running Time :	3295 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	165	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.02	kN	No		
HEP :	25.0 %	10.59	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.65	kN	Yes	15	Times
Ref :		8.48	kN			
LCP :	2.0 %	8.31	kN	Yes	15	Times
LEP :	25.0 %	6.36	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.83	kN	Punch NO.;	15
SD :	3.30	%	Max :	2.11	kN	Punch NO.;	46
Mean Main Pressure :	8.51	kN	Min :	8.08	kN	Punch NO.;	37
SD :	2.70	%	Max :	9.04	kN	Punch NO.;	39
Filling Depth :	Increase ;	41	Times	Decrease ;	62	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.60	mm
Filling Depth :	8.70	mm	Current Cam :	Cam C	
Main Air pressure :	0.763	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	18
Lower Punch :	Average ;	0.25	kN		
	Max ;	0.54	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250052	Tablets			
A.W.C Counter :	243570	Tablets			
HEP :	171 (0.1%)	Tablets	LEP :	152 (0.1%)	Tablets
GOOD :	243247 (99.9%)	Tablets			