

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	sp98936	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 22 Sec
Total Counter :	550136	Total Running Time :	3298 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	198	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.21	kN	No		
HEP :	25.0 %	9.82	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.01	kN	Yes 15	Times	
Ref :		7.86	kN			
LCP :	2.0 %	7.70	kN	Yes 15	Times	
LEP :	25.0 %	5.89	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.50	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.32	kN	Min :	1.04	kN	Punch NO.;	32
SD :	10.80	%	Max :	1.75	kN	Punch NO.;	22
Mean Main Pressure :	7.11	kN	Min :	5.99	kN	Punch NO.;	19
SD :	8.40	%	Max :	8.13	kN	Punch NO.;	45
Filling Depth :	Increase ;	470	Times	Decrease ;	408	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.55	mm	Main Thickness ;	3.55	mm
Filling Depth :	10.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	46
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.84	kN	Max Punch ;	33
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550136	Tablets			
A.W.C Counter :	540735	Tablets			
HEP :	758 (0.1%)	Tablets	LEP :	608 (0.1%)	Tablets
GOOD :	539369 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	sp98936	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 22 Sec
Total Counter :	550136	Total Running Time :	3298 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	198	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.31	kN	No		
HEP :	25.0 %	10.87	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.87	kN	Yes 15	Times	
Ref :		8.70	kN			
LCP :	2.0 %	8.52	kN	Yes 15	Times	
LEP :	25.0 %	6.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.09	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.99	kN	Min :	1.85	kN	Punch NO.;	1
SD :	4.40	%	Max :	2.24	kN	Punch NO.;	22
Mean Main Pressure :	8.51	kN	Min :	8.01	kN	Punch NO.;	21
SD :	3.20	%	Max :	9.26	kN	Punch NO.;	31
Filling Depth :	Increase ;	134	Times	Decrease ;	131	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	10.06	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.788	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	44
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.84	kN	Max Punch ;	33
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550136	Tablets			
A.W.C Counter :	540735	Tablets			
HEP :	758 (0.1%)	Tablets	LEP :	608 (0.1%)	Tablets
GOOD :	539369 (99.7%)	Tablets			