

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	12 Hour 35 Min 02 Sec
Total Counter :	2050884	Total Running Time :	3311 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	114	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.50	kN	No		
HEP :	25.0 %	14.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.16	kN	Yes 15	Times	
Ref :		11.92	kN			
LCP :	2.0 %	11.69	kN	Yes 15	Times	
LEP :	25.0 %	8.94	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.36	kN	Min :	1.24	kN	Punch NO.;	50
SD :	3.70	%	Max :	1.48	kN	Punch NO.;	12
Mean Main Pressure :	11.95	kN	Min :	11.37	kN	Punch NO.;	36
SD :	2.10	%	Max :	12.61	kN	Punch NO.;	14
Filling Depth :	Increase ; 82	Times	Decrease ;	101	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.01	mm
Filling Depth :	7.34	mm	Current Cam :	Cam C	
Main Air pressure :	0.746	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	26
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2050884	Tablets			
A.W.C Counter :	2043189	Tablets			
HEP :	321 (0.0%)	Tablets	LEP :	360 (0.0%)	Tablets
GOOD :	2042508 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	12 Hour 35 Min 02 Sec
Total Counter :	2050884	Total Running Time :	3311 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	118	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.20	kN	No		
HEP :	25.0 %	15.58	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.71	kN	Yes 15	Times	
Ref :		12.47	kN			
LCP :	2.0 %	12.22	kN	Yes 15	Times	
LEP :	25.0 %	9.35	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.73	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.64	kN	Punch NO.;	49
SD :	3.50	%	Max :	1.89	kN	Punch NO.;	9
Mean Main Pressure :	12.58	kN	Min :	11.70	kN	Punch NO.;	53
SD :	3.50	%	Max :	13.46	kN	Punch NO.;	29
Filling Depth :	Increase ;	215	Times	Decrease ;	240	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	33	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.16	mm	Main Thickness ;	3.17	mm
Filling Depth :	7.05	mm	Current Cam :	Cam C	
Main Air pressure :	0.746	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	26
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2050884	Tablets			
A.W.C Counter :	2043189	Tablets			
HEP :	321 (0.0%)	Tablets	LEP :	360 (0.0%)	Tablets
GOOD :	2042508 (100.0%)	Tablets			