

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET BP500mg<br>STMR2A00 |
| User ID :        | rp98927       | Batch NO. :          | MRM2504350              |
| Print Interval : | 50000 Tablets | Running Time :       | 06 Hour 09 Min 36 Sec   |
| Total Counter :  | 1100440       | Total Running Time : | 3331 Hour 6 Min         |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 107               | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |             | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50                | Min     | Supply Time ;      | 0.1          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 30                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 2.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 1.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 15.70             | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 15.10             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 12.32             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 12.08             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 11.84             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 9.06              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 8.46              | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |                |       |            |       |       |            |    |
|----------------------|----------------|-------|------------|-------|-------|------------|----|
| Mean Pre Pressure :  | 1.31           | kN    | Min :      | 1.19  | kN    | Punch NO.; | 50 |
| SD :                 | 4.50           | %     | Max :      | 1.50  | kN    | Punch NO.; | 29 |
| Mean Main Pressure : | 12.07          | kN    | Min :      | 11.08 | kN    | Punch NO.; | 50 |
| SD :                 | 3.00           | %     | Max :      | 13.02 | kN    | Punch NO.; | 6  |
| Filling Depth :      | Increase ; 332 | Times | Decrease ; | 338   | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 30       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.10    | mm  | Pre Thickness ;  | 3.11     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.00    | mm  | Main Thickness ; | 3.01     | mm           |
| Filling Depth :               | 7.16    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.755   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 29      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 22      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.02 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 29 |
| Lower Punch :    | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 23 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 1100440             | Tablets |       |            |         |
| A.W.C Counter : | 1097715             | Tablets |       |            |         |
| HEP :           | 68 (0.0%)           | Tablets | LEP : | 223 (0.0%) | Tablets |
| GOOD :          | 1097424<br>(100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET BP500mg<br>STMR2A00 |
| User ID :        | rp98927       | Batch NO. :          | MRM2504350              |
| Print Interval : | 50000 Tablets | Running Time :       | 06 Hour 09 Min 36 Sec   |
| Total Counter :  | 1100440       | Total Running Time : | 3331 Hour 6 Min         |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 96        | %       | Manual ;           | 45           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 4500000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50        | Min     | Supply Time ;      | 0.1          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 30        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 2.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 1.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 16.83     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 16.18     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 13.20     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 12.94     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 12.69     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 9.71      | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 9.06      | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.80       | kN  | Min : | 1.67       | kN  | Punch NO.; | 36 |
| SD :                 | 3.30       | %   | Max : | 1.95       | kN  | Punch NO.; | 21 |
| Mean Main Pressure : | 13.23      | kN  | Min : | 11.72      | kN  | Punch NO.; | 36 |
| SD :                 | 4.00       | %   | Max : | 14.46      | kN  | Punch NO.; | 47 |
| Filling Depth :      | Increase ; | 950 | Times | Decrease ; | 979 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 27       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.20    | mm  | Pre Thickness ;  | 3.21     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.16    | mm  | Main Thickness ; | 3.17     | mm           |
| Filling Depth :               | 7.15    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.755   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 29      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 22      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 2  |
| Lower Punch :    | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 23 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 1100440             | Tablets |       |            |         |
| A.W.C Counter : | 1097715             | Tablets |       |            |         |
| HEP :           | 68 (0.0%)           | Tablets | LEP : | 223 (0.0%) | Tablets |
| GOOD :          | 1097424<br>(100.0%) | Tablets |       |            |         |