

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	21 Hour 43 Min 10 Sec
Total Counter :	3880198	Total Running Time :	3346 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.51	kN	No		
HEP :	25.0 %	14.92	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.17	kN	Yes	15	Times
Ref :		11.93	kN			
LCP :	2.0 %	11.69	kN	Yes	15	Times
LEP :	25.0 %	8.95	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.38	kN	Min :	1.25	kN	Punch NO.;	52
SD :	4.00	%	Max :	1.54	kN	Punch NO.;	37
Mean Main Pressure :	11.79	kN	Min :	11.11	kN	Punch NO.;	52
SD :	2.30	%	Max :	12.35	kN	Punch NO.;	47
Filling Depth :	Increase ;	112	Times	Decrease ;	90	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.06	mm	Main Thickness ;	3.07	mm
Filling Depth :	7.37	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.731	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	12
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3880198	Tablets			
A.W.C Counter :	3874532	Tablets			
HEP :	257 (0.0%)	Tablets	LEP :	1060 (0.0%)	Tablets
GOOD :	3873215 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	21 Hour 43 Min 10 Sec
Total Counter :	3880198	Total Running Time :	3346 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.03	kN	No		
HEP :	25.0 %	14.45	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.79	kN	Yes 15	Times	
Ref :		11.56	kN			
LCP :	2.0 %	11.33	kN	Yes 15	Times	
LEP :	25.0 %	8.67	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.09	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.71	kN	Min :	1.59	kN	Punch NO.;	51
SD :	3.30	%	Max :	1.86	kN	Punch NO.;	47
Mean Main Pressure :	11.45	kN	Min :	10.49	kN	Punch NO.;	51
SD :	3.80	%	Max :	12.44	kN	Punch NO.;	47
Filling Depth :	Increase ;	442	Times	Decrease ;	434	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.21	mm	Main Thickness ;	3.22	mm
Filling Depth :	7.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.731	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	12
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3880198	Tablets			
A.W.C Counter :	3874532	Tablets			
HEP :	257 (0.0%)	Tablets	LEP :	1060 (0.0%)	Tablets
GOOD :	3873215 (100.0%)	Tablets			