

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	23 Hour 07 Min 10 Sec
Total Counter :	4130318	Total Running Time :	3348 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.38	kN	No		
HEP :	25.0 %	14.79	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.07	kN	Yes 15	Times	
Ref :		11.83	kN			
LCP :	2.0 %	11.59	kN	Yes 15	Times	
LEP :	25.0 %	8.87	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.37	kN	Min :	1.26	kN	Punch NO.;	52
SD :	3.70	%	Max :	1.48	kN	Punch NO.;	21
Mean Main Pressure :	11.76	kN	Min :	11.12	kN	Punch NO.;	52
SD :	2.30	%	Max :	12.17	kN	Punch NO.;	32
Filling Depth :	Increase ; 129	Times	Decrease ;	115	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.06	mm	Main Thickness ;	3.07	mm
Filling Depth :	7.12	mm	Current Cam :	Cam C	
Main Air pressure :	0.744	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	12
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	12
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4130318	Tablets			
A.W.C Counter :	4124639	Tablets			
HEP :	275 (0.0%)	Tablets	LEP :	1060 (0.0%)	Tablets
GOOD :	4123304 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	23 Hour 07 Min 10 Sec
Total Counter :	4130318	Total Running Time :	3348 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.36	kN	No		
HEP :	25.0 %	14.77	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.05	kN	Yes 15	Times	
Ref :		11.81	kN			
LCP :	2.0 %	11.58	kN	Yes 15	Times	
LEP :	25.0 %	8.86	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.67	kN	Punch NO.;	36
SD :	4.40	%	Max :	2.12	kN	Punch NO.;	21
Mean Main Pressure :	12.12	kN	Min :	11.19	kN	Punch NO.;	36
SD :	4.50	%	Max :	14.44	kN	Punch NO.;	21
Filling Depth :	Increase ;	561	Times	Decrease ;	556	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.21	mm	Main Thickness ;	3.22	mm
Filling Depth :	7.12	mm	Current Cam :	Cam C	
Main Air pressure :	0.744	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	12
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	12
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4130318	Tablets			
A.W.C Counter :	4124639	Tablets			
HEP :	275 (0.0%)	Tablets	LEP :	1060 (0.0%)	Tablets
GOOD :	4123304 (100.0%)	Tablets			