

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2504450
Print Interval :	50000 Tablets	Running Time :	15 Hour 18 Min 09 Sec
Total Counter :	2413868	Total Running Time :	3365 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	118	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.78	kN	No		
HEP :	25.0 %	17.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.95	kN	Yes 15	Times	
Ref :		13.68	kN			
LCP :	2.0 %	13.41	kN	Yes 15	Times	
LEP :	25.0 %	10.26	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.20	kN	Min :	1.10	kN	Punch NO.;	4
SD :	4.40	%	Max :	1.35	kN	Punch NO.;	44
Mean Main Pressure :	13.72	kN	Min :	12.71	kN	Punch NO.;	12
SD :	3.40	%	Max :	15.06	kN	Punch NO.;	44
Filling Depth :	Increase ; 32	Times	Decrease ;	73	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	2.96	mm
Filling Depth :	7.43	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.24	kN	Max Punch ;	22
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.21	kN	Max Punch ;	37
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2413868	Tablets			
A.W.C Counter :	2405861	Tablets			
HEP :	83 (0.0%)	Tablets	LEP :	273 (0.0%)	Tablets
GOOD :	2405505 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2504450
Print Interval :	50000 Tablets	Running Time :	15 Hour 18 Min 09 Sec
Total Counter :	2413868	Total Running Time :	3365 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.81	kN	No		
HEP :	25.0 %	19.05	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.54	kN	Yes 15	Times	
Ref :		15.24	kN			
LCP :	2.0 %	14.93	kN	Yes 15	Times	
LEP :	25.0 %	11.43	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.67	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.82	kN	Min :	1.69	kN	Punch NO.;	20
SD :	3.10	%	Max :	2.04	kN	Punch NO.;	10
Mean Main Pressure :	15.33	kN	Min :	13.98	kN	Punch NO.;	12
SD :	3.90	%	Max :	16.77	kN	Punch NO.;	8
Filling Depth :	Increase ;	109	Times	Decrease ;	118	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.06	mm
Filling Depth :	7.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.24	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.21	kN	Max Punch ;	37
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2413868	Tablets			
A.W.C Counter :	2405861	Tablets			
HEP :	83 (0.0%)	Tablets	LEP :	273 (0.0%)	Tablets
GOOD :	2405505 (100.0%)	Tablets			