

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2504550
Print Interval :	50000 Tablets	Running Time :	11 Hour 18 Min 02 Sec
Total Counter :	1800850	Total Running Time :	3389 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	118	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.96	kN	No		
HEP :	25.0 %	16.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.31	kN	Yes 15	Times	
Ref :		13.05	kN			
LCP :	2.0 %	12.79	kN	Yes 15	Times	
LEP :	25.0 %	9.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.42	kN	Min :	1.25	kN	Punch NO.;	53
SD :	5.60	%	Max :	1.71	kN	Punch NO.;	42
Mean Main Pressure :	13.21	kN	Min :	11.95	kN	Punch NO.;	53
SD :	4.20	%	Max :	15.20	kN	Punch NO.;	42
Filling Depth :	Increase ; 457	Times	Decrease ;	557	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	2.96	mm
Filling Depth :	7.49	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.747	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.27	kN	Max Punch ;	37
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1800850	Tablets			
A.W.C Counter :	1796101	Tablets			
HEP :	574 (0.0%)	Tablets	LEP :	720 (0.0%)	Tablets
GOOD :	1794807 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2504550
Print Interval :	50000 Tablets	Running Time :	11 Hour 18 Min 02 Sec
Total Counter :	1800850	Total Running Time :	3389 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.73	kN	No		
HEP :	25.0 %	17.05	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.91	kN	Yes 15	Times	
Ref :		13.64	kN			
LCP :	2.0 %	13.37	kN	Yes 15	Times	
LEP :	25.0 %	10.23	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.55	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.84	kN	Min :	1.73	kN	Punch NO.;	12
SD :	3.30	%	Max :	2.03	kN	Punch NO.;	10
Mean Main Pressure :	13.95	kN	Min :	12.88	kN	Punch NO.;	12
SD :	4.40	%	Max :	15.56	kN	Punch NO.;	10
Filling Depth :	Increase ;	813	Times	Decrease ;	790	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.07	mm	Main Thickness ;	3.08	mm
Filling Depth :	7.31	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.747	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.28	kN	Max Punch ;	37
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1800850	Tablets			
A.W.C Counter :	1796101	Tablets			
HEP :	574 (0.0%)	Tablets	LEP :	720 (0.0%)	Tablets
GOOD :	1794807 (99.9%)	Tablets			