

Template for XCPC

SUNCHAOYI

2025-2026

Contents

1	Compile	3
1.1	Fast I/O	3
1.2	Run.bash	3
1.3	Run.ps1	3
2	Graph	4
2.1	Diameter of a Tree	4
2.2	Centroid of a Tree	4
2.3	Minimum Spanning Tree	5
2.3.1	Prim	5
2.3.2	Kruskal	5
2.4	LCA	6
2.5	Topological Sorting	6
2.6	Shortest Path	7
2.6.1	Dijkstra	7
2.6.2	SPFA	7
2.7	Tarjan	8
2.8	Bipartite Graph Matchings	9
2.9	Flow	9
2.9.1	Edmonds–Karp	9
2.9.2	Dinic	10
3	Data Structure	12
3.1	Segment Tree	12
3.2	Fenwick Tree	12
3.3	Heavy-Light Decomposition	12
3.4	Splay Tree	12
3.5	Sparse Table	12
3.6	Persistent Data Structure	12
3.7	Linear-Basis	12
4	Math	13
4.1	Elementary Arithmetic Bucket	13
4.2	Combination	13
4.3	The Sieve of Primes	14
4.4	exgcd	14
4.5	Möbius Inversion	14
4.6	Gaussian Elimination	14
4.7	Euler’s Totient Function	14
4.8	FFT	14
5	Computational Geometry	14
5.1	Computation Geometry Bucket	16

6	String	17
6.1	Hash	17
6.2	KMP	17
6.3	Manacher	17
6.4	Trie	17
6.4.1	Trie	17
6.4.2	01-Trie	17
6.5	Aho-Corasick Automaton	18
6.6	SA/SAM	18
6.7	Border/Fail Tree	18

1 Compile

1.1 Fast I/O

```
#include <bits/stdc++.h>
#define init(x) memset (x,0,sizeof (x))
#define ll long long
#define ull unsigned long long
#define INF 0x3f3f3f3f
#define pii pair <int,int>
using namespace std;
const int MAX = 1e5 + 5;
const int MOD = 1e9 + 7;
char s[200];
inline int read ();
inline void output ();
int main ()
{
    //freopen (".in","r",stdin);
    //freopen (".out","w",stdout);
    return 0;
}
inline int read ()
{
    int s = 0;int f = 1;
    char ch = getchar ();
    while ((ch < '0' || ch > '9') && ch != EOF)
    {
        if (ch == '-') f = -1;
        ch = getchar ();
    }
    while (ch >= '0' && ch <= '9')
    {
        s = s * 10 + ch - '0';
        ch = getchar ();
    }
    return s * f;
}
inline void output (int x)
{
    if (x < 0) putchar ('-');
    x = (x > 0) ? x : -x;
    int cnt = 0;
    while (x)
    {
        s[cnt++] = x % 10 + '0';
        x /= 10;
    }
    while (cnt) putchar (s[--cnt]);
}
```

1.2 Run.bash

```
#!/bin/bash
g++ -std=c++17 -O2 -Wall "$1" -o main
./main < in.txt > out.txt
```

1.3 Run.ps1

```
# Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass
# new file : 'type nul > filename.cpp'
# run : '.\run.ps1 filename.cpp'
g++ -std=c++17 -O2 -Wall $args[0] -o main
cat in.txt | .\main | Out-File -FilePath out.txt
```

2 Graph

2.1 Diameter of a Tree

```
template <typename T>
class Diameter
{
    int n,p;
    vector <T> dis;
    vector <vector <pair <int,T>>> ve;
    void dfs (int u,int fa)
    {
        for (const auto& [v,w] : ve[u])
        {
            if (v == fa) continue;
            dis[v] = dis[u] + w;
            if (dis[v] > dis[p]) p = v;
            dfs (v,u);
        }
    }

public:
    Diameter (int n) : n(n),ve(n + 1) {}
    void add (int u,int v,T w = 1) {ve[u].push_back ({v,w});ve[v].push_back ({u,w});}
    T calc ()
    {
        dis.assign (n + 1,0);
        p = 1;dfs (1,0);
        dis[p] = 0;dfs (p,0);
        return dis[p];
    }
};
```

2.2 Centroid of a Tree

```
class Centroid
{
    int n;
    vector <int> sz,w,cen;
    vector <vector <int>> ve;
    void dfs (int u,int fa)
    {
        sz[u] = 1;w[u] = 0;
        for (auto v : ve[u])
        {
            if (v == fa) continue;
            dfs (v,u);
            sz[u] += sz[v];
            w[u] = max (w[u],sz[v]);
        }
        w[u] = max (w[u],n - sz[u]);
        if (w[u] <= n / 2) cen.push_back (u);
    }

public:
    Centroid (int n) : n(n),ve (n + 1),sz (n + 1),w (n + 1) {}
    void add (int u,int v) {ve[u].push_back (v);ve[v].push_back (u);}
    vector <int> calc ()
    {
        cen.clear ();
        dfs (1, 0);
        sort (cen.begin (),cen.end ());
    }
};
```

```

        return cen;
    }
};

```

2.3 Minimum Spanning Tree

2.3.1 Prim

```

template <typename T>
class MST
{
    int n;T ans;
    vector <int> vis;
    vector <vector <int>> g;
    vector <T> dis;

public :
    MST (int n) : n (n),vis (n + 1,0),g (n + 1,vector <int> (n + 1,INF)),dis (n + 1,INF) {dis[1] = ans = 0;vis[1] = 1;}
    void add (int u,int v,T w) {g[u][v] = g[v][u] = w;}
    T calc ()
    {
        for (int i = 2;i <= n;++i) dis[i] = g[1][i];
        for (int i = 1;i < n;++i)
        {
            int k = 0;
            for (int j = 1;j <= n;++j)
                if (!vis[j] && dis[j] < dis[k]) k = j;
            vis[k] = 1;
            ans += dis[k];
            for (int j = 1;j <= n;++j)
                if (!vis[j] && g[k][j] < dis[j]) dis[j] = g[k][j];
        }
        return ans;
    }
};

```

2.3.2 Kruskal

```

template <typename T>
class MST
{
    int n,m,e_cnt,cnt;T ans;
    struct node
    {
        int u,v;T w;
    };
    vector <int> fa;
    vector <node> g;
public:
    MST (int n,int m) : n (n),m(m),fa (n + 1,0),g (m + 1) {cnt = e_cnt = ans = 0;}
    void add (int u,int v,int w) {g[++e_cnt].u = u,g[e_cnt].v = v,g[e_cnt].w = w;}
    int getfa (int u) {return fa[u] == u ? u : fa[u] = getfa (fa[u]);}
    T calc ()
    {
        sort (g.begin (),g.end (),[] (auto &x,auto &y) {return x.w < y.w;});
        for (int i = 1;i <= n;++i) fa[i] = i;
        for (int i = 1;cnt < n && i <= m;++i)
        {
            int dx = getfa (g[i].u),dy = getfa (g[i].v);
            if (dx == dy) continue;
            ans += g[i].w;fa[dx] = dy;++cnt;
        }
    }
};

```

```

    }
    return ans;
}
};

```

2.4 LCA

```

class LCA
{
    static constexpr int lg = 20;
    int n;
    vector<int> dep;
    vector<vector<int>> f, ve;

public:
    LCA (int n) : n (n), ve (n + 1), dep (n + 1), f (n + 1, vector<int> (lg + 1, 0))
    {}
    void add (int u, int v) {ve[u].push_back (v); ve[v].push_back (u);}
    void pre (int u, int fa)
    {
        f[u][0] = fa; dep[u] = dep[fa] + 1;
        for (int i = 0; i < lg; ++i) f[u][i + 1] = f[f[u][i]][i];
        for (auto v : ve[u])
            if (v != fa) pre (v, u);
    }
    int query (int u, int v)
    {
        if (dep[u] < dep[v]) swap (u, v);
        for (int i = lg; ~i; --i)
        {
            if (dep[f[u][i]] >= dep[v]) u = f[u][i];
            if (u == v) return u;
        }
        for (int i = lg; ~i; --i)
            if (f[u][i] != f[v][i]) u = f[u][i], v = f[v][i];
        return f[u][0];
    }
};

```

2.5 Topological Sorting

```

class Topo
{
    int n;
    vector<int> deg;
    vector<vector<int>> ve;

public:
    Topo (int n) : n (n), ve (n + 1), deg (n + 1, 0) {}
    void add (int u, int v)
    {
        ve[u].push_back (v);
        ++deg[v];
    }
    vector<int> calc ()
    {
        queue<int> q;
        vector<int> lst;
        for (int i = 1; i <= n; ++i)
            if (!deg[i]) q.push (i);
        while (!q.empty ())
        {
            int u = q.front (); q.pop ();
            lst.push_back (u);

```

```

        for (auto v : ve[u])
        {
            --deg[v];
            if (!deg[v]) q.push (v);
        }
    }
    return lst;
}
};

```

2.6 Shortest Path

2.6.1 Dijkstra

```

class dijkstra
{
    int n,m,cnt;
    vector <int> head,to,nxt,val,vis;
    vector <ll> dis;

public:
    dijkstra (int n,int m) :
        n (n),m (m),vis (n + 1,0),head (n + 1,0),dis (n + 1,INF),
        to (2 * m + 1,0),nxt (2 * m + 1,0),val (2 * m + 1,0) {cnt = 0;}
    void add (int u,int v,int w)
    {
        to[++cnt] = v;val[cnt] = w;nxt[cnt] = head[u];head[u] = cnt;
        to[++cnt] = u;val[cnt] = w;nxt[cnt] = head[v];head[v] = cnt;
    }
    vector <ll> calc (int s)
    {
        priority_queue <pii> q;
        for (int i = 1;i <= n;++i) vis[i] = 0,dis[i] = INF;
        q.push ({0,s});
        dis[s] = 0;
        while (!q.empty ())
        {
            int u = q.top ().second;q.pop ();
            if (vis[u]) continue;
            vis[u] = 1;
            for (int i = head[u];i;i = nxt[i])
            {
                int v = to[i];
                if (dis[v] > dis[u] + val[i])
                {
                    dis[v] = dis[u] + val[i];
                    q.push ({-dis[v],v});
                }
            }
        }
        return dis;
    }
};

```

2.6.2 SPFA

```

class SPFA
{
    int n,m,cnt;
    vector <int> head,to,nxt,val,vis,times;
    vector <ll> dis;

public:
    SPFA (int n,int m) :

```

```

    n (n),m (m),times (n + 1,0),vis (n + 1,0),head (n + 1,0),dis (n + 1,INF),
    to (2 * m + 1,0),nxt (2 * m + 1,0),val (2 * m + 1,0) {cnt = 0;}
void add (int u,int v,int w)
{
    to[++cnt] = v;val[cnt] = w;nxt[cnt] = head[u];head[u] = cnt;
    to[++cnt] = u;val[cnt] = w;nxt[cnt] = head[v];head[v] = cnt;
}
vector <ll> calc (int s)
{
    queue <int> q;
    for (int i = 1;i <= n;++i) vis[i] = 0,dis[i] = INF;
    dis[s] = 0,vis[s] = 1;q.push (s);
    while (!q.empty())
    {
        int u = q.front ();
        q.pop (),vis[u] = 0;
        for (int i = head[u];i;i = nxt[i])
        {
            int v = to[i];
            if (dis[v] > dis[u] + val[i])
            {
                dis[v] = dis[u] + val[i];
                times[v] = times[u] + 1;
                if (times[v] >= n) return {-1};//Negative Cycle
                if (!vis[v]) q.push (v),vis[v] = 1;
            }
        }
    }
    return dis;
}
};

```

2.7 Tarjan

```

class Tarjan
{
    int n,m,cnt,times,scc_cnt;
    vector <int> head,to,nxt,low,scc,dfn;
    stack <int> s;
    void tarjan (int u)
    {
        low[u] = dfn[u] = ++times;
        s.push (u);
        for (int i = head[u];i;i = nxt[i])
        {
            int v = to[i];
            if (!dfn[v])
            {
                tarjan (v);
                low[u] = min (low[u],low[v]);
            }
            else if (!scc[v]) low[u] = min (low[u],dfn[v]);
        }
        if (low[u] == dfn[u])
        {
            ++scc_cnt;
            while (1)
            {
                int x = s.top ();s.pop ();
                scc[x] = scc_cnt;
                if (x == u) break;
            }
        }
    }
}

```



```

public:
Tarjan (int n,int m) :
    n (n),m (m),head (n + 1,0),low (n + 1,0),dfn (n + 1,0),scc (n + 1,0),
    to (2 * m + 1,0),nxt (2 * m + 1,0) {cnt = times = scc_cnt = 0;}
void add (int u,int v) // Note that the bidirectional edges
{
    to[++cnt] = v;nxt[cnt] = head[u];head[u] = cnt;
    to[++cnt] = u;nxt[cnt] = head[v];head[v] = cnt;
}
vector <int> calc ()
{
    for (int i = 1;i <= n;++i)
        if (!dfn[i]) tarjan (i);
    return scc;
}
};

```

2.8 Bipartite Graph Matchings

```

class Matching
{
    int l,r;//the number of left/right side points
    vector <vector <int>> ve;
    vector <int> vis,op;
    bool dfs (int u)
    {
        for (auto v : ve[u])
        {
            if (vis[v]) continue;
            vis[v] = 1;
            if (!op[v] || dfs (op[v])) {op[v] = u;return true;}
        }
        return false;
    }

public:
Matching (int l,int r) : l (l),r (r),vis (r + 1,0),op (r + 1,0),ve (l + 1) {}
void add (int u,int v) {ve[u].push_back (v);}
int calc ()
{
    int ans = 0;
    for (int i = 1;i <= l;++i)
    {
        vis.assign (r + 1,0);
        if (dfs (i)) ++ans;
    }
    return ans;
}
};

```

2.9 Flow

2.9.1 Edmonds–Karp

```

template <typename T>
class EK
{
    int n,m,s,t,cnt;
    vector <int> head,to,nxt,vis,pre,edge;
    vector <T> val;
    bool bfs ()
    {
        queue <T> q;

```

```

    for (int i = 1; i <= n; ++i) vis[i] = 0, pre[i] = edge[i] = -1;
    vis[s] = 1; q.push (s);
    while (!q.empty ())
    {
        int u = q.front (); q.pop ();
        for (int i = head[u]; i; i = nxt[i])
        {
            int v = to[i];
            if (!vis[v] && val[i])
            {
                pre[v] = u; edge[v] = i; vis[v] = 1;
                q.push (v);
                if (v == t) return 1;
            }
        }
    }
    return 0;
}

public :
EK (int n, int m, int s, int t) :
    n (n), m (m), s (s), t (t),
    vis (n + 1, 0), head (n + 1, 0), pre (n + 1, -1), edge (n + 1, -1),
    to (m + 1, 0), nxt (m + 1, 0), val (m + 1, 0) {cnt = 1;}
void add (int u, int v, T w)
{
    to[++cnt] = v; val[cnt] = w; nxt[cnt] = head[u]; head[u] = cnt;
    to[++cnt] = u; val[cnt] = 0; nxt[cnt] = head[v]; head[v] = cnt;
}
T calc ()
{
    T ans = 0;
    while (bfs ())
    {
        T mn = INF;
        for (int i = t; i != s; i = pre[i]) mn = min (mn, val[edge[i]]);
        for (int i = t; i != s; i = pre[i]) val[edge[i]] -= mn, val[edge[i]] ^= 1;
        ans += mn;
    }
    return ans;
}
};

```

2.9.2 Dinic

```

template <typename T>
class Dinic
{
    int n, m, s, t, cnt;
    vector <int> head, to, nxt, cur, dep;
    vector <T> val;
    int bfs ()
    {
        for (int i = 0; i <= n; ++i) dep[i] = 0, cur[i] = head[i];
        queue <int> q;
        q.push (s), dep[s] = 1;
        while (!q.empty ())
        {
            int u = q.front (); q.pop ();
            for (int i = head[u]; i; i = nxt[i])
            {
                int v = to[i];
                if (val[i] && !dep[v]) q.push (v), dep[v] = dep[u] + 1;
            }
        }
    }
};

```

```

    }
}
return dep[t];
}
T dfs (int u,int t,T flow)
{
    if (u == t) return flow;
    T ans = 0;
    for (int &i = cur[u];i && ans < flow;i = nxt[i])
    {
        int v = to[i];
        if (val[i] && dep[v] == dep[u] + 1)
        {
            int x = dfs (v,t,min (val[i], flow - ans));
            if (x) val[i] -= x,val[i ^ 1] += x,ans += x;
        }
    }
    if (ans < flow) dep[u] = -1;
    return ans;
}

public :
Dinic (int n,int m,int s,int t) :
    n (n),m (m),s (s),t (t),
    head (n + 1,0),cur (n + 1,0),dep (n + 1,0),
    to (m + 1,0),nxt (m + 1,0),val (m + 1,0) {cnt = 1;}
void add (int u,int v,T w)
{
    to[++cnt] = v;val[cnt] = w;nxt[cnt] = head[u];head[u] = cnt;
    to[++cnt] = u;val[cnt] = 0;nxt[cnt] = head[v];head[v] = cnt;
}
T calc ()
{
    T ans = 0;
    while (bfs ())
    {
        T x;
        while ((x = dfs (s,t,INF))) ans += x;
    }
    return ans;
}
};

```

3 Data Structure

3.1 Segment Tree

3.2 Fenwick Tree

3.3 Heavy-Light Decomposition

3.4 Splay Tree

3.5 Sparse Table

3.6 Persistent Data Structure

3.7 Linear-Basis

```
template <typename T>
class Basis
{
    int n,lg;
    vector <T> p;
public :
    Basis (int n,int lg) : n (n),lg (lg),p (lg + 2,0) {}
    void modify (T x)
    {
        for (int i = lg - 1;~i;--i)
        {
            if (!(1ll << i) & x) continue;
            if (!p[i]) {p[i] = x;break;}
            else x ^= p[i];
        }
    }
    T query ()
    {
        T ans = 0;
        for (int i = lg - 1;~i;--i)
            if ((ans ^ p[i]) > ans) ans ^= p[i];
        return ans;
    }
};
```

4 Math

4.1 Elementary Arithmetic Bucket

```
template <typename T,int MOD = 1000000007>
class Z
{
    T x;
    Z <T,MOD> qpow (Z x,T y)
    {
        Z <T,MOD> res (1);
        while (y)
        {
            if (y & 1) res *= x;
            x *= x;
            y >>= 1;
        }
        return res;
    }
public :
    Z () : x(0) {}
    Z (T x) : x (x) {}
    Z & operator = (T o) {x = o;return *this;}
    Z & operator += (Z o) {x = (x + o.x + MOD) % MOD;return *this;}
    Z & operator -= (Z o) {x = (x - o.x + MOD) % MOD;return *this;}
    Z & operator *= (Z o) {x = 1ll * o.x * x % MOD;return *this;}
    Z & operator ^= (Z o) {x = qpow (x,o.x).x;return *this;}
    Z & operator /= (Z o) {*this *= o ^ (MOD - 2);return *this;}
    friend Z operator + (Z x,Z y) {return x += y;}
    friend Z operator - (Z x,Z y) {return x -= y;}
    friend Z operator * (Z x,Z y) {return x *= y;}
    friend Z operator / (Z x,Z y) {return x /= y;}
    friend Z operator ^ (Z x,Z y) {return x ^= y;}
    friend bool operator == (Z x,Z y) {return x.x == y.x;}
    friend bool operator != (Z x,Z y) {return x.x != y.x;}
    friend istream& operator >> (istream& is, Z& o) {T val;is >> val;o = Z(val);
        return is;}
    friend ostream& operator << (ostream &os, const Z &z) {return os << z.x;}
};
```

4.2 Combination

```
template <typename T,int MOD = 1000000007>
class COM
{
    int n;
    vector <Z <T,MOD>> fac,inv;
public :
    COM (int n) : n (n),fac (n + 1),inv (n + 1)
    {
        fac[0] = inv[0] = 1;
        for (int i = 1;i <= n;++i) fac[i] = fac[i - 1] * Z <T,MOD> (i);
        inv[n] = fac[n] ^ (MOD - 2);
        for (int i = n - 1;i >= 0;--i) inv[i] = inv[i + 1] * Z <T,MOD> (i + 1);
    }
    Z <T,MOD> f (int x) {return fac[x];}
    Z <T,MOD> inv_f (int x) {return inv[x];}
    Z <T,MOD> comb (int x,int y)
    {
        if (y < 0 || y > x) return Z <T,MOD> (0);
        else return fac[x] * inv[x - y] * inv[y];
    }
    Z <T,MOD> arr (int x,int y)
```

```

{
    if (y > x) return Z <T,MOD> (0);
    else return fac[x] * inv[x - y];
}
};

```

4.3 The Sieve of Primes

4.4 exgcd

4.5 Möbius Inversion

4.6 Gaussian Elimination

4.7 Euler's Totient Function

4.8 FFT

5 Computational Geometry

```

const double eps = 1e-8;
int dcmp (double x) {return x < -eps ? -1 : (x > eps ? 1 : 0);}
struct Point
{
    double x,y;
    Point (double x = 0,double y = 0) : x (x),y (y) {}
    bool operator == (const Point& p) const {return dcmp (x - p.x) == 0 && dcmp (
        y - p.y) == 0;}
};
typedef Point Vector;
Vector operator + (Vector A,Vector B) {return Vector (A.x + B.x,A.y + B.y);}
Vector operator - (Vector A,Vector B) {return Vector (A.x - B.x,A.y - B.y);}
Vector operator * (Vector A,double k) {return Vector (A.x * k,A.y * k);}
Vector operator / (Vector A,double k) {return Vector (A.x / k,A.y / k);}

double dot (Vector A,Vector B) {return A.x * B.x + A.y * B.y;}
double dis (Point A,Point B) {return sqrt ((A.x - B.x) * (A.x - B.x) + (A.y - B.y
) * (A.y - B.y));}
double cross (Vector A,Vector B) {return A.x * B.y - A.y * B.x;} // A -> B
counter-clockwise if cross (A,B) > 0
double len (Point A) {return sqrt (A.x * A.x + A.y * A.y);}
double angle (Vector A,Vector B) {return acos (dot (A,B) / (len (A) * len (B)));}
Vector proj (Vector A,Vector B) {return A * (dot (A,B) / dot (A,A));} //project
onto A
Point foot (Point P,Point A,Point B) {Vector AP = P - A,AB = B - A;return A +
    proj (AB,AP);} //foot
Point reflect (Point P,Point A,Point B) {Point F = foot (P,A,B);return F * 2 - P
    ;} //symmetry point
Point rotate (Point P,double theta) {return (Point){P.x * cos (theta) - P.y * sin
    (theta),P.x * sin (theta) + P.y * cos (theta)};}
bool on_line (Point P,Point A,Point B) {return dcmp (cross (P - A,B - A)) == 0;}
bool on_seg (Point P,Point A,Point B) {return on_line (P,A,B) && dcmp (dot (P - A
    ,P - B)) <= 0;} //judge whether on segment AB
double dis_seg (Point P,Point A,Point B)
{
    if (dcmp (dot (B - A,P - A)) < 0) return dis (P,A);
    if (dcmp (dot (A - B,P - B)) < 0) return dis (P,B);
    return fabs (cross (P - A,P - B)) / dis (A,B);
}
Point inter (Point A,Point B,Point C,Point D) {return A + (B - A) * cross (C - A,
    D - C) / cross (B - A,D - C);}
bool pd_ll_inter (Point A,Point B,Point C,Point D) {return dcmp (cross (B - A,D -
    C)) != 0;} // line - line

```

```

bool pd_ls_inter (Point A,Point B,Point C,Point D) {return on_line (inter (A,B,C,
D),C,D);} //The intersection of AB(line) and CD (line) is on the CD (seg).
bool pd_ss_inter (Point A,Point B,Point C,Point D) // seg - seg
{
    double c1 = cross (B - A,C - A),c2 = cross (B - A,D - A);
    double d1 = cross (D - C,A - C),d2 = cross (D - C,B - C);
    if (dcmp (c1) * dcmp (c2) < 0 && dcmp (d1) * dcmp (d2) < 0) return true;
    if (dcmp(c1) == 0 && on_seg (C,A,B)) return true;
    if (dcmp(c2) == 0 && on_seg (D,A,B)) return true;
    if (dcmp(d1) == 0 && on_seg (A,C,D)) return true;
    if (dcmp(d2) == 0 && on_seg (B,C,D)) return true;
    return false;
}

double area (vector <Point> P)
{
    int n = P.size ();
    double res = 0;
    for (int i = 0;i < n;++i) res += cross (P[i],P[(i + 1) % n]);
    return res / 2.0;
}

bool is_convex (vector <Point> P)
{
    int n = P.size ();
    for(int i = 0;i < n - 1;++i)
        if (dcmp (cross (P[i + 1] - P[i],P[(i + 2) % n] - P[i])) < 0) return
            false;
    return true;
}

int in_Poly (vector <Point> P,Point A)
{
    int cnt = 0,n = P.size ();
    for (int i = 0;i < n;++i)
    {
        int j = (i + 1) % n;
        if (on_seg (A,P[i],P[j])) return 2;// on the edge
        if (A.y >= min (P[i].y,P[j].y) && A.y < max (P[i].y,P[j].y)) // the
            intersection is on the right
            cnt += dcmp (((A.y - P[i].y) * (P[j].x - P[i].x) / (P[j].y - P[i].y)
                + P[i].x) - A.x) > 0;
    }
    return cnt & 1;
}

vector <Point> convex_hull (vector <Point> P) // Non-strict convex hull
{
    int n = P.size ();
    sort (P.begin (),P.end (),[](Point &x,Point &y) {return x.x == y.x ? x.y < y.
        y : x.x < y.x;});
    vector <Point> hull;
    hull.resize (2 * n + 1);
    int k = 0;
    for (int i = 0;i < n;++i)
    {
        while (k >= 1 && dcmp (cross (hull[k - 1] - hull[k - 2],P[i] - hull[k -
            2])) < 0) --k;
        hull[k++] = P[i];
    }
    for (int i = n - 2,t = k;i >= 0;--i)
    {
        while (k > t && dcmp (cross (hull[k - 1] - hull[k - 2],P[i] - hull[k -
            2])) < 0) --k;
        hull[k++] = P[i];
    }
}

```

```

        hull.resize (k - 1);
        return hull;
    }
    double diameter (vector <Point> P)
    {
        int n = P.size ();
        if (n <= 1) return 0;
        if (n == 2) return len (P[1] - P[0]);
        double res = 0;
        for (int i = 0, j = 2; i < n; ++i)
        {
            while (dcmp (cross (P[(i + 1) % n] - P[i], P[j] - P[i]) - cross (P[(i + 1) % n] - P[i], P[(j + 1) % n] - P[i])) <= 0) j = (j + 1) % n;
            res = max (res, max (len (P[j] - P[i]), len (P[j] - P[(i + 1) % n])));
        }
        return res;
    }
}

```

5.1 Computation Geometry Bucket

6 String

6.1 Hash

6.2 KMP

6.3 Manacher

6.4 Trie

6.4.1 Trie

```
struct Trie
{
    int n,m,cnt;//m total len
    vector <vector <int>> ch;
    vector <int> vis;
    public :
    Trie (int n,int m) : n (n),m (m),ch (m,vector <int> (26,0)),vis (n) {cnt = 0;}
    void insert (char *s)
    {
        int u = 1,len = strlen (s + 1);
        for (int i = 1;i <= len;++i)
        {
            int c = s[i] - 'a';
            if (!ch[u][c]) ch[u][c] = ++cnt;
            u = ch[u][c];
        }
        ++vis[u];
    }
    int query (char *s)
    {
        int u = 1,len = strlen (s + 1);
        for (int i = 1;i <= len;++i)
        {
            int c = s[i] - 'a';
            if (!ch[u][c]) return 0;
            u = ch[u][c];
        }
        return vis[u];
    }
};
```

6.4.2 01-Trie

```
class Trie
{
    int n,cnt;
    vector <vector <int>> ch;
    vector <int> val,w;
    public :
    Trie (int n,int lg) : n (n),val (2 * lg * n + 1,0),w (2 * lg * n + 1,0),ch (2 * lg * n + 1,vector <int> (2,0)) {cnt = 1;}
    void pushup (int u)
    {
        w[u] = val[u] = 0;
        //w[u] Number of values (weights) on the edge between node u and its
        //parent node
        //val[u] XOR sum maintained by the subtree rooted at u
        if (ch[u][0]) w[u] ^= w[ch[u][0]],val[u] ^= val[ch[u][0]] << 1;
        if (ch[u][1]) w[u] ^= w[ch[u][1]],val[u] ^= (val[ch[u][1]] << 1) | w[ch[u][1]];
    }
};
```

```

void modify (int &u,int v,int dep)
{
    if (!u) u = ++cnt;
    w[u] ^= 1;
    if (dep < 0) return ;
    modify (ch[u][v & 1],v >> 1,dep - 1);
    pushup (u);
}
void erase (int u,int v,int dep)
{
    if (!u) return ;
    w[u] ^= 1;
    if (dep < 0) return ;
    erase (ch[u][v & 1],v >> 1,dep - 1);
    pushup (u);
}
void add (int u) // add 1 in [1,n]
{
    swap (ch[u][0],ch[u][1]);
    if (ch[u][0]) add (ch[u][0]);
    pushup (u);
}
};

```

6.5 Aho-Corasick Automaton

6.6 SA/SAM

6.7 Border/Fail Tree