



Template for XCPC

Dft Fan Club

2025 ~ 2026	Verifying We Are Human.	Chaoyi Sun, Liwen Zhang, Tian Zhou
2026 ~ 2027	Human verification passed.	Chaoyi Sun, Liwen Zhang, Fengting Deng

Contents

1	Graph	1
1.1	Diameter of a Tree	1
1.2	Centroid of a Tree	1
1.3	Minimum Spanning Tree	1
1.3.1	Prim	1
1.3.2	Kruskal	1
1.4	LCA	1
1.5	Topological Sorting	1
1.6	Shortest Path	2
1.6.1	Dijkstra	2
1.6.2	SPFA	2
1.7	DCC	2
1.8	Tarjan	2
1.9	Bipartite Graph Matchings	3
1.10	Flow	3
1.10.1	Edmonds-Karp	3
1.10.2	Dinic	3
2	Data Structure	5
2.1	Segment Tree	5
2.2	Fenwick Tree	5
2.3	Heavy-Light Decomposition	5
2.4	Treap	5
2.5	Cartesian Tree	6
2.6	Sparse Table	6
2.7	Persistent Data Structure	6
2.8	Linear-Basis	6
3	Math	8
3.1	Subset Enumeration	8
3.2	Elementary Arithmetic Bucket	8
3.3	Fraction	8
3.4	Combination	8
3.5	The Sieve of Primes & Euler's Totient Function & Möbius Function	8
3.6	Exgcd	8
3.7	CRT	8
3.8	Lagrange Interpolation	9
3.9	Gaussian Elimination	9
3.10	FFT	9
3.11	NTT	9
3.12	FWT	10
4	Computational Geometry	11
5	String	13
5.1	Hash	13
5.2	KMP	13
5.3	Manacher	13
5.4	Trie	13
5.4.1	Trie	13
5.4.2	01-Trie	13
5.5	Aho-Corasick Automaton	13
5.6	SA	14
5.7	SAM	14
6	Other	15
6.1	Fast I/O	15
6.2	Random Number Generator	15
6.3	Execution	15
6.4	Comparsion	15
6.5	Python	15

1 Graph

1.1 Diameter of a Tree

```

1 template <typename T>
2 class Diameter
3 {
4     int n, p;
5     vector<T> dis;
6     vector<vector<pair<int, T>>> ve;
7     void dfs(int u, int fa)
8     {
9         for (const auto& [v, w] : ve[u])
10        {
11            if (v == fa) continue;
12            dis[v] = dis[u] + w;
13            if (dis[v] > dis[p]) p = v;
14            dfs(v, u);
15        }
16    }
17 public:
18     Diameter(int n) : n(n), ve(n + 1) {}
19     void add(int u, int v, T w = 1) {ve[u].push_back({v, w}); ve[v].
20         push_back({u, w});}
21     T calc()
22     {
23         dis.assign(n + 1, 0);
24         p = 1; dfs(1, 0);
25         dis[p] = 0; dfs(p, 0);
26         return dis[p];
27     }
28 };

```

1.2 Centroid of a Tree

```

1 class Centroid
2 {
3     int n;
4     vector<int> sz, w, cen;
5     vector<vector<int>> ve;
6     void dfs(int u, int fa)
7     {
8         sz[u] = 1; w[u] = 0;
9         for (auto v : ve[u])
10        {
11            if (v == fa) continue;
12            dfs(v, u);
13            sz[u] += sz[v];
14            w[u] = max(w[u], sz[v]);
15        }
16        w[u] = max(w[u], n - sz[u]);
17        if (w[u] <= n / 2) cen.push_back(u);
18    }
19 public:
20     Centroid(int n) : n(n), ve(n + 1), sz(n + 1), w(n + 1) {}
21     void add(int u, int v) {ve[u].push_back(v); ve[v].push_back(u);}
22     auto calc()
23     {
24         cen.clear();
25         dfs(1, 0);
26         sort(cen.begin(), cen.end());
27         return cen;
28     }
29 };

```

1.3 Minimum Spanning Tree

1.3.1 Prim

```

1 template <typename T>
2 class MST
3 {
4     int n; T ans;
5     vector<int> vis; vector<vector<int>> g; vector<T> dis;
6     public:
7     MST(int n) : n(n), vis(n + 1, 0), g(n + 1, vector<int>(n + 1, INF))
8         , dis(n + 1, INF) {dis[1] = ans = 0; vis[1] = 1;}
9     void add(int u, int v, T w) {g[u][v] = g[v][u] = w;}
10    T calc()
11    {
12        for (int i = 2; i <= n; ++i) dis[i] = g[1][i];
13        for (int i = 1; i < n; ++i)
14        {
15            int k = 0;
16            for (int j = 1; j <= n; ++j)
17                if (!vis[j] && dis[j] < dis[k]) k = j;
18            vis[k] = 1;
19            ans += dis[k];
20        }
21    }
22 };

```

```

19         for (int j = 1; j <= n; ++j)
20             if (!vis[j] && g[k][j] < dis[j]) dis[j] = g[k][j];
21     }
22     return ans;
23 }
24 };

```

1.3.2 Kruskal

```

1 template <typename T>
2 class MST
3 {
4     int n, m, e_cnt, cnt; T ans;
5     struct node {int u, v; T w;};
6     vector<int> fa; vector<node> g;
7     public:
8     MST(int n, int m) : n(n), m(m), fa(n + 1, 0), g(m + 1) {cnt = e_cnt
9         = ans = 0;}
10    void add(int u, int v, int w) {g[++e_cnt].u = u, g[e_cnt].v = v, g[
11        e_cnt].w = w;}
12    int getfa(int u) {return fa[u] == u ? u : fa[u] = getfa(fa[u]);}
13    T calc()
14    {
15        sort(g.begin(), g.end(), [] (auto &x, auto &y) {return x.w < y.w
16            ;});
17        for (int i = 1; i <= n; ++i) fa[i] = i;
18        for (int i = 1; cnt < n && i <= m; ++i)
19        {
20            int dx = getfa(g[i].u), dy = getfa(g[i].v);
21            if (dx == dy) continue;
22            ans += g[i].w; fa[dx] = dy; ++cnt;
23        }
24        return ans;
25    }
26 };

```

1.4 LCA

```

1 class LCA
2 {
3     static constexpr int lg = 20;
4     int n;
5     vector<int> dep;
6     vector<vector<int>> f, ve;
7     public:
8     LCA(int n) : n(n), ve(n + 1), dep(n + 1), f(n + 1, vector<int>(lg +
9         1, 0)) {}
10    void add(int u, int v) {ve[u].push_back(v); ve[v].push_back(u);}
11    void pre(int u, int fa)
12    {
13        f[u][0] = fa; dep[u] = dep[fa] + 1;
14        for (int i = 1; i < lg; ++i) f[u][i] = f[f[u][i-1]][i-1];
15        for (auto v : ve[u])
16            if (v != fa) pre(v, u);
17    }
18    int query(int u, int v)
19    {
20        if (dep[u] < dep[v]) swap(u, v);
21        for (int i = lg; ~i; --i)
22        {
23            if (dep[f[u][i]] >= dep[v]) u = f[u][i];
24            if (u == v) return u;
25        }
26        for (int i = lg; ~i; --i)
27            if (f[u][i] != f[v][i]) u = f[u][i], v = f[v][i];
28        return f[u][0];
29    }
30 };

```

1.5 Topological Sorting

```

1 class Topo
2 {
3     int n;
4     vector<int> deg;
5     vector<vector<int>> ve;
6     public:
7     Topo(int n) : n(n), ve(n + 1), deg(n + 1, 0) {}
8     void add(int u, int v)
9     {
10        ve[u].push_back(v);
11        ++deg[v];
12    }
13    vector<int> calc()
14    {
15        queue<int> q;
16        vector<int> lst;
17    }
18 };

```

```

18     for (int i = 1; i <= n; ++i)
19         if (!deg[i]) q.push(i);
20     while (!q.empty())
21     {
22         int u = q.front(); q.pop();
23         lst.push_back(u);
24         for (auto v : ve[u])
25         {
26             --deg[v];
27             if (!deg[v]) q.push(v);
28         }
29     }
30     return lst;
31 }
32 };

```

1.6 Shortest Path

1.6.1 Dijkstra

```

1 class dijkstra
2 {
3     int n, m, cnt;
4     vector<int> head, to, nxt, vis;
5     vector<ll> dis, val;
6     public:
7     dijkstra(int n, int m) :
8         n(n), m(m), vis(n + 1, 0), head(n + 1, 0), dis(n + 1, 1e18),
9         to(2 * m + 1, 0), nxt(2 * m + 1, 0), val(2 * m + 1, 0) {cnt = 0;}
10
11     void add(int u, int v, int w)
12     {
13         to[++cnt] = v; val[cnt] = w; nxt[cnt] = head[u]; head[u] = cnt;
14         to[++cnt] = u; val[cnt] = w; nxt[cnt] = head[v]; head[v] = cnt;
15     }
16     auto calc(int s)
17     {
18         priority_queue<pair<ll, int>> q;
19         for (int i = 1; i <= n; ++i) vis[i] = 0, dis[i] = INF;
20         q.push({0, s});
21         dis[s] = 0;
22         while (!q.empty())
23         {
24             int u = q.top().second; q.pop();
25             if (vis[u]) continue;
26             vis[u] = 1;
27             for (int i = head[u]; i; i = nxt[i])
28             {
29                 int v = to[i];
30                 if (dis[v] > dis[u] + val[i])
31                 {
32                     dis[v] = dis[u] + val[i];
33                     q.push({-dis[v], v});
34                 }
35             }
36         }
37         return dis;
38     };

```

1.6.2 SPFA

```

1 class SPFA
2 {
3     int n, m, cnt;
4     vector<int> head, to, nxt, val, vis, times;
5     vector<ll> dis;
6     public:
7     SPFA(int n, int m) :
8         n(n), m(m), times(n + 1, 0), vis(n + 1, 0), head(n + 1, 0), dis(
9         n + 1, INF),
10         to(2 * m + 1, 0), nxt(2 * m + 1, 0), val(2 * m + 1, 0) {cnt = 0;}
11
12     void add(int u, int v, int w)
13     {
14         to[++cnt] = v; val[cnt] = w; nxt[cnt] = head[u]; head[u] = cnt;
15         to[++cnt] = u; val[cnt] = w; nxt[cnt] = head[v]; head[v] = cnt;
16     }
17     auto calc(int s)
18     {
19         queue<int> q;
20         for (int i = 1; i <= n; ++i) vis[i] = 0, dis[i] = INF;
21         dis[s] = 0, vis[s] = 1; q.push(s);
22         while (!q.empty())
23         {
24             int u = q.front();
25             q.pop(), vis[u] = 0;
26             for (int i = head[u]; i; i = nxt[i])
27             {
28                 int v = to[i];

```

```

27         if (dis[v] > dis[u] + val[i])
28         {
29             dis[v] = dis[u] + val[i];
30             times[v] = times[u] + 1;
31             if (times[v] >= n) return {-1}; //Negative Cycle
32             if (!vis[v]) q.push(v), vis[v] = 1;
33         }
34     }
35     return dis;
36 }
37 };
38 };

```

1.7 DCC

```

1 class DCC
2 {
3     public:
4     struct Edge {int to, nxt;};
5     vector<Edge> G;
6     vector<int> head, dfn, low, col;
7     vector<bool> cut;
8     stack<int> stk;
9     int cnt, cct, n;
10     void init(int nn = 0)
11     {
12         G.assign(2, {0, 0});
13         n = nn; head.assign(n + 1, 0);
14     }
15     void dfs(int u, int f = -1)
16     {
17         dfn[u] = low[u] = ++cnt;
18         int ch = 0;
19         for (int i = head[u]; i; i = G[i].nxt)
20             if (i != f)
21             {
22                 int v = G[i].to;
23                 if (dfn[v] < dfn[u]) stk.push(i >> 1);
24                 if (!dfn[v])
25                 {
26                     dfs(v, i ^ 1); ++ch;
27                     low[u] = min(low[u], low[v]);
28                     if (low[v] >= dfn[u])
29                     {
30                         int I = 0;
31                         ++cct; cut[u] = true;
32                         do
33                         {
34                             assert(!stk.empty());
35                             I = stk.top(); stk.pop();
36                             col[I] = cct;
37                         }
38                         while (I != (i >> 1));
39                     }
40                 }
41                 else if (dfn[v] < low[u]) low[u] = dfn[v];
42             }
43         if (f == -1 && ch == 1) cut[u] = false;
44     }
45     void tarjan()
46     {
47         cnt = cct = 0;
48         col.assign(G.size() >> 1, 0);
49         dfn.assign(n + 1, 0);
50         low.assign(n + 1, 0);
51         cut.assign(n + 1, false);
52         while (!stk.empty()) stk.pop();
53         for (int i = 1; i <= n; ++i) if (!dfn[i]) dfs(i);
54     }
55     void insert(int u, int v)
56     {
57         G.push_back({v, head[u]}); head[u] = G.size() - 1;
58         G.push_back({u, head[v]}); head[v] = G.size() - 1;
59     }
60     void insert(vector<vector<int>> &G1)
61     {
62         for (unsigned u = 1; u < G1.size(); ++u)
63             for (int v : G1[u]) insert(u, v);
64     }
65     bool operator [] (const int &x) const {return cut[x];}
66 };

```

1.8 Tarjan

```

1 class Tarjan
2 {
3     int n, m, cnt, times, scc_cnt;
4     vector<int> head, to, nxt, low, scc, dfn;
5     stack<int> s;
6     void tarjan(int u)

```

```

7  {
8      low[u] = dfn[u] = ++times;
9      s.push(u);
10     for (int i = head[u]; i; i = nxt[i])
11     {
12         int v = to[i];
13         if (!dfn[v])
14         {
15             tarjan(v);
16             low[u] = min(low[u], low[v]);
17         }
18         else if (!scc[v]) low[u] = min(low[u], dfn[v]);
19     }
20     if (low[u] == dfn[u])
21     {
22         ++scc_cnt;
23         while (true)
24         {
25             int x = s.top(); s.pop();
26             scc[x] = scc_cnt;
27             if (x == u) break;
28         }
29     }
30 }
31 public:
32 Tarjan(int n, int m) :
33     n(n), m(m), head(n + 2, 0), low(n + 1, 0), dfn(n + 1, 0), scc(n +
34     1, 0),
35     to(2 * m + 2, 0), nxt(2 * m + 2, 0) {cnt = 1; times = scc_cnt =
36     0;}
37 void add(int u, int v) {to[++cnt] = v; nxt[cnt] = head[u]; head[u] =
38     cnt;}
39 auto calc()
40 {
41     for (int i = 1; i <= n; ++i)
42         if (!dfn[i]) tarjan(i);
43     return scc;
44 }
45 };

```

```

14     int u = q.front(); q.pop();
15     for (int i = head[u]; i; i = nxt[i])
16     {
17         int v = to[i];
18         if (!vis[v] && val[i])
19         {
20             pre[v] = u; edge[v] = i; vis[v] = 1;
21             q.push(v);
22             if (v == t) return 1;
23         }
24     }
25 }
26 return 0;
27 }
28 public :
29 EK(int n, int m, int s, int t) :
30     n(n), m(m), s(s), t(t),
31     vis(n + 1, 0), head(n + 1, 0), pre(n + 1, -1), edge(n + 1, -1),
32     to(m + 1, 0), nxt(m + 1, 0), val(m + 1, 0) {cnt = 1;}
33 void add(int u, int v, T w)
34 {
35     to[++cnt] = v; val[cnt] = w; nxt[cnt] = head[u]; head[u] = cnt;
36     to[++cnt] = u; val[cnt] = 0; nxt[cnt] = head[v]; head[v] = cnt;
37 }
38 T calc()
39 {
40     T ans = 0;
41     while (bfs())
42     {
43         T mn = INF;
44         for (int i = t; i != s; i = pre[i]) mn = min(mn, val[edge[i
45         ]]);
46         for (int i = t; i != s; i = pre[i]) val[edge[i]] -= mn, val[
47         edge[i] ^ 1] += mn;
48         ans += mn;
49     }
50     return ans;
51 }
52 };

```

1.9 Bipartite Graph Matchings

```

1  class Matching
2  {
3      int l, r; //the number of left/right side points
4      vector<vector<int>> ve;
5      vector<int> vis, op;
6      bool dfs(int u)
7      {
8          for (auto v : ve[u])
9          {
10             if (vis[v]) continue;
11             vis[v] = 1;
12             if (!op[v] || dfs(op[v])) {op[v] = u; return true;}
13         }
14         return false;
15     }
16     public:
17     Matching(int l, int r) : l(l), r(r), vis(r + 1, 0), op(r + 1, 0), ve
18     (l + 1, {})
19     void add(int u, int v) {ve[u].push_back(v);}
20     int calc()
21     {
22         int ans = 0;
23         for (int i = 1; i <= l; ++i)
24         {
25             vis.assign(r + 1, 0);
26             if (dfs(i)) ++ans;
27         }
28         return ans;
29     }
30 };

```

1.10 Flow

1.10.1 Edmonds-Karp

```

1  template <typename T>
2  class EK
3  {
4      int n, m, s, t, cnt;
5      vector<int> head, to, nxt, vis, pre, edge;
6      vector<T> val;
7      bool bfs()
8      {
9          queue<T> q;
10         for (int i = 1; i <= n; ++i) vis[i] = 0, pre[i] = edge[i] = -1;
11         vis[s] = 1; q.push(s);
12         while (!q.empty())
13         {

```

1.10.2 Dinic

```

1  template <typename T>
2  class Dinic
3  {
4      int n, m, s, t, cnt;
5      vector<int> head, to, nxt, cur, dep;
6      vector<T> val;
7      int bfs()
8      {
9          for (int i = 0; i <= n; ++i) dep[i] = 0, cur[i] = head[i];
10         queue<int> q;
11         q.push(s), dep[s] = 1;
12         while (!q.empty())
13         {
14             int u = q.front(); q.pop();
15             for (int i = head[u]; i; i = nxt[i])
16             {
17                 int v = to[i];
18                 if (val[i] && !dep[v]) q.push(v), dep[v] = dep[u] + 1;
19             }
20         }
21         return dep[t];
22     }
23     T dfs(int u, int t, T flow)
24     {
25         if (u == t) return flow;
26         T ans = 0;
27         for (int &i = cur[u]; i && ans < flow; i = nxt[i])
28         {
29             int v = to[i];
30             if (val[i] && dep[v] == dep[u] + 1)
31             {
32                 int x = dfs(v, t, min(val[i], flow - ans));
33                 if (x) val[i] -= x, val[i ^ 1] += x, ans += x;
34             }
35         }
36         if (ans < flow) dep[u] = -1;
37         return ans;
38     }
39     public :
40     Dinic(int n, int m, int s, int t) :
41         n(n), m(m), s(s), t(t),
42         head(n + 1, 0), cur(n + 1, 0), dep(n + 1, 0),
43         to(m + 1, 0), nxt(m + 1, 0), val(m + 1, 0) {cnt = 1;}
44     void add(int u, int v, T w)
45     {
46         to[++cnt] = v; val[cnt] = w; nxt[cnt] = head[u]; head[u] = cnt;
47         to[++cnt] = u; val[cnt] = 0; nxt[cnt] = head[v]; head[v] = cnt;
48     }
49     T calc()
50     {
51         T ans = 0;
52         while (bfs())

```

```

53     {
54         T x;
55         while ((x = dfs(s, t, INF))) ans += x;
56     }
57     return ans;
58 }
59 };

1 class Dinic
2 {
3     typedef long long ll;
4     static const int N=1e6+10, M=4e6+10;
5     static const ll INF=4e18;
6     int cgt, head[N], des[M], nxt[M], dep[N], que[N], H, T, h2[N];
7     ll cap[M];
8     inline ll dfs(const int &u, ll in=INF)
9     {
10         if(u==t)return in; ll out=0;
11         for(int i=h2[u]; i; i=nxt[i])
12         {
13             int v=des[i];
14             if(cap[i]&&dep[v]==dep[u]+1)
15             {
16                 ll tmp=dfs(v, min(in, cap[i]));
17                 out+=tmp; cap[i]-=tmp; cap[i^1]+=tmp;
18                 if(!(in-=tmp))break;
19             }
20         }
21         return out;out:dep[u]=0;
22     }
23     inline bool bfs()
24     {
25         memset(dep+1, 0, n*sizeof(ll));
26         dep[que[H=T=0]]=s=1;
27         while(H<=T)
28         {
29             int u=que[H++];
30             for(int i=head[u]; i; i=nxt[i])if(cap[i])
31             {
32                 int v=des[i];
33                 if(!dep[v])dep[que[++T]=v]=dep[u]+1;
34             }
35         }
36         return dep[t];
37     }
38 public:
39     int n, s, t;
40     inline void Init(const int &sz=0)
41     {
42         memset(head+1, 0, n*sizeof(ll));
43         cgt=1; n=sz;
44     }
45     inline ll Max_Flow(const int &ss, const int &tt)
46     {
47         s=ss; t=tt; ll ans=0;
48         while(bfs())
49         {
50             memcpy(h2+1, head+1, n*sizeof(ll));
51             ans+=dfs(s, INF);
52         }
53         return ans;
54     }
55     inline bool ins(const int &x, const int &y, const ll &w)
56     {
57         if(x>n||y>n||x<1||y<1)return false;
58         nxt[++cgt]=head[x]; des[head[x]=cgt]=y; cap[cgt]=w;
59         nxt[++cgt]=head[y]; des[head[y]=cgt]=x; cap[cgt]=0;
60         return true;
61     }
62     inline int newNode(){return ++n;}
63 }a;

64
65 namespace MCMF
66 {
67     typedef long long Val_Type; typedef long long Cap_Type;
68     const Val_Type INF_v=4e18; const Cap_Type INF_c=4e18;
69     const int N=1e6+10, M=2e6+10; int head[N], des[M], nxt[M], cgt=1;
70     Cap_Type cap[M]; Val_Type val[M];
71     template<typename T> inline T Abs(T x){return x<0?-x:x;}
72     inline void ins(const int &x, const int &y, const int &c, const
73         Val_Type &w)
74     {
75         nxt[++cgt]=head[x]; des[head[x]=cgt]=y; cap[cgt]=c; val[cgt]=w;
76         nxt[++cgt]=head[y]; des[head[y]=cgt]=x; cap[cgt]=0; val[cgt]=-w;
77     }
78     int que[20000010], H, T; Val_Type dis[N], mnc; int s, t, S; bool inq
79     [N];
80     inline bool spfa()
81     {
82         for(int i=0; i<=S+2; ++i)dis[i]=INF_v; dis[que[H=T=0]]=s=0;
83         while(H<=T)
84         {
85             int u=que[H++]; inq[u]=false; for(int i=head[u]; i; i=nxt[i]

```

```

84         {int v=des[i]; if(cap[i]&&dis[v]>dis[u]+val[i]){dis[v]=
85             dis[u]+val[i]; if(!inq[v])inq[que[++T]=v]=true;}}
86         }
87         return dis[t]<INF_v;
88     }
89     inline Cap_Type dfs(const int &u=s, Cap_Type in=INF_c)
90     {
91         if(u==t)return in; Cap_Type out=0; inq[u]=true;
92         for(int i=head[u]; i; i=nxt[i])
93         {
94             int v=des[i]; if(cap[i]&&!inq[v]&&dis[v]==(dis[u]+val[i]))
95             {
96                 Cap_Type tmp=dfs(v, cap[i]<in?cap[i]:in); mnc+=val[i]*
97                 tmp;
98                 cap[i]-=tmp; cap[i^1]+=tmp; out+=tmp; if(!(in-=tmp))
99                 break;
100             }
101             if(!out)dis[u]=4e18; inq[u]=false; return out;
102         }
103     }
104     inline Cap_Type dinic(){Cap_Type res=0; while(spfa())res+=dfs();
105     return res;}
106     inline void Clear(){memset(head, 0, (S+2)*sizeof(head[0])); cgt=1; S
107     =0; mnc=0;}
108 }
109 using MCMF::ins; using MCMF::s; using MCMF::t; using MCMF::S; using MCMF::
110     dinic; using MCMF::mnc;

```

2.4 Treap

```

1 namespace VAL
2 {
3     inline void update(int k){t[k].siz=t[t[k].l].siz+t[t[k].r].siz+1;}
4     inline int new_node(int k){t[++cnt].val=k;t[cnt].siz=1;t[cnt].key=
5         rand();return cnt;}
6     inline void split(int k,int cur,int &x,int &y)
7     {
8         if(!cur){x=y=0;return;}pushdown(cur);
9         else if(t[cur].val<=k)x=cur,split(k,t[cur].r,t[cur].r,y);
10        else y=cur,split(k,t[cur].l,x,t[cur].l);update(cur);
11    }
12    inline int merge(int L,int R)
13    {
14        if(!L||!R)return L+R;
15        pushdown(L);pushdown(R);
16        if(t[L].key<t[R].key)
17        {
18            t[L].r=merge(t[L].r,R);
19            update(L);return L;
20        }
21        else
22        {
23            t[R].l=merge(L,t[R].l);
24            update(R);return R;
25        }
26    }
27 }
28 namespace SIZ
29 {
30     inline void split(int k,int cur,int &x,int &y)
31     {
32         if(!cur){x=y=0;return;}pushdown(cur);
33         if(k<=t[t[cur].l].siz){split(k,t[cur].l,x,t[y=cur].l);update(cur)}
34         ;return;}
35         else {split(k-t[t[cur].l].siz-1,t[cur].r,t[x=cur].r,y);update(
36             cur);return;}
37     }
38     inline int merge(int L,int R)
39     {
40         if(!L||!R)return L+R;pushdown(L);pushdown(R);
41         if(t[L].key<t[R].key){t[L].r=merge(t[L].r,R);update(L);return L;}
42         else{t[R].l=merge(L,t[R].l);update(R);return R;}
43     }
44     inline int rnk(int k){int res=t[t[k].l].siz;while(t[k].f){res+=(k==t
45         [t[k].f].r)?
46         t[t[k].f].l.siz+1:0;k=t[k].f;}return res+1;}
47 }
48 namespace MERGE//âĖšăđŽăÿçžăŕŇăĂăŘăžűêĞşăÿĂăÿîçĆż
49 {
50     struct Node
51     {
52         int l,r,f,ct,sz,vl;
53         Node(){l=r=vl=sz;}
54         Node(ll v,ll c){l=r=f;ct=sz=c;vl=v;}
55     }t[N];
56     int n,stk[N],top,cnt,T1,T2,T3,T4,T5,Rt;
57     inline int node(ll v,ll c)
58     {
59         int u=top?stk[top--]:++cnt;
60         t[u]=Node(v,c);return u;
61     }
62     inline int copy(int x)
63     {
64         int u=top?stk[top--]:++cnt;
65         t[u]=t[x];return u;
66     }
67     inline void update(int x)
68     {
69         pushdown(x);
70         t[x].sz=t[t[x].l].sz+t[t[x].r].sz+t[x].ct;
71         if(t[x].l)t[t[x].l].f=x;
72         if(t[x].r)t[t[x].r].f=x;
73         t[x].f=0;
74     }
75     inline void split(int cur,int k,int &x,int &y)
76     {
77         if(!cur){x=y=0;return;}
78         pushdown(cur);
79         if(t[t[cur].l].sz>=k)
80         {
81             y=cur;
82             split(t[cur].l,k,x,t[y].l);

```

```

80         }
81         else if(t[t[cur].l].sz+t[cur].ct>=k)
82         {
83             k=t[t[cur].l].sz;
84             if(k==t[cur].ct)
85             {
86                 y=t[cur].r;
87             }
88             else
89             {
90                 y=copy(cur);
91                 t[y].ct=-k;
92                 t[y].l=0;
93             }
94             x=cur; t[x].ct=k;
95             t[x].r=0;
96             update(x);
97             update(y);
98         }
99         else
100         {
101             x=cur;
102             split(t[cur].r,k-t[t[cur].l].sz-t[cur].ct,t[x].r,y);
103             update(x);
104         }
105     }
106     inline int merge(int x,int y)
107     {
108         if(!x||!y)return x|y;
109         pushdown(x);pushdown(y);
110         if(int(rnd())%(t[x].sz+t[y].sz)<t[x].sz)
111         {
112             t[x].r=merge(t[x].r,y);
113             update(x);
114             return x;
115         }
116         else
117         {
118             t[y].l=merge(x,t[y].l);
119             update(y);
120             return y;
121         }
122     }
123 }
124 namespace PFHQ//ăŃžėŮťăďňăŮ
125 {
126     #include<bits/stdc++.h>
127     #define rep(a,b,c) for(register int c=(a);c<=(b);++c)
128     using namespace std;
129     const int Mod=1e9+7,INF=0x3f3f3f3f,N=4e6+5;
130     inline int read()
131     {
132         int res=0;char ch=getchar();while(ch<'0' || ch>'9')ch=getchar();
133         while(ch<='9' && ch>='0')res=res*10+(ch^48),ch=getchar();return res;
134     }
135     inline int add(int &x,int y){x=((x+y>=Mod)?(x+y-Mod):(x+y));}
136     struct FHQ{int l,r,siz,val,sum,tag[3];}t[N];
137     int a[N],cnt,Root,top,n,m,T1,T2,T3,T4,T5;
138     inline int Node(int val)
139     {
140         t[++cnt].siz=1;t[cnt].sum=t[cnt].val=val;t[cnt].tag[0]=INF;
141         t[cnt].l=t[cnt].r=t[cnt].tag[1]=t[cnt].tag[2]=0;return cnt;
142     }
143     inline int copy(int x){t[++cnt]=t[x];return cnt;}
144     inline void update(int x)
145     {
146         t[x].siz=t[t[x].l].siz+t[t[x].r].siz+1;
147         t[x].sum=((t[t[x].l].sum+t[t[x].r].sum)%Mod+t[x].val)%Mod;
148     }
149     inline void push2(int x){swap(t[x].l,t[x].r);t[x].tag[2]^=1;}
150     inline void push1(int x,int k){add(t[x].val,k);add(t[x].tag[1],k);t[x].sum=
151     (t[x].sum+1ll*t[x].siz*k%Mod)%Mod;}
152     inline void push0(int x,int k)
153     {t[x].tag[1]=0;t[x].tag[0]=t[x].val=k;t[x].sum=1ll*t[x].siz*k%Mod;}
154     inline void pushdown(int cur)
155     {
156         if(t[cur].tag[0]!=INF||t[cur].tag[1]||t[cur].tag[2])
157         {
158             if(t[cur].l) t[cur].l = copy(t[cur].l);
159             if(t[cur].r) t[cur].r = copy(t[cur].r);
160         }
161         if(t[cur].tag[0]!=INF)
162         {
163             if(t[cur].l) push0(t[cur].l,t[cur].tag[0]);
164             if(t[cur].r) push0(t[cur].r,t[cur].tag[0]);
165             t[cur].tag[0] = INF;
166         }
167         if(t[cur].tag[1])
168         {
169             if(t[cur].l) push1(t[cur].l,t[cur].tag[1]);
170             if(t[cur].r) push1(t[cur].r,t[cur].tag[1]);
171             t[cur].tag[1] = 0;
172         }
173     }

```

```

173     if(t[cur].tag[2]){if(t[cur].l)push2(t[cur].l);if(t[cur].r)push2(
174         t[cur].r);t[cur].tag[2]=0;}
175     inline int merge(int x,int y)
176     {
177         if(!x||!y)return x+y;pushdown(x);pushdown(y);
178         if(rand()%(t[x].siz+t[y].siz)<t[x].siz){x=copy(x);t[x].r=merge(t
179             [x].r,y);update(x);return x;}
180         y=copy(y);t[y].l=merge(x,t[y].l);update(y);return y;
181     }
182     inline void split(int cur,int k,int &x,int &y)
183     {
184         if(!cur){x=y=0;return;} pushdown(cur);
185         if(t[t[cur].l].siz>=k)y=copy(cur),split(t[y].l,k,x,t[y].l),
186         update(y);
187         else x=copy(cur),split(t[x].r,k-t[t[cur].l].siz-1,t[x].r,y),
188         update(x);
189     }
190     inline void build(int l,int r,int &cur)
191     {
192         int mid=(l+r)>>1;cur=Node(a[mid]);
193         if(l<mid)build(l,mid-1,t[cur].l);
194         if(r>mid)build(mid+1,r,t[cur].r);update(cur);
195     }
196     inline void change(int l,int r,int k)
197     {
198         split(Root,l-1,T1,T2);split(T2,r-1+1,T2,T3);
199         T2=copy(T2);push0(T2,k);Root=merge(merge(T1,T2),T3);
200     }
201     inline void modify(int l,int r,int k)
202     {
203         split(Root,l-1,T1,T2);split(T2,r-1+1,T2,T3);
204         T2=copy(T2);push1(T2,k);Root=merge(merge(T1,T2),T3);
205     }
206     inline void Copy(int l1,int r1,int l2,int r2)//swap
207     {
208         if(l1>l2)swap(l1,l2),swap(r1,r2);
209         split(Root,l1-1,T1,T2);split(T2,r1-1+1,T2,T3);
210         split(T3,l2-r1-1,T3,T4);split(T4,r2-l2+1,T4,T5);
211         Root=merge(merge(merge(merge(T1,T4),T3),T2),T5);
212     }
213     inline void paste(int l1,int r1,int l2,int r2)//copy
214     {
215         bool flag = 0;if(l1>l2)swap(l1,l2),swap(r1,r2),flag=1;
216         split(Root,l1-1,T1,T2);split(T2,r1-1+1,T2,T3);
217         split(T3,l2-r1-1,T3,T4);split(T4,r2-l2+1,T4,T5);
218         if(flag) T2=copy(T4);else T4=copy(T2);
219         Root=merge(merge(merge(merge(T1,T2),T3),T4),T5);
220     }
221     inline int query(int l,int r)
222     {
223         split(Root,l-1,T1,T2);split(T2,r-1+1,T2,T3);
224         int res=t[T2].sum;Root=merge(merge(T1,T2),T3);return res;
225     }
226     inline void dfs(int cur)
227     {
228         pushdown(cur);if(t[cur].l)dfs(t[cur].l);
229         a[++top]=t[cur].val;if(t[cur].r)dfs(t[cur].r);
230     }
231     inline void reverse(int l,int r)
232     {
233         split(Root,l-1,T1,T2);split(T2,r-1+1,T2,T3);
234         T2=copy(T2);push2(T2);Root=merge(merge(T1,T2),T3);
235     }
236     int main()
237     {
238         srand(time(0));
239         n=read();m=read();rep(1,n,i)a[i]=read();build(1,n,Root);rep(1,m,
240             i)
241         {
242             int opt=read(),l1=read(),r1=read(),l2,r2;
243             switch(opt)
244             {
245                 case 1: printf("%d\n",query(l1,r1));break;
246                 case 2: change(l1,r1,read());break;
247                 case 3: modify(l1,r1,read());break;
248                 case 4: l2=read();r2=read();paste(l1,r1,l2,r2);break;
249                 case 5: l2=read();r2=read();Copy(l1,r1,l2,r2);break;//
250                 swap
251                 case 6: reverse(l1,r1);break;
252             }
253             if(cnt>N-1000000)dfs(Root),top=Root=cnt=0,build(1,n,Root);
254         }
255         top=0;dfs(Root);rep(1,n,i)printf("%d ",a[i]);return 0;
256     }
257 }

```

2.5 Cartesian Tree

```

1 //heap-order on values and BST-order on keys
2 stack<int> s;
3 vector<int> L(n + 1, 0), R(n + 1, 0);
4 for (int i = 1; i <= n; ++i)

```

```

5 {
6     int la = -1;
7     while (!s.empty() && a[s.top()] > a[i]) la = s.top(), s.pop();
8     if (!s.empty()) R[s.top()] = i;
9     if (la != -1) L[i] = la;
10    s.push(i);
11 }

```

2.6 Sparse Table

```

1 vector<int> lg(n + 1, -1);
2 vector<vector<int>> f(20, vector<int>(n + 1, INF));
3 for (int i = 1; i <= n; ++i) lg[i] = lg[i >> 1] + 1;
4 for (int i = 1; i <= n; ++i) f[0][i] = a[i];
5 for (int j = 1; j < 20; ++j)
6     for (int i = 1; i + (1 << j) - 1 <= n; ++i) f[j][i] = min(f[j - 1][i]
7         , f[j - 1][i + (1 << (j - 1))]);
8 auto query = [&](int l, int r) -> int {return min(f[lg[r - l + 1]][l],
9     f[lg[r - l + 1]][r - (1 << lg[r - l + 1]) + 1]);};

```

2.7 Persistent Data Structure

2.8 Linear-Basis

```

1 template<typename T>
2 class Basis
3 {
4     int n, lg;
5     vector<T> p, ex, nw; vector<vector<int>> id;
6     public :
7     Basis(int n, int lg) : n(n), lg(lg), p(lg + 1, 0), nw(lg + 1, 0), id
8         (lg + 1) {}
9     void modify(T x, int idx)
10    {
11        vector<int> cur(n + 1, 0); cur[idx] = 1;
12        for (int i = lg; ~i; --i)
13        {
14            if (!(l1 << i) & x) continue;
15            if (!p[i]) {p[i] = x; id[i] = cur; break;}
16            else
17            {
18                x ^= p[i];
19                for (int j = 1; j <= n; ++j) cur[j] ^= id[i][j];
20            }
21        }
22    }
23    T get_max()
24    {
25        T ans = 0;
26        for (int i = lg; ~i; --i)
27            if ((ans ^ p[i]) > ans) ans ^= p[i];
28        return ans;
29    }
30    T get_min()
31    {
32        T ans = 0; int cnt = 0;
33        for (int i = 0; i <= lg; ++i) cnt += p[i] > 0;
34        if (cnt < n) return 0;
35        for (int i = 0; i <= lg; ++i)
36            if (p[i] > 0) return p[i];
37    }
38    void change()
39    {
40        for (int i = 0; i <= lg; ++i) nw[i] = p[i];
41        for (int i = 0; i <= lg; ++i)
42            for (int j = i - 1; ~j; --j)
43                if (nw[i] >> j & 1) nw[i] ^= nw[j];
44        for (int i = 0; i <= lg; ++i)
45            if (nw[i]) ex.push_back(i);
46    }
47    T get_min_k(T k)
48    {
49        int sz = (int)ex.size();
50        if (sz < n) --k; // element 0
51        if (k > (l1 << sz) - 1) return -1;
52        T ans = 0;
53        for (int j = 0; j < sz; ++j)
54            if (k >> j & 1) ans ^= nw[ex[j]];
55        return ans;
56    }
57    bool find(T x)
58    {
59        for (int i = lg; ~i; --i)
60        {
61            if (!(x >> i & 1)) continue;
62            if (!p[i]) return false;
63            x ^= p[i];
64        }
65        return true;
66    }
67 }

```

```
66 vector<int> getid(T x) // if find (x) == 1
67 {
68     vector<int> res(n + 1, 0);
69     for (int i = lg; ~i; --i)
70     {
71         if (!(x >> i & 1)) continue;
72         x ^= p[i];
73         for (int j = 1; j <= n; ++j) res[j] ^= id[i][j];
74     }
75     return res;
76 }
77 };
```

3 Math

3.1 Subset Enumeration

```
1 for (int S = 1; S < (1 << n); ++S)
2   for (int S0 = S; S0; S0 = (S0 - 1) & S)
```

3.2 Elementary Arithmetic Bucket

```
1 template <typename T, int MOD = 1000000007>
2 class Z
3 {
4     T x;
5     Z <T, MOD> qpow(Z x, T y)
6     {
7         Z <T, MOD> res(1);
8         while (y)
9         {
10             if (y & 1) res *= x;
11             x *= x;
12             y >>= 1;
13         }
14         return res;
15     }
16     public :
17     Z() : x(0) {}
18     Z(T x) : x(x) {}
19     T get() {return x;}
20     Z & operator = (T o) {x = o % MOD; return *this;}
21     Z & operator += (Z o) {x = (x + o.x + MOD) % MOD; return *this;}
22     Z & operator -= (Z o) {x = (x - o.x + MOD) % MOD; return *this;}
23     Z & operator *= (Z o) {x = 1ll * o.x * x % MOD; return *this;}
24     Z & operator ^= (Z o) {x = qpow(x, o.x).x; return *this;}
25     Z & operator /= (Z o) {*this *= o ^ (MOD - 2); return *this;}
26     Z & operator %= (Z o) {x = x % o.x; return *this;}
27     friend Z operator + (Z x, Z y) {return x + y;}
28     friend Z operator - (Z x, Z y) {return x - y;}
29     friend Z operator * (Z x, Z y) {return x * y;}
30     friend Z operator / (Z x, Z y) {return x / y;}
31     friend Z operator ^ (Z x, Z y) {return x ^ y;}
32     friend Z operator % (Z x, Z y) {return x % y;}
33     friend bool operator == (Z x, Z y) {return x.x == y.x;}
34     friend bool operator != (Z x, Z y) {return x.x != y.x;}
35     friend istream& operator >> (istream &is, Z& o) {T val; is >> val; o = Z(val); return is;}
36     friend ostream& operator << (ostream &os, const Z &z) {return os << z.x;}
37 };
```

3.3 Fraction

```
1 template <typename T>
2 class Frac
3 {
4     T p, q; // p / q
5     void reduce()
6     {
7         assert(q != 0);
8         T g = gcd(p, q);
9         p /= g, q /= g;
10        if (q < 0) p = -p, q = -q;
11    }
12    public :
13    Frac(T p = 0, T q = 1) : p(p), q(q) {assert(q != 0); reduce();}
14    T get_p() {return p;}
15    T get_q() {return q;}
16    double get_val() {return 1.0 * p / q;}
17    Frac operator + (const Frac &o) {return Frac(p * o.q + o.p * q, q * o.q);}
18    Frac operator - (const Frac &o) {return Frac(p * o.q - o.p * q, q * o.q);}
19    Frac operator * (const Frac &o) {return Frac(p * o.p, q * o.q);}
20    Frac operator / (const Frac &o) {return Frac(p * o.q, q * o.p);}
21    Frac& operator += (const Frac &o) {*this = *this + o; return *this;}
22    Frac& operator -= (const Frac &o) {*this = *this - o; return *this;}
23    Frac& operator *= (const Frac &o) {*this = *this * o; return *this;}
24    Frac& operator /= (const Frac &o) {*this = *this / o; return *this;}
25    Frac operator ~() {return Frac(-p, q);}
26    bool operator >= (const Frac &o) {return p * o.q >= o.p * q;}
27    bool operator > (const Frac &o) {return p * o.q > o.p * q;}
28    bool operator == (const Frac &o) {return p * o.q == o.p * q;}
29    bool operator <= (const Frac &o) {return !(*this > o);}
30    bool operator < (const Frac &o) {return !(*this >= o);}
31    bool operator != (const Frac &o) {return !(*this == o);}
32 };
```

3.4 Combination

```
1 template <typename T, int MOD = 1000000007>
2 class COM
3 {
4     int n;
5     vector <Z <T, MOD>> fac, inv;
6     public :
7     COM(int n) : n(n), fac(2 * n + 2), inv(2 * n + 2)
8     {
9         fac[0] = inv[0] = inv[1] = 1;
10        for (int i = 1; i <= 2 * n; ++i) fac[i] = fac[i - 1] * i;
11        inv[2 * n] = fac[2 * n] ^ (MOD - 2);
12        for (int i = 2 * n - 1; i > 0; --i) inv[i] = inv[i + 1] * (i + 1);
13    }
14    Z <T, MOD> f(int x) {return fac[x];}
15    Z <T, MOD> inv_f(int x) {return inv[x];}
16    Z <T, MOD> comb(int x, int y)
17    {
18        if (x < 0 || y < 0 || y > x) return 0;
19        else return fac[x] * inv[x - y] * inv[y];
20    }
21    Z <T, MOD> arr(int x, int y)
22    {
23        if (x < 0 || y < 0 || y > x) return 0;
24        else return fac[x] * inv[x - y];
25    }
26    Z <T, MOD> catalan(int x) {return comb(2 * x, x) / (x + 1);}
27 };
```

3.5 The Sieve of Primes & Euler's Totient Function & Möbius Function

```
1 class Prime
2 {
3     int mx;
4     vector <int> p, phi, mu;
5     void pre()
6     {
7         vector <int> fl(mx + 1, 0);
8         phi[1] = mu[1] = 1;
9         for (int i = 2; i <= mx; ++i)
10        {
11            if (!fl[i]) p.push_back(i), phi[i] = i - 1, mu[i] = -1;
12            for (auto v : p)
13            {
14                if (i * v > mx) break;
15                fl[i * v] = 1;
16                if (i % v == 0) {phi[i * v] = phi[i] * v, mu[i * v] = 0; break;}
17                phi[i * v] = phi[i] * (v - 1); mu[i * v] = -mu[i];
18            }
19        }
20    }
21    public :
22    Prime(int mx) : mx(mx), phi(mx + 1, 0), mu(mx + 1, 0) {pre();}
23    auto get_prime() {return p;}
24    auto get_phi() {return phi;}
25    auto get_mu() {return mu;}
26 };
```

3.6 Exgcd

```
1 ll exgcd(ll a, ll b, ll &x, ll &y)
2 {
3     if (!b) {x = 1; y = 0; return abs(a);}
4     ll d = exgcd(b, (a % b + b) % b, y, x);
5     y -= a / b * x;
6     return d;
7 }
```

3.7 CRT

```
1 ll CRT()
2 {
3     //ans % a[i] = b[i] if gcd(a[i], a[j]) = 1
4     ll sum = 1, ans = 0;
5     for (int i = 1; i <= n; ++i) sum *= a[i];
6     for (int i = 1; i <= n; ++i)
7     {
8         ll x, y, tmp = sum / a[i];
9         exgcd(tmp, a[i], x, y);
10        ans = (ans + tmp * x * b[i]) % sum;
11    }
```

```

12     return (ans + sum) % sum;
13 }

```

3.8 Lagrange Interpolation

```

1 ll Lagrange(ll num)
2 {
3     ll ans = 0;
4     for (int i = 1; i <= n; ++i)
5     {
6         ll p = y[i] % MOD, q = 1;
7         for (int j = 1; j <= n; ++j)
8         {
9             if (i == j) continue;
10            p = p * (num - x[j]) % MOD;
11            q = q * (x[i] - x[j]) % MOD;
12        }
13        ans = (ans + p * qpow(q, MOD - 2) % MOD + MOD) % MOD;
14    }
15    return ans;
16 }

```

3.9 Gaussian Elimination

```

1 vector<vector<double>> a(n + 1, vector<double>(n + 2)); // n * (n +
2 1)
3 for (int i = 1; i <= n; ++i)
4 {
5     int p = cur, ok = 0;
6     while (p <= n)
7     {
8         if (a[p][i] != 0) {ok = 1; break;}
9         ++p;
10    }
11    if (!ok) continue;
12    for (int j = i; j <= n + 1; ++j) swap(a[p][j], a[cur][j]);
13    for (int j = n + 1; j >= i; --j) a[cur][j] /= a[cur][i];
14    for (int j = 1; j <= n; ++j)
15    {
16        if (j == cur) continue;
17        for (int k = n + 1; k >= i; --k) a[j][k] -= a[cur][k] * a[j][i];
18    }
19    ++cur;
20 }
21 if (cur <= n) puts("No Solution"); //0 solution or infinte solutions
22 else {for (int i = 1; i <= n; ++i) printf("%.6lf\n", a[i][n + 1]);}

```

3.10 FFT

```

1 using cd = complex<double>;
2 class FFT
3 {
4     const double Pi = acos(-1);
5     vector<int> rev; int n = 1;
6     void fft(vector<cd> &a, int op)
7     {
8         for (int i = 0; i < n; ++i)
9             if (i < rev[i]) swap(a[i], a[rev[i]]);
10        for (int len = 1; len < n; len <= 1)
11        {
12            cd wn(cos(Pi / len), op * sin(Pi / len));
13            for (int i = 0; i < n; i += len <= 1)
14            {
15                cd w(1);
16                for (int j = 0; j < len; ++j)
17                {
18                    cd u = a[i + j], v = a[i + j + len] * w;
19                    a[i + j] = u + v; a[i + j + len] = u - v;
20                    w *= wn;
21                }
22            }
23        }
24        if (op == -1) {for (auto &x : a) x /= n;}
25    }
26    public:
27    vector<double> conv(vector<cd> a, vector<cd> b)
28    {
29        int L = 0, tot = (int)a.size() + (int)b.size() - 1; n = 1;
30        while (n < tot) n <= 1, ++L;
31        rev.resize(n); a.resize(n); b.resize(n);
32        for (int i = 0; i < n; ++i) rev[i] = (rev[i >> 1] >> 1) | ((i &
33 1) << (L - 1));
34        fft(a, 1); fft(b, 1);
35        for (int i = 0; i < n; ++i) a[i] = a[i] * b[i];
36        fft(a, -1);
37        vector<double> ans(tot);
38        for (int i = 0; i < tot; ++i) ans[i] = a[i].real();

```

```

38     return ans;
39 }
40 };

```

3.11 NTT

```

1 template<int MOD = 998244353>
2 class NTT
3 {
4     vector<int> rev; int n = 1;
5     const int P = MOD; //998244353 469762049 50000000001507329LL 4179340
6     454199820289
7     const int G = 3;
8     //1945555039024054273 for G = 5
9     int qpow(int x, int y)
10    {
11        int res = 1;
12        while (y)
13        {
14            if (y & 1) res = 1ll * res * x % P;
15            x = 1ll * x * x % P;
16            y >>= 1;
17        }
18        return res;
19    }
20    void init_rev(int tot)
21    {
22        int L = 0; n = 1;
23        while (n < tot) n <= 1, ++L;
24        rev.resize(n);
25        for (int i = 0; i < n; ++i) rev[i] = (rev[i >> 1] >> 1) | ((i &
26 1) << (L - 1));
27    }
28    void ntt(vector<int> &a, int op)
29    {
30        for (int i = 0; i < n; ++i)
31            if (i < rev[i]) swap(a[i], a[rev[i]]);
32        for (int len = 1; len < n; len <= 1)
33        {
34            int wn = qpow(G, (P - 1) / (len <= 1));
35            if (op == -1) wn = qpow(wn, P - 2);
36            for (int i = 0; i < n; i += len <= 1)
37            {
38                int w = 1;
39                for (int j = 0; j < len; ++j)
40                {
41                    int u = a[i + j] >= P ? a[i + j] - P : a[i + j], v =
42                    1ll * a[i + j + len] * w % P;
43                    a[i + j] = u + v >= P ? u + v - P : u + v;
44                    a[i + j + len] = u - v <= 0 ? u - v + P : u - v;
45                    w = 1ll * w * wn % P;
46                }
47            }
48            if (op == -1)
49            {
50                int inv_n = qpow(n, P - 2);
51                for (auto &x : a) x = 1ll * x * inv_n % P;
52            }
53        }
54    }
55    public:
56    vector<int> Conv(vector<int> a, vector<int> b)
57    {
58        int tot = (int)a.size() + (int)b.size() - 1;
59        init_rev(tot);
60        a.resize(n); b.resize(n);
61        ntt(a, 1); ntt(b, 1);
62        for (int i = 0; i < n; ++i) a[i] = 1ll * a[i] * b[i] % P;
63        ntt(a, -1); a.resize(tot);
64        return a;
65    }
66    vector<int> Inv(vector<int> a, int m)
67    {
68        int inv = qpow(a[0], P - 2);
69        vector<int> b(inv);
70        for (int len = 2; (len >> 1) < m; len <= 1)
71        {
72            int sz = min((int)a.size(), len);
73            vector<int> f(a.begin(), a.begin() + sz);
74            init_rev(len <= 1);
75            f.resize(n);
76            ntt(f, 1); ntt(h, 1);
77            for (int i = 0; i < n; ++i)
78                h[i] = 1ll * h[i] * (2ll - 1ll * f[i] * h[i] % P + P) %
79                P;
80            ntt(h, -1);
81            b.assign(h.begin(), h.begin() + min(len, m));
82        }
83        b.resize(m);
84        return b;
85    }

```

```

83 pair <vector <int>, vector <int>> Divmod(vector <int> a, vector <int>
84 b)
85 {
86     int n_sz = a.size(), m_sz = b.size();
87     if (n_sz < m_sz) return {{0}, a};
88     int dq = n_sz - m_sz + 1;
89     vector <int> ra = a, rb = b;
90     reverse(ra.begin(), ra.end()); reverse(rb.begin(), rb.end());
91     ra.resize(dq); rb.resize(dq);
92     vector <int> inv_rb = Inv(rb, dq);
93     vector <int> q = Conv(ra, inv_rb);
94     q.resize(dq);
95     reverse(q.begin(), q.end());
96     vector <int> qb = Conv(q, b);
97     vector <int> r(m_sz - 1);
98     for (int i = 0; i < m_sz - 1; ++i)
99         r[i] = (0ll + a[i] - (i < (int)qb.size() ? qb[i] : 0) + P) %
100         P;
101     return {q, r};
102 }
103 vector <int> Sqrt(vector <int> a, int m) // b[0] = 1
104 {
105     vector <int> b{1};
106     int inv2 = qpow(2, P - 2);
107     for (int len = 2; (len >> 1) < m; len <= 1)
108     {
109         int sz = min((int)a.size(), len);
110         vector <int> f(a.begin(), a.begin() + sz);
111         vector <int> inv_b = Inv(b, len);
112         init_rev(len <= 1);
113         f.resize(n); inv_b.resize(n);
114         ntt(f, 1); ntt(inv_b, 1);
115         for (int i = 0; i < n; ++i)
116             f[i] = 1ll * f[i] * inv_b[i] % P;
117         ntt(f, -1);
118         b.resize(len);
119         for (int i = 0; i < len; ++i)
120             b[i] = 1ll * (b[i] + f[i]) % P * inv2 % P;
121     }
122     b.resize(m);
123     return b;
124 };

```

```

45 }
46 vector <T> mul(vector <T> A, vector <T> B)
47 {
48     int n = A.size();
49     vector <T> C(n);
50     for (int i = 0; i < n; ++i) C[i] = A[i] * B[i] % P;
51     return C;
52 }
53 public :
54 FWT() {}
55 vector <T> calc_Or(vector <T> A, vector <T> B)
56 {
57     Or(A); Or(B);
58     auto C = mul(A, B);
59     Or(C, P - 1);
60     return C;
61 }
62 vector <T> calc_And(vector <T> A, vector <T> B)
63 {
64     And(A); And(B);
65     auto C = mul(A, B);
66     And(C, P - 1);
67     return C;
68 }
69 vector <T> calc_Xor(vector <T> A, vector <T> B)
70 {
71     Xor(A); Xor(B);
72     auto C = mul(A, B);
73     Xor(C, inv_2);
74     return C;
75 }
76 };

```

3.12 FWT

```

1 template <typename T>
2 class FWT
3 {
4     public:
5     const int P = 998244353;
6     const ll inv_2 = 499122177; //500000004 for 1e9 + 7
7     private:
8     void Or(vector <T> &F, int op = 1)
9     {
10         int n = F.size();
11         for (int i = 2; i <= n; i <= 1)
12         {
13             int o = i >> 1;
14             for (int j = 0; j < n; j += i)
15                 for (int k = 0; k < o; ++k) F[j + k + o] = (F[j + k + o]
16                 + F[j + k] * op % P) % P;
17         }
18     }
19     void And(vector <T> &F, int op = 1)
20     {
21         int n = F.size();
22         for (int i = 2; i <= n; i <= 1)
23         {
24             int o = i >> 1;
25             for (int j = 0; j < n; j += i)
26                 for (int k = 0; k < o; ++k) F[j + k] = (F[j + k] + F[j +
27                 k + o] * op % P) % P;
28         }
29     }
30     void Xor(vector <T> &F, int op = 1)
31     {
32         int n = F.size();
33         for (int i = 2; i <= n; i <= 1)
34         {
35             int o = i >> 1;
36             for (int j = 0; j < n; j += i)
37             {
38                 for (int k = 0; k < o; ++k)
39                 {
40                     F[j + k] = (F[j + k] + F[j + k + o]) % P;
41                     F[j + k + o] = (F[j + k] - 2 * F[j + k + o] % P + P)
42                     % P;
43                     F[j + k] = F[j + k] * op % P;
44                     F[j + k + o] = F[j + k + o] * op % P;
45                 }
46             }
47         }
48     }
49 };

```

4 Computational Geometry

```

1 using LD = long double;
2 const LD pi = acos(-1.0);
3 const LD eps = 1e-8L;
4 int dcmp(LD x) {return x < -eps ? -1 : (x > eps ? 1 : 0);}
5 struct Point {LD x, y; Point(LD x = 0, LD y = 0) : x(x), y(y) {};}
6 struct Circle {Point O; LD r; Circle(Point O = Point(), LD r = 0) : O(O),
7   r(r) {};}
8 typedef Point Vector;
9 Vector operator + (Vector A, Vector B) {return Vector(A.x + B.x, A.y + B.y);}
10 Vector operator - (Vector A, Vector B) {return Vector(A.x - B.x, A.y - B.y);}
11 Vector operator * (Vector A, LD k) {return Vector(A.x * k, A.y * k);}
12 Vector operator / (Vector A, LD k) {return Vector(A.x / k, A.y / k);}
13 bool operator == (Vector A, Vector B) {return dcmp(A.x - B.x) == 0 && dcmp(A.y - B.y) == 0;}
14 bool operator != (Vector A, Vector B) {return !(A == B);}
15 LD dot(Vector A, Vector B) {return A.x * B.x + A.y * B.y;}
16 LD dis(Point A, Point B) {return sqrt((A.x - B.x) * (A.x - B.x) + (A.y - B.y) * (A.y - B.y));}
17 LD cross(Vector A, Vector B) {return A.x * B.y - A.y * B.x;} // A -> B counter-clockwise if cross(A, B) > 0
18 LD len(Point A) {return sqrt(A.x * A.x + A.y * A.y);}
19 LD angle(Vector A, Vector B) {return acos(dot(A, B) / (len(A) * len(B)))};
20 Vector proj(Vector A, Vector B) {return A * (dot(A, B) / dot(A, A));} // project onto A
21 Point foot(Point P, Point A, Point B) {Vector AP = P - A, AB = B - A; return A + proj(AB, AP);} // foot
22 Point reflect(Point P, Point A, Point B) {Point F = foot(P, A, B); return F * 2 - P;} // symmetry point
23 Point rotate(Point P, LD theta) {return (Point){P.x * cos(theta) - P.y * sin(theta), P.x * sin(theta) + P.y * cos(theta)}}; // counterclockwise
24 bool chk_on_line(Point P, Point A, Point B) {return dcmp(cross(P - A, B - A)) == 0;} // judge whether on line AB
25 bool chk_on_seg(Point P, Point A, Point B) {return chk_on_line(P, A, B) && dcmp(dot(P - A, P - B)) <= 0;} // judge whether on segment AB
26 LD dis_seg(Point P, Point A, Point B) // the distance from point P to segment AB.
27 {
28   if (dcmp(dot(B - A, P - A)) < 0) return dis(P, A);
29   if (dcmp(dot(A - B, P - B)) < 0) return dis(P, B);
30   return fabs(cross(P - A, P - B)) / dis(A, B);
31 }
32 Point ll_inter_pt(Point A, Point B, Point C, Point D) {return A + (B - A) * cross(C - A, D - C) / cross(B - A, D - C);}
33 bool chk_ll_inter(Point A, Point B, Point C, Point D) {return dcmp(cross(B - A, D - C)) != 0;} // line - line
34 bool chk_ls_inter(Point A, Point B, Point C, Point D) {return chk_on_seg(ll_inter_pt(A, B, C, D), C, D);} // The intersection of AB(line) and CD (line) is on the CD (seg).
35 bool chk_ss_inter(Point A, Point B, Point C, Point D) // seg - seg
36 {
37   LD c1 = cross(B - A, C - A), c2 = cross(B - A, D - A);
38   LD d1 = cross(D - C, A - C), d2 = cross(D - C, B - C);
39   if (dcmp(c1) * dcmp(c2) < 0 && dcmp(d1) * dcmp(d2) < 0) return true;
40   if (dcmp(c1) == 0 && chk_on_seg(C, A, B)) return true;
41   if (dcmp(c2) == 0 && chk_on_seg(D, A, B)) return true;
42   if (dcmp(d1) == 0 && chk_on_seg(A, C, D)) return true;
43   if (dcmp(d2) == 0 && chk_on_seg(B, C, D)) return true;
44   return false;
45 }
46 bool SameSide(Point A, Point B, Point C, Point D) {return cross(A - C, D - C) * cross(D - C, B - C) < 0;} // Point A,B Line C,D
47 LD area(vector<Point> &P)
48 {
49   int n = P.size();
50   LD res = 0;
51   for (int i = 0; i < n; ++i) res += cross(P[i], P[(i + 1) % n]);
52   return res / 2.0;
53 }
54 bool is_convex(vector<Point> &P)
55 {
56   int n = P.size();
57   for(int i = 0; i < n - 1; ++i)
58     if (dcmp(cross(P[i + 1] - P[i], P[(i + 2) % n] - P[i])) < 0)
59       return false;
60   return true;
61 }
62 int in_Poly(vector<Point> &P, Point A) // 0 (n) for any polygons
63 {
64   int cnt = 0, n = P.size();
65   for (int i = 0; i < n; ++i)
66   {
67     int j = (i + 1) % n;
68     if (chk_on_seg(A, P[i], P[j])) return 2; // on the edge
69     if (A.y >= min(P[i].y, P[j].y) && A.y < max(P[i].y, P[j].y)) // the intersection is on the right
70       cnt += dcmp(((A.y - P[i].y) * (P[j].x - P[i].x) / (P[j].y - P[i].y) + P[i].x) - A.x) > 0;
71   }
72   return cnt & 1;
73 }
74 int in_convex_Poly(vector<Point> &P, Point A) // 0 (log n) only for convex polygons
75 {
76   int n = P.size();
77   if (chk_on_seg(A, P[0], P[1]) || chk_on_seg(A, P[0], P[n - 1])) return 2;
78   if (dcmp(cross(P[n - 1] - P[0], A - P[0])) > 0 || dcmp(cross(P[1] - P[0], A - P[0])) < 0) return 0;
79   int l = 1, r = n - 2, res = -1;
80   while (l <= r)
81   {
82     int mid = (l + r) >> 1;
83     if (dcmp(cross(P[mid] - P[0], A - P[0])) >= 0) res = mid, l = mid + 1;
84     else r = mid - 1;
85   }
86   if (chk_on_seg(A, P[res], P[res + 1])) return 2;
87   if (dcmp(cross(P[res + 1] - P[res], A - P[res])) < 0) return 0;
88   return 1;
89 }
90 auto convex_hull(vector<Point> &P) // strict convex hull (<= 0)
91 {
92   int n = P.size();
93   sort(P.begin(), P.end(), [](Point &x, Point &y) {return x.x == y.x ? x.y < y.y : x.x < y.x;});
94   vector<Point> hull;
95   hull.resize(2 * n + 1);
96   int k = 0;
97   for (int i = 0; i < n; ++i)
98   {
99     while (k >= 2 && dcmp(cross(hull[k - 1] - hull[k - 2], P[i] - hull[k - 2])) <= 0) --k;
100    hull[k++] = P[i];
101  }
102  for (int i = n - 2, t = k; i >= 0; --i)
103  {
104    while (k > t && dcmp(cross(hull[k - 1] - hull[k - 2], P[i] - hull[k - 2])) <= 0) --k;
105    hull[k++] = P[i];
106  }
107  hull.resize(k - 1);
108  return hull;
109 }
110 LD diameter(vector<Point> &P)
111 {
112   int n = P.size();
113   if (n <= 1) return 0;
114   if (n == 2) return len(P[1] - P[0]);
115   LD res = 0;
116   for (int i = 0, j = 2; i < n; ++i)
117   {
118     while (dcmp(cross(P[(i + 1) % n] - P[i], P[j] - P[i]) - cross(P[(i + 1) % n] - P[i], P[(j + 1) % n] - P[i])) <= 0) j = (j + 1) % n;
119     res = max(res, max(len(P[j] - P[i]), len(P[j] - P[(i + 1) % n])));
120   }
121   return res;
122 }
123 template<typename Line = pair<Point, Point>>
124 LD half_plane(vector<Line> &Vec)
125 {
126   int n = Vec.size();
127   auto get_angle = [&] (Line line) -> LD {return atan2(line.second.y - line.first.y, line.second.x - line.first.x);};
128   sort(Vec.begin(), Vec.end(), [&] (Line A, Line B)
129   {
130     LD angA = get_angle(A), angB = get_angle(B);
131     return fabs(angA - angB) > eps ? angA < angB : cross(A.second - A.first, B.second - A.first) < 0;
132   });
133   int h = 1, t = 0;
134   auto check = [&] (Line x, Line y, Line z) -> bool
135   {
136     Point P = ll_inter_pt(y.first, y.second, z.first, z.second);
137     return dcmp(cross(x.second - x.first, P - x.first)) < 0;
138   };
139   vector<Line> q(n + 10); q[++] = Vec[0];
140   for (int i = 1; i < n; ++i)
141   {
142     if (get_angle(Vec[i]) - get_angle(Vec[i - 1]) < eps) continue;
143     while (h < t && check(Vec[i], q[t], q[t - 1])) --t;
144     while (h < t && check(Vec[i], q[h], q[h + 1])) ++h;
145     q[++] = Vec[i];
146   }
147   while (h < t && check(q[h], q[t], q[t - 1])) --t;
148   q[++] = q[h];
149   vector<Point> p;
150   for (int i = h; i < t; ++i) p.push_back(ll_inter_pt(q[i].first, q[i].second, q[i + 1].first, q[i + 1].second));
151   return area(p);
152 }
153 vector<Point> minkowski(vector<Point> &vecA, vector<Point> &vecB)

```

```

154 {
155     int n = vecA.size(), m = vecB.size();
156     vector<Point> A(n), B(m), C {vecA[0] + vecB[0]};
157     for (int i = 0; i < n; ++i) A[i] = vecA[(i + 1) % n] - vecA[i];
158     for (int i = 0; i < m; ++i) B[i] = vecB[(i + 1) % m] - vecB[i];
159     int posa = 0, posb = 0;
160     while (posa < n || posb < m)
161     {
162         if (posa == n) C.push_back(C.back() + B[posb++]);
163         else if (posb == m) C.push_back(C.back() + A[posa++]);
164         else if (dcmp(cross(A[posa], B[posb])) >= 0) C.push_back(C.back()
165             + A[posa++]);
166         else C.push_back(C.back() + B[posb++]);
167     }
168     return convex_hull(C);
169 }
170 bool chk_convex_inter_strict(vector<Point> A, vector<Point> B) //
171     Check if two convex polygons strictly intersect
172 {
173     vector<Point> negB;
174     for (auto p : B) negB.push_back(Point(-p.x, -p.y));
175     negB = convex_hull(negB);
176     vector<Point> C = minkowski(A, negB);
177     if (C.size() < 3) return false;
178     Point origin(0, 0);
179     return in_convex_Poly(C, origin) == 1;
180 }
181 bool chk_in_cir(Circle C, Point P) {return dcmp(len(P - C.O) - C.r) <= 0;
182 }
183 Point get_cir_pt(Circle C, LD theta) {return {C.O.x + C.r * cos(theta),
184     C.O.y + C.r * sin(theta)};
185 }
186 int chk_lc_inter(Point A, Point B, Circle C)
187 {
188     LD d = dis_seg(C.O, A, B);
189     if (dcmp(d - C.r) == 0) return 0; // tangent
190     if (dcmp(d - C.r) > 0) return -1; // separation
191     return 1; // intersection
192 }
193 int chk_cc_inter(Circle A, Circle B) // the number of tangent lines
194 {
195     LD d = len(A.O - B.O);
196     if (dcmp(A.r + B.r - d) < 0) return 4; // externally separate
197     if (dcmp(A.r + B.r - d) == 0) return 3; // externally tangent
198     if (dcmp(fabs(A.r - B.r) - d) == 0) return 1; // internally tangent
199     if (dcmp(fabs(A.r - B.r) - d) > 0) return 0; // one circle inside
200     the other
201     return 2; // intersection
202 }
203 pair<Point, Point> lc_inter(Point A, Point B, Circle C)
204 {
205     Point F = foot(C.O, A, B); LD d = dis(C.O, F);
206     Vector E = (B - A) / dis(A, B);
207     Point P1 = F - E * sqrt(C.r * C.r - d * d);
208     Point P2 = F + E * sqrt(C.r * C.r - d * d);
209     return {P1, P2};
210 }
211 pair<Point, Point> cc_inter(Circle A, Circle B)
212 {
213     Vector k = B.O - A.O;
214     LD d = len(k);
215     LD alpha = atan2(k.y, k.x), beta = acos((A.r * A.r + d * d - B.r * B.r) / (2 * A.r * d));
216     Point P1 = get_cir_pt(A, alpha - beta), P2 = get_cir_pt(A, alpha + beta);
217     return {P1, P2};
218 }
219 pair<Point, Point> tan_cir(Point P, Circle C)
220 {
221     LD d = len(C.O - P), theta = asin(C.r / d);
222     Vector E = (C.O - P) / d;
223     Vector P1 = P + (rotate(E, theta) * sqrt(d * d - C.r * C.r));
224     Vector P2 = P + (rotate(E, -theta) * sqrt(d * d - C.r * C.r));
225     return {P1, P2};
226 }
227 Circle tri_incir(Point A, Point B, Point C)
228 {
229     LD a = dis(B, C), b = dis(A, C), c = dis(A, B);
230     Point O = (A * a + B * b + C * c) / (a + b + c);
231     return {O, dis_seg(O, A, B)};
232 }
233 Circle tri_circum(Point A, Point B, Point C)
234 {
235     LD Bx = B.x - A.x, By = B.y - A.y, Cx = C.x - A.x, Cy = C.y - A.y;
236     LD D = 2 * (Bx * Cy - By * Cx);
237     LD x = (Cy * (Bx * Bx + By * By) - By * (Cx * Cx + Cy * Cy)) / D + A.x;
238     LD y = (Bx * (Cx * Cx + Cy * Cy) - Cx * (Bx * Bx + By * By)) / D + A.y;
239     Point P(x, y);
240     return Circle(P, dis(A, P));
241 }
242 auto get_tangents(Circle A, Circle B)
243 {
244     vector<pair<Point, Point>> tangents;
245     LD d = len(A.O - B.O), dif = A.r - B.r, sum = A.r + B.r;

```

```

246     if (dcmp(d - fabs(dif)) < 0) return tangents;
247     LD base = atan2(B.O.y - A.O.y, B.O.x - A.O.x);
248     if (dcmp(d - fabs(dif)) == 0)
249     {
250         tangents.push_back({get_cir_pt(A, base + (A.r < B.r ? pi : 0)),
251             get_cir_pt(A, base + (A.r < B.r ? pi : 0))});
252         return tangents;
253     }
254     LD theta = acos(dif / d);
255     tangents.push_back({get_cir_pt(A, base + theta), get_cir_pt(B, base + theta)});
256     tangents.push_back({get_cir_pt(A, base - theta), get_cir_pt(B, base - theta)});
257     if (dcmp(d - sum) == 0) tangents.push_back({get_cir_pt(A, base),
258         get_cir_pt(A, base)});
259     if (dcmp(d - sum) > 0)
260     {
261         theta = acos(sum / d);
262         tangents.push_back({get_cir_pt(A, base + theta), get_cir_pt(B,
263             base + theta + pi)});
264         tangents.push_back({get_cir_pt(A, base - theta), get_cir_pt(B,
265             base - theta + pi)});
266     }
267     return tangents;
268 }
269 LD tri_cir_area(Point A, Point B, Circle C)
270 {
271     Vector OA = A - C.O, OB = B - C.O;
272     LD S = cross(OA, OB), sign = dcmp(cross(OA, OB)) > 0 ? 1 : -1;
273     bool da = dcmp(len(OA) - C.r) < 0, db = dcmp(len(OB) - C.r) < 0;
274     if (dcmp(S) == 0) return 0;
275     if (da && db) return S * 0.5; // triangle
276     if (!da && !db)
277     {
278         if (chk_lc_inter(A, B, C) == 1) // arc + triangle + arc
279         {
280             auto [P1, P2] = lc_inter(A, B, C);
281             Vector OP1 = P1 - C.O, OP2 = P2 - C.O;
282             if (dis(A, P1) > dis(A, P2)) swap(P1, P2);
283             return cross(OP1, OP2) * 0.5 + sign * 0.5 * C.r * C.r * (
284                 angle(OA, OP1) + angle(OB, OP2));
285         }
286         else return sign * 0.5 * C.r * C.r * angle(OA, OB); // arc
287     }
288     else // triangle + arc
289     {
290         auto [P1, P2] = lc_inter(A, B, C);
291         if (chk_on_seg(P2, A, B)) swap(P1, P2);
292         Vector OP1 = P1 - C.O;
293         if (dcmp(len(OA) - C.r) < 0) return cross(OA, OP1) * 0.5 + sign *
294             0.5 * C.r * C.r * angle(OP1, OB);
295         else return cross(OP1, OB) * 0.5 + sign * 0.5 * C.r * C.r *
296             angle(OP1, OA);
297     }
298 }
299 LD cc_area(Circle C1, Circle C2)
300 {
301     int op = chk_cc_inter(C1, C2);
302     if (op <= 1) return pi * min(C1.r, C2.r) * min(C1.r, C2.r);
303     else if (op == 4) return 0;
304     else
305     {
306         LD d = dis(C1.O, C2.O);
307         LD alpha = 2 * acos((C1.r * C1.r - C2.r * C2.r + d * d) / (2 * C1.r * d));
308         LD beta = 2 * acos((C2.r * C2.r - C1.r * C1.r + d * d) / (2 * C2.r * d));
309         return 0.5 * (C1.r * C1.r * (alpha - sin(alpha)) + C2.r * C2.r * (beta - sin(beta)));
310     }
311 }

```

5 String

5.1 Hash

```

1 template <unsigned long long base = 13331>
2 class Hash
3 {
4     using u64 = unsigned long long;
5     vector <u64> pw, hsh;
6     public:
7     Hash(char *s)
8     {
9         int n = strlen(s);
10        pw.assign(n + 1, 0), hsh.assign(n + 1, 0);
11        pw[0] = 1; hsh[0] = 0;
12        for (int i = 1; i <= n; ++i) pw[i] = pw[i - 1] * base, hsh[i] =
13            hsh[i - 1] * base + s[i - 1];
14    }
15    u64 get(int l, int r) {return hsh[r] - hsh[l - 1] * pw[r - l + 1];}
16    u64 link(int l1, int r1, int l2, int r2) {return get(l1, r1) * pw[r2
17        - l2 + 1] + get(l2, r2);}
18    bool same(int l1, int r1, int l2, int r2) {return get(l1, r1) == get
19        (l2, r2);}
20 };

```

5.2 KMP

```

1 class KMP
2 {
3     vector <int> fail, ans;
4     void getfail(char *s) // Match a with b
5     {
6         int len = strlen(s);
7         fail.assign(len + 1, 0);
8         fail[0] = -1;
9         for (int i = 1; i < len; ++i)
10        {
11            int cnt = fail[i - 1];
12            while (cnt >= 0 && s[cnt + 1] != s[i]) cnt = fail[cnt];
13            if (s[cnt + 1] == s[i]) ++cnt;
14            fail[i] = cnt;
15        }
16    }
17    public:
18    auto get_pos(char *s, char *t)
19    {
20        getfail(t);
21        int lens = strlen(s), lent = strlen(t), cnt = -1;
22        for (int i = 0; i < lens; ++i)
23        {
24            while (cnt >= 0 && t[cnt + 1] != s[i]) cnt = fail[cnt];
25            if (t[cnt + 1] == s[i])
26            {
27                ++cnt;
28                if (cnt + 1 == lent) ans.push_back(i - lent + 2), cnt =
29                    fail[cnt];
30            }
31        }
32        return ans;
33    }
34 };

```

5.3 Manacher

```

1 int Manacher(char *s)
2 {
3     int n = strlen(s), cnt = 0, r = 0, mid = 0, ans = 0;
4     vector <char> a(2 * n + 5); vector <int> p(2 * n + 5);
5     a[++cnt] = '!'; a[++cnt] = '#';
6     for (int i = 0; i < n; ++i) a[++cnt] = s[i], a[++cnt] = '#';
7     a[++cnt] = '~';
8     for (int i = 2; i < cnt; ++i)
9     {
10        if (i <= r) p[i] = min(r - i + 1, p[mid * 2 - i]);
11        else p[i] = 1;
12        while (a[i - p[i]] == a[i + p[i]]) ++p[i];
13        if (i + p[i] > r) r = i + p[i] - 1, mid = i;
14        ans = max(ans, p[i]);
15    }
16    return ans - 1;
17 }

```

5.4 Trie

5.4.1 Trie

```

1 struct Trie
2 {
3     int n, m, cnt; //m total len
4     vector <vector <int>> ch; vector <int> vis;
5     public:
6     Trie(int n, int m) : n(n), m(m), ch(m, vector <int> (26, 0)), vis(m)
7     {cnt = 0;}
8     void insert(char *s)
9     {
10        int u = 0, len = strlen(s);
11        for (int i = 0; i < len; ++i)
12        {
13            int c = s[i] - 'a';
14            if (!ch[u][c]) ch[u][c] = ++cnt;
15            u = ch[u][c];
16        }
17        ++vis[u];
18    }
19    int query(char *s)
20    {
21        int u = 0, len = strlen(s);
22        for (int i = 0; i < len; ++i)
23        {
24            int c = s[i] - 'a';
25            if (!ch[u][c]) return 0;
26            u = ch[u][c];
27        }
28        return vis[u];
29    }
30 };

```

5.4.2 01-Trie

```

1 class Trie
2 {
3     int n, cnt;
4     vector <vector <int>> ch;
5     vector <int> val, w;
6     public :
7     Trie(int n, int lg) : n(n), val(2 * lg * n + 1, 0), w(2 * lg * n + 1,
8         0), ch(2 * lg * n + 1, vector <int> (2, 0)) {cnt = 1;}
9     void pushup(int u)
10    {
11        w[u] = val[u] = 0;
12        //w[u] Number of values (weights) on the edge between node u and
13        //its parent node
14        //val[u] XOR sum maintained by the subtree rooted at u
15        if (ch[u][0]) w[u] ^= w[ch[u][0]], val[u] ^= val[ch[u][0]] << 1;
16        if (ch[u][1]) w[u] ^= w[ch[u][1]], val[u] ^= (val[ch[u][1]] << 1)
17        | w[ch[u][1]];
18    }
19    void modify(int &u, int v, int dep)
20    {
21        if (!u) u = ++cnt;
22        w[u] ^= 1;
23        if (dep < 0) return ;
24        modify(ch[u][v & 1], v >> 1, dep - 1);
25        pushup(u);
26    }
27    void erase(int u, int v, int dep)
28    {
29        if (!u) return ;
30        w[u] ^= 1;
31        if (dep < 0) return ;
32        erase(ch[u][v & 1], v >> 1, dep - 1);
33        pushup(u);
34    }
35    void add(int u) // add 1 in [1,n]
36    {
37        swap(ch[u][0], ch[u][1]);
38        if (ch[u][0]) add(ch[u][0]);
39        pushup(u);
40    }
41 };

```

5.5 Aho-Corasick Automaton

```

1 class AC
2 {
3     int n, m, cnt; //m total len
4     vector <vector <int>> tr; vector <int> val;
5     public :
6     Trie(int n, int m) : n(n), m(m), tr(m + 1, vector <int> (26, 0)),
7         val(m + 1), fail(m + 1) {cnt = 1;}
8     void insert(char *s)
9     {
10        int n = strlen(s + 1), u = 1;
11        for (int i = 1; i <= N; ++i)
12        {
13            if (!tr[u][s[i] - 'a']) tr[u][s[i] - 'a'] = ++cnt;

```

```

13     u = tr[u][s[i] - 'a'];
14 }
15 ++val[u];
16 }
17 void build()
18 {
19     for (int i = 0; i < 26; ++i) tr[0][i] = 1;
20     queue<int> q; q.push(1);
21     while (!q.empty())
22     {
23         int u = q.front(); q.pop();
24         for (int i = 0; i < 26; ++i)
25         {
26             if (!tr[u][i]) tr[u][i] = tr[fail[u]][i];
27             else fail[tr[u][i]] = tr[fail[u]][i], q.push(tr[u][i]);
28         }
29     }
30 }
31 int query(char *s)
32 {
33     int n = strlen(s + 1), u = 1, res = 0;
34     for (int i = 1; i <= n; ++i)
35     {
36         u = tr[u][s[i] - 'a'];
37         for (int j = u; j && ~val[j]; j = fail[j]) res += val[j],
38         val[j] = -1;
39     }
40     return res;
41 }
42 /*
43 s :
44 a
45 aa
46 aa
47 aaa
48 t :
49 aaaa
50 ans : 4
51 */

```

5.6 SA

```

1 struct SA
2 {
3     string s;
4     vector<int> sa, rk, ht;
5     // all 0-base including sa
6     // suffix order
7     // rank of suffix i
8     // LCP(sf[i], sf[i+1])
9     vector<int> tmp;
10    int n;
11    SA(string &t) {init(t);}
12    inline void tSort(int m) //size of char set (base sort)
13    {
14        vector<int> tmp1(m + 1, 0);
15        for (int i = 0; i < n; ++i) ++tmp1[rk[tmp[i]]];
16        for (int i = 1; i <= m; ++i) tmp1[i] += tmp1[i - 1];
17        for (int i = n - 1; i >= 0; --i) sa[--tmp1[rk[tmp[i]]]] = tmp[i];
18    }
19    inline void init(string &t)
20    {
21        s = t; n = s.size();
22        sa.assign(n, 0); rk.assign(n, 0); ht.assign(n, 0); tmp.assign(n, 0);
23        for (int i = 0; i < n; ++i) rk[i] = s[i], tmp[i] = i;
24        int m = 127; tSort(m);
25        for (int k = 1, p = 0; p < n; k <= 1)
26        {
27            p = 0;
28            for (int i = n - k; i < n; ++i) tmp[p++] = i;
29            for (int i = 0; i < n; ++i)
30                if (sa[i] >= k) tmp[p++] = sa[i] - k;
31            tSort(m);
32            vector<int> old_rk = rk;
33            rk[sa[0]] = p = 1;
34            for (int i = 1; i < n; ++i)
35            {
36                int a = sa[i], b = sa[i - 1];
37                if (old_rk[a] == old_rk[b] && (a + k < n ? old_rk[a + k]
38                : 0) == (b + k < n ? old_rk[b + k] : 0))
39                    rk[a] = p;
40                else
41                    rk[a] = ++p;
42            }
43            m = p;
44            if (p == n) break;
45        }
46        for (int i = 0; i < n; ++i) --rk[i];
47        int h = 0;
48        for (int i = 0; i < n; ++i)

```

```

48    {
49        if (rk[i] == 0) continue;
50        int j = sa[rk[i] - 1];
51        while (i + h < n && j + h < n && s[i + h] == s[j + h]) ++h;
52        ht[rk[i] - 1] = h;
53        if (h > 0) --h;
54    }
55 }
56 inline void clear()
57 {
58     s.clear(); sa.clear(); rk.clear(); ht.clear(); tmp.clear();
59     n = 0;
60 }
61 inline int size() const {return n;}
62 inline int operator[] (int p) const {return sa[p];}
63 };

```

5.7 SAM

```

1 class SAM
2 {
3     class node
4     {
5     public: int ch[26], len, fa;
6         node(const int &L = 0) {memset(ch, 0, sizeof(ch)); fa = 0; len = L;}
7     };
8     public:
9     vector<node> t; int lst;
10    void GetParentTree(vector<vector<int>> &G)
11    {
12        G.resize(t.size());
13        for (unsigned i = 1; i < t.size(); ++i) G[t[i].fa].push_back(i);
14    }
15    void extend(const int &c)
16    {
17        int p = lst, np = lst = t.size();
18        t.push_back(node(t[p].len + 1));
19        for (; p && t[p].ch[c]; p = t[p].fa) t[p].ch[c] = np;
20        if (!p) t[np].fa = 1;
21        else
22        {
23            int v = t[p].ch[c];
24            if (t[v].len == t[p].len + 1) t[np].fa = v;
25            else
26            {
27                int nv = t.size(); t.push_back(t[v]);
28                t[nv].len = t[p].len + 1;
29                for (; p && t[p].ch[c] == v; p = t[p].fa) t[p].ch[c] =
30                nv;
31                t[np].fa = t[v].fa = nv;
32            }
33        }
34    }
35    SAM() {t.assign(2, node()); lst = 1;}
36    inline void clear() {t.assign(2, node()); lst = 1;}
37    inline int next(int p, int c) {return t[p].ch[c];}
38    inline int Len(int p) {return t[p].len;}
39 };

```

6 Other

6.1 Fast I/O

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 constexpr int MAX = 1e5 + 5;
4 constexpr int MOD = 1e9 + 7;
5 constexpr int INF = 0x3f3f3f3f;
6 using i64 = long long;
7 using u64 = unsigned long long;
8 using pii = pair<int, int>;
9 using vi = vector<int>;
10 using vii = vector<pii>;
11 using LD = long double;
12 inline int read()
13 {
14     int s = 0; int f = 1;
15     char ch = getchar();
16     while ((ch < '0' || ch > '9') && ch != EOF)
17     {
18         if (ch == '-') f = -1;
19         ch = getchar();
20     }
21     while (ch >= '0' && ch <= '9')
22     {
23         s = s * 10 + ch - '0';
24         ch = getchar();
25     }
26     return s * f;
27 }
28 inline void write(int x)
29 {
30     if (x < 0) {putchar('-'); write(-x); return;}
31     if (x > 9) write(x / 10);
32     putchar(x % 10 + '0');
33 }
34 int main()
35 {
36     //freopen(".in", "r", stdin);
37     //freopen(".out", "w", stdout);
38     return 0;
39 }

```

6.2 Random Number Generator

```

1 int rd(int a, int b)
2 {
3     static std::mt19937 gen(std::random_device{}());
4     std::uniform_int_distribution<int> dist(a, b);

```

```

5     return dist(gen);
6 }

```

6.3 Execution

```

1 #!/bin/bash
2 ulimit -s 102400
3 g++ -std=c++17 -O2 -Wall "$1" -o main
4 ./main < in.txt > out.txt

```

```

1 # Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass
2 # new file : `type nul > filename.cpp`
3 # run : `.\run.ps1 filename.cpp`
4 g++ -std=c++17 -O2 -Wall $args[0] -o main
5 cat in.txt | .\main | Out-File -FilePath out.txt

```

6.4 Comparsion

```

1 #!/bin/bash
2 for ((i=1; ; i++)); do
3     ./gen > input.txt # generator
4     ./code < input.txt > output1.txt # your code
5     ./std < input.txt > output2.txt # std code
6     if diff output1.txt output2.txt; then # compare
7         echo "Test $i: Accepted"
8     else
9         echo "Test $i: Wrong Answer"
10        echo "Input:"
11        cat input.txt
12        echo "Your Output:"
13        cat output1.txt
14        echo "Standard Output:"
15        cat output2.txt
16        break
17    fi
18 done

```

6.5 Python

```

1 import sys
2 sys.set_int_max_str_digits(value) # set big number
3 sys.setrecursionlimit(deep) # set deeper recursion
4 lst = sorted(lst, key = lambda x : x[1]) # sort by the second element

```