

2
4
5
1 4 5 3 2
4
4
2 2 4 3

Sample Output

1 4
1 2

Explanation

Sunny and Johnny make the following two trips to the parlor:

1. The first time, they pool together $m = 4$ dollars. Of the five flavors available that day, flavors 1 and 4 have a total cost of $1 + 3 = 4$.
2. The second time, they pool together $m = 4$ dollars. Of the four flavors available that day, flavors 1 and 2 have a total cost of $2 + 2 = 4$.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int t,n,m,c=0;
4     scanf("%d",&t);
5     for (int i=0;i<t;i++){
6         c=0;
7         scanf("%d\n%d",&m,&n);
8         int arr[n];
9         for(int j=0;j<n;j++){
10             scanf("%d",&arr[j]);
11         }
12         for(int a=0;a<n;a++){
13             for(int b=a+1;b<n;b++){
14                 if(arr[a]+arr[b]==m){
15                     printf("%d %d\n",a+1,
16                         b+1);
17                     c=1;break;
18                 }
19             }
20         }
21         if(c==1)break;
22     }
23     return 0;}
```

	Input	Expected	Got	
✓	2 4 5 1 4 5 3 2 4 4 2 2 4 3	1 4 1 2	1 4 1 2	✓

Passed all tests! ✓

3 204 205 206 207 208 203 204 205 206

3 204 204 205 206 207 205 208 203 206 205 206 204

Sample Output

4 205 206

Explanation

204 is present in both arrays. Its frequency in *arr* is 2, while its frequency in *brr* is 3. Similarly, 205 and 206 occur twice in *arr*, but three times in *brr*. The rest of the numbers have the same frequencies in both lists.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,m,c,c1=0,co;
5     scanf("%d",&n);
6     int arr[n];
7     for(int a=0;a<n;a++){
8         scanf("%d",&arr[a]);
9     }
10    scanf("%d",&m);
11    int brr[m],ans[m];
12    for(int b=0;b<m;b++){
13        scanf("%d",&brr[b]);
14    }
15    for(int j=0;j<m;j++)
16    {
17        c=0;
18        for(int i=0;i<n;i++){
19            if(arr[i]==brr[j]){
20                c++;
21                arr[i]=-1;
22                break;
23            }
24        }
25        if(c==0){
26            ans[c1]=brr[j];
27            c1++;
28        }
29    }
30    for(int a=0;a<c1;a++){
31        co=0;
32        for(int b=0;b<c1;b++){
33            if(ans[b]<ans[a])
34                co++;
35        }
36        int temp=ans[a];
37        ans[a]=ans[co];
38        ans[co]=temp;
39    }
40    for(int i=0;i<c1;i++)
41        printf("%d ",ans[i]);
42 }
```

Input

✓ 10
203 204 205 206 207 208 203 204 205 206

13

203 204 204 205 206 207 205 208 203 206 205

Passed all tests! ✓

Let t be the number of test cases and n be the size of the array.

For each test case, you are given t and n . The array arr is of size n . The array arr is given in the next line.

Sample Input 1:

3
5

1 1 4 1 1
4

2 0 0 0
4

0 0 2 0

Sample Output 1:

YES

YES

YES

Explanation 1:

In the first test case, $arr[2] = 4$ is between two subarrays summing to 2.

In the second case, $arr[0] = 2$ is between two subarrays summing to 0.

In the third case, $arr[2] = 2$ is between two subarrays summing to 0.

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int t,n,ls,rs,m;
5     scanf("%d",&t);
6     for(int i=0;i<t;i++){
7         ls=0;
8         rs=0;
9         scanf("%d",&n);
10        int arr[n];
11        for(int j=0;j<n;j++){
12            scanf("%d",&arr[j]);
13        }
14        m=n/2;
15        if (arr[m]==0){
16            for(m=0;arr[m]==0 && m<n;m++){
17                for(int j=0;j<=m;j++){
18                    ls=ls+arr[j];
19                }
20                for(int j=m;j<n;j++){
21                    rs=rs+arr[j];
22                }
23                printf("%s\n",(ls==rs)?"YES":"NO");
24            }
25        }
26        return 0;
27    }
28 }

```

	Input	Expected	Got	
✓	3	YES	YES	✓
	5	YES	YES	
	1 1 4 1 1	YES	YES	
	4			
	2 0 0 0			
	4			
	0 0 2 0			
✓	2	NO	NO	✓
	3	YES	YES	
	1 2 3			
	4			
	1 2 3 3			

Passed all tests! ✓