

# Assignment3

---

12110208宋子烨

---

## Statement

Since the model I wrote by myself got a quite bad accuracy, I referred a github open source code and made some necessary modifications to generate the results image. both codes that I wrote and I referred are available in my pull request. the link of the github open source code I referred is [yihong-chen/neural-collaborative-filtering: pytorch version of neural collaborative filtering](https://github.com/yihong-chen/neural-collaborative-filtering_pytorch_version_of_neural_collaborative_filtering). ([github.com](https://github.com)).

## Compare the three methods:

### 1. Training Loss:

- NeuMF's training loss remains relatively stable throughout the training process with minor fluctuations.
- GMF exhibits larger fluctuations in training loss, with occasional spikes at certain iterations.
- MLP shows noticeable fluctuations in training loss, particularly in the middle stages, but the overall trend is decreasing.

### 2. HR@10 (Hit Ratio @ 10):

- NeuMF achieves the highest HR@10 throughout the training process, showing significant improvement from initial to final iterations, reaching approximately 0.65.
- GMF and MLP have comparable HR@10 values, with GMF slightly outperforming MLP, reaching around 0.58 and 0.57, respectively, at the final iteration.

### 3. NDCG@10 (Normalized Discounted Cumulative Gain @ 10):

- NeuMF also outperforms in NDCG@10 throughout the training process, reaching approximately 0.4 at the final iteration.
- GMF and MLP exhibit similar trends in NDCG@10, with GMF slightly higher than MLP, reaching approximately 0.36 and 0.35, respectively, at the final iteration.

## Ablation Study Analysis:

The impact of different layer configurations on HR@10 and NDCG@10 for MLP models from the ablation study table is as follows:

### 1. Layer Configuration: [16, 64, 32, 16, 8]:

- HR: 0.6396
- NDCG: 0.3705
- This configuration performs the best among all, with more layers and complex parameters, leading to superior model performance.

### 2. Layer Configuration: [16, 32, 16, 8]:

- HR: 0.6257
- NDCG: 0.3607

- With one fewer layer compared to the previous configuration, there's a slight performance drop, although still relatively high.

### 3. Layer Configuration: [16, 16, 8]:

- HR: 0.6076
- NDCG: 0.3474
- Further reduction in the number of layers results in continued performance decline.

### 4. Layer Configuration: [16, 8]:

- HR: 0.5803
- NDCG: 0.3245
- With the minimum number of layers, performance is the lowest but still noticeable.

## Number of Negatives

Regarding the number of negatives, I have written code to generate this part of the model results chart. However, due to GPU and time constraints, I am unable to complete the model training and provide the data to generate these line charts. You can find the code for this part at the end of my code.

## Conclusion:


### 1. Method Comparison:

- Overall, NeuMF outperforms GMF and MLP in both HR@10 and NDCG@10 metrics.
- GMF slightly outperforms MLP, but their performance is relatively close.

### 2. Ablation Study:

- Increasing the number of layers improves MLP's performance, indicating that more layers lead to a more complex model and better performance.
- However, increasing layers also increases computational complexity and training time, necessitating a trade-off between performance and resources.

## The output screenshots are illustrated below:



轮数 19: HR = 0.5802980132450332, NDCG = 0.32449722176454476

层配置: [16, 64, 32, 16, 8], HR: 0.6396, NDCG: 0.3705

层配置: [16, 32, 16, 8], HR: 0.6257, NDCG: 0.3607

层配置: [16, 16, 8], HR: 0.6076, NDCG: 0.3474

层配置: [16, 8], HR: 0.5803, NDCG: 0.3245