



**PRIME INTUIT**

Finishing School

# Pandas – Data Frame Objects

**DataFrame is a 2-dimensional labeled data structure with columns of potentially different types. You can think of it like a spreadsheet or SQL table, or a dict of Series objects.**



# Pandas – Data Frame Objects

**DataFrame is a 2-dimensional labeled data structure with columns of potentially different types. You can think of it like a spreadsheet or SQL table, or a dict of Series objects.**



**PRIME INTUIT**

Finishing School

# Pandas – Data Frame Objects

**Import Numpy as np**

**Import Pandas as pd**

**#Creating Dataframe Objects**

**Arr = np.random.randint(0, 10, (5, 3))**

**Arr**

**Df = pd.DataFrame(arr)**

**Df**

**Df.values**

**Df.index**

**Df.columns**

**Df.values[0]**



# Pandas – Data Frame Objects

```
Df.index = ['R1', 'R2', 'R3', 'R4', 'R5']
```

```
Df.columns = [c1, c2, c3]
```

**DF**

Implicitly obtain the appropriate locks for your application at the point at which they are needed. An operation that reads an object will obtain a read lock; an operation that modifies an object will obtain a write lock.

**Explicit Lock:** - Lock is explicitly requested for a record or table.

**Implicit Lock:** - Lock is implied but is not acquired

```
Df.loc[R3, C2]
```

```
Df.iloc[2, 1]
```

```
Df.iloc[2:4, 1:3]
```



# Pandas – Data Frame Objects

`Df.loc = ['R3': 'R5', 'c2' : 'c3']`

`Df.iloc[0]`


`Type(df.iloc[0])` # you can think of df as a collection of series in both x and y axis

`Df.iloc[:, 0]`

`Df.shape`

`Df.T`

# Transpose





# Pandas – Data Frame Objects

# Write a function to create data frame with n rows and n columns

Def create\_df(nrows, ncols, maxrand = 10):

arr = np.random.randint(0, maxrand, (nrows, ncols))

df = pd.DataFrame(arr)

df.index = ['R' + str(x) for x in np.arange(1, nrows + 1)]

df.coloumns = ['C' + str(x) for x in np.arange(1, ncols + 1)]

return df

Create\_df(5, 3)

Create\_df(2, 5)

```
[27] def create_df(nRows, nCols, maxRand=10):  
    arr = np.random.randint(0, maxRand, (nRows, nCols))  
    df = pd.DataFrame(arr)  
    df.index = ['R' + str(x) for x in np.arange(1, nRows+1)]  
    df.columns = ['C' + str(x) for x in np.arange(1, nCols+1)]  
    return df
```



# Pandas – Data Frame Objects

## # Creating a Data Frame using multiple Series

```
mass1 = pd.Series((0.33, 4.07, 5.97, 0.642, 1090, 568, 86.0, 102, 0.0146, 0.000292), index = ['mercury', 'venus', 'earth', 'mars', 'jupiter', 'saturn', 'uranus', 'neptune', 'pluto', 'eris'])
#print(mass1)
dia1 = pd.Series((4079, 12104, 12756, 3475, 6792, 142904, 120536, 51110, 49528, 2370, 2326), index = ['mercury', 'venus', 'earth', 'moon', 'mars', 'jupiter', 'saturn', 'uranus', 'neptune', 'pluto', 'eris'])
#print(dia1)
```

```
Df = pd.DataFrame({'mass' : mass1, 'diameter', dia1})
```

Df

```
df['mass']
```

```
Df['diameter']
```

```
Df['earth']
```



# Pandas – Data Frame Objects

**# Creating a Data Frame using multiple Series**

**Df['mass']['earth']**

**Df.mass.earth**

**# Creating a new coloumn**

**Df['pop'] = 0**

**Df**

**Df['pop']['earth'] = 8000000000**

**df**





# Pandas – Data Frame Objects

# Creating a Data Frame using multiple Series

Df['mass'] == df.mass

df['mass'] is df.mass

Df[pop] is df.pop

Df.pop                      # pop function pops an item from the data frame

Df.loc ['earth']

Df.loc[:, mass]



# Pandas – Data Frame Objects

**# Creating a new row**

**Df.loc['mean'] = 0**

**Df**

**Df.drop('mean')**

**Df.drop('pop', axis =1)**

**df**

**Df.drop('mean', inplace = True)**

**Df.drop('pop', axis =1, inplace = True)**

**df**

**Np.mean(df['mass'])**

**Df.loc['mean'] = [np.mean(df['mass']), np.mean(df['diameter'])]**

**df**



# Pandas – Data Frame Objects

# Creating a function to create a new row

```
Def create_mean_row(df):  
    df.loc['col_mean'] = [np.mean(df[col1]) for col in df.columns]  
    return df
```

Create\_mean\_row(df)

```
Def create_mean_row(df):  
    df.loc['col_mean1'] = df.mean()  
    return df
```

Create\_mean\_row(df)

Df = create\_df(5, 3)

Df

Df.mean()



# Pandas – Data Frame Objects

# Creating a function to create a new row

# what if I want to compute mean for the row:

`Df.mean(axis =1)`

`Df['row_mean'] = df.mean(axis =1)`

`Df`

`Df.loc['col_mean'] = df.mean()`

`Df`

`Df.median()`

`Df.min()`

`Df.max()`

`Df.quantile(0.25)`

`Df.drop('row_mean', axis =1)`



# Pandas – Data Frame Objects

## # Other ways of computing the details

### **Df.describe()**

```
mass1 = pd.Series((0.33, 4.07, 5.97, 0.642, 1090, 568, 86.0, 102, 0.0146, 0.000292), index = ['mercury', 'venus', 'earth', 'mars', 'jupiter', 'saturn', 'uranus', 'neptune', 'pluto', 'eris'])
```

```
#print(mass1)
```

```
dia1 = pd.Series((4079, 12104, 12756, 3475, 6792, 142904, 120536, 51110, 49528, 2370, 2326), index = ['mercury', 'venus', 'earth', 'moon', 'mars', 'jupiter', 'saturn', 'uranus', 'neptune', 'pluto', 'eris'])
```

```
#print(dia1)
```

```
Planets = pd.DataFrame({'mass' : mass1, 'diameter', dia1})
```

```
Planets.describe()
```



# Pandas – Data Frame Objects

Seaborn – Planets data set

Import seaborn as sns

```
Df = sns.load_dataset('planets')
```

```
df.info()
```

```
Df.head()
```

```
Df.tail()
```

```
Df.describe()
```



# Pandas – Data Frame Objects

**# Task 1: Go through each row of the df and delete (drop) if any of the cols is null**

**# Regular way**

```
For r in df.index:  
    for c in df.columns:  
        if pd.isnull(df.loc[r, c]):  
            df.drop(r, inplace = True)  
            break
```

**Df.describe()**

```
For i, r in df.iterrows():  
    print(i)  
    print(r)  
    break
```



# Pandas – Data Frame Objects

**# Task 1: Go through each row of the df and delete (drop) if any of the cols is null**

```
For l, r in df.iterrows():  
    print(pd.isnull(r))  
    break
```

```
For l, r in df.iterrows():  
    print(pd.isnull(r).any()):  
    break
```

```
For l, r in df.iterrows():  
    if pd.isnull(r).any():  
        df.drop(l, inplace = True)
```





# Pandas – Data Frame Objects

**Df.describe()**

**# most efficient way**

**Df.dropna(inplace = true)**

**Df.describe()**


**# Task 2: filter rows for planets found in 2010s and methods is 'Radial Velocity' & 'Transit' & distance is > 75%**



# Pandas – Data Frame Objects

**# Method: 1**

```
Df_1 = df.copy()
Per_75 = df.distance.quantile(0.75)
For l, r in df_1.iterrows():
    if r['year'] < 2010:
        df_1.drop(l, inplace = True)
        continue
    if r['method'] != 'Radial Velocity' and r['method'] != 'Transit':
        df_1.drop(l, inplace = True)
        continue
    if r['distance'] < per_75:
        df_1.drop(l, inplace = True)
        continue
Df_1.describe()
df_1.head()
Per_75
Df_1.tail()
```



**# Method: 2 using indexing with conditions**

```
Df_2 = df.copy()
Df_3 = df_2[
    (df_2['year'] >= 2010) &
    ((df_2['method'] == 'Radial Velocity') | (df_2['method'] == 'Transit')) &
    (df_2['distance'] > per_75)
]

Df.describe()
```

**# Task 3: Modify the method column to have only the abbreviation of each method**



# Pandas – Data Frame Objects

# Method: 1

```
Df_2.method.unique()
```

```
S = 'Radial Velocity'
```

```
S.split(' ')
```

```
[x[0] for x in S.split(' ')]
```

```
' '.join([x[0] for x in S.split(' ')])
```

```
Short_Names = {}
```

```
For s in df.method.unique():
```

```
    short_name[s] = ' '.join([x[0] for x in S.split(' ')])
```

```
Print(Short_Name)
```



# Pandas – Data Frame Objects

**# Method: 1 Continued.....**

**For l, r in df.iterrows():**

**df.loc[l, 'short\_method'] = Short\_Names.get(r['method'], r['method'])**

**# new column**

**Get names form short\_names dict by using get function**

**Df.head()**

**Df.tail()**



# Pandas – Data Frame Objects

**# Method: 2**

```
Df5 = sns.load_dataset('planets')
```

```
Def Shorten_method(s):
```

```
    Short_Names.get(s,s)
```

```
df5['Short_Method'] = df['method'].apply(Shorten_method)
```

**#Apply Shorten\_method to each column in df5/method column take the result and put it into Short\_Method column.**

**# Task 4: count the number of planets discovered for each method type**



# Pandas – Data Frame Objects

**# Task 4: count the number of planets discovered for each method type**

**# Step 1. Split the data frame into smaller chunks (in this case they should have the same method name)**

**# Step 2. Apply some function in each smaller chunk (count function)**

**# Step 3. Aggregate the results from each chunk together.**



# Pandas – Data Frame Objects

## # Method 1

```
D = {}    # for printing
For m in df5.method.unique():
    df5[df5.method == m]           # aggregation
    df5[df5.method == m].count()   # count
    print(m)
    print(df5[df5.method == m].count())    # print all the coloums

    print(df5[df5.method == m]['method'].count())    # aggregation
    d[m] = df[df.method == m]['method'].count()
print(d)
```





# Pandas – Data Frame Objects

## # Method 2

```
Df5.groupby('method').count()
```

```
# grouping based on column 'method'
```

```
Df5.groupby('method')['method'].count()
```

```
# grouping based on column 'method' and count on column 'method'
```

```
Print(d)
```

```
Df5.groupby('method')['distance'].mean()
```

**# Task 5: Find out what fraction of planets have been found in the last decade(2010s) across each method type**



# Pandas – Data Frame Objects

**# Task 5: Find out what fraction of planets have been found in the last decade(2010s) across each method type**

**# Step 1: Filter the data for given condition ( planets found in last decade)**

**# Step 2: Split based on the method**

**# Step 3: Apply count function**

**# Step 4: Aggregate the final results**



# Pandas – Data Frame Objects

**# Task 5: Find out what fraction of planets have been found in the last decade(2010s) across each method type**

```
Df5[df5.year >= 2010]
```

```
Df5[df5.year >= 2010].groupby('method')
```

```
Df5[df5.year >= 2010].groupby('method')['method'].count()
```

```
S_2010s = Df5[df5.year >= 2010].groupby('method')['method'].count()
```

```
S_alltime = Df5.groupby('method')['method'].count()
```

```
S_2010s / s_alltime
```