```
1 import numpy as np
1 \times (2,3) #2d array
2 print(x)
3 print("----")
4 \text{ y=np.ones}((2,3,2)) #3d array
5 print(y)
   [[0. 0. 0.]
    [0. 0. 0.]]
    [[[1. 1.]
     [1. 1.]
     [1. 1.]]
    [[1. 1.]
     [1. 1.]
     [1. 1.]]]
1 7*y
   array([[[7., 7.],
           [7., 7.],
           [7., 7.]],
           [[7., 7.],
           [7., 7.],
           [7., 7.]]])
1 np.random.rand(2,3) #0-1
   array([[0.30023249, 0.20008134, 0.11240225],
           [0.80631065, 0.31349979, 0.42699784]])
1 #generate random
2 np.random.randn(2,3)
   array([[-0.87883443, -0.23482361, 0.0447543],
          [-0.64630004, -1.34078847, -0.4041143]])
1 np.random.randint(0,100,(2,3))
   array([[43, 89, 83],
          [77, 99, 75]])
1 np.arange(7,70,10) #step size at end
   array([ 7, 17, 27, 37, 47, 57, 67])
   np.linspace(1,100,5) #no of equally spaced at end
```

```
array([ 1. , 25.75, 50.5 , 75.25, 100. ])
1 x=np.array([[True,False],[False,True]])
2 print(x)
   [[ True False]
    [False True]]
1 str_array = np.array(['1.4','6.8','9.6','10.1'])
2 str_array
   array(['1.4', '6.8', '9.6', '10.1'], dtype='<U4')
1 str_array=np.array(str_array,dtype=float)
2 str_array
   array([ 1.4, 6.8, 9.6, 10.1])
   str_array=np.array(str_array,dtype=int)
2 str_array
   array([ 1, 6, 9, 10])
1 #indexing an array and fancy indexing
2 arr4=np.random.randint(0,100,(2,5,5))
3 arr4
   array([[[83, 64, 76, 74, 43],
           [78, 26, 13, 1, 38],
           [40, 47, 43, 78, 32],
            [4, 87, 98, 57, 70],
           [ 8, 45, 96, 2, 49]],
           [[35, 3, 80, 35, 78],
           [80, 53, 41, 62, 49],
           [90, 31, 48, 49, 26],
           [98, 21, 11, 83, 65],
            [96, 17, 37, 82, 94]]])
1 arr4.flatten()
   array([83, 64, 76, 74, 43, 78, 26, 13, 1, 38, 40, 47, 43, 78, 32, 4, 87,
          98, 57, 70, 8, 45, 96, 2, 49, 35, 3, 80, 35, 78, 80, 53, 41, 62,
          49, 90, 31, 48, 49, 26, 98, 21, 11, 83, 65, 96, 17, 37, 82, 94])
1 arr4[1,2:4,2:5]
2 #or
3 arr4[1,2:4,2:]
   array([[48, 49, 26],
          [11, 83, 65]])
```

```
1 arr4[1,3:5,1:4]
   array([[21, 11, 83],
          [17, 37, 82]])
1 arr4[:,4,:]
   array([[ 8, 45, 96, 2, 49],
          [96, 17, 37, 82, 94]])
1 arr4[:,2:4,2:4]
   array([[[43, 78],
           [98, 57]],
          [[48, 49],
           [11, 83]])
1 i=int(input("i "))
2 j=int(input("j "))
3 k=int(input("k "))
4 arr4[i,j,k]
   i 1
   j 1
   k 1
   53
1 arr4%2==0
   array([[[False, True, True, False],
           [ True, True, False, False, True],
           [ True, False, False, True, True],
           [ True, False, True, False, True],
           [ True, False, True, True, False]],
           [[False, False, True, False, True],
           [ True, False, False, True, False],
           [ True, False, True, False, True],
           [ True, False, False, False],
           [ True, False, False, True, True]]])
   str_array=np.array(arr4%2==0,dtype=int)
1
2
   str_array
   array([[[0, 1, 1, 1, 0],
           [1, 1, 0, 0, 1],
           [1, 0, 0, 1, 1],
           [1, 0, 1, 0, 1],
           [1, 0, 1, 1, 0]],
           [[0, 0, 1, 0, 1],
           [1, 0, 0, 1, 0],
           [1, 0, 1, 0, 1],
```

```
[1, 0, 0, 0, 0],
[1, 0, 0, 1, 1]]])
```

```
1 arre=arr4[arr4 % 2 == 0]
2 arre
   array([64, 76, 74, 78, 26, 38, 40, 78, 32, 4, 98, 70, 8, 96, 2, 80, 78,
           80, 62, 90, 48, 26, 98, 96, 82, 94])
1 arre=np.array(arr4[arr4 % 2 == 0])
2 arre
   array([64, 76, 74, 78, 26, 38, 40, 78, 32, 4, 98, 70, 8, 96, 2, 80, 78,
           80, 62, 90, 48, 26, 98, 96, 82, 94])
   arro=arr4[arr4\cdot\%\cdot2\cdot==\cdot1]
2
   arro
   array([83, 43, 13, 1, 47, 43, 87, 57, 45, 49, 35, 3, 35, 53, 41, 49, 31,
           49, 21, 11, 83, 65, 17, 37])
   arro=arr4[(arr4 \% 2 == 1)&(arr4 > 5)] # dont use and
1
2
   arro
   array([83, 43, 13, 47, 43, 87, 57, 45, 49, 35, 35, 53, 41, 49, 31, 49, 21,
           11, 83, 65, 17, 37])
```

Os completed at 1:53 PM

X