#### 1 mass1

mercury 0.330000 venus 4.070000 5.970000 earth mars 0.642000 jupiter 1090.000000 568.000000 saturn 86.000000 uranus neptune 102.000000 pluto 0.014600 eris 0.000292

dtype: float64

#### 1 dia1

mercury 4079 venus 12104 earth 12756 mars 3475 jupiter 6792 saturn 142904 uranus 120536 neptune 51110 pluto 49528 eris 2370 dtype: int64

```
1 df100 = pd.DataFrame(mass1,dia1)
2 df100
```

```
4079 NaN
12104 NaN
```

```
df100 = pd.DataFrame({'mass' : mass1 ,'dia' : dia1})
df100
```

	mass	dia
mercury	0.330000	4079
venus	4.070000	12104
earth	5.970000	12756
mars	0.642000	3475
jupiter	1090.000000	6792
saturn	568.000000	142904
uranus	86.000000	120536
neptune	102.000000	51110
pluto	0.014600	49528
eris	0.000292	2370

# 1 df100['mass']

0.330000 mercury 4.070000 venus earth 5.970000 mars 0.642000 1090.000000 jupiter saturn 568.000000 86.000000 uranus 102.000000 neptune pluto 0.014600 0.000292 eris Name: mass, dtype: float64

# 1 df100['dia']

4079 mercury venus 12104 earth 12756 mars 3475 6792 jupiter 142904 saturn uranus 120536 neptune 51110 pluto 49528 eris 2370 Name: dia, dtype: int64

```
1 df100['mass']['earth']
```

5.97

1 df100.mass.earth

5.97

- 1 #adding new column to df
- 2 df100['Population']=0

#### 1 df100

	mass	dia	Population	1
mercury	0.330000	4079	0	
venus	4.070000	12104	0	
earth	5.970000	12756	0	
mars	0.642000	3475	0	
jupiter	1090.000000	6792	0	
saturn	568.000000	142904	0	
uranus	86.000000	120536	0	
neptune	102.000000	51110	0	
pluto	0.014600	49528	0	
eris	0.000292	2370	0	

```
1 df100.Population.earth = 8000000000000000
```

/usr/local/lib/python3.7/dist-packages/pandas/core/generic.py:5516: SettingWithCopyWa A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: <a href="https://pandas.pydata.org/pandas-docs/stable/usself">https://pandas.pydata.org/pandas-docs/stable/usself</a>[name] = value

```
1 df100['Population']['mars'] = 1
```

/usr/local/lib/python3.7/dist-packages/ipykernel\_launcher.py:1: SettingWithCopyWarnir A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: <a href="https://pandas.pydata.org/pandas-docs/stable/us">https://pandas.pydata.org/pandas-docs/stable/us</a>
"""Entry point for launching an IPython kernel.

#### 1 df100

	mass	dia	Population
mercury	0.330000	4079	0
venus	4.070000	12104	0
earth	5.970000	12756	8000000000
mars	0.642000	3475	1
jupiter	1090.000000	6792	0
saturn	568.000000	142904	0
uranus	86.000000	120536	0
neptune	102.000000	51110	0
pluto	0.014600	49528	0
eris	0.000292	2370	0

1 df100['mass'] is df100.mass

True

1 df100.loc['earth',:]

mass 5.970000e+00 dia 1.275600e+04 Population 8.000000e+09 Name: earth, dtype: float64

1 df100['MeanMass']=0

1 df100

mass dia Population MeanMass 🧦

1 df100['MeanMass']=np.mean(df100.mass)

VGIIU3 7.070000 12107

1 df100

	mass	dia	Population	MeanMass
mercury	0.330000	4079	0	185.702689
venus	4.070000	12104	0	185.702689
earth	5.970000	12756	8000000000	185.702689
mars	0.642000	3475	1	185.702689
jupiter	1090.000000	6792	0	185.702689
saturn	568.000000	142904	0	185.702689
uranus	86.000000	120536	0	185.702689
neptune	102.000000	51110	0	185.702689
pluto	0.014600	49528	0	185.702689
eris	0.000292	2370	0	185.702689

1 df100.drop('MeanMass',axis=1)

	mass	dia	Population
mercury	0.330000	4079	0
venus	4.070000	12104	0
earth	5.970000	12756	8000000000
mars	0.642000	3475	1
jupiter	1090.000000	6792	0
saturn	568.000000	142904	0
uranus	86.000000	120536	0
neptune	102.000000	51110	0
pluto	0.014600	49528	0
eris	0.000292	2370	0

1 df100

	mass	dia	Population	MeanMass
mercury	0.330000	4079	0	185.702689
venus	4.070000	12104	0	185.702689
earth	5.970000	12756	8000000000	185.702689
mars	0.642000	3475	1	185.702689
jupiter	1090.000000	6792	0	185.702689
saturn	568.000000	142904	0	185.702689
uranus	86.000000	120536	0	185.702689
neptune	102.000000	51110	0	185.702689

1 df100.drop('MeanMass',axis=1,inplace=True)

9119 0.000E0E E010 0 100.10E000

#### 1 df100

	mass	dia	Population
mercury	0.330000	4079	0
venus	4.070000	12104	0
earth	5.970000	12756	8000000000
mars	0.642000	3475	1
jupiter	1090.000000	6792	0
saturn	568.000000	142904	0
uranus	86.000000	120536	0
neptune	102.000000	51110	0
pluto	0.014600	49528	0
eris	0.000292	2370	0

#### 1 df100.mean

<bound method NDFrame.\_add\_numeric\_operations.<locals>.mean of mass 0.330000 4079 mercury 4.070000 12104 0 venus earth 5.970000 12756 8000000000 0.642000 3475 1 mars jupiter 1090.000000 6792 0 568.000000 0 saturn 142904 0 uranus 86.000000 120536 neptune 102.000000 51110 0 pluto 0.014600 49528 0 eris 0.000292 2370 0>

```
1 df100.mean()
```

mass 1.857027e+02 dia 4.056540e+04 Population 8.000000e+08

dtype: float64

### 1 df100.median()

mass 5.02 dia 12430.00 Population 0.00

dtype: float64

### 1 df100.mean(axis=1)

mercury 1.359777e+03 4.036023e+03 venus earth 2.666671e+09 1.158881e+03 mars jupiter 2.627333e+03 4.782400e+04 saturn uranus 4.020733e+04 neptune 1.707067e+04 1.650934e+04 pluto eris 7.900001e+02

dtype: float64

### 1 df100.mean(axis=0)

mass 1.857027e+02 dia 4.056540e+04 Population 8.000000e+08

dtype: float64

### 1 df100.min()

mass 0.000292 dia 2370.000000 Population 0.000000

dtype: float64

## 1 df100.max()

mass 1.090000e+03 dia 1.429040e+05 Population 8.000000e+09

dtype: float64

### 1 df100.quantile(0.25)

mass 0.408 dia 4757.250 Population 0.000 Name: 0.25, dtype: float64

1 df100.shape

(10, 3)

1 df100.size

30

## 1 df100.describe()

	mass	dia	Population
count	10.000000	10.000000	1.000000e+01
mean	185.702689	40565.400000	8.000000e+08
std	362.663272	51585.854011	2.529822e+09
min	0.000292	2370.000000	0.000000e+00
25%	0.408000	4757.250000	0.000000e+00
50%	5.020000	12430.000000	0.000000e+00
75%	98.000000	50714.500000	0.000000e+00
max	1090.000000	142904.000000	8.000000e+09

# 1 df100.info()

<class 'pandas.core.frame.DataFrame'>
Index: 10 entries, mercury to eris
Data columns (total 3 columns):

# Column Non-Null Count Dtype
--- 0 mass 10 non-null float64
1 dia 10 non-null int64
2 Population 10 non-null int64

dtypes: float64(1), int64(2)
memory usage: 620.0+ bytes

#### 1 import seaborn as sb

- sb.load\_dataset('planets')
- 2 #https://github.com/mwaskom/seaborn-data/blob/master/planets.csv

	method	number	orbital_period	mass	distance	year	2
0	Radial Velocity	1	269.300000	7.10	77.40	2006	
1	Radial Velocity	1	874.774000	2.21	56.95	2008	
2	Radial Velocity	1	763.000000	2.60	19.84	2011	
3	Radial Velocity	1	326.030000	19.40	110.62	2007	
4	Radial Velocity	1	516.220000	10.50	119.47	2009	
1030	Transit	1	3.941507	NaN	172.00	2006	
1031	Transit	1	2.615864	NaN	148.00	2007	
1032	Transit	1	3 191524	NaN	174 ೧೧	2007	

df\_planets=sb.load\_dataset('planets')

<sup>2</sup> df\_planets

	method	number	orbital_period	mass	distance	year	•	
0	Radial Velocity	1	269.300000	7.10	77.40	2006		
1	Radial Velocity	1	874.774000	2.21	56.95	2008		
2	Radial Velocity	1	763.000000	2.60	19.84	2011		
3	Radial Velocity	1	326.030000	19.40	110.62	2007		
4	Radial Velocity	1	516.220000	10.50	119.47	2009		
1030	Transit	1	3.941507	NaN	172.00	2006		
1031	Transit	1	2.615864	NaN	148.00	2007		
1032	Transit	1	3.191524	NaN	174.00	2007		
1033	Transit	1	4.125083	NaN	293.00	2008		
1034	Transit	1	4.187757	NaN	260.00	2008		
1035 rows × 6 columns								

1 df\_planets.shape

(1035, 6)

1 df\_planets.size

6210

1 df\_planets.describe()

	number	orbital_period	mass	distance	year
count	1035.000000	992.000000	513.000000	808.000000	1035.000000
mean	1.785507	2002.917596	2.638161	264.069282	2009.070531
std	1.240976	26014.728304	3.818617	733.116493	3.972567
min	1.000000	0.090706	0.003600	1.350000	1989.000000
25%	1.000000	5.442540	0.229000	32.560000	2007.000000
50%	1.000000	39.979500	1.260000	55.250000	2010.000000
75%	2.000000	526.005000	3.040000	178.500000	2012.000000
max	7.000000	730000.000000	25.000000	8500.000000	2014.000000
_planet	s.info()				

```
1 df_
```

SEARCH STACK OVERFLOW

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1035 entries, 0 to 1034
Data columns (total 6 columns):
 #
     Column
                     Non-Null Count Dtype
 0
    method
                    1035 non-null
                                     object
                                     int64
 1
    number
                     1035 non-null
 2
    orbital_period 992 non-null
                                     float64
 3
    mass
                     513 non-null
                                     float64
 4
    distance
                     808 non-null
                                     float64
 5
                     1035 non-null
                                     int64
     year
dtypes: float64(3), int64(2), object(1)
memory usage: 48.6+ KB
```

```
1 for row in df_planets :
2
      for col in df planets :
3
          if pd.isnull(df_planets.loc(row,col)) :
              df_planets.drop(row,inplace=True)
4
5
              break
```

```
TypeError
                                          Traceback (most recent call last)
<ipython-input-70-90e78c5214a7> in <module>()
      1 for row in df planets:
            for col in df_planets :
      2
---> 3
                if pd.isnull(df_planets.loc(row,col)) :
                    df_planets.drop(row,inplace=True)
      5
                    break
TypeError: call () takes from 1 to 2 positional arguments but 3 were given
```

```
1 for row in df_planets.index :
2
      for col in df_planets.columns :
3
          if pd.isnull(df planets.loc[row,col]) :
```

```
df_planets.drop(row,inplace=True)
```

```
1 df_planets.describe()
```

	number	orbital_period	mass	distance	year	1
count	498.00000	498.000000	498.000000	498.000000	498.000000	
mean	1.73494	835.778671	2.509320	52.068213	2007.377510	
std	1.17572	1469.128259	3.636274	46.596041	4.167284	
min	1.00000	1.328300	0.003600	1.350000	1989.000000	
25%	1.00000	38.272250	0.212500	24.497500	2005.000000	
50%	1.00000	357.000000	1.245000	39.940000	2009.000000	
75%	2.00000	999.600000	2.867500	59.332500	2011.000000	
max	6.00000	17337.500000	25.000000	354.000000	2014.000000	

### 1 df\_planets.info()

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 498 entries, 0 to 784
Data columns (total 6 columns):
```

#	Column	Non-Null Count	Dtype	
0	method	498 non-null	object	
1	number	498 non-null	int64	
2	orbital_period	498 non-null	float64	
3	mass	498 non-null	float64	
4	distance	498 non-null	float64	
5	year	498 non-null	int64	
dtyp	es: float64(3),	int64(2), object(1)		

memory usage: 27.2+ KB

```
1 for rows,columns in df_planets.iterrows() : #used for traversing instead of for loop
2  print(rows)
3  print(columns)
```

4 break

0
method Radial Velocity
number 1
orbital\_period 269.3
mass 7.1
distance 77.4
year 2006

Name: 0, dtype: object

```
for columns,rows in df_planets.iterrows():
    #used for traversing instead of for loop
    if pd.isnull(rows).any():
        df.planets.drop(rows,inplace=True)
    break
```

# 1 df\_planets.info()

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 498 entries, 0 to 784
Data columns (total 6 columns):
```

#	Column	Non-Null Count	Dtype
0	method	498 non-null	object
1	number	498 non-null	int64
2	orbital_period	498 non-null	float64
3	mass	498 non-null	float64
4	distance	498 non-null	float64
5	year	498 non-null	int64
	C7 (C4/2)		141

dtypes: float64(3), int64(2), object(1)

memory usage: 27.2+ KB