

Rajalakshmi Engineering College

Name: Sweta Suresh
Email: 240701549@rajalakshmi.edu.in
Roll no: 2116240701549
Phone: 9344119216
Branch: REC
Department: I CSE FF
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 3_CY

Attempt : 1
Total Mark : 30
Marks Obtained : 25

Section 1 : Coding

1. Problem Statement

Write a program to check if a given string is perfect.

A perfect string must satisfy the following conditions:

The string starts with a consonant. The string alternates between consonants and vowels. Each consonant appears exactly once. Vowels can occur consecutively multiple times but should not be followed immediately by a consonant.

If the string satisfies all these conditions, print "True"; otherwise, print "False".

Input Format

The input consists of a string.

Output Format

The output prints "True" if the string is perfect. Otherwise, print "False".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: capacitor

Output: True

Answer

```
# You are using Python
def perfect(s):
    vowels="aeiou"
    consonants=set()
    if s[0] in vowels:
        return False
    prev='consonant' if s[0] not in vowels else 'vowel'
    if prev=='consonant':
        consonants.add(s[0])
    for i in range(1,len(s)):
        current=s[i]
        current2='vowel' if current in vowels else 'consonant'
        prevch=s[i-1]
        prev='vowel' if prevch in vowels else 'consonant'

        if prev == 'vowel' and current2 == 'consonant':
            return False
        if current2 == 'consonant':
            if current in consonants:
                return False
            consonants.add(current)
    return True
s=input().strip()
print("True" if perfect(s) else "False")
```

Status : Partially correct

Marks : 5/10

2. Problem Statement

Sarah is a technical writer who is responsible for formatting two important documents. Both documents contain a certain placeholder character that needs to be replaced with another character before they can be finalized. To ensure consistency in formatting, Sarah wants you to help her write a program that processes both documents by replacing the placeholder character with the new one.

Sarah also prefers a neat and structured output, so she wants you to ensure that both modified documents are printed in a single line, separated by a space, using the `format()` function.

Example

Input:

Hello

World

o

a

Output:

Hella World

Explanation:

Here the character 'o' is replaced with 'a' in the concatenated string.

Input Format

The first line contains `string1`, the first document.

The second line contains `string2`, the second document.

The third line contains `char1`, the placeholder character that needs to be replaced.

The fourth line contains `char2`, the new character that will replace the placeholder.

Output Format

The output displays a single line containing the modified string1 and string2, separated by a space.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: Hello

World

o

a

Output: Hella World

Answer

```
# You are using Python
```

```
x=input()
```

```
y=input()
```

```
l1=input()
```

```
l2=input()
```

```
a=x+" "+y
```

```
r=a.replace(l1,l2)
```

```
print(r)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Gina is working on a data analysis task where she needs to extract sublists from a given list of integers and find the median of each sublist. For each median found, she also needs to determine its negative index in the original list.

Help Gina by writing a program that performs these tasks.

Note: The median is the middle value in the sorted list of numbers, or the first value of the two middle values if the list has an even number of

elements.

Example

Input

10

1 2 3 4 5 7 8 9 10 11

3

1 5

2 6

3 10

Output

3 : -8

4 : -7

7 : -5

Explanation

For the first range (1 to 5), the sublist is [1, 2, 3, 4, 5]. The median is 3, and its negative index in the original list is -8.

For the second range (2 to 6), the sublist is [2, 3, 4, 5, 7]. The median is 4, and its negative index in the original list is -7.

For the third range (3 to 10), the sublist is [3, 4, 5, 7, 8, 9, 10, 11]. The median is 7, and its negative index in the original list is -5.

Input Format

The first line of input consists of an integer N, representing the number of elements in the list.

The second line consists of N space-separated integers representing the elements of the list.

The third line consists of an integer R, representing the number of ranges.

The next R lines each consist of two integers separated by space representing the start and end indices (1-based) of the ranges.

Output Format

The output consists of n lines, displaying "X : Y" where X is the median of the sublist and Y is the negative index in the original list.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10

1 2 3 4 5 7 8 9 10 11

3

1 5

2 6

3 10

Output: 3 : -8

4 : -7

7 : -5

Answer

You are using Python

```
a=int(input())
```

```
b=list(map(int,input().split()))
```

```
m=int(input())
```

```
sub=[]
```

```
for i in range(m):
```

```
    start,end=list(map(int,input().split()))
```

```
    sub.append((start,end))
```

```
for start,end in sub:
```

```
    temp=b[start-1:end]
```

```
    leng=len(temp)
```

```
    temp1=sorted(temp)
```

```
    if(leng%2==0):
```

```
        mi=leng//2-1
```

```
    else:
```

```
        mi=leng//2
```

```
    mid=temp[mi]
```

```
ind=b.index(mid)
ind=a-ind
print(mid,":-",-1*ind)
```

Status : Correct

Marks : 10/10