


COS 125 Fall 2016 Lab #5


Due Weds Nov 2 EoD

The goal of this exercise is to build a very simple program using Tkinter that will roll three dice, displayed as text labels as illustrated below.



You can use the Tic-Tac-Toe game as a model for this program. TTT has a cell class, and a TTTgame class. This program will have a Die class and a DiceRoller class. This program is much simpler than TTT however; it should have fewer than 30 non-blank lines of code (if you put arguments to Tkinter functions on the same line); fewer than 40 lines otherwise.

Each time you hit the roll button, you will roll the three dice and the screen will change:



If you can't get the entire program written, then write as much as you can. You will receive points according to the following guidelines.

1. (10 points): Start the program with a docstring containing at least the text "COS 125 Fall 2016 Lab #5" and your name. Determine which packages that you need to import and write statements that import them.
2. (20 points): Define a class called Die that has two instance variables and one method.
 - a) The instance variables should be called value (self.value) and display (self.display). Value is value of the die and display is a Tkinter label that displays the current value of the die. The constructor will assign a random value when the die is created
 - b) The one method should be called roll and when it is invoked it randomly selects an integer from 1 to 6 ,and then changes the text in display to match the new value of the die.
 - c) The Die constructor needs one arguments besides self: the parent for self.display (a Tkinter frame)

- d) The die label in example above was created using the parameters `relief='ridge'`, `borderwidth=5` and `bg='white'`. You can of course experiment with other variations – be creative! if you are interested see <http://infohost.nmt.edu/tcc/help/pubs/tkinter/web/label.html>
- e) Call `pack(side='left')` in the Die constructor after creating the label.

3. (30 points) Create a class called `DiceRoller` with a constructor (`__init__`) and one method: `rollDice()`. `DiceRoller` has only one instance variable:

`dice` a list of Die objects

The constructor should create a Tkinter window and change the title and then start mainloop. The `rollDice` method at this point can have a single statement: `pass`.

Because we do not need to refer to the game window again within the object code (there is no quit button, unlike Tic-Tac-Toe) it does not need to be an instance variable, although it certainly can be created as one.

The main program has only one line of code: `varName = DiceRoller()`. The program should be runnable at this point although it doesn't do anything except display a window with a title.

4. (30 points) In the `DiceRoller` constructor, create a frame to hold the three dice that you will create. Then create three dice with this frame as a parent. Then create a button with the text "Roll Again". Finally pack the frame and button.

Note that the button does not need a frame to contain it. The window can be its parent, and after packing the frame you can pack the button with the argument `side='bottom'`. Again neither the frame nor the button need to be instance variables.

5. (10 points) Implement the `rollDice()` method. You should now have the finished program.

Please submit your program as a .py file.