Appendix: complete_tf_cpc module

Marco Garieri
Alexander Matrunich
Christian A. Mongeau Ospina
Bo Werth
Food and Agriculture Organization of the United Nations
3 January 2017

Input Data

Supplementary Datasets:

- 1. hsfclmap2: Mmapping between HS and FCL codes extracted from MDB files used to archive information existing in the previous trade system (Shark, Jellyfish).
- 2. adjustments: Adjustment notes containing manually added conversion factors to obtain quantities from traded values
- 3. unsdpartnersblocks: UNSD Tariffline reporter and partner dimensions use different list of geographic are codes. The partner dimesion is more detailed than the reporter dimension. Since we can not split trade flows of the reporter dimension, trade flows of the corresponding partner dimensions have to be assigned the reporter dimension's geographic area code. For example, the code 842 is used for the United States includes Virgin Islands and Puerto Rico and thus the reported trade flows of those territories. Analogous steps are taken for France, Italy, Norway, Switzerland and US Minor Outlying Islands.
- 4. fclunits: For UNSD Tariffline units of measurement are converted to meet FAO standards. According to FAO standard, all weights are reported in metric tonnes, animals in heads or 1000 heads and for certain commodities, only the value is provided.
- 5. comtradeunits:
- 6. EURconversionUSD: Annual EUR/USD currency exchange rates table from SWS
- 7. Chapters: The module downloads only records of commodities of interest. The HS chapters are the following: 01, 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 33, 35, 38, 40, 41, 42, 43, 50, 51, 52, 53. In the future, if other commotidy are of interest for the division, it is important to include additional chapter in the first step of the downloading.

```
## Chapter provided by team B/C
## creating object to provision re-use with Eurostat data

hs_chapters <- c(1:24, 33, 35, 38, 40:43, 50:53)
hs_chapters_str <-
formatC(hs_chapters, width = 2, format = "d", flag = "0") %>%
as.character %>%
shQuote(type = "sh") %>%
paste(collapse = ", ")
```

Extract Eurostat Combined Nomenclature Data

- 1. Remove reporters with area codes that are not included in MDB commodity mapping area list
- 2. Convert HS to FCL
- 3. Remove unmapped FCL codes

- 4. Join fclunits
- 5. NA fclunits set to mt
- 6. Specific ES conversions: some FCL codes are reported in Eurostat with different supplementary units than those reported in FAOSTAT

Extract UNSD Tariffline Data

Tariff line data is obtained from SWS datatables. Data is filtered for chapters of interest.

Harmonize UNSD Tariffline Data

- 1. Geographic Area: UNSD Tariffline data reports area code with Tariffline M49 standard (which are different for official M49). The area code is converted in FAO country code using a specific convertion table provided by Team ENV. Area codes not mapping to any FAO country code or mapping to code 252 (which correpond not defined area) are separately saved and removed from further analyses.
- 2. Commodity Codes: Commodity codes are reported in HS codes (Harmonized Commodity Description and Coding Systpem). The codes are converted in FCL (FAO Commodity List) codes. This step is performed using table incorporated in the SWS. In this step, all the mapping between HS and FCL code is stored. If a country is not included in the package of the mapping for that specific year, all the records for the reporting country are removed. All records without an FCL mapping are filtered out and saved in specific variables.
- 3. Remove non-numeric comm (hs) code; comm (hs) code has to be digit. This probably should be part of the faoswsEnsure
- 4. The tariffline data from UNSD contains multiple rows with identical combination of reporter / partner / commodity / flow / year / qunit. Those are separate registered transactions and the rows containing non-missing values and quantities are summed.
- 5. **Note:** missing quantity weight or value will be handled below by imputation
- 6. Aggregate UNSD Tariffline Data to FCL: here we select column qtyfcl which contains weight in tons (requested by FAO).

Combine Trade Data Sources

- 1. The adjustment notes developed for national data received from countries are not applied to HS data any more (see instructions 2016-08-10). Data harvested from UNSD are standardised and therefore many (if not most) of the quantity adjustment notes (those with no year) need not be applied. The "notes" refer to the "raw" non-standardised files that we used to regularly receive from UNSD and/or the countries. Furthermore, some data differences will also arise due to more recent data revisions in these latest files that have been harvested.
- 2. Convert currency of monetary values from EUR to USD using the EURconversionUSD table (see above).
- 3. Combine UNSD Tariffline and Eurostat Combined Nomenclature data sources to single data set.
 - TL: assign weight to qty
 - ES: assign weight to qty if fclunit is equal to mt, else keep qty

Outlier Detection and Imputation

- 1. Unit values are calculated for each observation at the HS level as ratio of monetary value over weight value / qty.
- 2. Median unit-values are calculated across the partner dimension by year, reporter, flow and HS. This can be problematic if only few records exist for the a specific combination of dimensions.

- 3. Observations are classified as outliers if the calculated unit value for a some partner country is below or above the median unit value. More specifically, the measure defined as median inter-quartile-range (IQR) multiplied by the outlier coefficient (default value: 1.5) is used to categorize outlier observations.
- 4. Impute missing quantities and quantities categorized as outliers by dividing the reported monetary value with the calculated median unit value.
- 5. Assign flagTrade to observations with imputed quantities. These flags are also assigned to monetary values. This may need to be revised (monetary values are not supposed to be modified).
- 6. Aggregate by FCL over HS dimension: reduce from around 15000 commodity codes to around 800 commodity codes.
- 7. Map FCL codes to CPC, remove observations that have not been mapped to CPC.

Mirror Trade Estimation

- 1. Obtain list of non-reporting countries as difference between the list of reporter countries and the list of partner countries.
- 2. Swap the reporter and partner dimensions: the value previously appearing as reporter country code becomes the partner country code (and vice versa).
- 3. Invert the flow direction: an import becomes an export (and vice versa).
- 4. Calculate monetary mirror value by adding a 12% mark-up on imports to account for the difference between CIF and FOB prices.
- 5. Reporting countries: Assign SWS observationStatus flag I and flagMethod e to records with with flagTrade unless the FCL unit is categorized as \$ value only.
- 6. Non-reporting countries: Assign SWS **observationStatus** flag E and **flagMethod e** to both quantities and values. Overwrite **flagMethod e** with c for quantities when transforming to normalized format below.

Output for SWS

- 1. Filter observations with FCL code 1181 (bees).
- 2. Filter observations with missing CPC codes.
- 3. Rename dimensions to comply with SWS standard, e.g. geographicAreaM49Reporter
- 4. Calculate unit value (US\$ per quantity unit) at CPC level if the quantity is larger than zero
- 5. Transform dataset seperating monetary values, quantities and unit values in different rows.
- 6. Convert monetary values, quantities and unit values to corresponding SWS element codes. For example, a quantity import measured in metric tons is assigned 5610.
- 7. Overwrite **flagMethod** for mirrored quantities: **e** becomes **c**
- 8. Add **flagMethod** i to unit values