

## Sequence models &amp; Attention mechanism

10/10 points (100.00%)

Quiz, 10 questions


**✓ Congratulations! You passed!**

Next Item

1 / 1  
points

1.

Consider using this encoder-decoder model for machine translation.



This model is a “conditional language model” in the sense that the encoder portion (shown in green) is modeling the probability of the input sentence  $x$ .

☐ True☒ False

Correct

1 / 1  
points

2.

In beam search, if you increase the beam width  $B$ , which of the following would you expect to be true? Check all that apply.

☒ Beam search will run more slowly.

Correct

☒ Beam search will use up more memory.

Correct

## Sequence models & Attention mechanism

Quiz, 10 questions

Correct



Beam search will converge after fewer steps.



Un-selected is correct



1 / 1  
points

3.

In machine translation, if we carry out beam search without using sentence normalization, the algorithm will tend to output overly short translations.



True



Correct



False



1 / 1  
points

4.

Suppose you are building a speech recognition system, which uses an RNN model to map from audio clip  $x$  to a text transcript  $y$ . Your algorithm uses beam search to try to find the value of  $y$  that maximizes  $P(y | x)$ .

On a dev set example, given an input audio clip, your algorithm outputs the transcript  $\hat{y} = \text{"I'm building an A Eye system in Silly con Valley."}$ , whereas a human gives a much superior transcript  $y^* = \text{"I'm building an AI system in Silicon Valley."}$

According to your model,

$$P(\hat{y} | x) = 1.09 * 10^{-7}$$

$$P(y^* | x) = 7.21 * 10^{-8}$$

Would you expect increasing the beam width  $B$  to help correct this example?



No, because  $P(y^* | x) \leq P(\hat{y} | x)$  indicates the error should be attributed to the RNN rather than to the search algorithm.



Correct

☐ No, because  $P(y^* | x) \leq P(\hat{y} | x)$  indicates the error should be attributed to the search algorithm rather than to the RNN.

## Sequence models & Attention mechanism

10/10 points (100.00%)

☐ Yes, because  $P(y^* | x) \leq P(\hat{y} | x)$  indicates the error should be attributed to the RNN rather than to the search algorithm.

☐ Yes, because  $P(y^* | x) \leq P(\hat{y} | x)$  indicates the error should be attributed to the search algorithm rather than to the RNN.



1 / 1  
points

5.

Continuing the example from Q4, suppose you work on your algorithm for a few more weeks, and now find that for the vast majority of examples on which your algorithm makes a mistake,  $P(y^* | x) > P(\hat{y} | x)$ . This suggests you should focus your attention on improving the search algorithm.



True.



**Correct**



False.



1 / 1  
points


6.

Consider the attention model for machine translation.

## Sequence models & Attention mechanism

10/10 points (100.00%)

Quiz, 10 questions



Further, here is the formula for  $\alpha^{<t,t'>}$ .

$$\alpha^{<t,t'>} = \frac{\exp(e^{<t,t'>})}{\sum_{t'=1}^{T_x} \exp(e^{<t,t'>})}$$

Which of the following statements about  $\alpha^{<t,t'>}$  are true? Check all that apply.

- ☒ We expect  $\alpha^{<t,t'>}$  to be generally larger for values of  $a^{<t'>}$  that are highly relevant to the value the network should output for  $y^{<t>}$ . (Note the indices in the superscripts.)

Correct

- ☐ We expect  $\alpha^{<t,t'>}$  to be generally larger for values of  $a^{<t>}$  that are highly relevant to the value the network should output for  $y^{<t'>}$ . (Note the indices in the superscripts.)

Un-selected is correct

- ☐  $\sum_t \alpha^{<t,t'>} = 1$  (Note the summation is over  $t$ .)

Un-selected is correct

- ☐  $\sum_{t'} \alpha^{<t,t'>} = 1$  (Note the summation is over  $t'$ .)

Correct

1 / 1  
points

## Sequence models & Attention mechanism

10/10 points (100.00%)

7.  
Quiz, 10 questions

The network learns where to “pay attention” by learning the values  $e^{<t,t'>}$ , which are computed using a small neural network:

We can't replace  $s^{<t-1>}$  with  $s^{<t>}$  as an input to this neural network. This is because  $s^{<t>}$  depends on  $\alpha^{<t,t'>}$  which in turn depends on  $e^{<t,t'>}$ ; so at the time we need to evaluate this network, we haven't computed  $s^{<t>}$  yet.



True

**Correct**

False

1 / 1  
points

8.

Compared to the encoder-decoder model shown in Question 1 of this quiz (which does not use an attention mechanism), we expect the attention model to have the greatest advantage when:

The input sequence length  $T_x$  is large.**Correct**The input sequence length  $T_x$  is small.1 / 1  
points

9.

Under the CTC model, identical repeated characters not separated by the “blank” character ( ) are collapsed. Under the CTC model, what does the following string collapse to?

\_\_c\_\_o\_\_o\_\_k\_\_k\_\_b\_\_o\_\_o\_\_o\_\_o\_\_o\_\_o\_\_o\_\_o\_\_o\_\_k\_\_k\_\_k



cokbok



cookbook

**Correct**

cook book



coookkboooooookkk

---

Sequence models & Attention mechanism

10/10 points (100.00%)

Quiz 10 questions  
10 points

10.

In trigger word detection,  $x^{<t>}$  is:



Features of the audio (such as spectrogram features) at time  $t$ .

Correct



The  $t$ -th input word, represented as either a one-hot vector or a word embedding.



Whether the trigger word is being said at time  $t$ .



Whether someone has just finished saying the trigger word at time  $t$ .

---

