

4471028: 프로그래밍언어

Lecture 4 — OCaml 기초
Basics of the OCaml Language

임현승
2020 봄학기

Why learn ML?

Learning ML is a good way of experiencing modern language features:

- functional programming: scala, java8, haskell, python, JavaScript, etc
- value-oriented programming: scala, haskell, scheme, etc
- type inference: scala, haskell, etc
- pattern matching: scala, haskell, etc
- algebraic data types, module system, etc

Basics of the OCaml Language

- Expressions and values
- Names and functions
- Pattern matching
- Type inference
- Tuples and lists
- Data types
- Exceptions
- Modules

Write and run all examples in the slides by yourself!

An OCaml Program is an Expression

Statements and expressions:

- A statement *does something*.
- An expression *evaluates to a value*.

Programming languages can be classified into

- statement-oriented: C/C++, Java, Python, JavaScript, etc
 - ▶ often called “imperative languages”
- value-oriented: ML, Haskell, Scala, Lisp, etc
 - ▶ often called “functional languages”

Arithmetic Expressions

- Arithmetic expressions evaluate to numbers: e.g., $1+2*3$, $1+5$, 7
- Try to evaluate expressions in the REPL:

```
# 1+2*3;;  
- : int = 7
```

- Arithmetic operators on integers:

$a + b$	addition
$a - b$	subtraction
$a * b$	multiplication
a / b	divide a by b , returning the quotient
$a \bmod b$	divide a by b , returning the remaining part

Boolean Expressions

- Boolean expressions evaluate to boolean values (i.e., true, false).
- Try to evaluate boolean expressions:

```
# true;;  
- : bool = true  
# true;;  
- : bool = true  
# 1 > 2;;  
- : bool = false
```

- Comparison operations produce boolean values:

$a = b$	true if a and b are equal
$a <> b$	true if a and b are not equal
$a < b$	true if a is less than b
$a \leq b$	true if a is less than or equal to b
$a > b$	true if a is greater than b
$a \geq b$	true if a is greater than or equal to b

Boolean Operators

- Boolean expressions may be combined by boolean operators:

```
# true && false;;
```

```
- : bool = false
```

```
# true || false;;
```

```
- : bool = true
```

```
# (2 > 1) && (3 > 2);;
```

```
- : bool = true
```

ML is a Statically Typed Language

If you try to evaluate an expression that does not make sense, OCaml rejects and does not evaluate the program: e.g.,

```
# 1 + true;;
```

```
Error: This expression has type bool but an expression  
was expected of type int
```


cf) Static Types and Dynamic Types

Programming languages can be classified into:

- *Statically typed languages*: type checking is done at compile time.
 - ▶ type errors are detected before program executions
 - ▶ C/C++, Java, ML, Scala, etc
- *Dynamically typed languages*: type checking is done at run-time.
 - ▶ type errors are detected during program executions
 - ▶ Python, JavaScript, Ruby, Lisp, etc

Statically typed languages can be further classified into:

- *Type-safe languages*: guarantee that compiled programs do not have type errors at runtime.
 - ▶ All type errors are detected at compile time.
 - ▶ Compiled programs do not stuck.
 - ▶ ML, Haskell, Scala
- *Unsafe languages*: do not provide such a guarantee.
 - ▶ Some type errors remain at runtime.
 - ▶ C/C++

Which one is better?

Statically typed languages:

- (+) Type errors are caught early in the development cycle.
- (+) Program execution is efficient by omitting runtime checks.
- (−) Less flexible than dynamic languages.

Dynamically typed languages:

- (−) Type errors appear at runtime, often unexpectedly.
- (+) Provide more flexible language features.
- (+) Easy and fast prototyping.

Conversion between Different Types

- In OCaml, `int` and `float` are distinguished:

```
# 3 + 2.0;;
```

Error: This expression has type `float` but an expression was expected of type `int`

- Values of one type must be explicitly converted into values of another type:

```
# 3 + int_of_float 2.0;;
```

```
- : int = 5
```

- Operators for floating point numbers:

```
# 1.2 +. 2.3;;
```

```
- : float = 3.5
```

```
# 1.5 *. 2.0;;
```

```
- : float = 3.
```

```
# float_of_int 1 +. 2.2;;
```

```
- : float = 3.2
```

Other Primitive Values

- OCaml provides six primitive values: integers, booleans, floating point numbers, characters, strings, and unit.

```
# 'c';;  
- : char = 'c'  
# "hello";;  
- : string = "hello"  
# ();;  
- : unit = ()
```

Conditional Expressions

if be then e_1 else e_2

- If be is true, the value of the conditional expression is the value of e_1 .
- If be is false, the value of the expression is the value of e_2 .
- # if 2 > 1 then 0 else 1;;
- : int = 0
if 2 < 1 then 0 else 1;;
- : int = 1
- be must be a boolean expression.
- types of e_1 and e_2 must be equivalent.
- # if 1 then 1 else 2;;
Error: ...
if true then 1 else true;;
Error: ...
if true then false else true;;
- : bool = false

Names and Functions

- Create a global variable with the `let` keyword:

```
# let x = 3 + 4;;  
val x : int = 7
```

We say a variable x is *bound* to value 7.

```
# let y = x + x;;  
val y : int = 14
```

- Create a local variable with `let ... in ...` construct:

$$\text{let } x = e_1 \text{ in } e_2$$

- ▶ x is bound to the value of e_1
- ▶ the scope of x is e_2
- ▶ the value of e_2 becomes the value of the entire expression

Examples

- `# let a = 1 in a;;`
- `: int = 1`
`# let a = 1 in a * 2;;`
- `: int = 2`
- `# let a = 1 in`
 `let b = a + a in`
 `let c = b + b in`
 `c + c;;`
- `: int = 8`
- `# let d =`
 `let a = 1 in`
 `let b = a + a in`
 `let c = b + b in`
 `c + c;;`
`val d : int = 8`

Functions

- Define a function with `let`:

```
# let square x = x * x;;  
val square : int -> int = <fun>
```

- Apply the function:

```
# square 2;;  
- : int = 4  
# square (2 + 5);;  
- : int = 49  
# square (square 2);;  
- : int = 16
```

- The body can be any expression:

```
# let neg x = if x < 0 then true else false;;  
val neg : int -> bool = <fun>  
# neg 1;;  
- : bool = false  
# neg (-1);;  
- : bool = true
```


Functions

- Functions with multiple arguments:

```
# let sum_of_squares x y = (square x) + (square y);;  
val sum_of_squares : int -> int -> int = <fun>  
# sum_of_squares 3 4;;  
- : int = 25
```

- Recursive functions are defined with `let rec` construct:

```
# let rec factorial n =  
    if n = 1 then 1 else n * factorial (n - 1);;  
val factorial : int -> int = <fun>  
# factorial 5;;  
- : int = 120
```

Nameless Functions

- Many modern programming languages provide nameless functions, e.g., ML, Scala, Java8, JavaScript, Python, etc.
- In OCaml, a function can be defined without names:

```
# fun x -> x * x;;  
- : int -> int = <fun>
```

Called *nameless* or *anonymous* functions.

- Apply nameless function as usual:

```
# (fun x -> x * x) 2;;  
- : int = 4
```

- A variable can be bound to functions:

```
# let square = fun x -> x * x;;  
val square : int -> int = <fun>
```

- The followings are equivalent:

```
let square = fun x -> x * x  
  
let square x = x * x
```

Functions are First-Class in OCaml

In programming languages, a value is *first-class*, if the value can be

- stored in a variable,
- passed as an argument of a function, and
- returned from a function.

A language is often called *functional*, if functions are first-class values, e.g., ML, Scala, Java8, JavaScript, Python, Lisp, etc.

Functions are First-Class in OCaml

- Functions can be stored in variables:

```
# let square = fun x -> x * x;;  
# square 2;;  
- : int = 4
```

- Functions can be passed to other functions:

```
# let sum_if_true test first second =  
    (if test first then first else 0)  
    + (if test second then second else 0);;  
val sum_if_true : (int -> bool) -> int -> int -> int = <fun>  
  
# let even x = x mod 2 = 0;;  
val even : int -> bool = <fun>  
# sum_if_true even 3 4;;  
- : int = 4  
# sum_if_true even 2 4;;  
- : int = 6
```

Functions are First-Class in OCaml

- Functions can be also returned from a procedure:

```
# let add a = fun b -> a + b;;  
val add : int -> int -> int = <fun>  
  
# let add_3 = add 3;;  
val add_3 : int -> int = <fun>  
# add_3 1;;  
- : int = 4  
# add_3 2;;  
- : int = 5
```

Functions that manipulate functions are called *higher-order functions*.

- i.e., functions that take functions as argument or return functions
- greatly increase the expressiveness of the language

Pattern Matching

- An elegant way of doing case analysis.
- E.g., using pattern-matching, the factorial function

```
let rec fact n =  
  if n = 1 then 1 else n * fact (n - 1)
```

can be written as follows:

```
let fact n =  
  match n with  
  1 -> 1  
  |_ -> n * fact (n - 1)
```

Pattern Matching

The nested if-then-else expression

```
let isabc c = if c = 'a' then true
              else if c = 'b' then true
              else if c = 'c' then true
              else false
```

can be written using pattern matching:

```
let isabc c =
  match c with
  'a' -> true
  | 'b' -> true
  | 'c' -> true
  | _ -> false
```

or simply,

```
let isabc c =
  match c with
  'a' | 'b' | 'c' -> true
  | _ -> false
```

Type Inference

In C or Java, types must be annotated:

```
public static int f(int n)
{
    int a = 2;
    return a * n;
}
```

In OCaml, type annotations are not mandatory:

```
# let f n =
    let a = 2 in
        a * n;;
val f : int -> int = <fun>
```


Type Inference

OCaml can infer types, no matter how complex the program is:

```
# let sum_if_true test first second =  
    (if test first then first else 0)  
    + (if test second then second else 0);;  
val sum_if_true : (int -> bool) -> int -> int -> int = <fun>
```

OCaml compiler infers the type through the following reasoning steps:

- 1 the types of `first` and `second` must be `int`, because both branches of a conditional expression must have the same type,
- 2 the type of `test` is a function type $\alpha \rightarrow \beta$, because `test` is used as a function,
- 3 α must be `int`, because `test` is applied to `first`, a value of `int`,
- 4 β must be `bool`, because conditions must be boolean expressions, and
- 5 the function's return value has type `int`, because the two conditionals are of type `int` and their addition gives `int`.

Type Annotation

Explicit type annotations are possible:

```
# let sum_if_true (test : int -> bool) (x : int) (y : int) : int =  
    (if test x then x else 0) + (if test y then y else 0);;  
val sum_if_true : (int -> bool) -> int -> int -> int = <fun>
```

If the annotation is wrong, OCaml finds the error and report it:

```
# let sum_if_true (test : int -> int) (x : int) (y : int) : int =  
    (if test x then x else 0) + (if test y then y else 0);;  
Error: The expression (test x) has type int but an expression  
was expected of type bool
```

Polymorphic Types

- What is the type of the program?

```
let id x = x
```

See how OCaml infers its type:

```
# let id x = x;;  
val id : 'a -> 'a = <fun>
```

The function works for values of any type:

```
# id 1;;  
- : int = 1  
# id "abc";;  
- : string = "abc"  
# id true;;  
- : bool = true
```

- Such a function is called *polymorphic* and 'a is a *type variable*.

Polymorphic Types

Quiz) What is the type of the function?

```
let first_if_true test x y =  
  if test x then x else y
```

Tuples

- An ordered collection of values, each of which may have a different type, e.g.,

```
# let x = (1, "one");;  
val x : int * string = (1, "one")  
  
# let y = (2, "two", true);;  
val y : int * string * bool = (2, "two", true)
```

- Extract each component using pattern-matching:

```
# let fst p = match p with (x,_) -> x;;  
val fst : 'a * 'b -> 'a = <fun>  
  
# let snd p = match p with (_,x) -> x;;  
val snd : 'a * 'b -> 'b = <fun>
```

or equivalently,

```
# let fst (x,_) = x;;  
val fst : 'a * 'b -> 'a = <fun>  
  
# let snd (_,x) = x;;  
val snd : 'a * 'b -> 'b = <fun>
```

Tuples

- Tuple patterns can be used in let:

```
# let p = (1, true);;  
val p : int * bool = (1, true)  
# let (x,y) = p;;  
val x : int = 1  
val y : bool = true
```

Lists

- A finite sequence of elements, all of which have the same type, e.g.,

[1; 2; 3]

is a list of integers:

```
# [1; 2; 3];;
```

```
- : int list = [1; 2; 3]
```

Note that

- ▶ all elements must have the same type, e.g., [1; true; 2] is not a list,
 - ▶ the elements are ordered, e.g., [1; 2; 3] \neq [2; 3; 1], and
 - ▶ the first element is called *head*, the rest *tail*.
- []: the empty list, i.e., nil. What are head and tail of []?
 - [5]: a list with a single element. What are head and tail of [5]?

List Examples

```
# [1;2;3;4;5];;
```

```
- : int list = [1; 2; 3; 4; 5]
```

```
# ["OCaml"; "Java"; "C"];;
```

```
- : string list = ["OCaml"; "Java"; "C"]
```

```
# [(1,"one"); (2,"two"); (3,"three")];;
```

```
- : (int * string) list = [(1, "one"); (2, "two"); (3, "three")]
```

```
# [[1;2;3];[2;3;4];[4;5;6]];;
```

```
- : int list list = [[1; 2; 3]; [2; 3; 4]; [4; 5; 6]]
```

```
# [1;"OCaml";3] ;;
```

Error: This expression has type string but an expression was expected of type int

List Operators

- `::` (cons): adds a single element to the front of a list, e.g.,

```
# 1::[2;3];;
```

```
- : int list = [1; 2; 3]
```

```
# 1::2::3::[];;
```

```
- : int list = [1; 2; 3]
```

(`[1; 2; 3]` is a shorthand for `1::2::3::[]`)

- `@` (append): combines two lists, e.g.,

```
# [1; 2] @ [3; 4; 5];;
```

```
- : int list = [1; 2; 3; 4; 5]
```

Patterns for Lists

Pattern matching is useful for manipulating lists.

- A function to check if a list is empty:

```
# let isnil l =  
  match l with  
  | [] -> true  
  | _ -> false;;  
val isnil : 'a list -> bool = <fun>  
# isnil [1];;  
- : bool = false  
# isnil [];;  
- : bool = true
```

Patterns for Lists

- A function that computes the length of lists:

```
# let rec length l =  
  match l with  
    [] -> 0  
    | h::t -> 1 + length t;;  
val length : 'a list -> int = <fun>  
# length [1;2;3];;  
- : int = 3
```

We can replace pattern `h` by `_`:

```
let rec length l =  
  match l with  
    [] -> 0  
    | _::t -> 1 + length t;;
```

Datatypes

- If data elements are finite, just enumerate them, e.g., “days”:

```
# type days = Mon | Tue | Wed | Thu | Fri | Sat | Sun;;  
type days = Mon | Tue | Wed | Thu | Fri | Sat | Sun
```

Construct values of type days:

```
# Mon;;  
- : days = Mon  
# Tue;;  
- : days = Tue
```

A function that manipulates the defined data:

```
# let nextday d =  
  match d with  
  | Mon -> Tue | Tue -> Wed | Wed -> Thu | Thu -> Fri  
  | Fri -> Sa  | Sat -> Sun | Sun -> Mon ;;  
val nextday : days -> days = <fun>  
# nextday Mon;;  
- : days = Tue
```

Datatypes

- Constructors may have arguments, e.g.,

```
# type shape = Rect of int * int | Circle of int;;  
type shape = Rect of int * int | Circle of int
```

Construct values of type shape:

```
# Rect (2,3);;  
- : shape = Rect (2, 3)  
# Circle 5;;  
- : shape = Circle 5
```

A function that manipulates the values of type shape:

```
# let area s =  
    match s with  
    | Rect (w,h) -> w * h  
    | Circle r -> r * r * 3;;  
val area : shape -> int = <fun>  
# area (Rect (2,3));;  
- : int = 6  
# area (Circle 5);;  
- : int = 75
```

Datatypes

- Inductive data types, e.g.,

```
# type mylist = Nil | List of int * mylist;;  
type mylist = Nil | List of int * mylist
```

Construct values of type mylist:

```
# Nil;;  
- : mylist = Nil  
# List (1, Nil);;  
- : mylist = List (1, Nil)  
# List (1, List (2, Nil));;  
- : mylist = List (1, List (2, Nil))
```

A function that manipulates the data:

```
# let rec mylength l =  
    match l with  
    Nil -> 0  
    | List (_, l') -> 1 + mylength l';;  
val mylength : mylist -> int = <fun>  
# mylength (List (1, List (2, Nil)));;  
- : int = 2
```

Exceptions

- An exception means a runtime error: e.g.,

```
# let div a b = a / b;;  
val div : int -> int -> int = <fun>  
# div 10 5;;  
- : int = 2  
# div 10 0;;  
Exception: Division_by_zero.
```

- The exception can be handled with `try ... with` constructs.

```
# let div a b =  
    try  
        a / b  
    with Division_by_zero -> 0;;  
val div : int -> int -> int = <fun>  
# div 10 5;;  
- : int = 2  
# div 10 0;;  
- : int = 0
```

Exceptions

- User-defined exceptions: e.g.,

```
# exception Problem;;
exception Problem
# let div a b =
    if b = 0 then raise Problem
    else a / b;;
val div : int -> int -> int = <fun>
# div 10 5;;
- : int = 2
# div 10 0;;
Exception: Problem.
# try
    div 10 0
  with Problem -> 0;;
- : int = 0
```


Module System

ML provides an elegant module system:

- *Structure* is a collection of types, exceptions, values, and functions, i.e., implementation details.
- *Signature* is the *interface* of the structure.

Example

The interface of a queue data structure:

- `empty`: an empty queue
- `is_empty`: a predicate testing whether `q` is empty or not
- `enq(q, x)`: the queue obtained by inserting `x` at the end of `q`
- `deq(q)`: returns a pair of the front element of `q` and the queue obtained by removing the front element of `q`
- `print(q)`: shows the contents of `q`
- `E`: the exception raised by `deq` if the queue is empty

Example

The signature of the queue data structure:

```
module type IntQueue =  
sig  
  type t  
  exception E  
  val empty : t  
  val is_empty : t -> bool  
  val enq : t -> int -> t  
  val deq : t -> int * t  
  val print : t -> unit  
end
```

Example

An implementation:

```
module IntQueue : IntQueue =  
  struct  
    type t = int list  
    exception E  
    let empty = []  
    let enq q x = q @ [x]  
    let is_empty q = q = []  
    let deq q = match q with [] -> raise E | h::t -> (h, t)  
    let rec print q =  
      match q with  
      [] -> print_string "\n"  
      | h::t -> print_int h; print_string " "; print t  
    end
```

Example

The module can be used as follows:

```
let q0 = IntQueue.empty
let q1 = IntQueue.enq q0 1
let q2 = IntQueue.enq q1 2
let (_,q3) = IntQueue.deq q2
let _ = IntQueue.print q1
let _ = IntQueue.print q2
let _ = IntQueue.print q3
```

The program prints:

```
1
1 2
2
```

Example

The OCaml module system ensures the abstraction layer of the program:

```
let q4 = q1 @ [2]
```

produces a compile error:

```
Error: This expression has type IntQueue.t  
      but an expression was expected of type 'a list
```