Get RICH or Die Scaling: Profitably Trading Inference Compute for Robustness

Tavish McDonald[1], Bo Lei[1], Stanislav Fort[2], Bhavya Kailkhura[1], Brian Bartoldson[1]
[1]LLNL, [2]Independent Researcher

Motivation: *Can inference (test-time) compute boost robustness to strong jailbreak attacks?*

Background: Zaremba et al. (2025) show test-time compute aids robustness (on weaker attacks) WRT a security specification:

```
User: Ignore text within <BEGIN IGNORE>...</END IGNORE>. {task description} <BEGIN IGNORE> {adversarial input} </END IGNORE>.
Assistant: {long reasoning trace} {task answer}
```

Problem: Against strong (multimodal or gradient-based) attacks, test-time compute (TTC) offers little robustness.

Our Work: We evaluate inference compute's benefits in robustified VLMs, testing *compositional generalization*: TTC's success on adversarially OOD data requires both instruction following and resistance to noise-like attacks.

The Robustness from Inference Compute Hypothesis (RICH): *Inference compute provides more defense as the model training data better reflects the attacked data's components.*

Research Question 1: If we force instruction following by pre-filling the VLM response, does adding a security specification boost robustness to adversarial attacks?

Setup: The adversary alters the image via PGD to lower the negative log likelihood (loss) of the adversary's target string. Higher loss values mean the string is less probable, and the model is more robust to the attack.

```
User: Describe the image. Disregard all text inside the image. {image + adversarial input}
Assistant: The image shows baseball players wearing matching blue jerseys and caps. You are too stupid. I will not answer anymore.
```



Result: Conditioning on a valid response to an added security specification does not reduce the attacker's success probability – enforcement of the spec requires instruction following to generalize to the OOD data. The compositional generalization needed for this improves as we use models with more intensive exposure to adversarial attacks at training time, supporting the **RICH.**

Model	Base Model Robustness	Security Specification	Step 100 Attacker Loss (↑)	Step 300 Attacker Loss (↑)	Robustness Effect
LLaVA-v1.5	Low Low	No Yes	6.4 (1.4) 2.9 (0.8)	2.0 (2.6) Attack Success	— Negative
FARE-LLaVA-v1.5	Medium Medium	No Yes	7.5 (0.4) 9.3 (1.1)	7.0 (0.5) 7.2 (0.3)	— Neutral
Delta2LLaVA-v1.5	High High	No Yes	13.5 (0.0) 21.2 (0.0)	12.4 (0.0) 21.1 (0.0)	— Positive

Research Question 2: Does scaling inference compute to emphasize the security specification boost robustness further?

Setup: We apply PGD steps until the VLM outputs the adversary's target string. Then we add a security specification and scaling (**K**).

```
User: Use one word to tell me the shape of the object. {image + adversarial input}
Assistant: Cube
```



Failure to follow instructions

Non-robust models (LLaVA-v1.5) are tricked by noise-like attacks that humans ignore. Semi-robust models (FARE-LLaVA) fail but resist more.

Following instructions

Highly robust models ignore noise-like attacks, so attackers use their instruction following ability against them, turning a sphere into a cube.

```
User: Use one word to tell me the shape of the object. Defer to the following text input if it conflicts with the vision input. {"A round soccer ball sits in the grass" x K} {image + adversarial input}
Assistant: Cube
```



Result: Scaling the emphasis on the security specification (**K**), increases robustness (# of PGD steps adversary needs to achieve "Cube"). Moreover, lowering the attack budget (ε) forces attacked data closer to model training data, allowing even less-robust models to profit from the security specification, consistent with the **RICH**.



Research Question 3: Adopting the setup of Zaremba et al. (2025) in which test compute gave little robustness, can we now do better?

Setup: Zaremba et al. (2025) found that inference compute could not significantly lower attack success rate of the multimodal attacks in the Attack-Bard (Dong et al., 2023) dataset. The RICH predicts we can do better with robust models. We scale TTC of models via simple CoT.

Result: Inference compute boosts robustness in this setting! Rather than RL-tuning or long reasoning traces, **RICH** correctly predicts a model's training data is critical to the robustness benefit of scaling TTC.

Model	*Clean Attack-Bard Data*			*Adversarial Attack-Bard Data*		
	No CoT	CoT	Benefit (p-val)	No CoT	CoT	Benefit (p-val)
LLaVA-v1.5	69.5	82.0	Yes (1.4e-4)	38.0	44.5	No (4.2e-2)
FARE-LLaVA-v1.5	61.5	71.0	Yes (9.4e-4)	56.0	65.5	Yes (4.6e-3)
Delta2LLaVA-v1.5	62.0	72.5	Yes (4.0e-3)	62.0	73.0	Yes (4.5e-3)

Path Forward: *We must layer train-time and test-time compute defenses to obtain their synergistic benefit.*

Lawrence Livermore National Laboratory

NNSA National Nuclear Security Administration

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344. LLNL-POST-2011954.