

API

Outline

Release Notes

Overview

[puppeteer vs](#)
[puppeteer-core](#)

Environment Variables

[Working with Chrome](#)
[Extensions](#)
[interface:](#)

[CustomQueryHandler](#)

 [Puppeteer](#)

 [BrowserFetcher](#)

 [Browser](#)

 [BrowserContext](#)

 [Page](#)

 [WebWorker](#)

 [Accessibility](#)

 [Keyboard](#)

page.pdf([options]) since v0.9.0

- `options` [<Object>](#) Options object which might have the following properties:
 - `path` [<string>](#) The file path to save the PDF to. If `path` is a relative path, then it is resolved relative to [current working directory](#). If no path is provided, the PDF won't be saved to the disk.
 - `scale` [<number>](#) Scale of the webpage rendering. Defaults to `1`. Scale amount must be between 0.1 and 2.
 - `displayHeaderFooter` [<boolean>](#) Display header and footer. Defaults to `false`.
 - `headerTemplate` [<string>](#) HTML template for the print header. Should be valid HTML markup with following classes used to inject printing values into them:
 - `date` formatted print date
 - `title` document title
 - `url` document location
 - `pageNumber` current page number
 - `totalPages` total pages in the document
 - `footerTemplate` [<string>](#) HTML template for the print footer. Should use the same format as the `headerTemplate`.
 - `printBackground` [<boolean>](#) Print background graphics. Defaults to `false`.
 - `landscape` [<boolean>](#) Paper orientation. Defaults to `false`.
 - `pageRanges` [<string>](#) Paper ranges to print, e.g., '1-5, 8, 11-13'. Defaults to the empty string, which means print all pages.
 - `format` [<string>](#) Paper format. If set, takes priority over `width` or `height` options. Defaults to 'Letter'.
 - `width` [<string|number>](#) Paper width, accepts values labeled with units.
 - `height` [<string|number>](#) Paper height, accepts values labeled with units.