



saad@Phantom-Pc: ~/project



```
$ make qemu-gdb
sixfive_all: OK (2.6s)
== Test memdump, examples ==
$ make qemu-gdb
memdump, examples: OK (1.1s)
== Test memdump, format ii, S, p ==
$ make qemu-gdb
memdump, format ii, S, p: OK (1.9s)
== Test find, in current directory ==
$ make qemu-gdb
find, in current directory: OK (1.5s)
== Test find, in sub-directory ==
$ make qemu-gdb
find, in sub-directory: OK (1.4s)
== Test find, recursive ==
$ make qemu-gdb
find, recursive: OK (1.8s)
== Test exec ==
$ make qemu-gdb
exec: OK (1.2s)
== Test exec, multiple args ==
$ make qemu-gdb
exec, multiple args: OK (1.8s)
== Test exec, recursive find ==
$ make qemu-gdb
exec, recursive find: OK
== Test time ==
time: OK
Score: 131/131
saad@Phantom-Pc:~/projects/xv6-labs-2025$ |
```



saad@Phantom-Pc: ~/project



```
hart 1 starting
hart 2 starting
init: starting sh
$ echo 5 100 18 6 > sixfive.txt
$ echo > b
mkdir a
echo > a/b
mkdir a/aa
echo > a/aa/b$ $ $ $
$ sleep 10
$ sixfive sixfive.txt
5
100
18
6
$ memdump
Example 1:
61810
2025
Example 2:
a string
Example 3:
another
Example 4:
c88
1819438967
100
z
xyzzzy
Example 5:
hello
w
o
r
l
d
$ find . b
./b
./a/b
./a/aa/b
$
```