

HTML/CSS discussed in class

Below is a brief synopsis of the HTML and CSS discussed in class. For more information such as additional property values visit www.w3schools.com/cssref/default.asp. For a complete list of current **browser support** visit www.w3schools.com/cssref/css3_browsersupport.asp

Description	Example
<p>Embedding Google fonts. Visit fonts.google.com to choose the fonts you would like to embed. Select them and copy the code provided into the head of your html document.</p> <p>Access the font using the CSS code provided by google.</p>	<p>HTML</p> <pre><link href="https://fonts.googleapis.com/css?family=Lato Raleway" rel="stylesheet"></pre> <p>CSS</p> <pre>h1 { font-family: 'Raleway', sans-serif; }</pre>
<p>Embedding font awesome icons. Font awesome is a free resource for adding icons to your site.</p> <ol style="list-style-type: none"> 1. Visit fontawesome.com/start to begin. 2. Copy the code provided into the head of your html document. 3. Visit the free gallery to choose an icon fontawesome.com/icons?d=gallery 4. Copy the provided code for the selected button 5. Past the code where you want the icon to appear. 	<p>HTML</p> <pre><link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.8.1/css/all.css" integrity="sha384- 50oBUHEmvpQ+1lw4y57PTFmhCaXp0ML5d60M1M7uH2+nqUivzIebhndOJK28anvf" crossorigin="anonymous"></pre> <pre><button><i class="far fa-envelope"></i> Contact me </button></pre>
<p>animation-name property. The name animation property sets the name of the animation you want to trigger.</p>	<pre>.multicolortransition { width: 100px; height: 100px; background-color: #red; animation-name: colorchangemulti; }</pre>
<p>@keyframes property. The @keyframes property defines what the named animation does.</p>	<pre>@keyframes colorchange { from { background-color: #red; } to { background-color: yellow; } }</pre>
<p>from Use from to define the properties at the beginning of the animation.</p> <p>to Use to, to define the properties at the end of the animation.</p>	<pre>@keyframes colorchange { from { background-color: #red; } to { background-color: yellow; } }</pre>

0% - 100%

Use percent to allow you to have multiple keyframes in an animation. You can set any number between 0% to 100% to define when the properties listed occur.

```
@keyframes colorchange {
  0% {
    background-color: #blue;
  }
  50% {
    background-color: yellow;
  }
  100% {
    background-color: #blue;
  }
}
```

animation-duration. The animation-duration sets the amount of time an animation takes from start to finish.

```
.multicolortransition {
  width: 100px;
  height: 100px;
  background-color: #red;
  animation-name: colorchangemulti;
  animation-duration: 4s;
}
```

animation-iteration-count. The animation-iteration-count defines how many times the animation will repeat.

```
.multicolortransition {
  width: 100px;
  height: 100px;
  background-color: #red;
  animation-name: colorchangemulti;
  animation-duration: 4s;
  animation-iteration-count: infinite;
}
```