

Conditionals and Control Flow

else Statement

The `else` statement executes a block of code when the condition inside the `if` statement is `false`. The `else` statement is always the last condition.

```
boolean condition1 = false;

if (condition1){
    System.out.println("condition1 is
true");
}
else{
    System.out.println("condition1 is not
true");
}

// Prints: condition1 is not true
```

else if Statements

else - if statements can be chained together to check multiple conditions. Once a condition is true, a code block will be executed and the conditional statement will be exited.

There can be multiple else - if statements in a single conditional statement.

```
int testScore = 76;
char grade;

if (testScore >= 90) {
    grade = 'A';
} else if (testScore >= 80) {
    grade = 'B';
} else if (testScore >= 70) {
    grade = 'C';
} else if (testScore >= 60) {
    grade = 'D';
} else {
    grade = 'F';
}

System.out.println("Grade: " + grade); //
Prints: C
```

if Statement

An if statement executes a block of code when a specified boolean expression is evaluated as true.

```
if (true) {
    System.out.println("This code
executes");
}
// Prints: This code executes

if (false) {
    System.out.println("This code does
not execute");
}
// There is no output for the above
statement
```

Nested Conditional Statements

A nested conditional statement is a conditional statement nested inside of another conditional statement. The outer conditional statement is evaluated first; if the condition is `true`, then the nested conditional statement will be evaluated.

```
boolean studied = true;
boolean wellRested = true;

if (wellRested) {
    System.out.println("Best of luck
today!");
    if (studied) {
        System.out.println("You are prepared
for your exam!");
    } else {
        System.out.println("Study before your
exam!");
    }
}

// Prints: Best of luck today!
// Prints: You are prepared for your exam!
```

NOT Operator

The NOT logical operator is represented by `!`. This operator negates the value of a boolean expression.

```
boolean a = true;
System.out.println(!a); // Prints: false

System.out.println(!false) // Prints: true
```

AND Operator

The AND logical operator is represented by `&&`. This operator returns `true` if the boolean expressions on both sides of the operator are `true`; otherwise, it returns `false`.

```
System.out.println(true && true); //  
Prints: true  
System.out.println(true && false); //  
Prints: false  
System.out.println(false && true); //  
Prints: false  
System.out.println(false && false); //  
Prints: false
```

The OR Operator

The logical OR operator is represented by `||`. This operator will return `true` if at least one of the boolean expressions being compared has a `true` value; otherwise, it will return `false`.

```
System.out.println(true || true); //  
Prints: true  
System.out.println(true || false); //  
Prints: true  
System.out.println(false || true); //  
Prints: true  
System.out.println(false || false); //  
Prints: false
```

Conditional Operators – Order of Evaluation

If an expression contains multiple conditional operators, the order of evaluation is as follows: Expressions in parentheses → NOT → AND → OR.

```
boolean foo = true && (!false || true); //  
true  
/*  
(!false || true) is evaluated first  
because it is contained within  
parentheses.
```

Then !false is evaluated as true because it uses the NOT operator.

Next, (true || true) is evaluation as true.

Finally, true && true is evaluated as true meaning foo is true. */

 **Print**  **Share** ▼