
- Graphy - Ultimate Stats Monitor & Debugger

Asset version: v1.0

Author: Martín Pane (Tayx)

Contact information:

- → Email (martintayx@gmail.com)
- → Twitter (@tayx94)
- → Discord (https://discord.gg/2KgNEHK)



Hi, and thank you for buying Graphy!

I hope you find this asset as useful as I have to debug and monitor your Unity projects. In here you will find a detailed overview of all the functions and options Graphy offers you. If something is still not clear after reading this, or if you want to request a feature or report a bug, scroll down to the bottom and you will find links to contact me through various ways.

- → Introduction: Graphy is a set of tools that offers the following:
 - ◆ FPS graph & counter.
 - Memory (RAM) graph & counter.
 - ◆ Audio spectrometer graph & dB counter.
 - ◆ Advanced device data.
 - Debugger script.

→ How to use:

- ◆ Just drag the prefab from "Tayx/Graphy Ultimate Stats Monitor/Prefab" into the scene you want!
- It will survive scene changes, it uses the Singleton pattern and DontDestroyOnLoad.
- ◆ Be careful not to try to access it from code if it's not instantiated in the scene, it won't work.

→ Common module features:

- ◆ Module Position: defines the position where the module will be located.
- ◆ Module state:
 - **FULL:** complete module with all its features.
 - **TEXT:** hides the graphs and just shows the text.
 - **BASIC:** shows just the basic module information.
 - **BACKGROUND:** monitors the data in the background, making it accessible from code.
 - OFF: turns the module completely off, making it inaccessible from code.
 Careful, this also breaks functionality with the debugger (that uses the monitors to read data).
- Graph color: sets the color of the graph.
- ◆ **Graph resolution:** sets the amount of points the graph is divided into. Be careful with very high graph resolutions with low resolution screens, the graph may have issues drawing all the points.
- ◆ Text update rate: defines how many times per second the text updates.

→ FPS module:

- ◆ Thresholds: values used to switch between the different colors associated with the text and graph.
- ◆ Time to reset min/max values: Time (in seconds) to reset the minimum and maximum framerates if they don't change in the specified time. Set to 0 if you don't want it to reset.




→ RAM module: has no specific controls.



→ Audio module:

- ◆ Find audio listener: this will only apply if AudioListener is null.
 - ALWAYS: constantly scans for the AudioListener component in the main camera.
 - **ON SCENE LOAD:** scans for the AudioListener in the main camera every time a scene loads.
 - **NEVER:** never scans for the AudioListener.
- ◆ Audio Listener: reference to the AudioListener you want to use.
- ◆ **FFT Window:** Used to reduce leakage between frequency bins/bands. Note, the more complex the window type, the better the quality, but reduced speed. Simplest is rectangular. Most complex is BlackmanHarris.
- ◆ Spectrum size: Has to be a power of 2 between 128-8192. The higher the sample rate, the less precision, but also more impact on performance. Careful with mobile devices.



- → Advanced data module: shows information about the device.
 - **Screen data:** resolution, refresh rate.
 - ◆ Window data: resolution, refresh rate, dpi.
 - ◆ Graphics API: OpenGL/DirectX/etc.
 - ◆ **GPU:** VRAM, Max texture size, Shader level.
 - ◆ RAM: system available memory.
 - OS: operating system.

Screen: 3840x2160@60Hz Window: 3840x2160@60Hz[96dpi] Graphics API: OpenGL ES 2.0 [emulated] GPU: Emulated GPU running OpenGL ES 2.0 VRAM: 4071MB. Max texture size: 4096px. Shader level: 30 CPU: Intel(R) Core(TM) i7-4770K CPU @ 3.50GHz [8 cores] RAM: 16291 MB OS: Windows 10 (10.0.0) 64bit [Desktop] → The Debugger: this component is a powerful feature that allows you to set a number of conditions, that, if met, will start a chain of actions defined by you. It's designed around Debug Packets. Each Debug Packet can have different conditions and actions.


♦ Common parameters:

- Active: If not active, it will be skipped when the debugger checks Debug Packets.
- ID: Optional, but it's used to operate with Debug Packets from code.
- **Execute once:** If true it will only be executed once, then it will delete itself.
- Init sleep time: Time to wait before checking this Debug Packet.
- **Sleep time after execute:** Only applies if "Execute Once" is false. Time to wait before checking this Debug Packet after it's been executed.



♦ Conditions:


- Condition evaluation: defines if all conditions must be met, or just one of them.
- Variable: which variable to compare against the value specified.
- Comparer: <, <=, ==, >=, >.
- Value: float value used to compare against the variable specified.



Actions:

- Message type: standard types of console log: Log, Warning, Error.
- **Message:** text message you want to send to the console.
- Take screenshot: takes a screenshot.
- Screenshot file name: screenshot name. Avoid this characters: "* . \" / \ [] :; | = ," (without the quotes). It will have the date appended at the end to avoid overwriting. The location where the image is written to can include a directory/folder list. With no directory/folder list the image will be written into the Project folder. On mobile platforms the filename is appended to the persistent data path.
- **Debug break:** pauses the Unity Editor.
- **Unity events:** a Unity event wrapper that can be serialized and modified from the Unity Editor.


 System.Action (only accessible from code): call your own methods from code adding System.Action to the Debug Packet you want, retrieving it with its ID.



→ **Keep Alive:** if true, Graphy will survive scene changes. Careful, if Graphy is set as a child of another object, both will survive scene changes.

→ Background

◆ If ticked, a background overlay will be applied to all modules. The color will be the selected one.



→ Hotkeys

- ◆ Toggle modes: switches between various layouts and modules.
- ◆ Toggle active: toggles Graphy ON/OFF



→ Scripting

- ◆ Add the namespace: Add "using Tayx.Graphy;" to the top of your .cs file.
- ◆ **GraphyManager:** through this class you can access all the stats related variables, like CurrentFPS, AllocatedMemory, etc.
- ◆ **GraphyDebugger:** through this class you can access the various Debug Packets to deactivate them, add System.Action callbacks, etc.

```
// Use this for initialization
Oreferences
void Start ()
{
   var fps = GraphyManager.Instance.CurrentFPS;
   GraphyDebugger.Instance.RemoveAllDebugPacketsWithId(2);
}
```

♦ Advanced stuff:

• Add callbacks to an existing Debug Packet:


```
Action TestAction = null;
TestAction += TestMethod;
GraphyDebugger.Instance.AddCallbackToFirstDebugPacketWithId(TestAction, 5);
```

Add a new Debug Packet:


```
Action TestAction = null;
TestAction += TestMethod;
GraphyDebugger.Instance.AddNewDebugPacket
(
    5,
    new GraphyDebugger.DebugCondition()
{
        Comparer = GraphyDebugger.DebugComparer.Equals_or_greater_than,
        Value = 45f,
        Variable = GraphyDebugger.DebugVariable.Fps_Avg
    },
    GraphyDebugger.MessageType.Warning,
    "Message Warning Test",
    true,
    TestAction
);
```

→ Customization Scene:

- ◆ It can be found at: "Assets\Tayx\Graphy Ultimate Stats Monitor\Scene\Customize Graphy"
- ◆ Allows setting all the parameters in runtime



• Once you have the desired values, just copy the component, exit play mode, and paste the component values, like this:



I've you've read until here, thank you! I hope that you enjoy Graphy and that it makes your developer life easier. It would be highly appreciated if you leave a review in the Asset Store, and if you want to **contact me**, don't hesitate to get in touch through:

- → Email (martintayx@gmail.com)
- → Twitter (@tayx94)
- → <u>Discord (https://discord.gg/2KgNEHK)</u>

