

Portfolio Backtesting

Daniel P. Palomar and Rui ZHOU
Hong Kong University of Science and Technology (HKUST)
2018-12-17

Contents

1	Installation	1
2	Usage of the package	1
2.1	Loading data	1
2.2	Backtesting a single portfolio	2
2.3	Backtesting multiple portfolios	5
2.4	Incorporate benchmarks	6
2.5	Progress bar	6
2.6	Parallel mode	8
3	Usage for grading students in a course	8
3.1	Example of a script file to be submitted by a student	9
4	Appendix	10
4.1	Performance criteria	10

This vignette illustrates the usage of the package `portfolioBacktest` for automated portfolio backtesting. It can be used by a researcher/practitioner to check a set of different portfolios, as well as by a course instructor to evaluate the students in their portfolio design in a fully automated and convenient manner.

1 Installation

The package can currently be installed from GitHub:

```
# install.packages("devtools")
devtools::install_github("dppalomar/portfolioBacktest")

# Getting help
library(portfolioBacktest)
help(package = "portfolioBacktest")
package?portfolioBacktest
?portfolioBacktest
```

2 Usage of the package

2.1 Loading data

We start by loading the package and some random sets of stock market data:

```
library(PerformanceAnalytics)
library(portfolioBacktest)
data(dataset)
```

The dataset `dataset` is a list of data that contains the prices of random sets of stock market data from the S&P 500, over random periods of two years with a random selection of 50 stocks of each universe.

```
length(dataset)
#> [1] 10
str(dataset[[1]])
#> List of 2
#> $ prices:An 'xts' object on 2013-07-03/2015-07-02 containing:
#> Data: num [1:504, 1:50] 51.2 51.8 51.8 51.9 52.3 ...
#> - attr(*, "dimnames")=List of 2
#> ..$ : NULL
#> ..$ : chr [1:50] "MSI" "CCI" "CMG" "KSU" ...
#> Indexed by objects of class: [Date] TZ: UTC
#> xts Attributes:
#> List of 2
#> ..$ src : chr "yahoo"
#> ..$ updated: POSIXct[1:1], format: "2018-12-05 14:26:04"
#> $ index :An 'xts' object on 2013-07-03/2015-07-02 containing:
#> Data: num [1:504, 1] 1615 1632 1640 1652 1653 ...
#> - attr(*, "dimnames")=List of 2
#> ..$ : NULL
#> ..$ : chr "INDEX"
#> Indexed by objects of class: [Date] TZ: UTC
#> xts Attributes:
#> List of 2
#> ..$ src : chr "yahoo"
#> ..$ updated: POSIXct[1:1], format: "2018-12-05 18:59:49"

colnames(dataset[[1]]$prices)
#> [1] "MSI" "CCI" "CMG" "KSU" "CSCO" "DLTR" "GLW" "FLIR" "AVGO" "JWN"
#> [11] "XLNX" "STZ" "XEL" "VZ" "SYN" "IFF" "MU" "CSX" "DFS" "ILMN"
#> [21] "XOM" "HP" "WM" "WEC" "CNP" "HBI" "INCY" "IT" "HBAN" "ISRG"
#> [31] "TIF" "AMAT" "GD" "NFLX" "ETR" "CI" "MSCI" "COTY" "FE" "ICE"
#> [41] "DIS" "TEL" "PM" "ALB" "MCD" "ALL" "EQR" "MAS" "PEP" "KEY"
```

2.2 Backtesting a single portfolio


We start by defining a simple portfolio design in the form of a function that takes as input the prices and outputs the portfolio vector `w`:

```
uniform_portfolio_fun <- function(prices) {
  N <- ncol(prices)
  w <- rep(1/N, N) # satisfies the constraints w>=0 and sum(w)=1
  return(w)
}
```

Now we are ready to use the function `backtestPortfolio()` that will execute and evaluate the portfolio design function on a rolling-window basis, and the result can be easily handled with provided function `backtestSelector()`

```
bt <- portfolioBacktest(uniform_portfolio_fun, dataset[1], shortselling = TRUE)
res <- backtestSelector(bt)
names(res)
#> [1] "performance" "error" "error_message" "cpu_time"
```

```
#> [5] "portfolio"      "return"          "cumPnL"
plot(res$cumPnL[[1]])
```



```
res$performance
#>      Sharpe ratio max drawdown annual return annual volatility
#> [1,]    0.9571932    0.06784576    0.1158755    0.1210576
#>      Sterling ratio Omega ratio RDT bps
#> [1,]      1.707925      1.173436 2205.467
```

Let's try with a slightly more sophisticated portfolio design, like the global minimum variance portfolio (GMVP):

```
GMVP_portfolio_fun <- function(prices) {
  X <- diff(log(prices))[-1] # compute log returns
  Sigma <- cov(X) # compute SCM
  # design GMVP
  w <- solve(Sigma, rep(1, nrow(Sigma)))
  w <- w/sum(abs(w)) # it may not satisfy w>=0
  return(w)
}
bt <- portfolioBacktest(GMVP_portfolio_fun, dataset[1])
res <- backtestSelector(bt)
res$error
#> [1] TRUE
res$error_message
#> [[1]]
#> [1] "No-shortselling constraint not satisfied."
```

Indeed, the GMVP does not satisfy the no-shortselling constraint. We can repeat the backtesting indicating that shortselling is allowed:

```

bt <- portfolioBacktest(GMVP_portfolio_fun, dataset[1], shortselling = TRUE)
res <- backtestSelector(bt)
res$error
#> [1] FALSE
res$error_message
#> [[1]]
#> [1] NA
res$cpu_time
#> [1] 0.003076923
res$performance
#>      Sharpe ratio max drawdown annual return annual volatility
#> [1,]    0.4437945    0.03670731    0.02007334    0.04523115
#>      Sterling ratio Omega ratio ROT bps
#> [1,]    0.5468486    1.078093 48.09867

```

We could be more sophisticated and design a Markowitz mean-variance portfolio satisfying the no-shortselling constraint:

```

Markowitz_portfolio_fun <- function(prices) {
  library(CVXR) #install.packages("CVXR")
  X <- diff(log(prices))[-1] # compute log returns
  mu <- colMeans(X) # compute mean vector
  Sigma <- cov(X) # compute the SCM
  # design mean-variance portfolio
  w <- Variable(nrow(Sigma))
  prob <- Problem(Maximize(t(mu) %*% w - 0.5*quad_form(w, Sigma)),
                  constraints = list(w >= 0, sum(w) == 1))
  result <- solve(prob)
  return(as.vector(result$getValue(w)))
}

```

We can now backtest it:

```

bt <- portfolioBacktest(Markowitz_portfolio_fun, dataset[1])
res <- backtestSelector(bt)
res$error
#> [1] FALSE
res$error_message
#> [[1]]
#> [1] NA
res$cpu_time
#> [1] 0.2107692
res$performance
#>      Sharpe ratio max drawdown annual return annual volatility
#> [1,]    0.6869208    0.2242704    0.2442601    0.3555871
#>      Sterling ratio Omega ratio ROT bps
#> [1,]    1.089132    1.151552 222.5966

```

Instead of backtesting a portfolio on a single `xts` dataset, it is more meaningful to backtest it on multiple datasets. This can be easily done simply by passing a list of `xts` objects:

```

mul_data_bt <- portfolioBacktest(Markowitz_portfolio_fun, dataset[1:5])
mul_data_res <- backtestSelector(mul_data_bt)
names(mul_data_res)

```

```

#> [1] "performance" "error" "error_message" "cpu_time"
#> [5] "portfolio" "return" "cumPnL"
mul_data_res$cpu_time
#> [1] 0.2192308 0.2069231 0.2115385 0.2076923 0.2084615
mul_data_res$performance
#> Sharpe ratio max drawdown annual return annual volatility
#> [1,] 0.6869208 0.2242704 0.2442601 0.3555871
#> [2,] 0.8321379 0.1658841 0.2570285 0.3088773
#> [3,] 0.6771134 0.1691014 0.1920689 0.2836584
#> [4,] -0.9416106 0.4485806 -0.3087014 0.3278440
#> [5,] 1.5639806 0.1520840 0.3985218 0.2548125
#> Sterling ratio Omega ratio ROT bps
#> [1,] 1.0891322 1.151552 222.5966
#> [2,] 1.5494463 1.168298 248.7841
#> [3,] 1.1358210 1.139493 370.9412
#> [4,] -0.6881736 0.850110 -220.7846
#> [5,] 2.6204051 1.325482 406.3804

```

The results from backtesting on multiple datasets can be further summarized by function `backtestSummary()` based on user customized summary functions. For example, we can summarize results using `median()` and `mean()`

```

res_summary <- backtestSummary(mul_data_bt, summary_funs = list('median' = median, 'mean' = mean))
names(res_summary)
#> [1] "performance_summary_median" "performance_summary_mean"
#> [3] "cpu_time_average" "failure_rate"
#> [5] "error_message"
res_summary$performance_summary_median
#> Sharpe ratio max drawdown annual return annual volatility
#> fun1 0.6869208 0.1691014 0.2442601 0.3088773
#> Sterling ratio Omega ratio ROT bps
#> fun1 1.135821 1.151552 248.7841
res_summary$performance_summary_mean
#> Sharpe ratio max drawdown annual return annual volatility
#> fun1 0.5637084 0.2319841 0.1566356 0.3061559
#> Sterling ratio Omega ratio ROT bps
#> fun1 1.141326 1.126987 205.5835

```

2.3 Backtesting multiple portfolios

Backtesting multiple portfolios is equally simple. It suffices to pass a list of functions to the backtesting function `portfolioBacktest()`:

```

bt <- portfolioBacktest(list(uniform_portfolio_fun, GMVP_portfolio_fun),
                        dataset[1:5], shortselling = TRUE)
names(bt)
#> [1] "fun1" "fun2"
res_summary <- backtestSummary(bt, summary_funs = list('median' = median))
res_summary$performance_summary_median
#> Sharpe ratio max drawdown annual return annual volatility
#> fun1 1.487428 0.08985275 0.1945884 0.14053581
#> fun2 1.254192 0.02528428 0.0300820 0.03616125
#> Sterling ratio Omega ratio ROT bps

```

```
#> fun1      1.984565      1.265575 3538.30371
#> fun2      1.189751      1.227148  74.02467
```

Note that the function names are given as `fun1` and `fun2` because only the function bodies are passed to `portfolioBacktest()`. To make the results more recognizable, we can manually pass the function names as follows:

```
bt <- portfolioBacktest(list('my_uniform' = uniform_portfolio_fun, 'my_GMVP' = GMVP_portfolio_fun),
                        dataset[1:5], shortselling = TRUE)
names(bt)
#> [1] "my_uniform" "my_GMVP"
res_summary <- backtestSummary(bt, summary_funs = list('median' = median))
res_summary$performance_summary_median
#>      Sharpe ratio max drawdown annual return annual volatility
#> my_uniform      1.487428      0.08985275      0.1945884      0.14053581
#> my_GMVP         1.254192      0.02528428      0.0300820      0.03616125
#>      Sterling ratio Omega ratio      ROT bps
#> my_uniform      1.984565      1.265575 3538.30371
#> my_GMVP         1.189751      1.227148  74.02467
```

2.4 Incorporate benchmarks

When perform the backtest of our designed portfolio functions, we may want to incorporate some benchmarks. Now the package support two benchmarks, which are `uniform` portfolio and `index` of the certain market. We can easily do that in any case by passing corresponding value to argument `benchmark`.

```
bt <- portfolioBacktest(list('my_uniform' = uniform_portfolio_fun, 'my_GMVP' = GMVP_portfolio_fun),
                        dataset[1:5], shortselling = TRUE, benchmark = c('uniform', 'index'))
names(bt)
#> [1] "my_uniform" "my_GMVP"      "uniform"      "index"
res_summary <- backtestSummary(bt, summary_funs = list('median' = median))
res_summary$performance_summary_median
#>      Sharpe ratio max drawdown annual return annual volatility
#> my_uniform      1.4874275      0.08985275      0.1945884      0.14053581
#> my_GMVP         1.2541919      0.02528428      0.0300820      0.03616125
#> uniform         1.4874275      0.08985275      0.1945884      0.14053581
#> index           0.8106446      0.10103485      0.1040745      0.12838492
#>      Sterling ratio Omega ratio      ROT bps
#> my_uniform      1.984565      1.265575 3538.30371
#> my_GMVP         1.189751      1.227148  74.02467
#> uniform         1.984565      1.265575 3538.30371
#> index           1.030086      1.154963      Inf
```

2.5 Progress bar

In order to monitor the backtest progress, we add the progress bar display in all cases. Users can turn on the progress bar by setting argument `show_progress_bar` be `TRUE`.

```
mul_data_bt <- portfolioBacktest(uniform_portfolio_fun, dataset[1:5], show_progress_bar = TRUE)
#> Evaluating function 1 of 1
#>
|
|=====| 20%
```

```

|
|=====| 40%
|=====| 60%
|=====| 80%
|=====| 100%
bt <- portfolioBacktest(list('my_uniform' = uniform_portfolio_fun, 'my_GMVP' = GMVP_portfolio_fun),
                        dataset[1:5], shortselling = TRUE, benchmark = c('uniform', 'index'),
                        show_progress_bar = TRUE)
#> Evaluating function 1 of 2
#>
|
|=====| 20%
|=====| 40%
|=====| 60%
|=====| 80%
|=====| 100%
#> Evaluating function 2 of 2
#>
|
|=====| 20%
|=====| 40%
|=====| 60%
|=====| 80%
|=====| 100%
#> Evaluating benchmark-uniform
#>
|
|=====| 20%
|=====| 40%
|=====| 60%
|=====| 80%
|=====| 100%
#> Evaluating benchmark-index
#>
|
|=====| 20%
|=====| 40%

```



2.6 Parallel mode

The backtest incurs very heavy computation load when numbers of portfolio functions or dataset go large. Therefore, we add support for parallel mode in this package. Users can choose if they want to parallel evaluate different portfolio functions or in a more fine-grained way, evaluating multiple datasets parallel for each function.

```
# parallel = 2 for functions
system.time(bt_nopar <- portfolioBacktest(list(Markowitz_portfolio_fun, Markowitz_portfolio_fun), dataset))
#>   user system elapsed
#> 60.47   0.02  60.55

system.time(bt_parfuncs <- portfolioBacktest(list(Markowitz_portfolio_fun, Markowitz_portfolio_fun), dataset,
                                                  par_portfolio = 2))
#>   user system elapsed
#>  0.01   0.01  32.63

# parallel = 5 for datasets
system.time(bt_nopar <- portfolioBacktest(Markowitz_portfolio_fun, dataset))
#>   user system elapsed
#> 31.06   0.04  31.11

system.time(bt_pardata <- portfolioBacktest(Markowitz_portfolio_fun, dataset, par_dataset = 5))
#>   user system elapsed
#>  0.03   0.00  11.84
```

It is obvious that the evaluation time for backtesting has been significantly reduced. Note that the parallel evaluation time can not be exactly equal to the original time divided by parallel cores because starting new R sessions also takes extra time. For some technical reasons, the loaded packages information can not be automatically passed to parallel R sessions. Therefore we highly recommend users to cover the `library(XXX)` inside function body like

```
portfolio_fun <- function(x) {
  library(required_package_name)
  # here whatever code
}
```

3 Usage for grading students in a course

If an instructor wants to evaluate the students of a course in their portfolio design, it can also be done very easily. It suffices to ask each student to submit a .R script (necessary to be named uniquely like STUDENTNUMBER-XXXX.R) containing the portfolio function called exactly `portfolio_fun()` as well as any other auxiliary functions that it may require (needless to say that the required packages should be loaded in that script with `library()`). Then the instructor can put all those files in a folder and evaluate all of them at once.


```

bt_all_students <- portfolioBacktest(folder_path = "folder_path", dataset = dataset[1:3])
res_all_students <- backtestSummary(bt_all_students, summary_funs = list('median' = median))
res_all_students$performance_summary
#>           Sharpe ratio max drawdown annual return annual volatility
#> 0001-GMVP      1.289693    0.08987167      0.1823384      0.1570694
#> 0002-Markowitz  1.151673    0.13325751      0.1930309      0.1648490
#> 0003-max       2.263314    0.05792298      0.2901059      0.1223607
#>           Sterling ratio Omega ratio ROT bps
#> 0001-GMVP      2.065793      1.234404  626.8139
#> 0002-Markowitz  2.034134      1.212634  405.6207
#> 0003-max       5.008477      1.456620  335.0793
res_all_students$cpu_time_average
#>      0001-GMVP 0002-Markowitz      0003-max
#>      0.05358974 0.21000000      0.05256410
res_all_students$failure_rate
#>      0001-GMVP 0002-Markowitz      0003-max
#>      0         0             0

```

Now we can rank the different portfolios/students based on a weighted combination of the rank percentiles (termed scores) of the performance measures:

```

leaderboard <- portfolioLeaderboard(bt_all_students, weights = list('Sharpe ratio' = 7, 'max drawdown' = 1, 'annual return' = 1, 'ROT bps' = 1))
# show leaderboard
library(gridExtra)
grid.table(leaderboard$leaderboard_scores)

```

	Sharpe ratio score	max drawdown score	annual return score	ROT bps score	final score
0003-max	100	100	100	0	90
0001-GMVP	50	50	0	100	50
0002-Markowitz	0	0	50	50	10

3.1 Example of a script file to be submitted by a student

Consider the student with id number 666. Then the script file should be named 666-XXX.R and should contain the portfolio function called exactly `portfolio_fun()` as well as any other auxiliary functions that it may require (needless to say that the required packages should be loaded in that script with `library()`):

```

library(CVXR)

auxiliary_function <- function(x) {
  # here whatever code
}

portfolio_fun <- function(prices) {
  X <- diff(log(prices))[-1] # compute log returns
  mu <- colMeans(X) # compute mean vector
  Sigma <- cov(X) # compute the SCM
  # design mean-variance portfolio
  w <- Variable(nrow(Sigma))

```

```

prob <- Problem(Maximize(t(mu) %*% w - 0.5*quad_form(w, Sigma)),
               constraints = list(w >= 0, sum(w) == 1))
result <- solve(prob)
return(as.vector(result$getValue(w)))
}

```

4 Appendix

4.1 Performance criteria

The definition of performance criteria used in this package is listed as below

- **expeted return:** the annualized return
- **volatility:** the annualized standard deviation of returns
- **max drawdown:** the maximum loss from a peak to a trough of a portfolio, see also here
- **Sharpe ratio:** annualized Sharpe ratio, the ratio between **annualized return** and **annualized standard deviation**
- **Sterling ratio:** the return over average drawdown, see here for complete definition. In the package, we use

$$\text{Sterling ratio} = \frac{\text{annualized return}}{\text{max drawdown}}$$

- **Omega ratio:** the probability weighted ratio of gains over losses for some threshold return target, see here for complete definition. The ratio is calculated as:

$$\Omega(r) = \frac{\int_r^\infty (1 - F(x))dx}{\int_{-\infty}^r F(x)dx}$$

In the package, we use $\Omega(0)$, which is also known as Gain-Loss-Ratio.

- **Return over Turnover (ROT):** the sum of cummulative return over the sum of turnover.