

PNETLab | TopologyStatic Route(128) WhatsAppIsfaq-File/PRACTICALshow - Google SearchCheck IP In CMDAsk Gemini

labs.surennetwork.com/legacy/topology

Win-1Win-2R1R2R3

C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.
C:\Documents and Settings\user>ping 40.0.0.10
Pinging 40.0.0.10 with 32 bytes of data:
Reply from 40.0.0.10: bytes=32 time<1ms TTL=128
Reply from 40.0.0.10: bytes=32 time<1ms TTL=128
Reply from 40.0.0.10: bytes=32 time<1ms TTL=128
Reply from 40.0.0.10: bytes=32 time<1ms TTL=128
Ping statistics for 40.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms
C:\Documents and Settings\user>

Static Route

10.0.0.1

StartC:\WINDOWS\system32\cmd.exeC:\WINDOWS\system32\cmd.exe1:48 PM

PNETLab | Topology x Static Route x (128) WhatsApp x Isfaq-File/PRACTICA x show - Google Search x Check IP In CMD x Ask Gemini

labs.surennetwork.com/legacy/topology

Win-1 x Win-2 x R1 x R2 x R3 x

```
R3#
R3#config terminal
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#
R3(config)#
R3(config)#
R3(config)#int e0/0
R3(config-if)#ip add 30.0.0.
*Aug 23 12:39:57.183: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R3(config-if)#ip add 30.0.0.2 255.0.0.0
R3(config-if)#no sh
R3(config-if)#exit
R3(config)#
R3(config)#
R3(config)#
R3(config)#int e0/1
R3(config-if)#ip add 40.0.0.1 255.0.0.0
R3(config-if)#no sh
R3(config-if)#exit
R3(config)#
R3(config)#
R3(config)#
R3(config)#
R3(config)#ip route 10.0.0.0 255.0.0.0 30.0.0.1
R3(config)#ip route 20.0.0.0 255.0.0.0 30.0.0.1
R3(config)#
R3(config)#
R3(config)#
R3(config)#
R3(config)#exit
R3#
R3#
R3#
R3#
*Aug 23 12:42:56.049: %SYS-5-CONFIG_I: Configured from console by console
R3#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
```

Static Route

PNETLab | Topology Static Route (128) WhatsApp Isfaq-File/PRACTICA show - Google Search Check IP In CMD Ask Gemini

labs.surennetwork.com/legacy/topology

Win-1 x Win-2 x R1 x R2 x R3 x

```
R2#
R2#config terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2(config)#int e0/0
R2(config-if)#ip add 20.0.0.2 255.0.0.0
R2(config-if)#no shutdown
R2(config-if)#e
*Aug 23 12:32:23.383: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R2(config-if)#exit
R2(config)#int e0/1
R2(config-if)#ip add 30.0.0.1 255.0.0.0
R2(config-if)#no shutdown
R2(config-if)#exit
R2(config)#
R2(config)#
R2(config)#
R2(config)#ip route 10.0.0.0 255.0.0.0 20.0.0.1
R2(config)#ip route 40.0.0.0 255.0.0.0 30.0.0.2
R2(config)#
R2(config)#
R2(config)#
R2(config)#
R2(config)#
R2(config)#
R2(config)#exit
R2#
*Aug 23 12:37:08.649: %SYS-5-CONFIG_I: Configured from console by console
R2#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set
```

Static Route

PNETLab | TopologyStatic Route(128) WhatsAppIsfaq-File/PRACTICALshow - Google SearchCheck IP In CMDAsk Gemini

labs.surennetwork.com/legacy/topology

Win-1Win-2R1

```
R1(config-if)#ip add 10.0.0.1 255.0.0.0
R1(config-if)#no shutdown
R1(config-if)#exit
R1(config)#exit
R1#
*Aug 23 12:20:33.311: %SYS-5-CONFIG_I: Configured from console by console
R1#config terminal
Enter configuration commands, one per line. End with CNTL/Z.
R1(config)#int e0/1
R1(config-if)#ip add 20.0.0.1 255.0.0.0
R1(config-if)#no shutdown
R1(config-if)#exit
R1(config)#exit
R1#
*Aug 23 12:23:02.333: %SYS-5-CONFIG_I: Configured from console by console
R1#config
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line. End with CNTL/Z.
R1(config)#show ip interface brief
^
% Invalid input detected at '^' marker.
R1(config)#show ip interface brief
^
% Invalid input detected at '^' marker.
R1(config)#show ip interface brief
^
% Invalid input detected at '^' marker.
R1(config)#
R1(config)#
R1(config)#
R1(config)#
```

10.0.0.1
e0/1
20.0.0.1
Win-2
40.0.0.10

Static Route

TERMINAL (3)

Physical01 : 00 : 00START



