

Philosophy / Discussion Topics

Data Science and AI for Neuroscience Summer School
Tara Chari and Lior Pachter
July 11, 2022

What is Exploratory Data Analysis (EDA) ?

1977 *Exploratory Data Analysis* - John Tukey

Alternative to 'confirmatory' data analysis → Allow data to generate hypotheses

Can be confounding to generate and test hypotheses on same data



Objectives

- Enable unexpected discoveries in the data
- Suggest hypotheses about the causes of observed phenomena
- **Assess assumptions** on which statistical inference will be based
- Support the **selection of appropriate statistical tools** and techniques
- Provide a basis for further data collection through surveys or experiments

Common Metrics and Methods for EDA



Visual techniques

- Box plots
- Histograms
- Scatterplots on various features



Statistical metrics

- Max, min, median, quartiles (mean, std dev)
- Covariance, correlations, autocorrelation
- Compare distribution properties to assumptions



Common Metrics and Methods for EDA

Dimensionality reduction (Unsupervised or Supervised)


- Find patterns/features in high dimensional data, determine separation between labeled data
- Remove noise (what is biological, what is technical ...)

PCA - weighted sum of features (in each principal component), maximizing variance captured

$T = XW$ where W transforms X to new coordinate system (to T)

NMF (Nonnegative Matrix Factorization): $X = WH$, W coefficients on row variables, H coefficients on columns


- Can represent gene 'modules', weighted contributions of genes to each 'module'
- Can 'cluster' column variables



$$\begin{bmatrix} W \\ \times \\ H \end{bmatrix} \approx \begin{bmatrix} V \end{bmatrix}$$

Avoiding Circular Analysis

Confounding 'exploratory' with 'all-in-one'



Nowicka et al. 2019

SNE Paper (Hinton & Roweis 2002):


“... placed similar objects nearby in a low-dimensional space while keeping dissimilar objects well separated”

What metric(s) defines
a ‘good job’?



Which
relationships are
incorrect?

How to avoid
circular logic?



[How to Effectively Use t-SNE](#)




Avoiding Circular Analysis





Avoiding Circular Analysis




Embed in 2D (with UMAP)





Avoiding Circular Analysis




Embed in 2D (with UMAP)



Avoiding Circular Analysis



- Use Euclidean distance by default to build neighbor graph
- Hard to say what metric is good/optimal (will always have poor neighborhood recapitulation)
- Same graph often fed to clustering algorithms in Scanpy and Seurat, thus the embedding does not provide an 'orthogonal' check



Questions for you:

- Have you used dimensionality reduction in your analyses, and for what purposes? How do you decide the number of dimensions to use?
- Have you normalized/pre-processed your data? How did you choose the transformations to apply?
 - What data type do you usually work with?
- What are the main metrics you use to assess data quality?