



**TRIBHUVAN UNIVERSITY
INSTITUTE OF ENGINEERING
PURWANCHAL CAMPUS
DHARAN-8**

**A MINOR PROJECT PROPOSAL ON
DECENTRALIZED PREPAID SMART POWER GRID**

**BY
PRATIMA CHAUDHARY (PUR080BCT064)
RABIN KATTEL (PUR080BCT067)
SABIN BASNET (PUR080BCT077)
SARBESH TIMSINA (PUR080BCT082)**

**DEPARTMENT OF ELECTRONICS AND COMPUTER ENGINEERING
PURWANCHAL CAMPUS
DHARAN, NEPAL**

2083/05/05



TRIBHUVAN UNIVERSITY
INSTITUTE OF ENGINEERING
PURWANCHAL CAMPUS, DHARAN
DEPARTMENT OF ELECTRONICS AND COMPUTER
ENGINEERING

LETTER OF APPROVAL

This undersigned certify that we have read, and recommended to the Department of Electronics and Computer Engineering, Purwanchal Campus, a minor project report entitled **“DECENTRALIZED PREPAID SMART POWER GRID”** submitted by **Pratima Chaudhary, Rabin Kattel, Sabin Basnet, Sarbesh Timsina** has been examined and it has been declared successful for the fulfillment of the academic requirements for the completion of Bachelor’s Degree in Computer Engineering.

.....

.....

.....

.....

Supervisor

Head of Department

Department of Electronics and

Department of Electronics and

Computer Engineering

Computer Engineering

Purwanchal Campus, Dharan

Purwanchal Campus, Dharan

Date of Approval:

Abstract

The increasing demand for efficient and transparent electricity management has highlighted the limitations of conventional postpaid and centralized electricity systems. These systems often provide limited real-time information about energy consumption and depend heavily on centralized mechanisms for billing and account management. This project proposes a software-based **Decentralized Prepaid Smart Power Grid** that combines blockchain-based prepaid electricity management, machine learning, simulated energy telemetry, and web-based monitoring within a hybrid system architecture.

The proposed system utilizes a Solidity smart contract deployed on a local blockchain testnet to immutably manage prepaid electricity tokens, user balances, and grid authorization states. Simulated edge telemetry—generated via an ESP32 microcontroller environment—is processed through a FastAPI middleware backend and stored in a SQLite database. Machine learning techniques provide intelligent analysis of this consumption data: a Linear Regression model forecasts short-term usage to estimate the exact time-to-exhaustion of a user's prepaid balance, while a current-differential classification algorithm actively monitors for grid anomalies and potential power theft. A React-based web interface features distinct Client and Provider dashboards, offering consumers real-time consumption metrics while providing grid administrators with automated, critical alert capabilities.

The architecture is fundamentally hybrid. The blockchain secures the decentralized financial and authorization layer, while the backend, database, and frontend deliver high-performance centralized application services. Because high-voltage infrastructure is outside the scope of this project, physical line-control enforcement is successfully demonstrated through a simulated IoT relay.

Ultimately, this prototype proves the technical feasibility of merging immutable blockchain billing with machine-learning analytics, serving as a scalable foundation for future integration with physical smart-metering hardware and live production blockchain networks.

TABLE OF CONTENTS

LIST OF FIGURES	iv
LIST OF TABLES	v
LIST OF ABBREVIATIONS	vi
1 INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	1
1.3 Motivation	2
1.4 Objectives	2
1.5 Scope	3
2 LITERATURE REVIEW	4
2.1 The Evolution of Advanced Metering Infrastructure (AMI)	4
2.2 Decentralization and the Physical-to-Digital Gap	4
3 RELATED THEORY	6
3.1 Smart Grid	6
3.2 Prepaid Electricity Management	6
3.3 Blockchain Technology	6
3.4 Smart Contracts	7
3.5 Blockchain-Based Decentralization	7
3.6 Internet of Things	8
3.7 Telemetry and Real-Time Monitoring	8
3.8 Machine Learning	9

3.9	Anomaly Detection	9
3.10	Isolation Forest	9
3.11	Energy Consumption Forecasting	10
3.12	Linear Regression	10
3.13	RESTful API	10
3.14	FastAPI Backend	11
3.15	Database Management	11
3.16	Web-Based Monitoring Dashboard	11
3.17	Software-Based Smart Grid Simulation	12
3.18	Summary	12
4	METHODOLOGY	13
4.1	Overview	13
4.2	System Architecture	13
4.3	Telemetry Simulation	14
4.4	Backend Development	14
4.5	Database Management	15
4.5.1	Telemetry Log	15
4.5.2	User Balance	15
4.5.3	Anomaly Alert	15
4.6	Blockchain Implementation	15
4.7	Prepaid Balance Management	16
4.8	Anomaly Detection	16
4.9	Energy Consumption Forecasting	17

4.10 Blockchain and Anomaly Management	17
4.11 Web-Based Monitoring System	18
4.12 System Workflow	18
4.13 Testing and Evaluation	19
4.14 Scope of Implementation	19
4.15 Summary	20
5 EXPECTED RESULTS	21
5.1 Overview	21
5.2 Prepaid Electricity Management	21
5.3 Blockchain-Based Balance and Authorization	21
5.4 Electricity Consumption Monitoring	21
5.5 Anomaly Detection	22
5.6 Electricity Consumption Forecasting	22
5.7 Web-Based Monitoring	22
5.8 Integration of System Components	23
5.9 Expected Benefits	23
5.10 Project Deliverables	23
5.11 Scope of Expected Results	24
6 CONCLUSION	25
REFERENCES	27
APPENDIX	28

LIST OF FIGURES

LIST OF TABLES

LIST OF ABBREVIATIONS

API : Application Programming Interface

Colab : Colaboratory

CHAPTER 1

INTRODUCTION

1.1 Background

Electrical utility distribution domains traditionally rely on centralized data hubs and infrastructure networks. In conventional systems, energy consumption data is metered at the consumer's end, transferred across proprietary channels, and recorded on private databases controlled entirely by a central authority. While this model has sustained basic distribution needs for decades, it introduces a systemic vulnerability: asymmetric information control. Consumers have zero real-time architectural visibility into the backend computations, resulting in frequent trust deficits, billing friction, and disputes regarding unexpected or hidden charges.

To address this structural trust gap, this project introduces a decentralized smart grid framework that completely decouples utility transaction computation from central database manipulation. By converging the Internet of Things (IoT), Blockchain architecture, and Machine Learning (ML), the proposed system transitions utility management into a transparent and self-governing ecosystem.

1.2 Problem Statement

Modern electrical utility structures suffer from deep operational challenges rooted in their centralized architecture:

Information Asymmetry and Trust Deficits: Because traditional meters stream data into closed corporate databases, consumers cannot independently verify billing logs, causing trust deficits.

Revenue Collection Risks: Postpaid billing causes payment delays and frequent defaults, trapping utility companies in inefficient debt-recovery cycles. **Unresolved Distribution Leakages:** Line-tampering, meter-bypassing, and infrastructure anomalies often go unflagged due to a lack of automated edge-analysis tools. **Data Integrity Risks:** Central databases represent single-point-of-failure vulnerabilities that are open to internal

manipulation or external security threats.

1.3 Motivation

The motivation for this project stems from the severe operational inefficiencies and financial losses prevalent in traditional utility distribution networks. In many developing regions, power theft—specifically through meter bypassing or direct line hooking—causes massive revenue leakage that goes entirely undetected by centralized administrative systems. Simultaneously, postpaid billing models force utility providers to absorb the financial risk of consumer defaults, leading to inefficient and costly debt-recovery cycles.

From a consumer standpoint, the reliance on closed, corporate databases creates a "black box" billing environment. Users are expected to blindly trust the calculations generated by the central authority, which frequently leads to disputes over hidden charges and inaccurate readings.

We were motivated to build this system because modern technology allows us to completely engineer these problems out of existence. By replacing trust with mathematics, a blockchain smart contract can guarantee absolute billing transparency, while edge-based machine learning can autonomously secure the grid against physical theft. This project demonstrates a future where utility grids are trustless, self-governing, and inherently secure.

1.4 Objectives

The main objective of this project is to design and develop a software-based **Decentralized Prepaid Smart Power Grid** that integrates prepaid electricity management, blockchain technology, machine learning, and real-time monitoring.

The specific objectives of the project are:

- To develop an automated, decentralized billing framework: To eliminate billing opacity and postpaid collection risks by integrating an IoT edge node (ESP32) for real-time load sampling with an immutable blockchain smart contract that executes transparent, prepaid token deductions and autonomous physical circuit

isolation.

- To enhance grid security and consumer visibility: To resolve hidden energy leakages and trust deficits by integrating machine learning models for predictive budget forecasting and current-differential theft detection, presenting these insights through a dual-role (Client and Provider) web dashboard.

1.5 Scope

The scope of this project focuses on providing transparent energy distribution and secure automated prepaid billing using a simulated low-voltage IoT environment. The system demonstrates:

- Real-time analog load sampling.
- Immutable smart contract ledger processing.
- Cryptographic backend middleware routing.
- Machine learning-based intelligence.

Because the deployment of actual utility meters on live high-voltage power lines requires industrial certification, the physical hardware layer is constrained to a low-voltage ESP32 simulation.

Furthermore, all blockchain calculations operate within a localized Hardhat test environment to bypass the live transaction gas costs associated with public mainnet deployments.

CHAPTER 2

LITERATURE REVIEW

2.1 The Evolution of Advanced Metering Infrastructure (AMI)

Historically, utility metering transitioned from electromechanical induction meters, which required manual and labor-intensive meter reading, to digital Advanced Metering Infrastructure (AMI). The integration of the Internet of Things (IoT) enabled AMI systems to automate data logging and support wireless telemetry for monitoring electricity consumption.

While these technological developments significantly improved the efficiency and frequency of energy-data collection, the underlying architecture of many AMI systems remains largely centralized. Consumer telemetry is typically transmitted to utility-controlled databases for storage, processing, and billing. This centralized approach limits consumers' ability to independently verify the processing of their consumption data and may contribute to concerns regarding data integrity, billing transparency, and system reliability.

2.2 Decentralization and the Physical-to-Digital Gap

Decentralization and the Physical-to-Digital Gap To eliminate the vulnerabilities of centralized databases, recent research has explored Web3 and blockchain frameworks for utility management. Decentralized ledgers offer an immutable, transparent method for recording transactions and executing automated prepaid billing without a central authority. However, a significant architectural gap exists in current implementations. Existing AMI frameworks rely on vulnerable centralized databases, while pure Web3 frameworks lack the physical control systems necessary to enforce ledger states on actual power lines.

A decentralized smart contract can mathematically update a user's token balance to zero, but without a dedicated hardware execution layer, it cannot physically stop the flow of electricity. Furthermore, these software-only systems fail to address localized power theft (such as line bypassing) because they lack real-time edge anomaly

detection. This project addresses these exact research gaps by unifying IoT edge enforcement, machine learning anomaly detection, and blockchain validation into a single automated pipeline.

CHAPTER 3

RELATED THEORY

3.1 Smart Grid

A smart grid is an advanced electricity management system that integrates electrical infrastructure with digital communication, monitoring, data processing, and control technologies. It enables electricity consumption and system conditions to be monitored more efficiently than in conventional power systems. Smart grid technologies can improve energy efficiency, reliability, transparency, and consumer awareness.

The proposed system applies smart grid concepts through a software-based architecture. Rather than directly controlling physical electrical infrastructure, the system processes simulated electricity consumption telemetry and provides mechanisms for prepaid balance management, anomaly detection, consumption forecasting, and authorization control.

3.2 Prepaid Electricity Management

A prepaid electricity system requires consumers to purchase electricity credit before consuming electrical energy. The available credit is reduced according to the amount of electricity consumed. When the available balance becomes insufficient, access to electricity can be restricted according to predefined rules.

Prepaid electricity management provides consumers with greater awareness of their electricity usage and can reduce issues associated with conventional postpaid billing. In the proposed system, prepaid electricity is represented using blockchain-based tokens. Each user is associated with a blockchain wallet address and a corresponding prepaid balance.

3.3 Blockchain Technology

Blockchain is a distributed ledger technology that records transactions in a verifiable and tamper-resistant manner. It provides a mechanism for maintaining transaction

records without relying entirely on a single centralized authority.

In the proposed system, blockchain is used for prepaid balance and authorization management. Token purchases, balance deductions, and authorization-related operations are handled through blockchain transactions. This provides traceability for important prepaid operations and forms the decentralized component of the proposed architecture.

3.4 Smart Contracts

A smart contract is a program deployed on a blockchain that defines and executes pre-defined rules through transactions and function calls. Smart contracts can automate operations and enforce conditions without requiring manual intervention for every transaction.

The proposed system uses a Solidity smart contract named `PrepaidGrid`. The contract provides functions for purchasing prepaid tokens, retrieving balances, checking authorization, deducting balances, and managing anomaly-related cutoff operations.

The major functions of the smart contract include:

- `purchaseTokens()` for purchasing prepaid electricity tokens.
- `getBalance()` for retrieving the current prepaid balance.
- `checkAuthorization()` for checking the authorization state of a user.
- `deductBalance()` for deducting the amount associated with electricity consumption.
- `triggerAnomalyCutoff()` for triggering a cutoff when a significant anomaly is detected.
- `clearAnomalyAndReauthorize()` for restoring authorization after an anomaly has been resolved.

3.5 Blockchain-Based Decentralization

The proposed system incorporates decentralization primarily through the blockchain layer used for prepaid balance and authorization management. Instead of maintaining the complete prepaid state exclusively within the application database, important

balance and authorization operations are implemented through a blockchain smart contract.

The `PrepaidGrid` smart contract maintains user-related prepaid balances and authorization states and provides functions for token purchase, balance retrieval, balance deduction, authorization checking, and anomaly-triggered cutoff operations. These operations are recorded as blockchain transactions, providing traceability and reducing dependence on the application database for the authoritative prepaid state.

However, the overall system is not fully decentralized. Telemetry ingestion, data storage, machine-learning processing, and dashboard services are handled by the FastAPI backend and SQLite database. Therefore, the proposed architecture is better described as a *hybrid architecture* that combines centralized application services with blockchain-based decentralized state management.

3.6 Internet of Things

The Internet of Things (IoT) refers to interconnected physical devices that can collect, transmit, and exchange data through communication networks. IoT is widely used in smart energy systems to collect electricity consumption and operational data from distributed devices.

The proposed architecture is designed to support telemetry generated by an edge device. However, physical IoT hardware is not implemented in the current project. Instead, electricity telemetry is simulated and submitted to the backend through an application programming interface. This provides a software representation of the data flow that could be generated by a physical smart-metering device in a future deployment.

3.7 Telemetry and Real-Time Monitoring

Telemetry refers to the collection and transmission of data from a remote source to a processing or monitoring system. In an electricity management system, telemetry may contain information such as power consumption, load percentage, device status, and authorization state.

In the proposed system, simulated telemetry is used to represent electricity consumption

data. The backend receives the telemetry through an HTTP endpoint and stores the information in the database. The stored data is then used for monitoring, anomaly detection, forecasting, and dashboard visualization.

3.8 Machine Learning

Machine learning is a branch of artificial intelligence in which computational models learn patterns from data and use those patterns to make predictions or decisions. Machine-learning techniques can be applied to smart energy systems for tasks such as consumption analysis, anomaly detection, and demand forecasting.

The proposed system applies machine learning to two major tasks: anomaly detection using Isolation Forest and electricity consumption forecasting using Linear Regression.

3.9 Anomaly Detection

Anomaly detection is the process of identifying observations that significantly differ from expected or normal behavior. In electricity management systems, unusual consumption patterns may indicate electricity theft, equipment malfunction, abnormal usage, or data inconsistencies.

The proposed system analyzes recent electricity consumption telemetry and identifies observations that deviate from the learned consumption pattern. The detected anomaly information is stored in the database and displayed through the monitoring dashboard. Significant anomalies can also be associated with the blockchain-based cutoff mechanism.

3.10 Isolation Forest

Isolation Forest is an unsupervised machine-learning algorithm designed for detecting anomalous observations. The algorithm isolates observations through recursive random partitioning. Observations that can be isolated using relatively few partitions are generally considered more likely to be anomalous.

In the proposed system, Isolation Forest is applied to a recent collection of simulated electricity consumption samples. The model produces an anomaly result and score for

incoming observations. The resulting information is stored in the database and used for anomaly monitoring and further system actions.

3.11 Energy Consumption Forecasting

Energy consumption forecasting is the process of estimating future electricity usage using historical consumption data. Forecasting can provide users with information about expected future demand and can also help estimate the approximate duration for which a prepaid balance may remain sufficient.

The proposed system uses historical electricity consumption data to generate a short-term forecast. The forecast is used to estimate future consumption and calculate an approximate remaining usage duration based on the available prepaid balance and estimated average consumption rate.

3.12 Linear Regression

Linear Regression is a supervised machine-learning technique used to model relationships between variables and predict future values. It estimates a mathematical relationship from historical observations and uses the resulting model to generate predictions.

In the proposed system, Linear Regression is used to estimate future electricity consumption. Historical consumption information is provided to the model, and the resulting prediction is used to generate an hourly consumption forecast. The predicted consumption rate is also used to estimate the approximate remaining usage time associated with the available prepaid balance.

3.13 RESTful API

A RESTful API is an application programming interface that enables communication between software components through standard HTTP operations. REST APIs commonly use methods such as GET and POST to retrieve and submit information.

The proposed system uses RESTful communication for interaction between its major software components. Simulated telemetry is submitted to the backend using an HTTP request, while other endpoints provide access to balance information, machine-learning

results, dashboard data, and system health information.

3.14 FastAPI Backend

FastAPI is a Python-based framework for developing web APIs. In the proposed system, FastAPI acts as the main backend application layer connecting telemetry processing, database management, machine-learning functions, blockchain interaction, and the frontend dashboard.

The backend receives simulated telemetry, stores and retrieves system information, interacts with the blockchain layer, processes machine-learning operations, and provides structured data to the frontend.

3.15 Database Management

A database is used to store, organize, and retrieve information generated by an application. The proposed system uses SQLite for persistent storage of telemetry, user balance information, and anomaly alerts.

The main logical entities maintained by the system are:

- `TelemetryLog`, which stores simulated electricity telemetry and related system status information.
- `UserBalance`, which stores wallet addresses, prepaid balances, authorization state, and related transaction information.
- `AnomalyAlert`, which stores detected anomalies, anomaly scores, severity, resolution state, and associated actions.

3.16 Web-Based Monitoring Dashboard

A web-based monitoring dashboard provides a graphical interface for displaying system information to users. Such dashboards can simplify the interpretation of current measurements, historical trends, warnings, and predictions.

The proposed system uses React with Vite to implement the frontend dashboard. The dashboard displays current load, prepaid balance, estimated remaining time, anomaly

score, recent consumption data, forecasted consumption, and recent anomaly alerts. Recharts is used to visualize consumption and forecasting information.

3.17 Software-Based Smart Grid Simulation

Since physical electrical measurement and power-control hardware are outside the scope of the current project, the proposed system uses simulated telemetry to represent electricity consumption.

The simulation provides a controlled environment in which the complete software architecture can be evaluated. It allows the project to demonstrate telemetry processing, database storage, machine-learning analysis, prepaid balance management, blockchain interaction, anomaly handling, and dashboard visualization without requiring physical electrical infrastructure.

3.18 Summary

The concepts presented in this chapter provide the theoretical foundation for the proposed Decentralized Prepaid Smart Power Grid. Smart grid principles provide the overall context, while prepaid electricity management and blockchain-based smart contracts provide the basis for prepaid balance and authorization management. Machine-learning techniques support anomaly detection and electricity consumption forecasting, while RESTful APIs, database management, and web technologies provide the software infrastructure required to integrate these components.

The resulting architecture is a hybrid system in which blockchain provides the decentralized component for prepaid balance and authorization management, while the backend, database, machine-learning engine, and frontend provide centralized application services. The project evaluates this architecture using simulated electricity telemetry rather than physical electrical hardware.

CHAPTER 4

METHODOLOGY

4.1 Overview

The proposed Decentralized Prepaid Smart Power Grid is developed as a software-based prototype that integrates prepaid electricity management, blockchain technology, machine learning, database management, and a web-based monitoring system.

The project follows a hybrid architecture. Blockchain technology is used for prepaid balance and authorization management, while the backend, database, machine-learning components, and frontend are implemented as conventional software services. Since physical electrical hardware is outside the scope of the project, electricity consumption data is simulated and used as input to the system.

4.2 System Architecture

The proposed system consists of the following major components:

- Simulated electricity telemetry
- FastAPI backend
- SQLite database
- Blockchain smart contract
- Machine-learning module
- Web-based monitoring dashboard

Simulated electricity consumption data is submitted to the backend through a RESTful API. The backend processes and stores the received information and coordinates communication with the machine-learning and blockchain components. The processed information is then made available through the web-based dashboard.

4.3 Telemetry Simulation

Since physical electricity meters and power measurement hardware are not implemented in the current project, electricity consumption is represented through simulated telemetry.

The simulated telemetry contains information such as:

- Device identifier
- Timestamp
- Power consumption
- Load percentage
- Relay status
- Authorization status

The simulated data is submitted to the backend at regular intervals. This allows the proposed system to reproduce the software-level data flow of a smart electricity monitoring system without requiring physical electrical infrastructure.

4.4 Backend Development

The backend is developed using Python and FastAPI. It acts as the primary application layer and provides communication between the telemetry source, database, machine-learning module, blockchain layer, and frontend.

The backend provides interfaces for:

- Receiving and retrieving telemetry data
- Managing prepaid balance information
- Providing machine-learning results
- Providing dashboard information
- Monitoring system health

The backend also communicates with the blockchain through a Web3-based interface

to retrieve and update prepaid and authorization-related information.

4.5 Database Management

SQLite is used as the database for storing application data. SQLAlchemy is used to manage interaction between the backend and the database.

The major database entities are:

4.5.1 Telemetry Log

The `TelemetryLog` entity stores simulated electricity telemetry, including power consumption, load percentage, timestamp, relay status, authorization state, anomaly information, and estimated remaining time.

4.5.2 User Balance

The `UserBalance` entity stores information related to users' blockchain wallets, prepaid balances, authorization status, and transaction information.

4.5.3 Anomaly Alert

The `AnomalyAlert` entity stores information related to detected abnormal consumption patterns, including anomaly type, severity, anomaly score, resolution status, and actions taken.

4.6 Blockchain Implementation

The blockchain component is implemented using Solidity and tested using the Hardhat development environment. The prepaid electricity functionality is represented through a smart contract named `PrepaidGrid`.

The smart contract provides functions for:

- Purchasing prepaid tokens
- Retrieving the prepaid balance

- Checking user authorization
- Deducting prepaid balance
- Triggering anomaly-related cutoff operations
- Restoring authorization after an anomaly is resolved

The backend communicates with the smart contract using Web3.py. This provides an interface between the conventional application layer and the blockchain layer.

4.7 Prepaid Balance Management

A user purchases prepaid tokens through the smart contract. The purchased amount is associated with the user's blockchain wallet address.

As simulated electricity consumption is received, the system calculates the corresponding consumption and updates the prepaid balance. The user's authorization state is also checked during the process.

If the available balance becomes insufficient, or if a predefined security condition is satisfied, the system can change the user's authorization state through the smart contract.

4.8 Anomaly Detection

The proposed system uses machine learning to identify abnormal electricity consumption patterns. The Isolation Forest algorithm is used for anomaly detection.

Recent consumption observations are provided to the model. The model evaluates the observations and determines whether a particular consumption pattern differs significantly from the normal pattern.

The anomaly detection process consists of the following steps:

1. Receive simulated electricity telemetry.
2. Extract the relevant consumption information.
3. Maintain a recent set of consumption observations.
4. Apply the Isolation Forest algorithm.

5. Generate the anomaly result and anomaly score.
6. Store the result in the database.
7. Display the detected anomaly through the monitoring interface.
8. Initiate the appropriate authorization action when required.

4.9 Energy Consumption Forecasting

The system uses Linear Regression to estimate future electricity consumption. Historical consumption data is used to train the forecasting model.

The model generates an estimated consumption forecast for the upcoming period. The predicted consumption rate is also used to estimate the approximate amount of time for which the available prepaid balance may remain sufficient.

The estimated remaining time is calculated using:

$$H_{\text{remaining}} = \frac{B}{R_{\text{avg}}} \quad (4.1)$$

where $H_{\text{remaining}}$ represents the estimated remaining time, B represents the available prepaid balance, and R_{avg} represents the estimated average consumption rate.

4.10 Blockchain and Anomaly Management

The proposed system links the anomaly detection process with blockchain-based authorization management.

When an abnormal consumption pattern is detected, the backend records the event and evaluates the associated condition. If the anomaly satisfies the required condition, the backend can invoke the smart contract function responsible for anomaly-related cutoff.

After the anomaly has been investigated or resolved, authorization can be restored through the corresponding smart contract function.

This integration connects machine-learning-based detection with rule-based authorization management.

4.11 Web-Based Monitoring System

A web-based monitoring interface is developed using React and Vite. The interface provides users with information about the current state of the proposed system.

The monitoring interface presents:

- Current electricity load
- Prepaid balance
- Estimated remaining time
- Authorization status
- Anomaly information
- Historical consumption
- Consumption forecast

The frontend obtains the required information from the FastAPI backend through HTTP requests.

4.12 System Workflow

The overall workflow of the proposed system is as follows:

1. Simulated electricity consumption data is generated.
2. The telemetry data is submitted to the FastAPI backend.
3. The backend validates and stores the received data in the SQLite database.
4. The recent consumption data is analyzed by the anomaly detection model.
5. Historical consumption data is processed by the forecasting model.
6. The backend communicates with the blockchain layer to obtain prepaid balance and authorization information.
7. The prepaid balance is updated according to the simulated electricity consumption.
8. If a significant anomaly is detected, the corresponding authorization or cutoff

operation can be initiated.

9. The processed information is provided to the frontend.
10. The web-based interface displays consumption, balance, forecast, and anomaly information to the user.

4.13 Testing and Evaluation

The proposed system is evaluated through software-based testing using simulated electricity telemetry.

The evaluation includes:

- Testing telemetry submission and processing
- Testing database storage and retrieval
- Testing prepaid token purchase and balance retrieval
- Testing prepaid balance deduction
- Testing authorization management
- Testing anomaly detection
- Testing electricity consumption forecasting
- Testing anomaly-triggered cutoff operations
- Testing communication between the backend and blockchain
- Testing the information displayed by the monitoring interface

4.14 Scope of Implementation

The current project focuses on the software implementation and simulation of the proposed Decentralized Prepaid Smart Power Grid.

The implementation includes simulated electricity telemetry, backend processing, database management, blockchain-based prepaid balance management, machine-learning-based anomaly detection, electricity consumption forecasting, and web-based monitoring.

Physical electricity meters, ESP32 devices, sensors, relays, and actual electrical dis-

tribution infrastructure are not included in the current implementation. The blockchain component is also evaluated using a local Hardhat development environment rather than a public production blockchain network.

4.15 Summary

The proposed methodology integrates simulated electricity telemetry, backend services, database management, blockchain-based prepaid management, machine-learning techniques, and a web-based monitoring interface into a single software prototype.

The hybrid architecture allows blockchain to handle prepaid balance and authorization-related operations while the backend manages telemetry processing, data storage, machine-learning analysis, and communication with the frontend. The methodology provides a controlled environment for demonstrating the proposed system without requiring physical electrical hardware.

CHAPTER 5

EXPECTED RESULTS

5.1 Overview

The proposed project is expected to result in a functional software prototype of a Decentralized Prepaid Smart Power Grid. The system will integrate prepaid electricity management, blockchain-based authorization, machine-learning-based analysis, database management, and web-based monitoring into a unified software environment.

The expected results of the project are described below.

5.2 Prepaid Electricity Management

The system is expected to provide a functional prepaid electricity management mechanism through a blockchain smart contract. Users will be able to purchase prepaid tokens, retrieve their available balance, and have their balance reduced according to simulated electricity consumption.

The system is also expected to maintain the authorization state of users and provide mechanisms for restricting and restoring authorization based on predefined conditions.

5.3 Blockchain-Based Balance and Authorization

The blockchain component is expected to provide a transparent and traceable mechanism for managing prepaid balances and authorization-related operations.

The smart contract is expected to support token purchase, balance retrieval, balance deduction, authorization checking, and anomaly-related cutoff operations. This will demonstrate the decentralized component of the proposed system.

5.4 Electricity Consumption Monitoring

The proposed system is expected to successfully receive and process simulated electricity telemetry through the backend. The telemetry will provide information related

to electricity consumption and system status.

The processed information is expected to be stored in the database and made available for further analysis and visualization.

5.5 Anomaly Detection

The machine-learning module is expected to identify abnormal electricity consumption patterns using the Isolation Forest algorithm.

The system is expected to generate anomaly information and anomaly scores for unusual consumption patterns and store the detected events in the database. The detected anomalies are also expected to be presented through the monitoring interface.

5.6 Electricity Consumption Forecasting

The proposed system is expected to generate short-term electricity consumption forecasts using Linear Regression.

The forecasting module is expected to provide estimated future consumption and an approximate remaining usage duration based on the available prepaid balance and estimated consumption rate.

5.7 Web-Based Monitoring

The system is expected to provide a web-based monitoring interface through which users can observe important system information.

The interface is expected to display:

- Current electricity consumption
- Prepaid balance
- Authorization status
- Estimated remaining time
- Historical consumption information
- Forecasted electricity consumption

- Detected anomaly information

5.8 Integration of System Components

The project is expected to demonstrate successful communication among the major software components, including the backend, database, blockchain, machine-learning module, and frontend.

The integrated system is expected to provide a continuous software workflow from simulated telemetry generation to data processing, anomaly detection, forecasting, prepaid balance management, and user visualization.

5.9 Expected Benefits

The proposed system is expected to provide the following benefits:

- Improved visibility of electricity consumption and prepaid balance.
- Automated management of prepaid electricity credit.
- Transparent and traceable prepaid transactions through blockchain.
- Detection of unusual electricity consumption patterns.
- Estimation of future electricity consumption.
- Improved monitoring through a unified web-based interface.
- A modular software architecture that can be extended in future work.

5.10 Project Deliverables

At the completion of the project, the following deliverables are expected:

- A functional blockchain smart contract for prepaid electricity management.
- A FastAPI-based backend for system communication and data processing.
- A SQLite database for storing telemetry, balance, and anomaly information.
- An anomaly detection module based on Isolation Forest.
- An electricity consumption forecasting module based on Linear Regression.

- A React-based web monitoring interface.
- A software-based simulation environment for evaluating the proposed system.

5.11 Scope of Expected Results

The expected results are limited to the software-based implementation and simulation of the proposed smart power grid. The project is not expected to demonstrate physical electricity measurement, electrical load switching, or actual power distribution.

Physical hardware integration, real electricity metering, deployment on a public blockchain network, and large-scale field testing may be considered as future extensions of the project.

CHAPTER 6

CONCLUSION

The proposed Decentralized Prepaid Smart Power Grid is intended to provide a software-based approach for prepaid electricity management by integrating blockchain technology, machine learning, backend services, database management, and web-based monitoring. The system is designed to address limitations associated with conventional prepaid electricity management by providing improved transparency, automated balance management, consumption analysis, and user monitoring.

The proposed architecture uses a blockchain smart contract to manage prepaid balances and authorization-related operations. The FastAPI backend is responsible for receiving and processing simulated electricity telemetry, managing application data, and communicating with the blockchain and machine-learning components. The Isolation Forest algorithm is proposed for detecting abnormal consumption patterns, while Linear Regression is used for short-term electricity consumption forecasting.

The system follows a hybrid architecture rather than a fully decentralized architecture. Blockchain provides the decentralized component for prepaid balance and authorization management, while the backend, database, machine-learning module, and web interface provide the remaining application services. This separation allows the proposed system to demonstrate the use of decentralized technology without requiring the complete application to operate on the blockchain.

Since physical electricity meters, sensors, relays, and other electrical hardware are outside the scope of the current project, electricity consumption will be represented using simulated telemetry. The project will therefore focus on evaluating the software architecture and the interaction among its major components in a controlled environment.

The proposed system is expected to demonstrate the feasibility of integrating blockchain-based prepaid management with machine-learning-based consumption analysis and web-based monitoring. The developed prototype may provide a foundation for future extensions involving physical smart-metering devices, real electrical load control, broader blockchain deployment, and real-world testing.

Overall, the project aims to demonstrate a practical software architecture for intelligent prepaid electricity management that combines blockchain-based authorization and balance management with automated analysis and monitoring.

REFERENCES

APPENDIX A

APPENDIX B