EX. NO: 11 DATE: 09/09/2026

EXAMINE NETWORK ADDRESS TRANSLATION (NAT) USING CISCO PACKET TRACER

AIM:

To implement Network Address Translation (NAT) in Cisco Packet Tracer and allow private devices to communicate with an outside network.

PROCEDURE:

1) Add devices:

- 2 PCs
- 1 Switch
- 1 Router
- 1 Cloud / another Router

2) Connect devices:

- PC1 & PC2 → Switch
- Switch → Router G0/0
- Router G0/1 → Outside Router / Cloud

IP ADDRESS ASSIGNMENT:

Device	IP Address	Gateway
PC1	192.168.1.10	192.168.1.1
PC2	192.168.1.11	192.168.1.1
Router G0/0	192.168.1.1	-
Router G0/1	200.1.1.1	-

ROUTER CONFIGURATION:

Open Router → CLI and execute the following commands:

```
enable
configure terminal
! Interface Configuration
interface GigabitEthernet0/0
 ip address 192.168.1.1 255.255.255.0
 ip nat inside
 no shutdown
 exit
interface GigabitEthernet0/1
 ip address 200.1.1.1 255.255.255.0
```

EST NAT / VERIFICATION:

- From PC1, open Command Prompt and type: **ping 200.1.1.2**
- Check NAT translations on the router CLI: **show ip nat translations**

RESULT:

NAT was successfully configured & private IP addresses were translated to public IP addresses for communication with the outside network.