CS 839 Programming Assignment
Sustained Two-Leg Support for MuJoCo Ant

Haoyang Tang

Fall 2026

1 Interesting Behavior

The Ant should remain upright with exactly two feet on the ground for as much of each episode as possible. Balancing this unstable body using eight joint torques, without support from another foot or body part, is non-trivial.

2 Task MDP

State.
A 118-dimensional vector: the standard Ant joint, velocity, and contact-force observation, plus four foot-contact indicators, normalized target hold progress, and a two-element target-pair indicator.

Action.
Eight continuous joint torques in $[-1, 1]^8$.

Reward.
Let I_t mark a valid two-leg pose, h_t and u_t be clipped height and upright scores, d_t target-contact quality, p_t hold progress, b_t a completed target hold, B_t body contact, and D_t termination:

$$r_t = c_t + h_t + u_t + 4I_t + 0.5d_t h_t u_t + 2p_t + 2b_t - 4B_t - 0.02\|\omega_t\|^2 - 0.02\|a_t\|^2 - 20D_t,$$

where $c_t = \max(0, 1 - 0.5|n_t - 2|)$ and n_t is the number of grounded feet.

Episode.
1,000 steps at 0.05 seconds per step, or 50 seconds.

Termination.
Terminate if torso up-alignment is below -0.2 or the simulation becomes non-finite; otherwise truncate at 1,000 steps.

The observation includes the mechanical state and reward-relevant task memory, so I treat it as Markov for this position-invariant task.

3 True Performance Metric

A valid pose has exactly two grounded feet, torso height at least 0.45 m, positive torso up-alignment, and no other body contact. Performance is

$$M = 0.05 \sum_{t=1}^{T} \mathbf{1}[\text{valid two-leg pose at } t],$$

measured in seconds from 0 to 50. It directly measures the intended behavior and excludes reward-shaping terms.

4 Training Performance

I used paired training seeds 1–5. I smoothed each seed with a 20-episode rolling mean, interpolated it onto a 5,000-step grid, and then averaged. Thin lines are individual seeds; shading is the 95% Student-t interval $\bar{x} \pm 2.776 s/\sqrt{5}$.




Figure 1: Mean episodic return. SAC ends at 300,000 steps; PPO continues to approximately 899,000 steps.




Figure 2: Mean true performance: valid two-leg seconds per 50-second episode.

5 Algorithm Comparison

Final deterministic evaluation used the same ten evaluation seeds for every policy. Values are means and 95% intervals across five training seeds.

	Return	Two-leg time (s)	Fraction	Longest hold (s)
PPO	6011 ± 386	36.11 ± 3.58	0.722 ± 0.072	0.969 ± 0.539
SAC	6777 ± 571	40.66 ± 3.09	0.813 ± 0.062	1.111 ± 0.287

SAC achieved higher observed final performance despite using 300,000 steps, versus 899,072 for PPO. Its smoothed mean exceeded 35 two-leg seconds near 65,000 steps; PPO first exceeded 30 seconds near 645,000 steps. SAC was likely more sample-efficient because its replay buffer reuses experience, while PPO is on-policy. True-metric standard deviation was 2.49 s for SAC and 2.89 s for PPO, although SAC's return varied more. The paired SAC improvement in two-leg time was 4.55 s with a 95% interval of $[-1.34, 10.44]$, so it is not conclusive with five seeds.

Earlier survival, height, sparse-bonus, and alternating-pair rewards produced upright motion or preference for one pair rather than reliable two-foot support. Dense valid-pose and hold-progress rewards improved total two-leg time. However, all final policies recorded zero valid pair switches and only about a one-second longest continuous hold. They solve aggregate two-leg time, not the more ambitious alternating-pair behavior.

6 Best Policy Video

`best_policy_sac_seed3.mp4` shows the best policy: SAC seed 3, averaging 43.12 two-leg seconds (86.24% of an episode). It stays upright but does not alternate support pairs.

7 Reproducibility

Code is included and available at https://github.com/Sacbill/839homework. Exact paired-run commands are:

```
for seed in 1 2 3 4 5; do
  .venv/bin/python cleanrl/ppo_two_leg.py --env-id AntTwoLeg-v0 \
    --exp-name ppo_sustained_hold_v4 --seed "$seed" \
    --total-timesteps 900000 --eval-episodes 10 --capture-video --save-model
done
for seed in 1 2 3 4 5; do
  .venv/bin/python cleanrl/sac_two_leg.py --env-id AntTwoLeg-v0 \
    --exp-name sac_sustained_hold_v4 --seed "$seed" \
    --total-timesteps 300000 --learning-starts 5000 --buffer-size 300000 \
    --eval-episodes 10 --capture-video --save-model
done
.venv/bin/python analysis/two_leg_five_seed/analyze_runs.py
```

AI Use Disclosure

I used OpenAI Codex for reward-design discussion, implementation and debugging assistance, result analysis, plotting, and report preparation. I reviewed the experiments and take responsibility for the submitted work.