Fixed Range Pressure Transmitter adopts stainless steel shell structure, built in stainless steel oil filled sensor, intelligent digital circuit with precise temperature characteristic compensation, it can be used reliably and stably.

It is suitable for gas, liquid, steam pressure measurement and pressure measurement with corrosive media, it can also be used for level measurement.



Specifications

Model	ISPPT | Gauge, Absolute
Range	-1 to 600 Bar
Units	mmH2O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH2o, mHg
Supply	12 - 32V DC
Output	4-20 mA, Two wire loop-powered
Accuracy	±0.5% of Span / ±0.25% of Span
Stability	±0.1% of URL per 10 years
Response Time	<100 ms
Permissible Temperature	-20°C to +85°C
Display Type	Withput Display
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316, SS316L, Gold Plated, Hastelloy C 276, Tantalum
Housing	SS304, SS316, SS316L
Process Connection	1/2" NPT (M), 1/2" BSP (M), 1/2" NPT (F), M20 X 1.5, 3/4" NPT (M) (Flushed) and as per requirements
Electrical Connection	4 Pin DIN Connector