The Smart Pressure Transmitter with HART protocol converts input pressure signals into 4 to 20 mA analogue output signal. The transmitter can be programmed via three buttons alternatively through PC. Following parameters can be adjusted : Zero, Span, Decimal Point, Damping, Display Mode, Restore Data and so on. For parameter setting and visualization of measured value, liquid crystal displays with backlit is available. The transmitter is protected against wrong wiring and transient over voltages.



Specifications

Model	ISPT-200 | Gauge, Absolute
Range	-1 to 700 Bar
Units	mmH2O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH2o, mHg
Supply	12 - 32V DC
Output	4-20 mA (2 Wire) with HART protocol
Accuracy	±0.075% of Span / ±0.065% of Span / ±0.04% of Span / ±0.025% of Span
Stability	±0.1% of URL per 10 years
Response Time	<100 ms
Load Impedence	600 ohms @ 24V DC
Permissible Temperature	-20°C to +70°C (for Electronics), -30°C to +100°C (for Process)
Span & Zero	Remote as well locally adjustable with zero elevation and supression by 100% o FS
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum Others : SS316, SS316L, Hastelloy
Housing	Die Cast Aluminium, Stainless Steel
Process Connection	1/2" NPT (M), 1/2" BSP (M), 1/2" NPT (F), M20 X 1.5, 3/4" NPT (M) (Flushed) and as per requirements
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Approval/Certification	ATEx, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO