***i*-TORK (Quarter Turn)** valve actuator is used for controlling 0~270 degree rotation valves and other similar products, such as butterfly valve, ball valve, damper, flapper valve, cock valve etc. If widely applies to petroleum, chemical, water treatment, shipping, paper making, power plant and other industries.

Drived by 380V/220V/110VAC or 24V/110VDC Power, Inputs 4~20 mA or 0~10 VDC control signal, moves valve to the right position and achieve to automatic control. The maximum output toque is 2000 N.m



Technical Standards

Model	*Power Supply*	*Torque*	*Stroke Time 50 Hz Only*	*Motor F Class In/Out*	*220 V Start Current*	*220 V Rati. Current*	*Weight*	*IP Class*	*Output Shaft Square (mm)*	*Output Shaft Depth (mm)*	*PCD*
i-Tork - QT 20A	AC24V AC220V 110V	20 NM	20/30 Sec	15W / 5W	0.12A	0.12A	1.8 kg	IP68	9	38	F05-50 / F07-70
i-Tork - QT 30A	AC380V 24V AC220V 110V	30 NM	20/30 Sec	30W / 10W	0.25A	0.25A	2.6 kg	IP68	11	38	F05-50 / F07-70
i-Tork - QT 50A	AC380V 24V AC220V 110V	50 NM	20/30 Sec	30W / 10W	0.25A	0.25A	2.6 kg	IP68	14	38	F05-50 / F07-70
i-Tork - QT 80A	AC380V 24V AC220V 110V	80 NM	30 Sec	80W / 23W	0.58A	0.5A	3.7 kg	IP68	14	32	F07-70
i-Tork - QT 100A	AC380V 24V AC220V 110V	100 NM	30 Sec	80W / 23W	0.58A	0.5A	3.7 kg	IP68	17	32	F07-70
i-Tork - QT 150A	AC380V 24V AC220V 110V	150 NM	45 Sec	100W / 30W	0.7A	0.6A	3.7 kg	IP68	17	32	F07-70
i-Tork - QT 200A	AC380V 24V AC220V 110V	200 NM	45 Sec	100W / 30W	0.72A	0.68A	3.7 kg	IP68	22	41	F10-102 / F12-125
i-Tork - QT 400A	AC380V 24V AC220V 110V	400 NM	30 Sec	300W / 90W	1.38A	1.2A	8.0 kg	IP68	22	41	F10-102 / F12-125
i-Tork - QT 600A	AC380V 24V AC220V 110V	600 NM	30 Sec	300W / 90W	1.38A	1.2A	12 kg	IP68	27	33	F10-102 / F12-125
i-Tork - QT 1000A	AC380V 24V AC220V 110V	1000 NM	50 Sec	300W / 90W	1.38A	1.2A	12 kg	IP68	27	33	F12-125
i-Tork - QT 2000A	AC380V 24V AC220V 110V	2000 NM	100 Sec	300W / 90W	1.38A	1.2A	12 kg	IP68	36	33	F12-125
i-Tork - QT 30B	DC24V AC24V AC220V 110V	30 NM	30 Sec	30W / 10W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	3.0 kg	IP68	11	38	F05-50 / F07-70
i-Tork - QT 50B	DC24V AC24V AC220V 110V	50 NM	30 Sec	30W / 10W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	3.0 kg	IP68	14	38	F05-50 / F07-70
i-Tork - QT 80B	DC24V AC24V AC220V 110V	80 NM	30 Sec	80W / 23W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	4.5 kg	IP68	14	32	F07-70
i-Tork - QT 100B	DC24V AC24V AC220V 110V	100 NM	30 Sec	80W / 23W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	4.5 kg	IP68	17	32	F07-70
i-Tork - QT 200B	DC24V AC24V AC220V 110V	200 NM	30 Sec	150W / 45W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	7.5 kg	IP68	22	41	F10-102 / F12-125
i-Tork - QT 400B	DC24V AC24V AC220V 110V	400 NM	30 Sec	300W / 90W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	8.7 kg	IP68	22	41	F10-102 / F12-125
i-Tork - QT 600B	DC24V AC24V AC220V 110V	600 NM	30 Sec	300W / 90W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	8.7 kg	IP68	27	33	F10-102 / F12-125
i-Tork - QT 1000B	DC24V AC24V AC220V 110V	1000 NM	50 Sec	300W / 90W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	12.8 kg	IP68	27	33	F12-125
i-Tork - QT 2000B	DC24V AC24V AC220V 110V	2000 NM	100 Sec	300W / 90W	Input Signal 4-20 mA 0-10 V	Output Signal 4-20 mA	12.8 kg	IP68	36	33	F12-125