A **differential pressure transmitter** is an instrument that can consistently and accurately create a pressure drop in a pipe and then use the pressure measurement on either side to provide the rate of flow within the pipe.

This transmitter uses two elements to measure the differences of pressure in a sealed container such as a pipe.



Specifications

Model	ISDPT-200 | Differential Pressure Transmitter
Range	-0.01 to 0.01 Bar | -100 to 100 Bar
Units	mmH2O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH2o, mHg
Supply	12 - 32V DC
Output	4-20 mA (2 Wire) with HART protocol
Accuracy	±0.075% of Span / ±0.065% of Span / ±0.04% of Span / ±0.025% of Span
Stability	±0.1% of URL per 10 years
Response Time	<100 ms
Load Impedence	600 ohms @ 24V DC
Permissible Temperature	-20°C to +70°C (for Electronics), -30°C to +85°C (for Process)
Span & Zero	Remote as well locally adjustable with zero elevation and supression by 100% o FS
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum Others : SS316, SS316L, Hastelloy
Housing	Die Cast Aluminium, Stainless Steel
Process Connection	1/4" NPT (F) | [with sockets - 1/2" NPT (M), 1/2" BSP (M), 1/2" BSP (F), 1/2" NPT (F), M20 X 1.5, and as per requirements]
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Approval/Certification	ATEx, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO