

A **i-TORK (Multi Turn)** valve actuator is the mechanism for opening and closing a valve. Manually operated valves require someone in attendance to adjust them using a direct or geared mechanism attached to the valve stem.



Standard Features

- Three phase electric Motor : Supply Voltage 415V AC/50Hz
- Motor Type : AC Three phase induction - TEFC
- Insulation : Class “F”
- Built in LCD display for real time actuator position and valves alarms.
- Limit Switches - Electronic Programmable.
- Motor load sensing instead of mechanical torque switch.
- Zero / Span programable & auto calibration.
- Inbuilt motor protection circuit including phase imbalance / phase failure / phase reversal / over voltage / under voltage.
- No extra voltage protection panel required.
- Over temperature sensing & tripping motor.

Technical Standards

Model	Output Data				Motor Date : Type			Output Bore Mounting PCD As per ISO 5211	Weight (Approx)
	Rated Torque	Adjustable Torque	Output Speed	Actuator Self Locking	415 VAC/50 Hzs, Three Phase Squirrel Cage Induction Motor				
					Output Rated	No. of Pole	Current Rated		
					Nm	Nm	Rpm		
iTork-MT 80	30	10-30	10, 15, 20, 30 40, 60 & 70	YES	0.37 / 0.5	4	1	F10	60
			80, 120 & 140						
			190, 240, 270 & 365	NO		2	1.1		
iTork-MT 80	60	18-80	10, 15, 20, 30 40, 60 & 70	YES	0.37 / 0.5	4	1	F10	60
			80, 120 & 140						
			190, 240, 270 & 365	NO		2	1.1		
iTork-MT 80	80	20-80	10, 15, 20, 30 40, 60 & 70	YES	0.75 / 1.0	4	1.8	F10	64
			80, 120 & 140						
			190, 240, 270 & 365	NO	0.75 / 1.0	2	1.7		
iTork-MT 250	100	25-100	10, 15, 20, 30 40, 60 & 70	YES	0.75 / 1.0	4	1.8	F10	65
			80, 120 & 140						
			190, 240, 270 & 365	NO	2.20 / 3.0	2	4.6		68
iTork-MT 250	150	30-150	10, 20 & 30	YES	0.75 / 1.0	4	1.8	F14	75
			40, 60, 70, 80 & 120	NO		2	1.7		
iTork-MT 250	200	60-200	10, 20 & 30	YES	0.75 / 1.0	1410	1.8	F14	75
			40, 60, 70, 80 & 120	NO		1.5 / 2.0	2800		4.6
			iTork-MT 250	250	75-250	10, 20 & 30	YES		1.5 / 2.0
			40, 60, 70, 80, 120 & 140	NO	3.70 / 5.0	2800	7.2		98