

The **Smart Pressure Transmitter** with HART protocol converts input pressure signals into 4 to 20 mA analogue output signal. The transmitter can be programmed via three buttons alternatively through PC. Following parameters can be adjusted : Zero, Span, Decimal Point, Damping, Display Mode, Restore Data and so on. For parameter setting and visualization of measured value, liquid crystal displays with backlit is available. The transmitter is protected against wrong wiring and transient over voltages.



## Specifications

|                                |                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                   | ISPT-200   Gauge, Absolute                                                                                                      |
| <b>Range</b>                   | -1 to 700 Bar                                                                                                                   |
| <b>Units</b>                   | mmH <sub>2</sub> O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH <sub>2</sub> O, mHg                                     |
| <b>Supply</b>                  | 12 - 32V DC                                                                                                                     |
| <b>Output</b>                  | 4-20 mA (2 Wire) with HART protocol                                                                                             |
| <b>Accuracy</b>                | ±0.075% of Span / ±0.065% of Span / ±0.04% of Span / ±0.025% of Span                                                            |
| <b>Stability</b>               | ±0.1% of URL per 10 years                                                                                                       |
| <b>Response Time</b>           | <100 ms                                                                                                                         |
| <b>Load Impedance</b>          | 600 ohms @ 24V DC                                                                                                               |
| <b>Permissible Temperature</b> | -20°C to +70°C (for Electronics), -30°C to +100°C (for Process)                                                                 |
| <b>Span &amp; Zero</b>         | Remote as well locally adjustable with zero elevation and suppression by 100% of FS                                             |
| <b>Display Type</b>            | 5 digits programmable and 0-100% bargraph, 360° rotation LCD                                                                    |
| <b>Protection Grade</b>        | IP68                                                                                                                            |
| <b>Wetted Parts</b>            | Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum<br>Others : SS316, SS316L, Hastelloy                                 |
| <b>Housing</b>                 | Die Cast Aluminium, Stainless Steel                                                                                             |
| <b>Process Connection</b>      | 1/2" NPT (M), 1/2" BSP (M), 1/2" NPT (F), M20 X 1.5, 3/4" NPT (M) (Flushed) and as per requirements                             |
| <b>Electrical Connection</b>   | 1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated) |
| <b>Approval/Certification</b>  | ATEX, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO                                                               |