



This micro-based full bore type electromagnetic flow meters specially used for various industrial applications. These flow meters accurately measure the flow rate of conductive liquid & slurries inclosed pipes. Due to simple & rigid design, the flow meter is an obstruction less & maintenance free instrument in place of conventional mechanical flow measuring device. The use of 'Pulsed DC' technology offers highest ability & better measuring accuracy in the form of electrical signal 4-20 mA DC linearly proportional to volumetric flow. The instrument is based on Faraday's law of electro-magnetic induction. A magnetic field is generated by the instrument in the flow tube. The fluid flowing through this magnetic field generates a voltage that is proportional to the flow velocity. Corresponding electrical output is provided with respect to measuring flow range.

Specifications

Accuracy	$\pm 0.5 \%$ and $\pm 0.2 \%$
Repeatability	$\pm 0.2\%$ of Span or Better
Electrode Q'ty	2pcs (Standard), 3pcs or others (Option)
Min. Conductivity	5 Micro Simens
Measuring Range	0.2-12m/sec, Bi-direction
Diameter (mm)	10-3000 mm
Working Pressure (kg/cm ²)	12,18,26,42 or as per requirement
Working Temperature (°C)	0- 120°C, 0-150°C (0-180°C with cooling pin) (Choice of lining material)
Body	MS,SS 304, SS 316,SS 316L
Electrode	SS 316L, Titanium, Tantalum, Hastelloy, , Platinum, SS Duplex
Measuring Tube	SS 304, SS 316, SS 316L
Lining	Hard Rubber, PTFE, Polyurethane, PFA, Polypropylene
Flange	DIN, ANSI, BS
Meter Protection Level	IP65
Ambient Temperature	-20- 60°C
Power supply	24 VDC, 90-260 VAC, 50Hz
Output	Standard output 4-20 mA, RS485 Option: RS232, HART
Display	LCD-2 Line LCD