

A **Hydrostatic level transmitter** is an instrument providing continuous level measurement. It can be used to determine the level of liquid or bulk-solid at a particular time. Levels of media such as water, viscous fluids, and fuels, or dry media such as bulk solids and powders can be measured using the transmitter.



Specifications

Model	ISPT-200 Hydrostatic Level Transmitter
Range	0 to 1000 Meters
Units	mmH ₂ O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH ₂ o, mHg
Supply	12 - 32V DC
Output	4-20 mA (2 Wire) with HART protocol
Accuracy	±0.075% of Span / ±0.065% of Span / ±0.04% of Span / ±0.025% of Span
Stability	±0.1% of URL per 10 years
Response Time	<100 ms
Permissible Temperature	-20°C to +70°C (for Electronics), -30°C to +125°C (for Process)
Span & Zero	Remote as well locally adjustable with zero elevation and supression by 100% o FS
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum,
Housing	Die Cast Aluminium, Stainless Steel
Flange Material	SS304, SS316, SS316L, Hastelloy
Flange Connection	3/4", 1" 2" 3" 4" 6" and as per requirement (with extended diaphragm)
Flange Class	150#, 300#, 600# and per requirement
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Approval/Certification	ATEX, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO