

Smart temperature transmitter supports various input signal, such as RTD, thermocouple, resistance and voltage signal, using PAD or PC for configuration freely, automatically adjusting input signal type, measuring range and thermocouple cold junction compensation, optional HART communication function, with high accurate, low temperature drift, long service life, and easy to replace.



Specifications

Model	ISTT-200 Temperature Transmitter
Range	-200° ~ 1370° C for Thermocouple -200° ~ 600° C for RTD
Units	°C, °F
Input Channel	Single/Dual Channel 2,3 & 4 wire RTD, Thermocouple, mV & ohm inputs
Supply	12-32V DC
Output	4-20 mA (2 Wire) with HART protocol
Accuracy	±0.15% of Span
Response Time	<100 ms
Load Impedence	600 ohms @ 24V DC
Span & Zero	Remote as well locally adjustable with zero elevation and supression by 100% o FS
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD
Protection Grade	IP68
Housing	Die Cast Aluminium, Stainless Steel
Max Load	600Ω @ 24V DC
Warm Up	2 Minutes
Start-Up Time	5 Seconds
Working Temperature	-20° to 70°C (For Electronics)
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Approval/Certificate	ATEX, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO