

The **DP Type Level Transmitter** device is used to measure level as an inferential measurement. In a DP Transmitter, the diaphragm senses the head pressure developed by the height of the material in the vessel. This quantity is multiplied by a density variable to get the correct level measurement.



Specifications

Model	ISDPT-200 DP Type Level Transmitter
Range	0 to 1000 meters
Units	mmH2O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH2o, mHg
Supply	12 - 32V DC
Output	4-20 mA (2 Wire) with superimposed communication signal (HART protocol)
Accuracy	±0.075% of Span
Stability	±0.1% of URL per 10 years
Response Time	<100 ms
Load Impedence	600 ohms @ 24V DC
Permissible Temperature	-20°C to +70°C (for Electronics), -30°C to +125°C (for Process)
Span & Zero	Remote as well locally adjustable with zero elevation and supression by 100% o FS
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum
Housing	Die Cast Aluminium, Stainless Steel
Flange Material	SS304, SS316, SS316L
Flange Connection	1" 2" 3" 4" 6" and as per requirement (with extended diaphragm)
Flange Class	150#, 300#, 600# and per requirement
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Approval/Certification	ATEX, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO