

A **Remote Seal Pressure Transmitter** that allows the pressure transmitter to make measures in situations where the immediate contact of the transmitter diaphragm with the process fluid it is not allowed. The remote seal is made up by one connection with the diaphragm and one capillary connection with filling fluid. The filling fluid transfers the pressure measured in the process fluid to the transmitter sensor. The capillary connection links the seal diaphragm to the transmitter.



Specifications

Model	ISPT-200 Remote Seal Pressure Transmitter
Range	0 to 1000 Meters
Units	mmH ₂ O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH ₂ o, mHg
Supply	12 - 32V DC
Output	4-20 mA (2 Wire) with HART protocol
Accuracy	±0.075% of Span / ±0.065% of Span / ±0.04% of Span / ±0.025% of Span
Stability	±0.1% of URL per 10 years
Response Time	<100 ms
Permissible Temperature	-20°C to +70°C (for Electronics), -30°C to +125°C (for Process)
Span & Zero	Remote as well locally adjustable with zero elevation and suppression by 100% of FS
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum
Housing	Die Cast Aluminium, Stainless Steel
Flange Material	SS304, SS316, SS316L, Hastelloy
Flange Connection	3/4", 1" 2" 3" 4" 6" and as per requirement (with extended diaphragm)
Flange Class	150#, 300#, 600# and per requirement
Capillary Material	SS304, SS316, SS316L, SS316+PVC
Capillary Length	1 mtr. 2 mtr. 3 mtr. 5 mtr. 6 mtr. 10 mtr. 15 mtr. and as per requirement
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Approval/Certification	ATEX, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO