

A **submersible level transmitter** is a device that measures and transmits the level of a liquid in a container, well, or other submerged application by measuring the hydrostatic pressure of the liquid.

These transmitters are designed to be submerged in liquids and are often used in industries where accurate and reliable liquid level monitoring is crucial.



Specifications

Model	ISSLT
Range	Upto 40 meters
Units	mmH2O, mmHg, Psi, Bar, mBar, gscm, kgscm, PA, kPA, MPA, mH2o, mHg
Wetted Parts	Diaphragm : SS316, SS316L, Gold Plated, Hastelloy C 276, Tantalum Case : SS316, SS316L, Hastelloy
Accuracy	$\pm 0.5\%$ of Span $\pm 0.25\%$ of Span (for non-smart) $\pm 0.075\%$ of Span / $\pm 0.065\%$ of Span / $\pm 0.04\%$ of Span / $\pm 0.025\%$ of Span (for smart)
Stability	$\pm 0.1\%$ of URL per 10 years
Response Time	<100 ms
Load Impedence	600 ohms @ 24V DC
Permissible Temperature	-20°C to +70°C (for Electronics), -30°C to +100°C (for Process)
Span & Zero	Remote as well locally adjustable with zero elevation and suppression by 100% of FS (for smart)
Display Type	5 digits programmable and 0-100% bargraph, 360° rotation LCD (for smart) Without Display (for non-smart)
Protection Grade	IP68
Wetted Parts	Diaphragm : SS316L, Gold Plated, Hastelloy C 276, Tantalum Others : SS316, SS316L, Hastelloy
Housing	Die Cast Aluminium, Stainless Steel
Process Connection	Submersible Type (No threaded connection)
Electrical Connection	1/2" NPT F (Plug & Socket Type, Harting Han Connector, Cable Gland - SS Double Compression, SS Plugs, PVC, Brass/Nickel Plated)
Cable Material	Polyurethane (PUR) or Polyethylene (PE)
Cable Lengths	Standard lengths of 5m, 10m, 15m ; Custom lengths available
Approval/Certification	ATEX, SIL2 and IEC Flameproof & Intrinsically safe approval, PESO