Evolve, Don't Retrain? Safety Adapters for Frozen Planners on Graded Hazards

Project page: https://sachin2911.github.io/evolveDontRetrain/

Sachin Mohan
sachinmohan29@gmail.com
University of the Witwatersrand
Johannesburg, South Africa

ABSTRACT

A small evolved adapter can make a frozen planner safer without retraining it. We evolve two kinds, each starting as an exact copy of the planner. Steer is a residual: it adds a sideways push to each move, away from the hazard. Choose is a re-ranker: it reorders the planner's own candidate plans and swaps in a clearer one when the planner's choice comes too close. Hazards sit on the planner's path at four graded levels, from clear of the path to an unavoidable one on the goal. A noticeable result we found was that the adapters transfer. One adapter, evolved on three systems driven by two different planners, ran unchanged on a fourth system it never saw and helped most there: safe finishes rose from 6 to 16/18 with no case lost, and every selected adapter beat the planner alone. On the training systems, safe finishes rose from 18 of 54 to between 23 and 34 (11 of 12 significant). The price is some unfinished tasks. CMA-ES held a slight edge over random search, all of it on the unseen system, yet one untrained adapter did nearly as well as both: the design, not the optimizer, did most of the work. On Block Plucking, an arm task, search found no signal.

CCS CONCEPTS

• **Computing methodologies** → **Bio-inspired approaches**; *Robotic planning*.

KEYWORDS

neuroevolution, CMA-ES, random search, world models, safe control, adapters

1 INTRODUCTION

A world model lets a planner try actions in imagination before it acts [11, 15]. Such planners now finish long tasks from camera images. But their cost measures only progress toward the goal. Nothing in it says what to avoid.

The usual fixes reach inside the planner: retrain it with a penalty whose weight must be tuned [1], or add a safety filter with hand-set thresholds [19]. We try a lighter fix from the outside. Evolution needs only a ranking, so safety can be ranked above progress with no weight to tune [8], and it can search a small layer beside a frozen planner, as in Ha and Schmidhuber's world models [9].

The planner is frozen and never sees the hazard; each adapter starts as an exact copy of it, so any change comes from the adapter. Each hazard sits on the planner's own path at one of four levels (Figure 1), from clear of the path to covering the goal.

Every adapter selected by search is compared, case by case, with three references: the bare planner, which we call *the planner alone*; random search with the same budget; and *untrained adapters*, whose genes are random and never searched. We ask:

- **RQ1.** Does an adapter add safe finishes over the planner alone, and at what cost?
- **RQ2.** Does CMA-ES beat random search?
- **RQ3.** Does search beat untrained adapters?
- **RQ4.** Does one shared adapter work on a system that search never saw?

Our contributions are:

- a test bed of graded hazards, placed on a frozen planner's own path, for adapters that start as exact copies;
- two adapters, Steer (a residual) and Choose (a re-ranker), that work with any planner and know which way is safe;
- transfer: one adapter, shared across two planners, ran unchanged on an unseen system and helped most there;
- a matched comparison of CMA-ES, random search and untrained adapters;

2 BACKGROUND

The planners. LeWorldModel (LeWM) [15] learns a world model from pixels. It plans with the cross-entropy method (CEM): sample many action sequences, keep the best, refit a Gaussian to them, and repeat. Far goals are hard for it, so we use Anchored Planning (AP) [14], which aims each plan at a nearby observation taken from memory instead of at the far goal. Every five actions, AP picks the five-action move whose imagined result lands closest to that anchor:

$$\mathbf{a}^{\star}_{t:t+4} = \arg\min_{\mathbf{a}} \left\| \hat{z}_{t+5}(\mathbf{a}) - z_t^{\text{anchor}} \right\|^2. \tag{1}$$

TD-MPC2 [11] learns from states instead, and plans with MPPI, a sampling method like CEM that weights samples by predicted value. We use its released Meta-World basketball checkpoint [21].

Safety and evolution. Constrained reinforcement learning treats risk as a limit [1, 6]; safety filters replace unsafe commands as they happen [12, 19]; residual learning adds a correction to a fixed controller [13, 20]. Evolution handles constraints without a penalty weight, by feasibility rules [8] or stochastic ranking [18], and has been used for safe reinforcement learning [4, 16]. CMA-ES [10] learns where to sample from the ranks of its samples, and its diagonal form [17] handles tens of genes; random search is its natural baseline [5]. As a few runs can hide large uncertainty [2], we compare methods case by case.

3 WHAT WE OPTIMIZE

An episode can go right in one way and wrong in two. It is a *safe finish* if the task is done and the body never touched the hazard. Let $g(\tau) = 1$ if episode τ finished the task, and $v(\tau) = 1$ if it touched the hazard at any step. For a policy π,

$$J_r(\pi) = \Pr_{\pi}[g = 1], \quad J_c(\pi) = \Pr_{\pi}[v = 1], \quad J_s(\pi) = \Pr_{\pi}[g = 1,\ v = 0]. \tag{2}$$

The textbook problem is a constrained Markov decision process [3]: finish as often as possible, $\max_\theta J_r(\pi_\theta)$, while keeping the chance of a touch below a limit, $J_c(\pi_\theta) \le \delta$, where π_θ is the planner with adapter θ [7]. The safe-finish rate ties the two goals together, $J_r - J_c \le J_s \le \min(J_r, 1 - J_c)$: raising J_s raises the floor on finishing and lowers the ceiling on touching. We fix no limit and no weight; ranking with safety first solves it only in that relaxed sense.

4 ADAPTERS

Frozen and blind. The world model, planner settings, memory and seeds never change. The planner never sees the hazard: it is not in its images or states. Only the adapter and a monitor know where it is. The monitor counts every touch, at every simulator sub-step, and never prevents one.

Ranking. We compare two candidates by asking, in order: Which lost fewer of the planner alone's safe finishes? Which has more safe finishes? Which finishes more often? Ties go to the one that went less deep into the hazard, ended closer to the goal, and acted less often. Cases lost come first, so an adapter that breaks something the planner did well cannot win on gains elsewhere. In symbols, with τ_i the candidate's episode on case i and τ_i^0 the planner alone's,

$$\begin{aligned} L &= \textstyle\sum_i \mathbb{1}[g(\tau_i^0) \wedge \neg v(\tau_i^0)]\ \mathbb{1}[\neg(g(\tau_i) \wedge \neg v(\tau_i))], \\ S &= \textstyle\sum_i \mathbb{1}[g(\tau_i) \wedge \neg v(\tau_i)], \qquad C = \textstyle\sum_i \mathbb{1}[g(\tau_i)], \end{aligned} \tag{3}$$

and candidates are sorted on

$$F(\theta) = \big(-L,\ S,\ C,\ -D,\ -E,\ -T\big), \tag{4}$$

largest first, element by element, where D is the depth inside the hazard, E the final distance to the goal and T the number of decisions where the adapter acted. None is a tuned weight, as in feasibility rules [8].

Steps. Every distance is measured in *steps*. One step is how far the planner alone typically travels in one decision, so one adapter can work across systems of very different size. The hazard's *contact ring* is its radius plus the body's; crossing it is a touch.

Senses. Each adapter reads the same eight numbers about the planner's next move: how far ahead the hazard is, how far to the side (ℓ, signed), how big its contact ring is (σ), how close the planned move comes to the ring (c, the predicted clearance), the distance to the goal, whether the hazard lies toward the goal, how much of the episode is left, and the adapter's own last push. Distances are capped at 6 steps and scaled to $[-1, 1]$.

The gate. An adapter acts only when its gate is open. The gate is a linear test on the senses $\tilde{s}$ (with the side offset replaced by its size, so mirror-image cases look alike). Once open, Steer's gate stays open until the score falls by a release margin ρ, so it does not flicker; Choose's gate has no margin ($\rho = 0$):

$$o_t = \begin{cases} \mathbb{1}[\,w^\top \tilde{s}_t + b > 0\,] & \text{if } o_{t-1} = 0, \\ \mathbb{1}[\,w^\top \tilde{s}_t + b > -\rho\,] & \text{if } o_{t-1} = 1. \end{cases} \tag{5}$$

The gate is always shut when the hazard is more than 6 steps away.

Starting as the planner. Genes live in a box, $x \in [-1, 1]^n$, and map linearly to each gene's range (Table 1). At the centre of the box every gate weight and the bias are zero, so the gate never opens. The centre *is* the planner alone, bit for bit; we checked this by hash on all four systems. It also lets us skip runs: if a candidate's gate would never open on the senses logged in the planner alone's run of a case, we copy the planner alone's outcome (a *skipped run*).

Steer (Algorithm 1, 15 genes) edits the move the planner proposes. When its gate is open, it always pushes sideways, away from the hazard. The push is the *shortfall*: how far the planned path falls short of passing the contact ring with a margin m. For example, if the path would cross 0.5 steps inside the ring and $m = 0.25$, the shortfall is 0.75 steps. A gain κ scales it, and an authority A caps it:

$$d_t = -\operatorname{sgn}(\ell_t)\ \min\big(A,\ \kappa\,[\max(m + \sigma_t - |\ell_t|,\ m - c_t)]_+\big). \tag{6}$$

The sign points the push away from the hazard. The push shifts the move sideways; Steer may also slow it by a factor f (Algorithm 1), and stops once the hazard is h steps behind.

Choose (13 genes) works inside the planner's search, which improves its candidate plans over several rounds. When Choose's gate is open, a checker that knows the hazard plays the best few candidates forward and measures their clearance c_i: 28 checks per decision, spread over the rounds that r_0 and r_1 pick, plus one each for the starting and the final plan. A candidate's key is its cost z_i plus a penalty λ per step it falls short of the margin, and the key replaces the cost when a round picks its best plans. Choose then runs the best-keyed plan $a^\star$ only if the planner's own plan comes inside the margin and $a^\star$ is predicted clearer:

$$k_i = z_i + \lambda\,[m - c_i]_+, \quad a_t = \begin{cases} a_t^\star & \text{if } c_t^{\text{own}} < m \text{ and } c^\star > c_t^{\text{own}}, \\ a_t^{\text{own}} & \text{otherwise.} \end{cases} \tag{7}$$

Choose + Steer runs Choose, then Steer on Choose's move.

5 GRADED HAZARDS

The planner cannot see the hazard, so its path is the same wherever we put it. We therefore run it once on the clean case, record its path, and place the hazard where we want relative to that path (Figure 1). The hazard's radius is one step. There are four levels:

- **Level 1, Clear:** 2 to 3 steps off the path. The planner alone stays clear, so an adapter can only lose cases.
- **Level 2, Graze:** the planner alone clips the edge by a quarter step; a small nudge clears it.
- **Level 3, On the path:** the planner alone drives through the middle; avoiding it takes a detour of a step or more.
- **Level 4, On the goal:** the hazard covers the whole goal region. No run can finish safely; the safe choice is to stop short.

Levels 1 and 2 appear on both sides of the path, so an adapter that always pushes one way fails half of them.

Systems. Search trains one shared adapter on TwoRoom, PushT and basketball together. Reacher is the unseen system, used only




Figure 1: Top: where each level puts the hazard on a path, and what it takes to avoid it. Bottom: the same four levels on one recorded run of the planner alone per system. Basketball is the real scene at the moment the ball scores, with the four keep-out boxes drawn in; Graze overlaps On the path, so it is an outline. Darker red means a harder level.

in the test. TwoRoom, PushT and Reacher use LeWM with AP; basketball uses TD-MPC2. One step is 12.5 px on TwoRoom, 41.1 px on PushT, 2.09 cm on basketball and 4.26 cm on Reacher. What counts as touching is the agent (7 px) on TwoRoom, only the pusher (15 px) on PushT, so the T-shaped block may pass through, the gripper on basketball, where the hazard is a cube across the path the ball is carried along, and the fingertip (1 cm) on Reacher. On an On-the-path case the planner alone goes 1.00 to 1.56 steps into the hazard.

Cases. Each training system has 18 training cases (levels 1–3), 6 selection cases, and 24 test cases (levels 1–4), each set drawn from different recorded episodes. Reacher has test cases only, for 96 test cases in all. The planner alone finishes every case, so it finishes safely on every Clear case and on none of the others.

6 SEARCH

Two methods in lockstep. We compare diagonal CMA-ES [17] (pycma; population 8, initial step size 0.6, started at the centre) with random search, which draws 8 uniform points per generation (Algorithm 2). Both run in lockstep: the same generations and the same cases, so both face the same luck.

Table 1: Gene ranges; each gene maps linearly from $[-1, 1]$. The gate's 8 weights and bias are zero at the centre.

Steer (15 genes)		Choose (13 genes)	
gate w_k, b (9)	[-3, 3]	margin m	[0, 2]
release ρ	[0, 2]	penalty λ	[0, 10]
margin m	[0, 2]	first round r_0	[0, 1]
gain κ	[0, 2]	last round r_1	[0, 1]
authority A	[0, 1.5]	gate w_k, b (9)	[-3, 3]
slow-down f	[0.5, 1.2]		
behind h	[0, 2]		

The same cases every generation. Each candidate runs the same 12 training cases in every generation: per system, one Clear, two Graze and one On-the-path case, so a rank reflects the candidate, not the draw. The two repeats use different cases.

Selecting before testing. Each method's best candidates by gain over the planner alone (random search's top four; CMA-ES's top three plus its final mean) are re-scored on the 18 selection cases. The best of each method becomes its *selected adapter*, fixed before any test case is opened. With two repeats, each method has two selected Steer and two selected Choose adapters; Choose + Steer pairs those of the same method and repeat.

Algorithm 1 One decision with an adapter. Steer's push is a residual on the planner's move.

Require: frozen planner; hazard (adapter only); genes x (Table 1)

$a_t \leftarrow$ the planner's own move.
if Choose **then** ▷ inside the planner's search
  Gate o_t on the senses of the starting plan (Eq. 5).
  if $o_t = 1$ **then**
    for each checked round (fractions r_0 to r_1 of the rounds) **do**
      Play the best few plans forward; measure clearance c_i.
      Rank them by $k_i = z_i + \lambda[m - c_i]_+$, not by cost z_i.
    end for
    $a_t \leftarrow a_t^\star$ if own plan is within m and $a_t^\star$ is clearer (Eq. 7).
  end if
end if
if Steer **then** ▷ the residual
  Gate o_t on the senses of a_t, with release ρ (Eq. 5).
  if $o_t = 1$ and the hazard is less than h steps behind **then**
    Push d_t steps away from the hazard (Eq. 6).
    Shift the planned displacement: $\delta_t \leftarrow f\,\delta_t + d_t\,u\,n_t$ if $d_t \neq 0$, with u one step and n_t the unit sideways direction.
    $a_t \leftarrow$ the action that moves by δ_t, within the action limits.
  end if
end if
Run a_t. With every gate shut this is the planner alone, bit for bit.

Algorithm 2 Lockstep search, one repeat

Require: frozen planner, adapter genes $x \in [-1, 1]^n$, 12 fixed training cases, selection cases

Run the planner alone once on every case and log its senses.
Start CMA-ES at $x = 0$ (the planner alone).
for each generation, until the deadline **do**
  Sample 8 CMA-ES candidates and 8 uniform random draws.
  for each candidate and each of the 12 cases **do**
    If its gate never opens on the logged run, reuse its outcome.
    Otherwise run the case.
  end for
  Rank every candidate by Eq. 4; update CMA-ES from its ranks.
end for
Each method's best candidates are re-scored on the selection cases.
Select one adapter per method; only then open the test cases.

Budget. One 60-minute deadline gave repeat 1 of each adapter 15 generations and repeat 2 12, on three cloud machines with RTX 4090 GPUs. The searches ran 8,583 episodes and the test 1,450, not counting skipped runs. Skipped runs saved 13 to 27% of each search. The design, comparisons and tests were fixed before any result.

7 RESULTS

All counts are safe finishes on the test cases, compared case by case with the planner alone, on levels 1–3 unless stated. A *gain* is a case the adapter finished safely and the other did not, a *loss* the reverse, and p is the two-sided exact sign test on them. On these levels the planner alone has 18 of 54 on the three training systems and 6 of 18 on Reacher, all of them Clear cases. Figure 2 shows every selected and untrained adapter; Table 2 breaks them down by level.

RQ1: many more safe finishes. On the three training systems, every selected adapter beat the planner alone's 18 of 54, scoring between 23 and 34. 11 of the 12 gains are significant by a paired sign test. The best was Choose + Steer from CMA-ES, repeat 2: 34 of 54, with 20 cases gained and 4 lost ($p = 0.002$) (Table 3, Figure 4).

The cost: fewer finishes. The planner alone finishes all 54 training-system test cases; the adapters finish less often. Choose kept 48 to 49 finishes; Steer and Choose + Steer kept 34 to 47. They also lost 0 to 4 of the 18 Clear cases the planner alone finished safely. A detour can leave the planner unable to reach its goal in time.

RQ4: the unseen system gained the most. On Reacher, which search never saw, Steer from CMA-ES, repeat 1, and Choose + Steer from CMA-ES, repeat 1, both reached 16 of 18 against the planner alone's 6: 10 cases gained and 0 lost ($p = 0.002$). Every selected adapter scored between 8 and 16 there.

RQ2: a slight edge to CMA-ES, on the unseen system. Of 12 paired tests of CMA-ES against random search (each adapter type and repeat, on the training systems and on Reacher), only 1 was significant: Steer, repeat 1, on Reacher, 6 cases to 0 ($p = 0.031$). Summed over the six pairs, CMA-ES won 24 cases and lost 8 on Reacher, but 38 and 43 on the training systems; Choose alone favoured random search, 10 to 17. The pairs share cases, so we do not test the sums. CMA-ES's adapters transferred better; where they were searched, the two tied.

RQ3: untrained adapters are a lottery. One untrained Choose adapter did as well as most selected adapters: 33 of 54, and 12 of 18 on Reacher, with 0 cases lost. The other opened its gate on only 33 of 96 test cases and matched the planner alone's safe finishes case for case: 18 and 6. The two untrained Steer adapters scored 26 and 19 of 54, each losing 3 cases. Search removes that luck; it did not reliably beat the best untrained adapter.

On the goal: stopping short. No adapter can finish an On-the-goal case safely; what changes is how often it touches. The planner alone finishes and touches on all 24 cases. Steer and Choose + Steer often stop short instead: they touched on only 10 to 21 of 24. Choose rarely stops; it touched on 18 to 24.

Training. Figure 3 shows each search. Both methods beat the planner alone on the training cases within a few generations. CMA-ES's population improved measurably in only one of the four searches (Steer, repeat 1: Spearman $\rho = 0.25$, $p = 0.007$).

8 WHAT THE ADAPTERS DID

The gates opened where they should. Every test episode logged each adapter decision (Figure 5). On Graze and On-the-path cases, the gates of the selected adapters opened in nearly every episode: the CMA-ES Choose adapter of repeat 1, for example, in 48 of 48.

Steer moved the path out of the hazard. By construction, every push went away from the hazard (100% of open decisions). On TwoRoom the planner alone's closest approach to the contact ring is -0.91 steps (inside it); with Steer it ranged from -0.01 to 1.04. On basketball it moved from -0.62 to between 0.64 and 1.54. PushT moved least, from -0.81 to between -0.61 and -0.23.

Choose swapped plans only when it helped. When its gate opened, Choose's checker found a plan predicted to clear the hazard in 82 to 88% of decisions. It ran that plan in only 20 to 30% of them; otherwise the planner's own plan was already clear enough, or no checked plan was clearer. It moved the closest approach less than Steer (TwoRoom -0.88 to -0.52 steps), fitting its higher finish rate.




Figure 2: The dashed line is the planner alone. Nearly every selected adapter sits to its right, on every system. Random search (orange) reaches as far as CMA-ES (blue) on the training systems, but not on Reacher. Grey squares: untrained.

Table 2: Safe finishes per level, of 6 cases each; bold cells beat the planner alone at that level, grey cells fall below it. On the goal (L4) has no safe finish, so it shows finishes / touches instead: fewer of both means the adapter stopped short.

	TwoRoom				PushT				Basketball				Reacher (unseen)			
Adapter	L1	L2	L3	L4	L1	L2	L3	L4	L1	L2	L3	L4	L1	L2	L3	L4
Planner alone	6	0	0	6/6	6	0	0	6/6	6	0	0	6/6	6	0	0	6/6
Steer, CMA-ES, repeat 1	3	**2**	**2**	3/3	6	**4**	0	2/6	6	**3**	**3**	0/4	6	**5**	**5**	0/5
Steer, CMA-ES, repeat 2	5	**4**	**3**	3/4	6	**3**	**1**	0/6	4	**2**	**1**	2/3	6	**4**	0	2/6
Steer, random search, repeat 1	5	**4**	**1**	3/3	5	**2**	0	0/5	4	**2**	**4**	3/5	6	**3**	**1**	2/5
Steer, random search, repeat 2	5	**2**	**3**	3/5	6	**2**	0	0/6	6	**3**	**3**	3/4	6	**2**	0	3/6
Steer, untrained adapter 1	4	**2**	0	6/6	5	**6**	0	4/6	6	**3**	0	4/4	6	**5**	**2**	1/6
Steer, untrained adapter 2	5	0	0	6/6	6	**2**	0	6/6	4	**2**	0	5/5	6	**4**	**2**	6/6
Choose, CMA-ES, repeat 1	6	**1**	0	1/1	6	**2**	0	4/6	5	**4**	**2**	5/5	6	**2**	0	6/6
Choose, CMA-ES, repeat 2	6	0	0	5/5	6	0	0	5/6	5	**4**	**2**	4/4	6	**3**	**1**	5/6
Choose, random search, repeat 1	6	**1**	0	6/6	6	**3**	0	4/6	6	**4**	**3**	5/6	6	**3**	**1**	6/6
Choose, random search, repeat 2	6	0	0	4/4	6	**3**	0	5/6	4	**4**	**4**	4/5	5	**2**	**1**	5/6
Choose, untrained adapter 1	6	**4**	0	2/2	6	**5**	0	4/6	6	**3**	**3**	3/6	6	**3**	**3**	6/6
Choose, untrained adapter 2	6	0	0	6/6	6	0	0	6/6	6	0	0	6/6	6	0	0	6/6
Choose + Steer, CMA-ES, repeat 1	3	**4**	**1**	1/1	6	**3**	0	0/6	6	**2**	**5**	0/1	6	**5**	**5**	0/6
Choose + Steer, CMA-ES, repeat 2	5	**5**	**3**	2/3	5	**3**	**1**	0/6	4	**5**	**3**	1/2	6	**4**	**1**	2/6
Choose + Steer, random search, repeat 1	5	**4**	**2**	1/1	6	**1**	0	0/0	4	**4**	**4**	2/5	6	**4**	0	1/4
Choose + Steer, random search, repeat 2	4	**4**	**2**	1/2	6	**2**	0	0/4	6	**4**	**5**	3/3	5	**3**	**1**	1/6

Table 3: Case-by-case comparisons on levels 1–3: cases gained–lost by the first method against the second, with the two-sided sign-test p, over the three training systems (54 cases) and on the unseen Reacher (18). Bold marks $p < 0.05$.

	CMA-ES vs planner alone				Random search vs planner alone				CMA-ES vs random search			
	Training		Reacher		Training		Reacher		Training		Reacher	
Adapter	g–l	p	g–l	p	g–l	p	g–l	p	g–l	p	g–l	p
Steer, repeat 1	14–3	**0.013**	10–0	**0.002**	13–4	**0.049**	4–0	0.12	9–7	0.80	6–0	**0.031**
Steer, repeat 2	14–3	**0.013**	4–0	0.12	13–1	**0.002**	2–0	0.50	9–10	1.00	2–0	0.50
Choose, repeat 1	9–1	**0.021**	2–0	0.50	11–0	**<0.001**	4–0	0.12	3–6	0.51	1–3	0.62
Choose, repeat 2	6–1	0.12	4–0	0.12	11–2	**0.022**	3–1	0.62	2–6	0.29	4–2	0.69
Choose + Steer, repeat 1	15–3	**0.008**	10–0	**0.002**	15–3	**0.008**	4–0	0.12	7–7	1.00	7–1	0.070
Choose + Steer, repeat 2	20–4	**0.002**	5–0	0.062	17–2	**<0.001**	4–1	0.38	8–7	1.00	4–2	0.69

9 BLOCK PLUCKING: AN ARM TASK

The graded hazards are discs placed beside a recorded path. Block Plucking tests the same procedure on a task whose failures are its own, with no hazard added.




Figure 3: Solid lines are each generation's average and dashed steps the best found so far, both as safe finishes minus the planner alone's on the 12 training cases. Both methods beat the planner alone early, and neither pulls clearly ahead.




Figure 4: Blue bars are test cases gained over the planner alone, red bars cases lost, per selected adapter and system, with the counts printed on the bars. Gains far outweigh losses everywhere; bold with a star marks $p < 0.05$.

The task. A simulated Franka arm must pull the middle block out of a stack of three (Figure 7), in Isaac Sim 6.2 and Isaac Lab 3.0 at 20 Hz. We use the Hard variant, with a lighter top block and a smaller base. A failure is any of: a block falls below 0.13 m, the top block slides more than 0.07 m from the base, or the gripper leaves its boundary. A finish is *sustained* if it still holds 40 controls later with no failure, and here S counts sustained safe finishes.

The planner. It is AP again, with a memory of the 161,709 steps in the 1,369 successful demonstrations released with UNISafe [19]. Each decision retrieves the 64 most similar moments and considers the five recorded actions that followed each one. UNISafe's safety filter only watches: its signals are logged, never applied. On Hard probes it finished 5 of 12 but failed in 8 of 12, so finishing and staying safe pull against each other.

The adapter. A *segment selector* re-ranks the 64 retrieved moments inside the planner's final choice. Five weights w trade the planner's imagined cost c_i (Equation 1) against five standardized features y_i: retrieval distance, imagined cost, mean arm-action size, the share of gripper-closing commands, and progress through the demonstration. With $w = 0$ it is the planner alone:

$$i^\star = \arg\min_i \left(c_i - w^\top y_i\right). \tag{8}$$

A selector can only replay recorded behavior. We chose it after a screen of 24 random adapters of each kind on 4 starts: a residual on the planner's command finished 1 of 96 episodes and failed in 85, while the selector finished 76 and failed in 18.

The search. Candidates are ranked by S, then finishes, then fewer failures. Diagonal CMA-ES (population 8, initial step size 0.5) ran 8 generations on two shared starts per generation. Random search ran 16 draws from the same starting distribution, $N(0, 0.5^2 I)$, on 8 starts, so each method used 128 episodes. The selected CMA-ES adapter is its final mean; the selected random one is its best draw. Each of three repeats was tested on 16 fresh starts. We fixed the rule first: over all 48 starts, the procedure *transfers* if CMA-ES gains




Figure 5: Left: the closest approach to the contact ring (below zero is a touch) for the planner alone and each selected adapter, on Graze and On-the-path cases. Right: what each adapter did when its gate was open.




Figure 6: Recorded paths, one test case per panel; a red × marks the first touch, and outcomes are listed below. In the first four panels Steer from CMA-ES goes around the hazard and finishes safely. In the last it stays clear but stops short; Choose finishes safely.




Figure 7: Block Plucking: the arm pulls the yellow middle block out of a stack of three without dropping or displacing the others. Frames from an earlier study on the regular task, not the pilot.

at least 9 sustained safe finishes over the planner alone with no more failures, and shows *no signal* if both differences are within 3.

The planner alone is a coin toss. On 48 fresh Hard starts it failed at a rate of 0.52 (Wilson 95% interval 0.38 to 0.66) and sustained a safe finish at only 0.29. It cannot see when the block is out, so it keeps following anchors.

The pilot found no signal (Figure 8). Over all 48 starts, CMA-ES and the planner alone both reached 10 sustained safe finishes, with 26 failures against 28. Start by start, CMA-ES gained 9 and lost 9 (McNemar exact $p = 1.00$). Three untrained adapters reached 12 and 25 failures; random search reached 7 and 30. All read no signal.

A residual looked like skill, but was not. We also tried a gated residual: a small correction to the arm joints, bounded at 0.1, that acts only when UNISafe's failure head predicts danger. With no search, 24 random residuals ran on the four starts where the planner alone failed (Table 4). They finished safely in 48 of 96 episodes. But a control bounded at 0.001, whose corrections are




Figure 8: Block Plucking over 48 fresh starts: every interval overlaps the planner alone's, for sustained safe finishes (left) and failures (right).

Table 4: Random residuals on the four starts where the planner alone failed (it had 0 safe finishes of 4). The near-zero control does as well as the real residuals.

Residual	Episodes	Safe	Sustained	Failed
Gated, bound 0.1	96	48	25	46
Ungated, bound 0.1	96	50	25	43
Ungated, gripper authority 2.0	48	16	9	31
Control: bound 0.001	48	28	20	19
Control: gate only above $p = 0.01$	48	4	1	44

about 0.0004 per coordinate, did as well: 28 of 48 safe finishes. On a Hard start, any change to the actions re-rolls the episode from roughly even odds. The failure head also gave almost no warning: it passed 0.01 on only 2.5% of the planner alone's steps.

The lesson. When an outcome turns on tiny differences, a gain counts as skill only if it beats a near-zero change. We ran no such control on the graded systems; there, the evidence against re-rolls is the mechanism of Section 8: every push went away from the hazard, and the closest approach moved outward.

10 DISCUSSION

The design did most of the work. Both adapters know which way is safe: Steer always pushes away, and Choose always prefers the clearer plan. With that built in, random genes are often good enough: one untrained adapter matched the selected ones, and random search matched CMA-ES. Search still removed the lottery: every selected adapter beat the planner alone, while untrained adapters ranged from no change to as good as the best.

Whether evolution helps is still open. CMA-ES had 15 or fewer generations of 8 candidates on 12 cases, and its population improved measurably in one search of four. With little to learn beyond the built-in direction, random search loses nothing by comparison.

Limits. Case sets are small (18 per system on levels 1–3, two repeats per method), so only large effects show, and we make no correction across tests. Hazards are placed against one recorded path, and the checker knows the hazard exactly, which a real robot may not. Nothing here certifies safety.

11 CONCLUSIONS

Can a small evolved adapter add safety to a frozen planner that cannot see the hazard? On hazards graded against the planner's own path, yes: adapters that know which way is safe raised safe finishes on all three training systems, and one shared adapter transferred unchanged to an unseen system, where it helped most. Safety cost some finishes. Whether evolution adds much is still open: CMA-ES's adapters transferred slightly better than random search's, but a lucky untrained adapter did nearly as well. On Block Plucking, a near-zero control matched the real adapters. The next test of evolution needs adapters whose right behavior is not built in.

REFERENCES

[1] Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. 2017. Constrained Policy Optimization. In *Proceedings of the 34th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 70)*. 22–31.

[2] Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G. Bellemare. 2021. Deep Reinforcement Learning at the Edge of the Statistical Precipice. In *Advances in Neural Information Processing Systems*, Vol. 34.

[3] Eitan Altman. 1999. *Constrained Markov Decision Processes*. Chapman and Hall/CRC.

[4] Lenz Belzner and Martin Wirsing. 2021. Synthesizing Safe Policies under Probabilistic Constraints with Reinforcement Learning and Bayesian Model Checking. *Science of Computer Programming* 206 (2021), 102620.

[5] James Bergstra and Yoshua Bengio. 2012. Random Search for Hyper-Parameter Optimization. *Journal of Machine Learning Research* 13 (2012), 281–305.

[6] Nicolas Carrara, Edouard Leurent, Romain Laroche, Tanguy Urvoy, Odalric-Ambrym Maillard, and Olivier Pietquin. 2019. Budgeted Reinforcement Learning in Continuous State Space. In *Advances in Neural Information Processing Systems*, Vol. 32.

[7] Weiqin Chen and Santiago Paternain. 2024. Generalized Constraint for Probabilistic Safe Reinforcement Learning. In *Proceedings of the 6th Annual Learning for Dynamics and Control Conference (Proceedings of Machine Learning Research, Vol. 242)*. 1606–1618.

[8] Kalyanmoy Deb. 2000. An Efficient Constraint Handling Method for Genetic Algorithms. *Computer Methods in Applied Mechanics and Engineering* 186, 2–4 (2000), 311–338.

[9] David Ha and Jürgen Schmidhuber. 2018. Recurrent World Models Facilitate Policy Evolution. In *Advances in Neural Information Processing Systems*, Vol. 31.

[10] Nikolaus Hansen and Andreas Ostermeier. 2001. Completely Derandomized Self-Adaptation in Evolution Strategies. *Evolutionary Computation* 9, 2 (2001), 159–195.

[11] Nicklas Hansen, Hao Su, and Xiaolong Wang. 2024. TD-MPC2: scalable, robust world models for continuous control. In *International Conference on Learning Representations*.

[12] Kai-Chieh Hsu, Haimin Hu, and Jaime F. Fisac. 2023. The safety filter: a unified view of safety-critical control in autonomous systems. *Annual Review of Control, Robotics, and Autonomous Systems* (2023).

[13] Tobias Johannink, Shikhar Bahl, Ashvin Nair, Jianlan Luo, Avinash Kumar, Matthias Loskyll, Juan Aparicio Ojea, Eugen Solowjow, and Sergey Levine. 2019. Residual reinforcement learning for robot control. In *IEEE International Conference on Robotics and Automation*.

[14] Xvyuan Liu, Jianjie Fang, Wei Wu, Chen Gao, and Yong Li. 2026. Aim Short to Reach Far: Your Frozen World Model Can Plan Better Than You Think. arXiv:2609.30036.

[15] Lucas Maes, Quentin Le Lidec, Damien Scieur, Yann LeCun, and Randall Balestriero. 2026. LeWorldModel: Stable End-to-End Joint-Embedding Predictive Architecture from Pixels. arXiv:2603.19312.

[16] Enrico Marchesini, Davide Corsi, and Alessandro Farinelli. 2022. Exploring Safer Behaviors for Deep Reinforcement Learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 36. 7701–7709.

[17] Raymond Ros and Nikolaus Hansen. 2008. A Simple Modification in CMA-ES Achieving Linear Time and Space Complexity. In *Parallel Problem Solving from Nature – PPSN X*. Springer, 296–305.

[18] Thomas P. Runarsson and Xin Yao. 2000. Stochastic Ranking for Constrained Evolutionary Optimization. *IEEE Transactions on Evolutionary Computation* 4, 3 (2000), 284–294.

[19] Junwon Seo, Kensuke Nakamura, and Andrea Bajcsy. 2025. Uncertainty-aware Latent Safety Filters for Avoiding Out-of-Distribution Failures. In *Proceedings of the 9th Conference on Robot Learning (Proceedings of Machine Learning Research, Vol. 305)*. 4442–4472.

[20] Tom Silver, Kelsey Allen, Josh Tenenbaum, and Leslie Kaelbling. 2018. Residual policy learning. *arXiv preprint arXiv:1812.06298* (2018).

[21] Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. 2020. Meta-World: a benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*.