Kubernetes On-Premises: Architecture and Setup Guide

Author: Sachin Dubey | **First published:** Oct 16, 2026 | **Revision 3:** Oct 23, 2026

On-prem Kubernetes runs on servers you own: bare metal or virtual machines (VMs) in your data center, with containers running your apps on top. This guide explains the architecture, virtualization versus containerization, and a step-by-step kubeadm setup with every command.

Revision 2 added an AWS EC2 section, a pre-flight checklist, a check after every step, and a problems and fixes chapter built from real errors hit while building a cluster.

Revision 3 adds Problem 14 (Calico stuck because the pod CIDR in `custom-resources.yaml` does not match `kubeadm init`), a mandatory CIDR check in Step 8b, and corrects the earlier statement that `192.168.0.0/16` is the default in the Calico download. The file downloaded for Calico v3.32.2 contains `10.244.0.0/16`.

How to use this guide

Every step is a short block of commands. Run the blocks in order, and run each **Check** before moving to the next step. If a check fails, stop and see Section 9 instead of continuing.

Rules that prevent most errors:

1. Copy commands from the .md file or GitHub, not from the PDF. PDF viewers can insert line breaks into long commands when you copy them. A broken line was the cause of the "NO_PUBKEY" error in Problem 9.
2. Use the same Kubernetes version on every node. Pick one version and use it everywhere.
3. Use private IPs in `/etc/hosts`, `kubeadm init` and `kubeadm join`. Replace every example IP in this guide with your real one (`hostname -I`).
4. Follow the order: Part A on all nodes, then Part B on the master, then Part C on the workers.
5. Run the check after each step. Do not move on until it passes.

6. Run the commands one block at a time, not the whole guide at once. Run `create`, `apply` and `watch` commands as separate commands, never pasted together on one line (see Problem 14).
7. The pod CIDR must be identical in two places: the `--pod-network-cidr` of `kubeadm init` (Step 6) and the `cidr:` line of Calico's `custom-resources.yaml` (Step 8b). Check it with `grep cidr custom-resources.yaml` before you install Calico.

Table of Contents

1. What does On-Prem mean?
2. On-Prem Architecture
3. Virtualization vs Containerization
4. Example Cluster Used in This Guide
5. Running on Cloud VMs (AWS EC2 notes)
6. Pre-flight Checklist
7. Step-by-Step Setup with kubeadm
8. On-Prem Extras You Must Plan
9. Common Problems and Fixes
10. Starting Over (Reset and Uninstall)
11. Command Cheat Sheet

1. What does On-Prem mean?


On-premises (on-prem) means the servers, network and storage are in your own office or data center, not rented from a cloud such as AWS, Azure or GCP.

The Kubernetes parts are the same as in the cloud (API Server, etcd, Scheduler, Controller Manager, Kubelet, kube-proxy). What changes is that you must provide things the cloud gives for free:

- The machines (physical servers or VMs)
- A load balancer for users and for the API Server
- Persistent storage for data
- Networking, firewall and DNS

2. On-Prem Architecture

The cluster sits on your own servers. Users enter through a load balancer, the control plane makes decisions, worker nodes run the Pods, and your own storage and network sit underneath.



Layers explained

Layer	What it is	On-prem choice
Users	People or apps that call your service	Office network, VPN or internet
Load balancer	Spreads traffic across Nodes and gives a stable IP	MetalLB, or HAProxy plus keepalived
Control plane (Master)	API Server, etcd, Scheduler, Controller Manager	1 node for a lab, 3 nodes for production

Layer	What it is	On-prem choice
Worker nodes	Run your Pods with Kubelet, kube-proxy and containerd	VMs or bare metal servers
Pod network (CNI)	Lets Pods on different Nodes talk	Calico, Flannel or Weave Net
Storage	Keeps data when Pods restart	NFS, Longhorn, Ceph
Physical layer	Servers, switches, power, hypervisor	VMware, Proxmox, KVM, or bare metal

3. Virtualization vs Containerization

These are two different ways to share one physical server between many workloads.

Virtualization uses a hypervisor to split one server into several virtual machines. Each VM has its own full operating system, so it is heavy (GBs of disk, minutes to boot) but strongly isolated. Examples: VMware vSphere, Proxmox, KVM, Hyper-V.

Containerization packages an app with its libraries and runs it on the host's shared OS kernel. Containers are light (MBs, start in seconds) but share the kernel. Examples: Docker, containerd, CRI-O.

```
Virtualization            Containerization          Kubernetes on-prem
--------------            ----------------          ------------------
App A  | App B            App A  | App B            Pods (your apps)
Guest OS | Guest OS       Container runtime         Node OS + containerd
Hypervisor                Host OS (shared)          Hypervisor, or skip it
Server hardware           Server hardware           Server hardware
```

On-prem Kubernetes stacks both: an optional hypervisor underneath, containers on top.

Comparison

Point	Virtualization (VM)	Containerization (Container)
Isolation	Own OS and kernel per VM	Shared host kernel
Size	GBs	MBs

Point	Virtualization (VM)	Containerization (Container)
Startup time	Minutes	Seconds
Performance	Some overhead from hypervisor and guest OS	Near native
Density per server	Tens of VMs	Hundreds of containers
Managed by	Hypervisor (vCenter, Proxmox)	Kubernetes
Best for	Running full OS, isolating teams, hosting the Nodes	Packaging and scaling apps

Which one do we use in an On-Prem setup?

Both, at different layers.

- **Containerization is always used.** Kubernetes exists to run containers, so your apps run as containers (via containerd) inside Pods.
- **Virtualization is optional and sits underneath.** The Nodes themselves can be VMs (most common, because they are easy to create, snapshot and resize) or bare metal servers (best raw performance, used for large or latency-sensitive clusters).

Simple rule: for labs, learning and small or medium companies, use VMs on VMware, Proxmox or KVM as your Nodes. For heavy workloads such as databases, AI or big data, consider bare metal Nodes. In both cases the apps are containers.

4. Example Cluster Used in This Guide

This guide uses three Ubuntu machines (VMs or physical). It was written for Ubuntu 22.04 and 24.04, and the AWS test ran on a newer Ubuntu release (apt showed the codename `resolute`). Change the IP addresses to match your network.

Hostname	Role	IP address (example)	CPU	RAM
k8s-master	Control plane	192.168.1.10	2 or more	2 GB or more (4 GB better)

Hostname	Role	IP address (example)	CPU	RAM
k8s-worker1	Worker	192.168.1.11	2	2 GB or more
k8s-worker2	Worker	192.168.1.12	2	2 GB or more

Requirements: static IPs, full network connectivity between the machines, unique hostnames, internet access to download packages, and a user with sudo rights.

Important: the `192.168.1.x` addresses are only examples. Everywhere this guide shows one, replace it with the real private IP of your machine. Find it with `hostname -I`.

5. Running on Cloud VMs (AWS EC2 notes)

If you build this lab on AWS EC2 (or any cloud) instead of your own servers, these points caused real failures:

1. **Use private IPs, not public IPs.** In `/etc/hosts`, in `--apiserver-advertise-address`, and in `kubeadm join`, always use the private IP (for example `172.31.x.x`). Public IPs change when an instance is stopped and started, cost data transfer, and are not assigned to the network interface, so the API server cannot bind to them.
2. **Find the real IP first.** The example `192.168.1.10` does not exist on an EC2 instance. Running `kubeadm init` with a non-existent IP makes the API server unreachable and init fails (Problem 3).
3. **Pod CIDR must not overlap your VPC.** The default AWS VPC uses `172.31.0.0/16`, so the pod range `192.168.0.0/16` used in this guide is safe. If your VPC uses `192.168.x.x`, pick another pod range (for example `10.244.0.0/16`) and use it everywhere (Step 6 and Step 8b).
4. **Instance size.** The control plane needs at least 2 vCPU and about 2 GB RAM. Use t3.medium (2 vCPU, 4 GB) or larger. t2.micro and t3.micro will fail.
5. **Security group.** The simplest working setup is one rule that allows all traffic from the same security group (so nodes can talk to each other), plus SSH from your IP. Put all three instances in the same security group. See the port table in Section 8 for the strict version.
6. **Name your machines.** EC2 gives names like `ip-172-31-8-191`. Rename each node (Step 1) so names match `/etc/hosts` and are unique.

7. **Testing a NodePort app.** Open the NodePort range (30000-32767) to your own IP in the security group, then browse to `http://<worker-public-ip>:<nodeport>`.
8. **MetalLB does not work on AWS.** Layer 2 mode needs ARP, which AWS VPCs do not support. Use the AWS Load Balancer Controller or a NodePort instead. MetalLB is for real on-prem networks.

6. Pre-flight Checklist

Complete this before you start. Fill in the table with your own values and keep it open while you work.

Item	Master	Worker 1	Worker 2
Hostname	k8s-master	k8s-worker1	k8s-worker2
Private IP (`hostname -I`)	(fill in)	(fill in)	(fill in)
CPU / RAM	2+ / 2 GB+	2+ / 2 GB+	2+ / 2 GB+

- [ ] Three Ubuntu machines, each with at least 2 CPU and 2 GB RAM (4 GB better on the master)
- [ ] You can SSH into each machine and use sudo
- [ ] Each machine has internet access (`curl -I https://pkgs.k8s.io` returns a response)
- [ ] The machines can reach each other (same security group on AWS, or firewall ports open on-prem)
- [ ] Hostnames are unique
- [ ] You wrote down the three private IPs above
- [ ] You chose one Kubernetes version for all nodes
- [ ] You chose one pod CIDR (this guide uses `192.168.0.0/16`) and wrote it down

Choosing the Kubernetes version

Check https://kubernetes.io/releases/ for the supported versions. As of Oct 2026, v1.34 reaches end of life on Oct 27, 2026, while v1.35 and v1.36 are supported and v1.37 is the newest release. This guide uses **v1.35** as the default.

- **Building a new cluster:** keep v1.35 (or choose another supported version) and use it on every node.
- **Already installed v1.34 on some nodes (for example your master)?** Use v1.34 on the remaining nodes too. Mixing versions causes confusing errors. You can upgrade the whole cluster later.
- Before choosing a version, also check that your Calico version supports it (see Step 8).

7. Step-by-Step Setup with kubeadm

kubeadm is the official tool to build a cluster. Part A runs on ALL nodes, then Part B runs on the master only, then Part C runs on the workers, then Part D verifies everything.

Part A: Prepare every node (master and workers)

Step 1. Set a hostname and name resolution

Run the matching hostname command on each machine. Then add the host entries on all machines, using your real private IPs from the checklist.

```
# On the master
sudo hostnamectl set-hostname k8s-master

# On worker 1
sudo hostnamectl set-hostname k8s-worker1

# On worker 2
sudo hostnamectl set-hostname k8s-worker2
```

On **all nodes** (replace the three IPs first):

```
printf '%s\n' '192.168.1.10 k8s-master' '192.168.1.11 k8s-worker1'
'192.168.1.12 k8s-worker2' | sudo tee -a /etc/hosts
```

Alternative (same result, multi-line version). On **all nodes** (replace the three IPs first):

```
cat <<EOF | sudo tee -a /etc/hosts
192.168.1.10 k8s-master
192.168.1.11 k8s-worker1
192.168.1.12 k8s-worker2
EOF
```

Use either this block or the `printf` command above, not both. Running both adds duplicate lines. Paste the whole block at once, including the final `EOF` line, and make sure `EOF` is alone on its line with no spaces before it.

If you already added wrong IPs, edit the file on every node and fix or delete the bad lines:

```
sudo nano /etc/hosts
```

Check:

```
hostname
cat /etc/hosts
```

Do Steps 2 to 5 on every node, one node at a time (finish a node completely, then go to the next), or open one terminal per node.

Step 2. Turn off swap

Kubelet refuses to run while swap is on.

```
sudo swapoff -a
sudo sed -i '/ swap / s/^\([^#]\)/#\1/' /etc/fstab
```

Step 3. Load kernel modules and network settings

These let containers use the bridge network and let the node forward packets. Run these one line at a time (each is a single line, so nothing can break when pasted):

```
printf '%s\n' 'overlay' 'br_netfilter' | sudo tee /etc/modules-
load.d/k8s.conf
sudo modprobe overlay
sudo modprobe br_netfilter
printf '%s\n' 'net.bridge.bridge-nf-call-iptables = 1' 'net.bridge.bridge-nf-
call-ip6tables = 1' 'net.ipv4.ip_forward = 1' | sudo tee
/etc/sysctl.d/k8s.conf
sudo sysctl --system
```

Each `tee` command prints back the lines it wrote. Check that they look exactly like the text inside the quotes.

What each part does:

Item	Purpose
`overlay` module	OverlayFS, used by containerd to stack image layers
`br_netfilter` module	Makes bridged traffic pass through iptables (needed by kube-proxy and the CNI)
`net.bridge.bridge-nf-call-iptables = 1`	Bridged IPv4 traffic goes through iptables rules
`net.bridge.bridge-nf-call-ip6tables = 1`	Same, for IPv6
`net.ipv4.ip_forward = 1`	Lets the node forward packets between interfaces (Pod-to-Pod and Pod-to-Service traffic)

Check:

```
lsmod | grep -E "overlay|br_netfilter"
sysctl net.bridge.bridge-nf-call-iptables net.bridge.bridge-nf-call-ip6tables
net.ipv4.ip_forward
cat /proc/sys/net/ipv4/ip_forward
```

Both modules must be listed. All three sysctl values must show `= 1`, and the last command must print `1`. Also check that `sudo sysctl --system` printed no error such as `Path is not under /proc/sys/`. If it did, see Problem 13.

Step 4. Install the container runtime (containerd)

This is the engine that actually runs containers.

```
sudo apt-get update
sudo apt-get install -y containerd
sudo mkdir -p /etc/containerd
containerd config default | sudo tee /etc/containerd/config.toml

# Use systemd cgroups (required by kubelet)
sudo sed -i 's/SystemdCgroup = false/SystemdCgroup = true/'
/etc/containerd/config.toml
sudo systemctl restart containerd
sudo systemctl enable containerd
```

Check:

```
grep SystemdCgroup /etc/containerd/config.toml
systemctl status containerd
```

The first must show `SystemdCgroup = true`. The second must show `active (running)`. Press `q` to leave the status screen.

Step 5. Install kubeadm, kubelet and kubectl

The commands are split into small pieces on purpose. Run them in order, and stop and fix if a check fails. Use the same version on every node.

5a. Set the version and prepare apt:

```
KUBE_VERSION=v1.35
KEYRING=/etc/apt/keyrings/kubernetes-apt-keyring.gpg
REPO=https://pkgs.k8s.io/core:/stable:/$KUBE_VERSION/deb

sudo apt-get update
sudo apt-get install -y apt-transport-https ca-certificates curl gpg
sudo mkdir -p -m 755 /etc/apt/keyrings
sudo rm -f $KEYRING
```

5b. Download the signing key, then convert it (two separate commands, no pipe):

```
curl -fsSL $REPO/Release.key -o /tmp/k8s-release.key
sudo gpg --dearmor -o $KEYRING /tmp/k8s-release.key
sudo chmod 644 $KEYRING
ls -l $KEYRING
```

Check: the `ls` line must show a file size greater than 0 (about 1 to 3 KB). If it says `No such file` or `0`, stop and see Problem 9.

5c. Add the repository:

```
echo "deb [signed-by=$KEYRING] $REPO/ /" | sudo tee
/etc/apt/sources.list.d/kubernetes.list
cat /etc/apt/sources.list.d/kubernetes.list
```

Check: the `cat` output must be one line that contains your version (for example `v1.35`) and no `$` characters.

5d. Install and pin the packages:

```
sudo apt-get update
sudo apt-get install -y kubelet kubeadm kubectl
sudo apt-mark hold kubelet kubeadm kubectl
sudo systemctl enable --now kubelet
```

Check: during `apt-get update` you must see a `pkgs.k8s.io` line starting with `Get:` or `Hit:`. If you see `Err:` or `NO_PUBKEY`, go back to 5b.

Part A final check (run on every node):

```
kubeadm version -o short
free -h
lsmod | grep -E "overlay|br_netfilter"
cat /proc/sys/net/ipv4/ip_forward
grep SystemdCgroup /etc/containerd/config.toml
systemctl is-active containerd
hostname
```

Every line must be right before you continue:

Command	Must show
`kubeadm version -o short`	A version such as `v1.35.x`, the same on every node
`free -h`	`Swap:` line with `0B`
`lsmod ...`	Both `overlay` and `br_netfilter` listed
`cat /proc/sys/net/ipv4/ip_forward`	`1`
`grep SystemdCgroup ...`	`SystemdCgroup = true`
`systemctl is-active containerd`	`active`
`hostname`	`k8s-master`, `k8s-worker1` or `k8s-worker2` (not `ip-172-...`)

Notes:

- `apt-mark hold` stops a routine `apt upgrade` from changing your Kubernetes version by accident.

- Until you run `kubeadm init` or `kubeadm join`, kubelet restarts in a loop (`activating (auto-restart)`). This is normal, not an error.
- If you open a new terminal, the variables from 5a are gone. Run 5a again, or type the values directly.

Part B: Create the control plane (master only)

Step 6. Initialize the cluster

First find the master's real private IP and confirm it looks right:

```
hostname -I
MASTER_IP=$(hostname -I | awk '{print $1}')
echo $MASTER_IP
```

The printed address must be the private IP you wrote in the checklist (on AWS it looks like `172.31.x.x` or `10.x.x.x`). Then initialize. This guide uses the pod CIDR `192.168.0.0/16`. Remember this value: Step 8b must use exactly the same one.

```
sudo kubeadm init --apiserver-advertise-address=$MASTER_IP --pod-network-
cidr=192.168.0.0/16
```

This takes 1 to 3 minutes. When it succeeds, the last lines look like this (your IP, token and hash will differ):

```
Your Kubernetes control-plane has initialized successfully!
...
You should now deploy a pod network to the cluster.
...
kubeadm join 172.31.2.148:6443 --token <token> \
    --discovery-token-ca-cert-hash sha256:<hash>
```

Do these three things right away:

1. **Do not run kubectl yet.** If you do, it fails with `The connection to the server localhost:8080 was refused`, because your user has no kubeconfig. This is not a cluster failure. Go straight to Step 7.
2. **Note the IP in the `kubeadm join` line.** It is the master's private IP. Every node's `/etc/hosts` must use the same IP for `k8s-master` (see "Keep /etc/hosts in sync" below Step 7).

3. **Treat the token and hash as secrets.** Do not post screenshots or paste them in public places. They expire after 24 hours, and you can always create a new join command with Step 9. The printed join command says "as root", so on Ubuntu run it with `sudo` in front.

Optional: reach the API server from outside the VPC (for example kubectl from your laptop). Add the master's public IP to the API server certificate:

```
sudo kubeadm init --apiserver-advertise-address=$MASTER_IP --pod-network-
cidr=192.168.0.0/16 --apiserver-cert-extra-sans=<MASTER_PUBLIC_IP>
```

If `kubeadm init` fails or times out, do not re-run it on top of the failed attempt. Reset first, then check the causes in Problem 3:

```
sudo kubeadm reset -f
sudo rm -rf /etc/cni/net.d $HOME/.kube
sudo systemctl restart containerd kubelet
```

Then run the init command again.

Step 7. Let your user run kubectl

```
mkdir -p $HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
sudo chown $(id -u):$(id -g) $HOME/.kube/config
kubectl get nodes
```

The master shows `NotReady` until a network plugin is installed. This is expected.

If `kubectl get nodes` prints `localhost:8080 ... connection refused` instead, the three `mkdir` / `cp` / `chown` lines did not run correctly. Run them again (Problem 8).

Keep /etc/hosts in sync. The master's private IP is the address in the `kubeadm join` line (also shown by `hostname -I` on the master). Make sure every node has this exact line, with that IP:

```
hostname -I
cat /etc/hosts
```

```
<MASTER_PRIVATE_IP> k8s-master
```

If you rebuilt or replaced the master instance, its private IP is different from before, and old `/etc/hosts` entries on the workers are now wrong. Fix them with `sudo nano /etc/hosts` on each node before joining.

Step 8. Install the Pod network (Calico v3.32.2)

Check https://docs.tigera.io/calico/latest/getting-started/kubernetes/quickstart for the current Calico version and its supported Kubernetes versions. Replace the version number in the URLs below if a newer one exists.

Rules for this step:

- Use `kubectl create`, not `kubectl apply`. The CRDs are large and `apply` can fail with an "annotation too long" error.
- Install only one network plugin. If you applied Flannel earlier, remove it first: `kubectl delete -f https://github.com/flannel-io/flannel/releases/latest/download/kube-flannel.yml`
- **The pod CIDR in Calico must equal the `--pod-network-cidr` used in Step 6.** The `custom-resources.yaml` you download in 8b is not guaranteed to contain your range. The v3.32.2 file contains `10.244.0.0/16`, so with this guide's `192.168.0.0/16` you must change it (Step 8b). Skipping this is the most likely reason Calico never starts (Problem 14).
- Run each command separately. Do not paste `kubectl create ...` and `watch ...` together, because the shell would treat `watch` as part of the first command.

8a. Install the CRDs and the Tigera Operator:

```
kubectl create -f
https://raw.githubusercontent.com/projectcalico/calico/v3.32.2/manifests/v1_crd_projectcalico_org.yaml
kubectl create -f
https://raw.githubusercontent.com/projectcalico/calico/v3.32.2/manifests/tigera-operator.yaml
```

Check: both commands print lines ending in `created`, and this shows the operator `Running` after a minute:

```
kubectl get pods -n tigera-operator
```

8b. Download the custom resources file and set the CIDR (mandatory):

```
curl -O
https://raw.githubusercontent.com/projectcalico/calico/v3.32.2/manifests/cust
om-resources.yaml
grep -n cidr custom-resources.yaml
```

The `grep` line must show exactly the CIDR you used in Step 6. With this guide that is `cidr: 192.168.0.0/16`. If it shows a different range (for example `cidr: 10.244.0.0/16`), change it now, before installing:

```
sed -i 's#10.244.0.0/16#192.168.0.0/16#' custom-resources.yaml
grep -n cidr custom-resources.yaml
```

Run the `grep` again. It must now show your Step 6 range. (If you chose a different pod range in Step 6, put that range in place of `192.168.0.0/16` in the `sed` command.)

Fallback if the curl download fails: create the file yourself.

```
cat > custom-resources.yaml <<EOF
apiVersion: operator.tigera.io/v1
kind: Installation
metadata:
  name: default
spec:
  calicoNetwork:
    ipPools:
    - name: default-ipv4-ippool
      blockSize: 26
      cidr: 192.168.0.0/16
      encapsulation: VXLANCrossSubnet
      natOutgoing: Enabled
      nodeSelector: all()
---
apiVersion: operator.tigera.io/v1
kind: APIServer
metadata:
  name: default
spec: {}
EOF
```

8c. Install Calico and wait:

```
kubectl create -f custom-resources.yaml
```

Then, as a separate command:

```
watch kubectl get pods -n calico-system
```

Press `Ctrl+C` to stop watching. All pods must reach `Running` (this takes a few minutes). Then:

```
kubectl get tigerastatus
kubectl get nodes
```

`tigerastatus` shows `Available` for each component, and the master turns `Ready`.

If `calico-system` is still empty after 3 to 4 minutes, run `kubectl get tigerastatus`. If the message mentions an IPPool CIDR that is "not within the platform's configured pod network CIDR", go to Problem 14. For any other cause, see Problem 6.

Part C: Join the workers (each worker)

Step 9. Get the join command (on the master)

This prints a complete, single-line join command. Tokens last 24 hours, so run it again whenever you need a new one:

```
kubeadm token create --print-join-command
```

Step 10. Run the join command on each worker

Copy the entire line the master printed and put `sudo` in front of it. The address in it must be the master's private IP. It looks like this:

```
sudo kubeadm join <MASTER_PRIVATE_IP>:6443 --token <token> --discovery-token-
ca-cert-hash sha256:<hash>
```

Before joining, make sure the worker passed the Part A final check and uses the same Kubernetes version as the master. Joining takes about a minute. If it hangs, see Problem 7.

Part D: Verify the cluster (master)

Step 11. Check nodes and system pods

```
kubectl get nodes -o wide
kubectl get pods -A
```

All three nodes must show `Ready`, and the pods must be `Running` (give it a few minutes after the last join). Optionally label the workers:

```
kubectl label node k8s-worker1 node-role.kubernetes.io/worker=
kubectl label node k8s-worker2 node-role.kubernetes.io/worker=
```

Step 12. Deploy a test app

```
kubectl create deployment nginx --image=nginx --replicas=2
kubectl expose deployment nginx --type=NodePort --port=80
kubectl get pods -o wide
kubectl get svc nginx
```

The service shows a port such as `80:31234/TCP`. Open `http://<worker-ip>:31234` in a browser (use your own port; on AWS use the worker's public IP and allow the port in the security group). The nginx welcome page means your cluster works. When you are done testing, clean up:

```
kubectl delete service nginx
kubectl delete deployment nginx
```

Final success checklist

- [ ] `kubectl get nodes` shows all three nodes `Ready`
- [ ] `kubectl get pods -A` shows everything `Running` or `Completed`
- [ ] `kubectl get tigerastatus` shows Calico components `Available`
- [ ] The nginx test page opens in the browser

8. On-Prem Extras You Must Plan

Load balancer for Services (MetalLB)

On-prem there is no cloud load balancer, so `type: LoadBalancer` Services stay `Pending`. MetalLB hands out IPs from a range you reserve on your network. (Not usable on AWS, see Section 5.)

```
kubectl apply -f
https://raw.githubusercontent.com/metallb/metallb/v0.14.9/config/manifests/me
tallb-native.yaml
```

Create `metallb-config.yaml` with a free IP range from your LAN, then apply it:

```
apiVersion: metallb.io/v1beta1
kind: IPAddressPool
metadata:
  name: lan-pool
  namespace: metallb-system
spec:
  addresses:
  - 192.168.1.200-192.168.1.220
---
apiVersion: metallb.io/v1beta1
kind: L2Advertisement
metadata:
  name: lan-adv
  namespace: metallb-system
```

```
kubectl apply -f metallb-config.yaml
```

Persistent storage

Pods lose local data when they restart, so use shared storage for databases and uploads. Common on-prem choices:

- **NFS** with an NFS provisioner: simplest, good for labs and small setups
- **Longhorn:** easy replicated storage using the Nodes' own disks
- **Ceph (Rook):** powerful and scalable, but more complex

High availability for production

One master is a single point of failure. For production use 3 control-plane nodes behind a virtual IP provided by HAProxy plus keepalived, and initialize with that address:

```
sudo kubeadm init --control-plane-endpoint=192.168.1.100:6443 --upload-certs
--pod-network-cidr=192.168.0.0/16
```

Back up etcd regularly; it holds the whole cluster state.

Firewall ports to open between nodes

Node type	Port	Used for
Control plane	6443 TCP	API Server (kubectl and nodes)
Control plane	2379-2380 TCP	etcd
Control plane	10257, 10259 TCP	Controller Manager, Scheduler
All nodes	10250 TCP	Kubelet API
All nodes	4789 UDP	Calico VXLAN (Pod traffic between nodes)
Workers	10256 TCP	kube-proxy
Workers	30000-32767 TCP	NodePort Services

On AWS, the easy way to cover all the node-to-node rows is one security group rule: allow all traffic from the same security group.

9. Common Problems and Fixes

Quick table

Symptom	Likely cause	Fix
Node stays `NotReady`	No Pod network installed, or Calico pods not running	Complete Step 8 and check `kubectl get pods -n calico-system`
`No resources found in calico-system namespace` and `tigerastatus` mentions an IPPool CIDR	CIDR in `custom-resources.yaml` differs from `kubeadm init`	See Problem 14
`kubeadm init` fails on preflight	Swap on, or required ports in use	Repeat Step 2, run `sudo kubeadm reset -f` and try again
Kubelet keeps restarting after init/join	containerd not using systemd cgroups	Repeat Step 4 and run `sudo systemctl restart containerd kubelet`

Symptom	Likely cause	Fix
Join command says token invalid	Token older than 24 hours	Run `kubeadm token create --print-join-command` on the master
Service stays `Pending` on LoadBalancer	No load balancer on-prem	Install MetalLB (on AWS use the AWS Load Balancer Controller)
`ip_forward` prints 0 or `Path is not under /proc/sys/`	sysctl file damaged when pasted	See Problem 13
kubectl says `localhost:8080 ... connection refused`	No kubeconfig for your user (Step 7 not done)	See Problem 8

Problems hit while building this cluster

Problem 1: `E: Unable to locate package kubelet` and `Unit kubelet.service does not exist`

What you see:

```
E: Unable to locate package kubelet
E: Unable to locate package kubeadm
E: Unable to locate package kubectl
E: No packages found
Failed to enable unit: Unit kubelet.service does not exist
```

Cause: the Kubernetes apt repository was never added. The `Hit:` lines show only ubuntu.com URLs and no `pkgs.k8s.io`.

Fix: run Step 5 (5a to 5d). If the repository is added but you now see `NO_PUBKEY`, go to Problem 9.

Problem 2: `/etc/hosts` contains public IPs

What you see: entries such as `16.4.72.94 k8s-master` (AWS public addresses).

Cause: public IPs were used instead of private IPs. They change on stop/start, are slower, and are not what the API server advertises.

Fix: run `hostname -I` on every node, then put the private IPs in `/etc/hosts` on all nodes:

```
172.31.11.184 k8s-master
<worker1-private-ip> k8s-worker1
<worker2-private-ip> k8s-worker2
```

Problem 3: `kubeadm init` fails at wait-control-plane with `context deadline exceeded`

What you see:

```
error execution phase wait-control-plane: cannot obtain client without
bootstrap:
could not bootstrap the admin user in file admin.conf: unable to create
ClusterRoleBinding:
Post
"https://192.168.1.10:6443/apis/rbac.authorization.k8s.io/v1/clusterrolebindi
ngs?timeout=10s":
context deadline exceeded
```

Cause: the guide's example IP `192.168.1.10` did not exist on the machine. `hostname -I` showed the real IP was `172.31.11.184`. The API server was told to advertise an address nobody could reach, so the init timed out. (Certificates and manifests are created fine before this point.)

Fix:

```
hostname -I
sudo kubeadm reset -f
sudo rm -rf /etc/cni/net.d $HOME/.kube
sudo systemctl restart containerd kubelet
MASTER_IP=$(hostname -I | awk '{print $1}')
sudo kubeadm init --apiserver-advertise-address=$MASTER_IP --pod-network-
cidr=192.168.0.0/16
```

Then repeat Step 7. If it still fails, check:

- `grep SystemdCgroup /etc/containerd/config.toml` shows `true`, and containerd was restarted
- The instance has at least 2 vCPU and about 2 GB RAM (use t3.medium or larger)
- `cat /proc/sys/net/ipv4/ip_forward` prints `1` (if not, repeat Step 3)
- The logs show the real error:

```
sudo journalctl -u kubelet --no-pager | tail -30
sudo crictl --runtime-endpoint unix:///run/containerd/containerd.sock ps -a
```

Problem 4: Pod CIDR overlaps your network

Cause: the pod range overlaps the VPC or LAN range. If your network already uses `192.168.x.x`, the pod range `192.168.0.0/16` collides with it and routing breaks. (For a mismatch between `kubeadm init` and Calico's file, see Problem 14.)

Fix: pick one pod range that does not overlap your network and use it in both places. The default AWS VPC (`172.31.0.0/16`) does not overlap with `192.168.0.0/16`. If your network uses `192.168.x.x`, choose another range such as `10.244.0.0/16`, use it in Step 6, and set the same value in `custom-resources.yaml` (Step 8b).

Problem 5: Calico install command errors (old URLs)

Cause: older guides use `v3.29.3`, with `tigera-operator.yaml` and `custom-resources.yaml` only. Newer Calico releases ship the CRDs as a separate manifest.

Fix: use the commands in Step 8 (v3.32.2) and use `kubectl create`, not `apply`.

Problem 6: `No resources found in calico-system namespace`

What you see: `watch kubectl get pods -n calico-system` shows nothing after the install commands.

Cause: one of these:

- It is only timing (wait 1 to 2 minutes).
- An earlier step did not complete: the operator is not running, or `custom-resources.yaml` was never applied.
- The CIDR in `custom-resources.yaml` does not match `kubeadm init`. This is the most common cause when waiting does not help. See Problem 14.

Fix, check in this order:

```
kubectl get pods -n tigera-operator
kubectl get tigerastatus
kubectl logs -n tigera-operator deploy/tigera-operator --tail=40
kubectl get installation
grep -n cidr custom-resources.yaml
```

If `tigerastatus` shows an IPPool / CIDR message, go to Problem 14. If `kubectl create -f custom-resources.yaml` says the resource already exists, it was created earlier, so skip it and wait. Also scroll up and check that each earlier `kubectl create` printed `created` and not an error. Remove any leftover Flannel install (see Step 8).

Problem 7: `kubeadm join` hangs or times out

Cause: the AWS security group (or firewall) blocks traffic between nodes, or the join address is wrong.

Fix:

- Join using the master's private IP on port 6443
- Allow all traffic from the same security group (or open the ports in the Section 8 table)
- From the worker, test the connection:

```
nc -vz <MASTER_PRIVATE_IP> 6443
```

Problem 8: `The connection to the server localhost:8080 was refused`

What you see (usually right after `kubeadm init` succeeded):

```
E1023 07:15:58.193144   10982 memcache.go:265] "Unhandled Error"
err="couldn't get current server API group list: Get
\"http://localhost:8080/api?timeout=32s\": dial tcp 127.0.0.1:8080: connect:
connection refused"
The connection to the server localhost:8080 was refused - did you specify the
right host or port?
```

Cause: kubectl has no kubeconfig for your user, so it falls back to `localhost:8080`, where nothing is listening. The cluster itself is fine. `kubeadm init` only creates the config at `/etc/kubernetes/admin.conf` (readable by root). It does not copy it for your user, so Step 7 is required.

Fix: run Step 7 on the master:

```
mkdir -p $HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
sudo chown $(id -u):$(id -g) $HOME/.kube/config
kubectl get nodes
```

`kubectl get nodes` must now list `k8s-master` (status `NotReady` until Calico is installed). Notes:

- Run these as your normal user (for example `ubuntu`), not as root with `sudo su`. The `$HOME/.kube/config` file must belong to the user who runs kubectl.
- If `cp` asks `overwrite?`, answer `y`.
- Kubectl only works on the master (where `admin.conf` exists). Workers do not need it.
- Quick temporary alternative for the current session only: `export KUBECONFIG=/etc/kubernetes/admin.conf` (you may need `sudo kubectl ...` with it). The permanent fix above is better.

Problem 9: `NO_PUBKEY` / "The repository ... is not signed" and packages still not found

What you see:

```
Err:4 https://pkgs.k8s.io/core:/stable:/v1.34/deb InRelease
  The following signatures couldn't be verified because the public key is not
available: NO_PUBKEY 234654DA9A296436
E: The repository 'https://pkgs.k8s.io/core:/stable:/v1.34/deb InRelease' is
not signed.
E: Unable to locate package kubelet
```

Cause: the repository line exists, but the signing key file is missing or empty. This happens when the long `curl ... | sudo gpg --dearmor -o ...` command gets a line break while copying (for example from a PDF), so the key file is never created. It can also happen if the old key file existed and gpg could not overwrite it.

Fix: redo the key in separate short commands on the failing node. Use the same version as the other nodes (shown here as `v1.35`; use `v1.34` if that is what your cluster uses):

```
KUBE_VERSION=v1.35
KEYRING=/etc/apt/keyrings/kubernetes-apt-keyring.gpg
REPO=https://pkgs.k8s.io/core:/stable:/$KUBE_VERSION/deb

sudo mkdir -p -m 755 /etc/apt/keyrings
sudo rm -f $KEYRING
curl -fsSL $REPO/Release.key -o /tmp/k8s-release.key
sudo gpg --dearmor -o $KEYRING /tmp/k8s-release.key
sudo chmod 644 $KEYRING
ls -l $KEYRING
```

The `ls` line must show a size greater than 0. Then make sure the repo file is one clean line:

```
echo "deb [signed-by=$KEYRING] $REPO/ /" | sudo tee
/etc/apt/sources.list.d/kubernetes.list
cat /etc/apt/sources.list.d/kubernetes.list
```

The `cat` output must be a single line with the real version number and no `$` or `${...}`. Then install:

```
sudo apt-get update
sudo apt-get install -y kubelet kubeadm kubectl
sudo apt-mark hold kubelet kubeadm kubectl
sudo systemctl enable --now kubelet
```

During `apt-get update` the `pkgs.k8s.io` line must show `Get:` or `Hit:` and no `Err:`.

Problem 10: Node still has the default hostname (for example `ip-172-31-8-191`)

Cause: the hostname was never set, or two machines share the same name (common with cloned VMs). Names must be unique and should match `/etc/hosts`.

Fix: on each node, before `kubeadm init` or `kubeadm join`:

```
sudo hostnamectl set-hostname k8s-worker1
hostname
```

Use `k8s-master`, `k8s-worker1` or `k8s-worker2` as appropriate. If the node already joined with the wrong name, reset it (Section 10), rename it, and join again.

Problem 11: Mixed Kubernetes versions across nodes

Cause: some nodes were installed with one minor version (for example `v1.34`) and others with another (for example `v1.35`) because the version variable differed.

Fix: check on every node with `kubeadm version -o short`. Reinstall the odd node using the version of the rest (Section 10, "Change the Kubernetes version on a node"), or upgrade the whole cluster properly.

Problem 12: Commands break when pasted

Cause: copying long commands from a PDF or a wrapped screenshot can insert line breaks. Pasting several commands at once can also glue them together on one line.

Fix: copy from the .md file or GitHub, copy one block at a time, and prefer one-line commands (this guide uses `printf ... | sudo tee` instead of multi-line `cat <<EOF` blocks for config files). If something looks cut off, run `history | tail` to see exactly what the shell received.

The `cat <<EOF` alternative in Step 1 is multi-line. If it breaks when pasted, use the `printf` one-liner instead.

Problem 13: `ip_forward` prints 0 and `sysctl: Path is not under /proc/sys/`

What you see:

```
net.bridge.bridge-nf-call-iptables = 1
net.bridge.bridge-nf-call-ip6tables = 1
sysctl: Path is not under /proc/sys/: /proc/sys/
```

and `cat /proc/sys/net/ipv4/ip_forward` prints `0`.

Cause: the third line of `/etc/sysctl.d/k8s.conf` (`net.ipv4.ip_forward = 1`) was damaged when the multi-line command was pasted, so sysctl stopped before applying it. The two bridge settings were applied, but ip_forward was not. Without `ip_forward = 1`, `kubeadm init` and `kubeadm join` fail their preflight checks.

Fix: look at the file, then rewrite it with a one-line command and apply it:

```
cat -A /etc/sysctl.d/k8s.conf
printf '%s\n' 'net.bridge.bridge-nf-call-iptables = 1' 'net.bridge.bridge-nf-
call-ip6tables = 1' 'net.ipv4.ip_forward = 1' | sudo tee
/etc/sysctl.d/k8s.conf
sudo sysctl --system
cat /proc/sys/net/ipv4/ip_forward
```

The last command must print `1`, and `sysctl --system` must not show the "Path is not under" error. If the error still appears, another file causes it. Find it with:

```
sudo grep -rn "/proc/sys" /etc/sysctl.d /etc/sysctl.conf
```

Quick temporary workaround (lost after a reboot, so still do the fix above):

```
sudo sysctl -w net.ipv4.ip_forward=1
```

Check every node, because the same paste problem can hit any of them:

```
cat /proc/sys/net/ipv4/ip_forward
```

Problem 14: Calico never starts: IPPool CIDR is "not within the platform's configured pod network CIDR"

What you see: after Step 8c, nothing appears in `calico-system`, even after 10 minutes or more. The master stays `NotReady` and both coredns pods stay `Pending`:

```
kubectl get pods -n calico-system
No resources found in calico-system namespace.
```

The operator pod is `Running` and `kubectl get installation` shows `default`, so it looks like everything is installed. The real error is in `tigerastatus`:

```
kubectl get tigerastatus
NAME        AVAILABLE   PROGRESSING   DEGRADED   MESSAGE
apiserver               True          Error creating / updating resource:
namespaces "calico-system" not found
calico                  True          waiting for enabled IP pools to be
created
goldmane                True          Error creating / updating resource:
namespaces "calico-system" not found
ippools                 True          error filling IP pool defaults: could
not resolve CalicoNetwork IPPool
                                      and kubeadm configuration: IPPool
10.244.0.0/16 is not within the
                                      platform's configured pod network
CIDR(s) [192.168.0.0/16]
tiers                   True          Waiting for Tigera API server to be
ready
whisker                 True          Error creating / updating resource:
namespaces "calico-system" not found
```

Cause: the pod CIDR is set in two places and they do not match:

- `kubeadm init --pod-network-cidr=192.168.0.0/16` (Step 6) sets the range Kubernetes expects for pods.
- `custom-resources.yaml` (Step 8b) sets the range Calico tries to create. The file downloaded for Calico v3.32.2 contains `cidr: 10.244.0.0/16`.

The Tigera operator reads the kubeadm range, sees that Calico's pool is outside it, and refuses to create the IP pool. Because it stops there, it never creates the `calico-system` namespace, and so no Calico pods start. Waiting does not help, and the operator itself shows no crash. The cause only appears in `tigerastatus` or the operator logs.

Fix (on the master):

1. Confirm the mismatch. Line 13 normally holds the CIDR:

```
grep -n cidr custom-resources.yaml
```

2. Change the file to the range used in Step 6, then check it:

```
sed -i 's#10.244.0.0/16#192.168.0.0/16#' custom-resources.yaml
grep -n cidr custom-resources.yaml
```

The second command must show `cidr: 192.168.0.0/16`.

3. Apply the corrected file. Use `apply` here (not `create`), because the resources already exist:

```
kubectl apply -f custom-resources.yaml
```

Each of the four resources should print `configured`. You will also see warnings that the `last-applied-configuration` annotation is missing. These are harmless: the resources were first made with `create`, and kubectl patches the annotation automatically.

4. Restart the operator so it retries immediately:

```
kubectl rollout restart deployment tigera-operator -n tigera-operator
```

5. Watch Calico start (as its own command). This takes 2 to 5 minutes:

```
watch kubectl get pods -n calico-system
```

Press `Ctrl+C` when `calico-node`, `calico-typha` and `calico-kube-controllers` are `Running`.

6. Confirm the cluster is healthy:

```
kubectl get tigerastatus
kubectl get nodes
kubectl get pods -n kube-system
```

Every component must show `Available`, the master must be `Ready`, and the coredns pods must change from `Pending` to `Running`.

If the `tigerastatus` message still mentions the old CIDR after step 5, the existing Installation kept the old value. Delete and recreate it. This is safe on a fresh cluster, because no workloads depend on Calico yet:

```
kubectl delete -f custom-resources.yaml
kubectl create -f custom-resources.yaml
kubectl rollout restart deployment tigera-operator -n tigera-operator
```

Related mistake: `watch` pasted onto the `create` line. If you paste these two lines together, the shell runs them as one command:

```
kubectl create -f custom-resources.yaml
watch kubectl get pods -n calico-system
```

and prints `watch kubectl get pods -n calico-system` as extra arguments. The create may still succeed, but the watch never runs, and you may see `Stopped watch kubectl ...` job messages. Ignore the stopped jobs, and run the two commands one at a time.

Prevention: before you run `kubectl create -f custom-resources.yaml` (Step 8c), always run `grep -n cidr custom-resources.yaml` and compare it with the `--pod-network-cidr` you used in Step 6. Both must be identical.

Useful debugging commands

```
sudo journalctl -u kubelet -f
kubectl describe pod <name> -n <namespace>
kubectl logs <pod-name> -n <namespace>
kubectl get tigerastatus
kubectl logs -n tigera-operator deploy/tigera-operator --tail=40
sudo crictl --runtime-endpoint unix:///run/containerd/containerd.sock ps -a
```

10. Starting Over (Reset and Uninstall)

Reset a node (keeps the installed packages)

On the node you want to wipe (master or worker):

```
sudo kubeadm reset -f
sudo rm -rf /etc/cni/net.d $HOME/.kube
sudo systemctl restart containerd kubelet
```

If that node was a worker that had joined, also remove it from the cluster on the master:

```
kubectl delete node <node-name>
```

`kubeadm reset` does not clean iptables rules. If you hit odd network problems after a reset, either reboot the node or flush them (this removes all firewall rules on the node, so only do it on a node you are rebuilding):

```
sudo iptables -F
sudo iptables -t nat -F
sudo iptables -t mangle -F
sudo iptables -X
```

Change the Kubernetes version on a node

Use this to fix a node installed with the wrong version, then rerun Step 5 with the right `KUBE_VERSION`:

```
sudo kubeadm reset -f
sudo apt-mark unhold kubelet kubeadm kubectl
sudo apt-get purge -y kubelet kubeadm kubectl
sudo rm -f /etc/apt/sources.list.d/kubernetes.list
sudo rm -f /etc/apt/keyrings/kubernetes-apt-keyring.gpg
```

Rebuild the whole cluster

1. Reset every node (first block above).
2. On the master, repeat Part B (Steps 6 to 8). Check the CIDR in Step 8b again.
3. Generate a new join command (Step 9) and join the workers (Step 10).

11. Command Cheat Sheet

Task	Command
List nodes	`kubectl get nodes -o wide`

Task	Command
List all pods	`kubectl get pods -A`
Describe a resource	`kubectl describe pod <name>`
See logs	`kubectl logs <pod-name>`
Apply a YAML file	`kubectl apply -f file.yaml`
Scale an app	`kubectl scale deployment nginx --replicas=4`
Delete an app	`kubectl delete deployment nginx`
New join command	`kubeadm token create --print-join-command`
Check installed version	`kubeadm version -o short`
Find the node's private IP	`hostname -I`
Check Calico health	`kubectl get tigerastatus`
Check pod CIDR in Calico file	`grep -n cidr custom-resources.yaml`
Reset a node	`sudo kubeadm reset -f`