

Yes, exactly — that makes sense.

You want:

Pot = controls main sensitivity / Channel 1 trigger
Delta spike = controls when MIDI Channel 2 and 3 open

So I made a new full Arduino IDE patch:

[Download PlantSong_Chromatic_MiddleC_DeltaSpike_CH2_CH3.ino](#)

This version is based on your uploaded Teensy patch structure.

The important difference:

Channel 1 = normal pot-controlled trigger
Channel 2 = raw delta spike only
Channel 3 = stronger raw delta spike only

So the pot **does not control Channel 2 and Channel 3 entry** anymore.

The new controls are near the top:

```
const float CH2_DELTA_SPIKE_RATIO = 2.2f;  
const float CH3_DELTA_SPIKE_RATIO = 4.0f;  
  
const unsigned long CH2_MIN_RAW_DELTA = 60;  
const unsigned long CH3_MIN_RAW_DELTA = 130;
```

To make Channel 2 and 3 come in **less often**, try:

```
const float CH2_DELTA_SPIKE_RATIO = 3.0f;  
const float CH3_DELTA_SPIKE_RATIO = 6.0f;  
  
const unsigned long CH2_MIN_RAW_DELTA = 100;  
const unsigned long CH3_MIN_RAW_DELTA = 220;
```

This patch watches for a **delta spike compared to the recent normal delta level**, so Channel 2 and 3 should open only when the plant data jumps strongly, not just because the pot is sensitive.