

Started on	Monday, 3 June 2024, 6:00 PM
State	Finished
Completed on	Monday, 3 June 2024, 6:15 PM
Time taken	15 mins 35 secs
Marks	5.00/5.00
Grade	100.00 out of 100.00

Question **1**

Correct

Mark 1.00 out of 1.00

An abundant number is a number for which the sum of its proper divisors is greater than the number itself. Proper divisors of the number are those that are strictly lesser than the number.

Input Format:

Take input an integer from stdin

Output Format:

Return Yes if given number is Abundant. Otherwise, print No

Example input:

12

Output:

Yes

Explanation

The proper divisors of 12 are: 1, 2, 3, 4, 6, whose sum is $1 + 2 + 3 + 4 + 6 = 16$. Since sum of proper divisors is greater than the given number, 12 is an abundant number.

Example input:

13

Output:

No

Explanation

The proper divisors of 13 is: 1, whose sum is 1. Since sum of proper divisors is not greater than the given number, 13 is not an abundant number.

For example:

Test	Result
<code>print(abundant(12))</code>	Yes
<code>print(abundant(13))</code>	No

Answer: (penalty regime: 0 %)

Reset answer

```
1 def abundant(num):
2     divisor_sum = 0
3     for i in range(1, num):
4         if num % i == 0:
5             divisor_sum += i
6     if divisor_sum > num:
7         return "Yes"
8     else:
9         return "No"
```

	Test	Expected	Got	
✓	print(abundant(12))	Yes	Yes	✓
✓	print(abundant(13))	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

For example:

Test	Result
print(checkUgly(6))	ugly
print(checkUgly(21))	not ugly

Answer: (penalty regime: 0 %)

Reset answer

```
1 def checkUgly(n):
2     if n <= 0:
3         return "not ugly"
4     for prime in [2, 3, 5]:
5         while n % prime == 0:
6             n //= prime
7     return "ugly" if n == 1 else "not ugly"
8
9
10
```

	Test	Expected	Got	
✓	print(checkUgly(6))	ugly	ugly	✓
✓	print(checkUgly(21))	not ugly	not ugly	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Write a code to check whether product of digits at even places is divisible by sum of digits at odd place of a positive integer.

Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

Test	Result
print(productDigits(1256))	True
print(productDigits(1595))	False

Answer: (penalty regime: 0 %)

Reset answer

```
1 from math import log10
2 def productDigits(n):
3     digit_count = int(log10(n))+1
4     total = 0
5     prod = 1
6     while n > 0 :
7         if digit_count % 2 == 0 :
8             prod *= n % 10
9         else:
10            total += n % 10
11
12            n = n // 10
13            digit_count -= 1
14
15 if prod % total == 0:
16     return True
17 else:
18     return False
```

	Test	Expected	Got	
✓	print(productDigits(1256))	True	True	✓
✓	print(productDigits(1595))	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1 def coinChange(target):
2     coins = [1, 2, 3, 4]
3     count = 0
4
5     while target > 0:
6         max2 = max([coin for coin in coins if coin <= target])
7
8         target -= max2
9         count += 1
10
11     return count
```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of 1.00

An e-commerce company plans to give their customers a special discount for Christmas. They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

$1 \leq \text{orderValue} < 10^6$

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
<code>print(christmasDiscount(578))</code>	12

Answer: (penalty regime: 0 %)

Reset answer

```

1 def is_prime(n):
2     if n <= 1:
3         return False
4     for i in range(2, int(n ** 0.5) + 1):
5         if n % i == 0:
6             return False
7     return True
8
9 def sum_of_prime_digits(n):
10     total = 0
11     while n > 0:
12         digit = n % 10
13         if is_prime(digit):
14             total += digit
15         n //= 10
16     return total
17
18 def christmasDiscount(orderValue):
19     return sum_of_prime_digits(orderValue)

```

	Test	Expected	Got	
✓	<code>print(christmasDiscount(578))</code>	12	12	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Jump to...

Searching ▶