#### **Problem Statement**

Write a MATLAB script to generate an ASK signal for the baseband digital data given below

Consider a sinusoidal carrier of

Q1. Vc\*sin(2 \* pi \*2000\* t)

Q2. (Vc/4)\*sin(2 \* pi \*2000\* t)

To represent '1' and '0' respectively.

	0	0	1	0	1	1	0	1	0	0
--	---	---	---	---	---	---	---	---	---	---

## **Digital Modulation**

• Process of encoding information into amplitude, frequency or phase of the transmitted signal.

#### **Types:**

- Amplitude Shift Keying (ASK)
- ON OFF Keying(OOK)
- Frequency Shift Keying(FSK)
- Phase Shift Key(PSK)
- Binary Phase Shift Key(BPSK)
- Quadrature Amplitude Modulation(QAM)

## Amplitude Shift Keying (ASK)

- Similar to Amplitude Modulation.
- Depending on digital data (amplitude vs time), as carrier wave changes, it is denoted as either 1 or 0.
- Amplitude gets shifted and there is switching between 0 and 1 (which is referred to as Keying)
- Derivative of ASK is ON-OFF Keying


#### MATLAB code

**Q1.** 

```
Editor - D:\College\MATLAB\Coms\ASKq1.m
   ASKq1.m × +
       %%% MATLAB script to simulate ASK :Qn 1
       %%% Vc = 2
       clear all; close all; clf;
       Vc = 2;
 4 -
       fc = 2000;
       t = linspace (0, 1/2000, 50);
       ec = Vc * sin(2*pi*fc*t);
       b = [0, 0, 1, 0, 1, 1, 0, 1, 0, 0];
       n = ['The Binary data is: ',num2str(b)];
       ask = []; bin = [];
10 -
11 -
      \Box for i = 1 : length(b)
12 -
           ask = [ask, b(i)*ec];
           bin = [bin, b(i)*ones(1,50)];
13 -
14 -
       end
15
16 -
       tm = [0 : length(ask)-1];
       plot(tm, bin, 'b--'); axis([0 length(bin) 0 2]); hold on;
17 -
18 -
       plot(tm, ask, 'r'); axis([0 length(tm) -4 4]); hold off;
       xlabel('Time index'); ylabel('Amplitude');
19 -
20 -
       legend('Binary data', 'ASK output');
       title('Simulation of Amplitude Shift keying');
21 -
22 -
       gtext(n); %Display the random binary string..
23
       %%% end of simul
```

# Output

### **A1.**



#### MATLAB code

**Q2.** 

```
Editor - D:\College\MATLAB\Coms\ASKq2.m
   ASKq2.m × +
       %%% MATLAB script to simulate ASK :Qn 2
       %%% Vc = 2
       clear all; close all; clf;
 4 —
       Vc = 2;
       fc = 2000;
       t = linspace (0, 1/2000, 50);
 7 -
       ec = (Vc/4) * sin(2*pi*fc*t);
       b = [0, 0, 1, 0, 1, 1, 0, 1, 0, 0];
       n = ['The Binary data is: ',num2str(b)];
       ask = []; bin = [];
10 -
     \neg for i = 1 : length(b)
12 -
           ask = [ask, b(i)*ec];
13 -
           bin = [bin, b(i)*ones(1,50)];
14 -
      ∟ end
15
       tm = [0 : length(ask)-1];
16 -
17 -
       plot(tm, bin, 'b--'); axis([0 length(bin) 0 2]); hold on;
       plot(tm, ask, 'r'); axis([0 length(tm) -2 2]); hold off;
18 -
19 -
       xlabel('Time index'); ylabel('Amplitude');
20 -
       legend('Binary data', 'ASK output');
21 -
       title('Simulation of Amplitude Shift keying');
22 -
       gtext(n); %Display the random binary string..
       %%% end of simul
23
```

## Output

**A2.** 

