Complete list of all Bootstrap 4 CSS classes with description and examples:

Class	Description	Exar
.active	Adds a white text color to the active link in a navbar .	Try i
.active	Adds a blue background color to the active list item in a list group	<u>Try i</u>
.active	Adds a dark-blue background color to simulate a "pressed" button	<u>Try i</u>
.active	Adds a blue background color to the active dropdown item in a dropdown	Try i
.active	Adds a blue background color to the active pagination link (to highlight the current page)	<u>Try i</u>
.active	Displays/shows the current carousel item	<u>Try i</u>
.alert	Creates an alert message box	<u>Try i</u>
.alert-danger	Red alert. Indicates a dangerous or potentially negative action	<u>Try i</u>
.alert-dark	Dark alert. Dark grey alert box	<u>Try i</u>

Class	Description	Exar
.alert- dismissible	Indicates a closable alert box. Together with the .close class, this class is used to close the alert (adds extra padding)	<u>Try i</u>
.alert- heading	Adds color:inherit to the specified element	<u>Try i</u>
.alert-info	Teal alert. Indicates a neutral informative change or action	<u>Try i</u>
.alert-light	Light alert. Light grey alert box	<u>Try i</u>
.alert-link	Used on links inside alerts to provide matching colored links	<u>Try i</u>
.alert- primary	Blue alert. Indicates an important action	<u>Try i</u>
.alert- secondary	Grey alert. Indicates a "less" important action	Try i
.alert- success	Green alert. Indicates a successful or positive action	Try i
.alert- warning	Yellow alert. Indicates caution should be taken with this action	<u>Try i</u>

Class	Description	Exar
.align- baseline	The element is aligned with the baseline of the parent. This is default	Try i
.align-bottom	The element is aligned with the lowest element on the line	<u>Try i</u>
.align-middle	The element is placed in the middle of the parent element	<u>Try i</u>
.align-top	The element is aligned with the top of the tallest element on the line	<u>Try i</u>
.align-text- top	The element is aligned with the top of the parent element's font	<u>Try i</u>
.align-text- bottom	The element is aligned with the bottom of the parent element's font	<u>Try i</u>
.align- content- around	Align gathered items "around"	Try i
.align- content-*- around	Align gathered items "around" on different screens	<u>Try i</u>

Class	Description	Exar
.align- content- center	Align gathered items in the center	<u>Try i</u>
.align- content-*- center	Align gathered items in the center on different screens	<u>Try i</u>
.align- content-end	Align gathered items at the end	<u>Try i</u>
.align- content-*-end	Align gathered items at the end on different screens	<u>Try i</u>
.align- content-start	Align gathered items from the start	<u>Try i</u>
.align- content-*- start	Align gathered items from the start on different screens	<u>Try i</u>
.align- content- stretch	Stretch gathered items	<u>Try i</u>

Class	Description	Exar
.align- content-*- stretch	Stretch gathered items on different screens	<u>Try i</u>
.align-items- start	Align single rows of items from the start	<u>Try i</u>
.align-items- *-start	Align single rows of items from the start on different screens	<u>Try i</u>
.align-items- end	Align single rows of items at the end	<u>Try i</u>
.align-items- *-end	Align single rows of items at the end on different screens	<u>Try i</u>
.align-items- center	Align single rows of items in the center	<u>Try i</u>
.align-items- *-center	Align single rows of items in the center on different screens	<u>Try i</u>
.align-items- baseline	Align single rows of items at the baseline	<u>Try i</u>

Class	Description	Exai
.align-items- *-baseline	Align single rows of items at the baseline on different screens	<u>Try i</u>
.align-items- stretch	Stretch single rows of items	<u>Try i</u>
.align-items- *-stretch	Stretch single rows of items on different screens	<u>Try i</u>
.align-self- start	Align a flex item from the start	<u>Try i</u>
.align-self- *-start	Align a flex item from the start on different screens	<u>Try i</u>
.align-self- end	Align a flex item at the end	<u>Try i</u>
.align-self- *-end	Align a flex item at the end on different screens	<u>Try i</u>
.align-self- center	Align a flex item in the center	<u>Try i</u>

Class	Description	Exar
.align-self- *-center	Align a flex item in the center on different screens	<u>Try i</u>
.align-self- baseline	Align a flex item at the baseline	<u>Try i</u>
.align-self- *-baseline	Align a flex item at the baseline on different screens	<u>Try i</u>
.align-self- stretch	Stretch a flex item	<u>Try i</u>
.align-self- *-stretch	Stretch a flex item on different screens	<u>Try i</u>
.badge	Creates a circular badge (grey circle - often used as a numerical indicator)	<u>Try i</u>
.badge-danger	Red badge. Indicates a dangerous or potentially negative action	<u>Try i</u>
.badge-dark	Dark badge. Dark grey alert box	<u>Try i</u>
.badge-info	Teal badge. Indicates a neutral informative change or action	<u>Try i</u>

Class	Description	Exar
.badge-light	Light badge. Light grey alert box	Try i
.badge-pill	Makes a badge more round	Try i
.badge- primary	Blue badge. Indicates an important action	<u>Try i</u>
.badge- secondary	Grey badge. Indicates a "less" important action	<u>Try i</u>
.badge- success	Green badge. Indicates a successful or positive action	<u>Try i</u>
.badge- warning	Yellow badge. Indicates caution should be taken with this action	<u>Try i</u>
.bg-danger	Adds a red background color to an element. Represents danger or a negative action	Try i
.bg-dark	Adds a dark grey background color to an element	Try i
.bg-info	Adds a teal background color to an element. Represents some information	<u>Try i</u>

Class	Description	Exar
.bg-light	Adds a light grey background color to an element	Try i
.bg-primary	Adds a blue background color to an element. Represents something important	Try i
.bg-secondary	Adds a grey background color to an element. Indicates a "less" important action	Try i
.bg-success	Adds a green background color to an element. Indicates success or a positive action	<u>Try i</u>
.bg-warning	Adds a yellow/orange background color to an element. Represents a warning or a negative action	<u>Try i</u>
.blockquote	Styles quoted blocks of content from another source (adds a larger font-size (1.25rem))	<u>Try i</u>
.blockquote- footer	Styles the source title inside the blockquote (light grey text with indentation)	Try i
.border	Adds a border to an element	<u>Try i</u>
.border- bottom-0	Removes the bottom border from an element	<u>Try i</u>

Class	Description	Exar
.border- danger	Adds a red border to an element (indicates danger)	<u>Try i</u>
.border-dark	Adds a dark border to an element	Try i
.border-info	Adds a teal border to an element (indicates information)	<u>Try i</u>
.border-left-	Removes the left border from an element	<u>Try i</u>
.border-light	Adds a light grey border to an element	<u>Try i</u>
.border- primary	Adds a blue border to an element	<u>Try i</u>
.border- right-0	Removes the right border from an element	<u>Try i</u>
.border-top-0	Removes the top border from an element	<u>Try i</u>
.border- secondary	Adds a grey border to an element	<u>Try i</u>

Class	Description	Exar
.border- success	Adds a green border to an element (indicates success)	<u>Try i</u>
.border- warning	Adds a orange border to an element (indicates warning)	<u>Try i</u>
.border-white	Adds a white border to an element	Try i
.border-0	Removes all borders from an element	<u>Try i</u>
.breadcrumb	A pagination. Indicates the current page's location within a navigational hierarchy	<u>Try i</u>
.breadcrumb- item	Styles list items or links inside the breadcrumb	<u>Try i</u>
.btn	Creates a basic button (gray background and rounded corners)	<u>Try i</u>
.btn-block	Creates a block level button that spans the entire width of the parent element	<u>Try i</u>
.btn-dark	Dark grey button	Try i

Class	Description	Exai
.btn-danger	Red button. Indicates danger or a negative action	Try i
.btn-group	Groups buttons together on a single line	Try i
.btn-group-lg	Large button group (makes all buttons in a button group larger - increased font-size and padding)	<u>Try i</u>
.btn-group-sm	Small button group (makes all buttons in a button group smaller)	<u>Try i</u>
.btn-group- vertical	Makes a button group appear vertically stacked	Try i
.btn-info	Teal button. Represents a neutral informative change or action	<u>Try i</u>
.btn-light	Light grey button	<u>Try i</u>
.btn-link	Makes a button look like a link (get button behavior)	<u>Try i</u>
.btn-lg	Large button	Try i

Class	Description	Exar
.btn-outline- dark	Dark grey bordered/outlined button	<u>Try i</u>
.btn-outline- danger	Red bordered/outlined button. Indicates danger or a negative action	Try i
.btn-outline- info	Teal bordered/outlined button. Represents a neutral informative change or action	Try i
.btn-outline- light	Light grey bordered/outlined button	<u>Try i</u>
.btn-outline- primary	Blue bordered/outlined button.	Try i
.btn-outline- secondary	Grey bordered/outlined button. Indicates a "less" important action	<u>Try i</u>
.btn-outline- success	Green bordered/outlined button. Indicates success or a positive action	Try i
.btn-outline- warning	Orange bordered/outlined button. Represents warning or a negative action	Try i

Class	Description	Exai
.btn-primary	Blue button. Indicates a something important	<u>Try i</u>
.btn-sm	Small button	<u>Try i</u>
.btn- secondary	Grey button. Indicates a "less" important action	<u>Try</u> i
.btn-success	Green button. Indicates success or a positive action	<u>Try i</u>
.btn-toolbar	Combine sets of button groups into button toolbars for more complex components	<u>Try i</u>
.btn-warning	Orange button. Represents warning or a negative action	<u>Try i</u>
.card	Creates a card	<u>Try i</u>
.card-body	Container for card content	<u>Try i</u>
.card-columns	Container to create a masonry-like grid of cards	<u>Try i</u>
.card-danger	Adds a red background color to the card. Represents danger or a negative action	<u>Try i</u>

Class	Description	Exar
.card-dark	Adds a grey background color to the card	Try i
.card-deck	Container to create a grid of cards that are of equal height and width	<u>Try i</u>
.card-footer	Card footer	<u>Try i</u>
.card-group	Container to create a grid of cards that are of equal height and width, without side margins	<u>Try i</u>
.card-header	Card header	<u>Try i</u>
.card-header- tabs	Styles navigation tabs inside the card header	<u>Try i</u>
.card-header- pills	Styles navigation pills inside the card header	<u>Try i</u>
.card-img- bottom	Place the image at the bottom inside a card	<u>Try i</u>
.card-img- overlay	Turns an image into a card background. Often used to add text on top of the image	<u>Try i</u>

Class	Description	Exar
.card-img-top	Place the image at the top inside a card	Try i
.card-info	Adds a teal background color to the card. Represents some information	Try i
.card-light	Adds a light grey background color to the card	<u>Try i</u>
.card-link	Adds a blue color to any link and a hover effect inside the card	Try i
.card-primary	Adds a blue background color to the card. Represents something important	Try i
.card- secondary	Adds a grey background color to the card. Represents something "less" important	Try i
.card- subtitle	The .card-subtitle is used after a .card-title, and adds the following to an element: margin-top:375rem; margin-bottom: 0;	Try i
.card-success	Adds a green background color to the card. Indicates success or a positive action	Try i
.card-text	Used to remove bottom margins for a p element if it is the last child (or the only one), inside .card-body	<u>Try i</u>

Class	Description	Exar
.card-title	Adds a title to any heading element inside the card	Try i
.card-warning	Adds a yellow/orange background color to the card. Represents a warning or a negative action	<u>Try i</u>
.carousel	Creates a carousel (slideshow)	Try i
.carousel- caption	Creates a caption text for each slide in the carousel	<u>Try i</u>
.carousel- control-next	Container for "next" carousel/item link	<u>Try i</u>
.carousel- control-next- icon	Used together with .carousel-control-next to create a "next" icon/button (right-pointed arrow)	<u>Try i</u>
.carousel- control-prev	Container for "previous" carousel/item link	<u>Try i</u>
.carousel- control-prev- icon	Used together with .carousel-control-prev to create a "previous" icon/button (left-pointed arrow)	Try i

Class	Description	Exar
.carousel- indicators	Adds little dots/indicators at the bottom of each slide (which indicates how many slides there is in the carousel, and which slide the user are currently viewing)	<u>Try i</u>
.carousel- inner	Container for slide items	Try i
.carousel- item	Specifies the content of each slide	<u>Try i</u>
.clearfix	Clears floats	<u>Try i</u>
.close	Styles a close icon. This is often used for alerts and modals. Often used together with the × symbol to create the actual icon (a better looking "x"). It floats right by default	Try i
.col-auto	Make form columns automatically size themselves based on their content	<u>Try i</u>
.col-*	Creates a column layout for extra small devices (and up/all devices, if not combined with other column classes). The * can be a number between 1 and 12	Try i
.col-sm-*	Creates a column layout for small devices (and up, if not combined with other column classes). The * can be a number between 1 and 12	Try i

Class	Description	Exar
.col-md-*	Creates a column layout for medium devices (and up, if not combined with other column classes). The * can be a number between 1 and 12	Try i
.col-lg-*	Creates a column layout for large devices (and up, if not combined with other column classes). The * can be a number between 1 and 12	<u>Try i</u>
.col-xl-*	Creates a column layout for extra large devices. The * can be a number between 1 and 12	<u>Try i</u>
.collapse	Indicates collapsible content - which can be hidden or shown on demand	<u>Try i</u>
.collapse show	Show the collapsible content by default	<u>Try i</u>
.container	Fixed width container with widths determined by screen sites. Equal margin on the left and right.	<u>Try i</u>
.container- fluid	A container that spans the full width of the screen	Try i
.container-*	Responsive containers	Try i
.custom-	A wrapper/container for custom checkboxes	<u>Try i</u>

Class	Description	Exar
checkbox		
.custom- control	A wrapper/container for custom forms	<u>Try i</u>
.custom- control-input	Customized form control	<u>Try i</u>
.custom- control- inline	Inline (horizontally - side by side) customized form controls	<u>Try i</u>
.custom- control-label	Customized label, when used together with a custom form control	<u>Try i</u>
.custom-file	Customized file upload	<u>Try i</u>
.custom-file- input	Customized file upload	<u>Try i</u>
.custom-file- label	Customized file label	<u>Try i</u>

Class	Description	Exai
.custom-radio	A wrapper/container for custom radio buttons	Try i
.custom-range	Customized range control	<u>Try i</u>
.custom- select	Customized select menu	Try i
.custom- select-lg	Large customized select menu	<u>Try i</u>
.custom- select-sm	Small customized select menu	Try i
.custom- switch	Customized toggle switch	Try i
.disabled	Disables a button (adds opacity and a "no-parking-sign" icon on hover)	<u>Try i</u>
.disabled	Disables a dropdown item (adds a grey text color and a "no-parking-sign" icon on hover)	<u>Try i</u>

Class	Description	Exar
.disabled	Disables a pagination link (cannot be clicked - adds a grey text color and a "no-parking-sign" icon on hover)	<u>Try i</u>
.disabled	Disables a list item in a list group (cannot be clicked - adds a light grey color and removes the hover effect on list item links)	<u>Try i</u>
.dropdown	Creates a toggleable menu that allows the user to choose one value from a predefined list	Try i
.dropdown- divider	Used to separate links in the dropdown menu with a thin horizontal border	Try i
.dropdown- header	Used to add headers inside the dropdown menu	<u>Try i</u>
.dropdown- item	Creates a dropdown item (added to links or buttons inside .dropdown-menu)	<u>Try i</u>
.dropdown- item-text	Used to add plain text to a dropdown item, or used on links for default link styling	<u>Try i</u>
.dropdown- menu	Adds the default styles for the dropdown menu container	Try i

Class	Description	Exai
.dropdown- menu-right	Right-aligns a dropdown menu	<u>Try i</u>
.dropdown- toggle	Used on the button that should hide and show (toggle) the dropdown menu	<u>Try i</u>
.dropleft	Left-aligns the dropdown	<u>Try i</u>
.dropright	Right-aligns the dropdown	Try i
.dropup	Indicates a dropup menu (upwards instead of downwards)	<u>Try i</u>
.d-block	Creates a block element (adds display:block)	<u>Try i</u>
.d-*-block	Creates a block element on a specific screen width	<u>Try i</u>
.d-inline	Makes an element inline	<u>Try i</u>
.d-*-inline	Makes an element inline on a specific screen size	Try i
.d-inline-	Makes an element inline block	<u>Try i</u>

Class	Description	Exar
block		
.d-*-inline- block	Makes an element inline block on a specific screen size	<u>Try i</u>
.d-flex	Creates a flexbox container and transforms direct children into flex items	<u>Try i</u>
.d-*-flex	Creates a flexbox container on a specific screen size	<u>Try i</u>
.d-inline- flex	Creates an inline flexbox container	<u>Try i</u>
.d-*-inline- flex	Creates an inline flexbox container on a specific screen size	<u>Try i</u>
.d-none	Hides an element	Try i
.d-*-none	Hides an element on a specific screen size	<u>Try i</u>
.d-table	Makes an element display as a table	<u>Try i</u>
.d-*-table	Makes an element display as a table on a specific screen size	<u>Try i</u>

Class	Description	Exar
.d-table-cell	Makes an element display as a table cell	Try i
.d-*-table- cell	Makes an element display as a table cell on a specific screen size	<u>Try i</u>
.d-table-row	Makes an element display as a table row	<u>Try i</u>
.d-*-table- row	Makes an element display as a table row on a specific screen size	<u>Try i</u>
.embed- responsive	Container for embedded content. Makes videos or slideshows scale properly on any device	<u>Try i</u>
.embed- responsive- 16by9	Container for embedded content. Creates an 16:9 aspect ratio embedded content	<u>Try i</u>
.embed- responsive- 3by4	Container for embedded content. Creates an 3:4 aspect ratio embedded content	<u>Try i</u>
.embed- responsive- item	Used inside .embed-responsive. Scales the video nicely to the parent element	Try i

Class	Description	Exar
.fade	Adds a fading effect when closing an alert box	<u>Try i</u>
.fade	Adds a fading effect when showing tab/pill content	<u>Try i</u>
.fade	Adds a fading effect when opening a modal	<u>Try i</u>
.fixed-bottom	Makes an element stay at the bottom of the screen (sticky/fixed)	<u>Try i</u>
.fixed-top	Makes an element stay at the top of the screen (sticky/fixed)	<u>Try i</u>
.flex-column	Display flex items vertically	<u>Try i</u>
.flex-*- column	Display flex items vertically on different screen sizes:	<u>Try i</u>
.flex-column- reverse	Display flex items vertically, reversed	<u>Try i</u>
.flex-*- column- reverse	Display flex items vertically, reversed, on different screen sizes	<u>Try i</u>

Class	Description	Exar
.flex-fill	Used on flex items to force it/them into equal width columns	<u>Try i</u>
.flex-*-fill	Force flex items into equal widths on different screens	<u>Try i</u>
.flex-grow- 0 1	Used on a single flex item to take up the rest of the available space	<u>Try i</u>
.flex-nowrap	Don't wrap flex items	<u>Try i</u>
.flex-*- nowrap	Don't wrap items on different screens	<u>Try i</u>
.flex-shrink- 0 1	Used on a single flex item to shrink it if necessary	
.flex-row	Display flex items horizontally (side by side)	<u>Try i</u>
.flex-*-row	Display flex items horizontally on a specific screen size	<u>Try i</u>
.flex-row- reverse	Display flex items right-aligned and horizontally	Try i

Class	Description	Exar
.flex-*-row- reverse	Display flex items right-aligned and horizontally on a specific screen size	<u>Try i</u>
.flex-wrap	Wrap flex items	Try i
.flex-*-wrap	Wrap items on different screens	<u>Try i</u>
.flex-wrap- reverse	Wrap flex items, in reversed order	<u>Try i</u>
.flex-*-wrap- reverse	Wrap flex items, in reversed order on different screens	Try i
.float-left	Floats an element to the left	<u>Try i</u>
.float-*-left	Floats an element to the left on different screens	<u>Try i</u>
.float-none	Remove floats from an element	<u>Try i</u>
.float-right	Floats an element to the right	<u>Try i</u>

Class	Description	Exar
.float-*- right	Floats an element to the left on different screens	<u>Try i</u>
.font-italic	Italic text	Try i
.font-weight- bold	Bold text	<u>Try i</u>
.font-weight- bolder	Bolder text (font-weight:bolder)	<u>Try i</u>
.font-weight- light	Light weight text (font-weight:300)	Try i
.font-weight- lighter	Lighter weight text (font-weight:lighter)	<u>Try i</u>
.font-weight- normal	Normal text (font-weight:400)	<u>Try i</u>
.form-check	Container for checkboxes. Adds proper padding	Try i
.form-check-	Makes checkboxes appear on the same line (horizontally)	Try i

Class	Description	Exar
inline		
.form-check- input	Styles checkboxes with proper margins	<u>Try i</u>
.form-check- label	Ensures proper margins for labels used together with checkboxes	<u>Try i</u>
.form-control	Used on input, textarea, and select elements to span the entire width of the page and make them responsive	<u>Try i</u>
.form- control-file	Adds display:block and width:100% to input filed with type="file"	<u>Try i</u>
.form- control-lg	Large form control	<u>Try i</u>
.form- control- plaintext	Styles a form control as plain text	<u>Try i</u>
.form- control-range	Adds display:block and width:100% to input filed with type="range"	<u>Try i</u>

Class	Description	Exar
.form- control-sm	Small form control	<u>Try i</u>
.form-group	Container for form input and label	<u>Try i</u>
.form-inline	Makes a <form> left-aligned with inline-block controls (This only applies to forms within viewports that are at least 768px wide)</form>	<u>Try i</u>
.form-row	Container for responsive columns (less left and right margins than .row/overrides default column gutters)	<u>Try i</u>
.h1h6	Makes an element look like a heading of the chosen class (h1-h6)	Try i
.h-25	Sets the height of an element to 25%	<u>Try i</u>
.h-50	Sets the height of an element to 50%	<u>Try i</u>
.h-75	Sets the height of an element to 75%	<u>Try i</u>
.h-100	Sets the height of an element to 100%	<u>Try i</u>

Class	Description	Exar
.img-fluid	Responsive image (adds max-width:100% and height:auto)	<u>Try i</u>
.img- thumbnail	Shapes an image to a thumbnail (thin light grey borders)	<u>Try i</u>
.initialism	Displays the text inside an <abbr> element in a slightly smaller font size</abbr>	<u>Try i</u>
.input-group	Container to enhance an input by adding an icon, text or a button in front or behind the input field as a "help text"	<u>Try i</u>
.input-group- append	Input group container for adding help text behind an input field	<u>Try i</u>
.input-group- lg	Large input group	<u>Try i</u>
.input-group- prepend	Input group container for adding help text in front of an input field	<u>Try i</u>
.input-group-	Small input group	Try i
.input-group-	Styles the specified help text in an input group	<u>Try i</u>

Class	Description	Exar
text		
.input-lg	Large input field	Try i
.input-sm	Small input field	Try i
.invalid- feedback	Creates a custom validation message used in validated forms (red text color)	Try i
.invalid- tooltip	Creates a custom validation message used in validated forms (red tooltip)	Try i
.invisible	Make an element invisible	Try i
.is-invalid	Validates a form element (adds a red border to input fields). Note: for server side	Try i
.is-valid	Validates a form element (adds a green border to input fields). Note: for server side	<u>Try i</u>
.jumbotron	Creates a padded grey heading/box with rounded corners that enlarges the font sizes of the text inside it. Used for calling extra attention to some special content or information	<u>Try i</u>

Class	Description	Exai
.jumbotron- fluid	Creates a full-width jumbotron (grey padded heading) without rounded borders	<u>Try i</u>
.justify- content-*	Aligns flex items from the start , at the end , centered , in between and " around "	<u>Try i</u>
.justify- content-*- around	Aligns flex items "around" on different screen sizes	<u>Try i</u>
.justify- content-*- between	Aligns flex items in "between" on different screen sizes	<u>Try i</u>
.justify- content-*- center	Aligns flex items in the center on different screen sizes	<u>Try i</u>
.justify- content-*-end	Aligns flex items at the end on different screen sizes	<u>Try i</u>
.justify- content-*- start	Aligns flex items from the start on different screen sizes	<u>Try</u> i

Class	Description	Exar
.lead	Increase the font size and line height of a paragraph	Try i
.list-group	Creates a bordered list group for elements	<u>Try i</u>
.list-group- flush	Removes some borders and rounded corners from list items in a list group	<u>Try i</u>
.list-group- horizontal	Display list items horizontally instead of vertically (side-by-side instead of on top of each other)	<u>Try i</u>
.list-group- horizontal-*	Display list items horizontally instead of vertically on different screen sizes	<u>Try i</u>
.list-group- item	Added to each element in the list group	<u>Try i</u>
.list-group- item-action	Added to links inside the list group to make them stand out on hover (darker background)	<u>Try i</u>
.list-group- item-danger	Red background color for a list item in a list group	Try i
.list-group-	Dark grey background color for a list item in a list group	<u>Try i</u>

Class	Description	Exar
item-dark		
.list-group- item-info	Light-blue background color for a list item in a list group	Try i
.list-group- item-light	Light grey background color for a list item in a list group	Try i
.list-group- item-primary	Blue background color for a list item in a list group	<u>Try i</u>
.list-group- item-success	Green background color for a list item in a list group	<u>Try i</u>
.list-group- item-warning	Yellow background color for a list item in a list group	<u>Try i</u>
.list-inline	Places all list items on a single line (used together with .list-inline-item on each elements)	Try i
.list-inline- item	Places all list items on a single line (used together with .list-inline on the parent 	Try i
.list-	Removes all default list-style (bullets, left margin, etc.) styling from	Try i

Class	Description	Exar
unstyled	a or list	
.mark	Highlights text: Highlighted text	Try i
.media	Aligns media objects together with content (like images or videos - often used for comments in a blog post etc)	<u>Try i</u>
.media-body	Container for media content	<u>Try i</u>
.modal	Identifies the content as a modal and brings focus to it	<u>Try i</u>
.modal-body	Defines the style for the body of the modal. Add any HTML markup here (p, img, etc)	<u>Try i</u>
.modal- content	Styles the modal (border, background-color, etc). Inside this, add the modal's header, body and footer, if needed	<u>Try i</u>
.modal- dialog- centered	Centers the modal vertically and horizontally within the page	Try i
.modal- dialog-	Adds a scrollbar inside the modal	<u>Try i</u>

Class	Description	Exar
scrollable		
.modal-footer	The footer of the modal (often contains an action button and a close button)	<u>Try i</u>
.modal-header	The header of the modal (often contains a title and a close button)	Try i
.modal-lg	Large modal (wider than default)	Try i
.modal-sm	Small modal (less width)	Try i
.modal-xl	Extra large modal	Try i
.m-# / m-*-#	Responsive margin classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	Try i
.mt-# / mt-*- #	Responsive top margin classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.mb-# / mb-*- #	Responsive bottom margin classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.ml-# / ml-*-	Responsive left margin classes. * can be sm, md, lg or xl. # can be a number	Try i

Class	Description	Exar
	between 0 and 5	
.mr-# / mr-*- #	Responsive right margin classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	Try i
.mx-# / mx-*- #	Responsive left and right margin auto (horizontal) classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.my-# / my-*- #	Responsive top and bottom margin auto (vertical) classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.mx-auto	Centers an element horizontally	<u>Try i</u>
.nav nav-tabs	Creates a tabbed menu	Try i
.nav nav- pills	Creates a pill menu	Try i
.nav- justified	Justifies tab/pill links with an equal width	Try i
.navbar	Creates a navigation bar	Try i

Class	Description	Exar
.navbar-nav	Container for navigation links inside the .navbar container	Try i
.navbar-brand	Added to a link or a header element inside the navbar to represent a logo or a header	<u>Try i</u>
.navbar- collapse	Collapses the navbar (hidden and replaced with a menu/hamburger icon on mobile phones and small tablets)	<u>Try i</u>
.navbar- expand-*	Responsive collapsible class - stacks the navbar vertically on small (sm), medium (md), large (lg) or extra large (xl) screens	<u>Try i</u>
.navbar-dark	Adds a white text color to all links in the navbar	<u>Try i</u>
.navbar-light	Adds a black text color to all links in the navbar	<u>Try i</u>
.navbar-text	Vertically align any elements inside the navbar that are not links (ensures proper padding)	<u>Try i</u>
.navbar- toggler	Styles the button that should open the navbar on small screens. Automatically styled as a hamburger/three bars	Try i
.nav-link	Used to style links/anchors inside the navbar	<u>Try i</u>

Class	Description	Exar
.nav-item	Used to style list items inside the navbar	Try i
.needs- validation	Adds validation styles to a submitted form	Try i
.no-gutters	Remove gutters/extra space from columns	Try i
.page-item	Styles list items inside a pagination	Try i
.page-link	Styles links inside a pagination	Try i
.pagination	Creates a pagination (Useful when you have a web site with lots of pages	<u>Try i</u>
.pagination- lg	Large pagination (each pagination link gets a bigger font-size and more padding)	<u>Try i</u>
.pagination- sm	Small pagination (each pagination link gets a smaller font size and less padding)	Try i
.pre- scrollable	Makes a <pre> element scrollable (max-height of 350px and provide a y-axis scrollbar)</pre>	<u>Try i</u>

Class	Description	Exar
.progress	Container for progress bars	<u>Try i</u>
.progress-bar	Creates a progress bar	<u>Try i</u>
.progress- bar-animated	Animates the progress bar (used together with stripes)	Try i
.progress- bar-striped	Adds stripes to the progress bar	<u>Try i</u>
.p-# / p-*-#	Responsive padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.pt-# / pt-*- #	Responsive top padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.pb-# / pb-*-	Responsive bottom padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.pl-# / pl-*- #	Responsive left padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>

Class	Description	Exar
.pr-# / pr-*- #	Responsive right padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.py-# / py-*- #	Responsive top and bottom padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.px-# / px-*- #	Responsive left and right padding classes. * can be sm, md, lg or xl. # can be a number between 0 and 5	<u>Try i</u>
.rounded	Adds rounded corners to an element	Try i
.rounded- bottom	Adds bottom rounded corners to an element	<u>Try i</u>
.rounded- circle	Shapes an element to a circle (not supported in IE8 and earlier)	Try i
.rounded-left	Adds left rounded corners of an element	<u>Try i</u>
.rounded- right	Adds right rounded corners to an element	Try
.rounded-top	Adds top rounded corners to an element	Try

Class	Description	Exar
.rounded-0	Removes rounded corners from an element	<u>Try i</u>
.row	Container for responsive columns	<u>Try i</u>
.row-cols-*	Set the number of columns that should appear next to each other	<u>Try i</u>
.shadow	Adds a shadow to an element	<u>Try i</u>
.shadow-lg	Adds a large shadow to an element	<u>Try i</u>
.shadow-none	Removes shadows from an element	<u>Try i</u>
.shadow-sm	Adds a small shadow to an element	<u>Try i</u>
.small	Creates a lighter, secondary text in any heading	<u>Try i</u>
.spinner- border	Creates a spinner/loader	<u>Try i</u>
.spinner- border-sm	Creates a smaller spinner/loader	<u>Try i</u>

Class	Description	Exar
.spinner-grow	Creates a spinner/loader that "grows"	<u>Try i</u>
.spinner- grow-sm	Creates a smaller spinner/loader that "grows"	<u>Try i</u>
.sr-only	Hides an element on all devices except for screen readers	<u>Try i</u>
.sr-only- focusable	Hides an element on all devices except for screen readers	<u>Try i</u>
.sticky-top	Makes an element stay sticky/fixed at the top of the page when you scroll past it	<u>Try i</u>
.stretched- link	Added to a link to make its containing block (parent) clickable (works only for parent elements with position:relative)	Try i
.tab-content	Used together with .tab-pane to creates toggleable/dynamic tabs/pills	<u>Try i</u>
.tab-pane	Used together with .tab-content to creates toggleable/dynamic tabs/pills	<u>Try i</u>
.table	Adds basic styling to a table (padding, bottom borders, etc)	Try i

Class	Description	Exar
.table-active	Adds a grey background color to the table row (or table cell () (same color used on hover)	Try i
.table- bordered	Adds borders on all sides of the table and cells	Try i
.table- borderless	Remove borders from a table	Try i
.table- condensed	Makes a table more compact by cutting cell padding in half	Try i
.table-dark	Adds a black background with white text to the table	<u>Try i</u>
.table-hover	Creates a hoverable table (adds a grey background color on table rows on hover)	Try i
.table- responsive-*	Makes a table responsive (adds a horizontal scrollbar when needed). By default, the scrollbar is added to the table on screens that are less than 992px wide (if needed). There's no difference when viewing anything lager than 992px wide. However, you can use sm md lg xl to decide WHEN the table should get a scrollbar, depending on the screen width	<u>Try i</u>
.table- striped	Adds zebra-stripes to a table	<u>Try i</u>

Class	Description	Exar
.text-break	Prevents long text from breaking layout	<u>Try i</u>
.text- capitalize	Indicates capitalized text	<u>Try i</u>
.text-center	Center-aligns text	<u>Try i</u>
.text-*- center	Center-aligns text on different screens	<u>Try i</u>
.text-danger	Red text color. Indicates danger	<u>Try i</u>
.text-dark	Dark grey text color	<u>Try i</u>
.text- decoration- none	Removes the underline from a link	<u>Try i</u>
.text-hide	Hides text (helps replace an element's text content with a background image)	<u>Try i</u>
.text-info	Light-blue text color. Indicates information	Try i

Class	Description	Exar
.text-light	Light grey text color	<u>Try i</u>
.text-justify	Indicates justified text	<u>Try i</u>
.text-left	Aligns the text to the left	<u>Try i</u>
.text-*-left	Left-aligns text on different screens	<u>Try i</u>
.text- lowercase	Changes text to lowercase	<u>Try i</u>
.text-muted	Grey text color	<u>Try i</u>
.text-nowrap	Prevents the text from wrapping	<u>Try i</u>
.text-primary	Blue text color. Indicates something important	<u>Try i</u>
.text- secondary	Grey text color. Indicates something "less" important	<u>Try i</u>
.text-reset	Resets the color of a text or a link (inherits the color from its parent)	<u>Try i</u>

Class	Description	Exar
.text-right	Aligns text to the right	<u>Try i</u>
.text-*-right	Right-aligns text on different screens	<u>Try i</u>
.text-success	Green text color. Indicates success	<u>Try i</u>
.text- uppercase	Makes text uppercase	<u>Try i</u>
.text-warning	Yellow/orange text color. Indicates warning	<u>Try i</u>
.text-white	White text color	<u>Try i</u>
.thead-dark	Adds a black background color to table headers	<u>Try i</u>
.thead-light	Adds a grey background color to table headers	<u>Try i</u>
.toast	Creates a toast (alert box that disappears after a few seconds)	Try i
.toast-body	Toast body	<u>Try i</u>

Class	Description	Exar
.toast-header	Toast header	<u>Try i</u>
.valid- feedback	Creates a custom validation message used in validated forms (green text color)	<u>Try i</u>
.valid- tooltip	Creates a custom validation message used in validated forms (green tooltip)	<u>Try i</u>
.visible	Make an element visible	Try i
.was- validated	Adds validation styles to a form element	<u>Try i</u>
.w-25	Sets the width of an element to 25%	<u>Try i</u>
.w-50	Sets the width of an element to 50%	Try i
.w-75	Sets the width of an element to 75%	Try i
.w-100	Sets the width of an element to 100%	<u>Try i</u>